

```
Usage:
    dispatch [options]

Options:
    -c, --config=FILE configuration file
```

-o, --output=FILE

-P, --procs=PROCS

-v, --verbose verbose mode

--version show version

display this help and exit

number of processes (default 1)

redirect output to file

-h, --help



tasks: - id: 1 type: psql name: create primary key indexes file: indexes.sql - id: 2 type: psql name: attach indexes to primary keys file: primarykeys.sql depends: [1]

tasks:
 - id: 1
 name: Copy t1 content
 command: |
 rm -f log/ora2pg_t1.log; \
 ora2pg -c config/ora2pg_t1.conf -t COPY
 - id: 2

command: vacuumdb --table log --analyze --freeze

name: Vacuuming t1 relation

depends_on: [1]

```
tasks:
 - id: 1
    type: sh
    name: Freeze vacuuming oldest relations to prevent txid wraparound
    loaded:
      from: psql
      command: |
       SELECT format('VACUUM FREEZE %I.%I', t.schemaname, t.relname)
       FROM pg_catalog.pg_stat_user_tables t
       JOIN pg_catalog.pg_class c ON t.relid=c.oid
       WHERE schemaname NOT LIKE 'pg_%temp%'
       ORDER BY
        (greatest(last_vacuum, last_autovacuum) < now() - interval '1 days') DESC NULLS FIRST,
        least(greatest(last_vacuum, last_autovacuum), now() - interval '1 days') ASC NULLS FIRST,
       age(c.relfrozenxid) DESC
       LIMIT 10
```