/Users/frankie/Dropbox/Harper College/CIS 2026/M14

/Users/frankie/Dropbox/Harper College/CIS 2026/M14/M14P3.py

Inheritance.py | DemoInheritanceB.py | classPerson.py | classVisitor.py | M14P3.py | M14P1.py | M14P2.py

```python
# -*- coding: utf-8 -*-
"""
Created on Thu Apr  9 18:47:56 2026

@author: flkc
Description:
    Modify problem 2 to use a dictionary for the district code pair. Make sure it works. Expand the
dictionary to include X for international students whose tuition is $800.00 per credit hour and G
for reciprocity students whose tuition the same as an I student. instantiate at least one student
of each district code.
Some colleges have reciprocity agreements where a student from another school can take
classes at in district rates. This usually applies to classes not offered by the home college. Harper
does not have a commercial truck driver program for example.
"""

class Student:
    firstName = ""
    lastName = ""
    districtCode = ""
    enrolledCredit = 0
    TUITION_PER_HOUR = {"I":250,
                        "O":500,
                        "X":800,
                        "G":250}

    def __init__(self,firstName,lastName,districtCode = "O",enrolledCredit = 0):
        self.firstName = firstName
        self.lastName = lastName
        self.districtCode = districtCode.upper()
        self.enrolledCredit = enrolledCredit
        self.name = self.fullName()

    def computeTuition (self):
        return self.enrolledCredit * self.TUITION_PER_HOUR[self.districtCode]


    def fullName (self):
        return self.firstName + " " + self.lastName

    def printStudent(self):
        print(f"\n{"Student Name:".ljust(30," ")}{self.name}")
        print(f"{"District Code:".ljust(30," ")}{self.districtCode}")
        print(f"{"Enrolled Credit:".ljust(30," ")}{self.enrolledCredit}")
        print(f"{"Tuition Owed:".ljust(30," ")}{self.computeTuition()}\n")

def main():
    # Create an instance of Student
    student1 = Student("Patrick",
                       "Chan",
                       "I",
                       12)
    student2 = Student("Johnson",
                       "Wong",
                       "O",
                       12)
    student3 = Student("Andy",
                       "Chan",
                       "X",
                       12)
    student4 = Student("Eric",
                       "Tang",
                       "G",
                       12)


    student1.printStudent()
    student2.printStudent()
    student3.printStudent()
    student4.printStudent()

main()
```

| Name | Date Modified |
|---|---|
| _norton_ | 4/9/26 7:08 PM |
| M14P1.pdf | 4/15/26 11:14 PM |
| M14P1.py | 4/15/26 10:46 PM |
| M14P2.pdf | 4/15/26 11:15 PM |
| M14P2.py | 4/15/26 11:10 PM |
| M14P3.py | 4/15/26 11:08 PM |

Help | Variable Explorer | Debugger | Profiler | Plots | Files

Console 1/A

```
In [66]: %runfile '/Users/frankie/Dropbox/Harper College/CIS 2026/M14/
M14P3.py' --wdir

Student Name:                  Patrick Chan
District Code:                 I
Enrolled Credit:               12
Tuition Owed:                  3000


Student Name:                  Johnson Wong
District Code:                 O
Enrolled Credit:               12
Tuition Owed:                  6000


Student Name:                  Andy Chan
District Code:                 X
Enrolled Credit:               12
Tuition Owed:                  9600


Student Name:                  Eric Tang
District Code:                 G
Enrolled Credit:               12
Tuition Owed:                  3000


In [67]:
```

IPython Console | History

Inline | Conda: spyder-runtime (Python 3.12.11) | LSP: Python | Line 66, Col 1 | UTF-8 | CRLF | RW | Mem 63%