Tabelle1

PitchBox Peripheral Diver Unit Connections

Valid for Driver Units PDU0401

To PitchBox Computer (Relay connector side)						
Pin#	DSUB15	Colour	Function	Description		
1	1 & 9	Blue & Purple	GND	Main Ground (0V)		
2	2 & 3	Red & Pink	UB	Main Power (+24V)		
3	4	Brown/Green	HL_C	Headlift Optocoupler Collector		
4	5	Yellow/Brown	HL_E	Headlift Optocoupler Emitter		
5	15	White/Green	LDIN	Leadin Diameter Switch		
6	8	Green	END	End Diameter Switch		
7	9	Black	V_GND	Vertical Ground		
8	10	White/Yellow	V_FB	Vertical Feedback		
9	11	White	V_DR	Vertical Drive		
10	13	Brown	T_GND	Servo Tacho Ground		
11	14	Red/Blue	T_IN	Servo Tacho Signal		
12	6 & 7	Grey & Yellow	MOTOR	Servo Motor Output		

To Cutting Lathe (12 & 4 pin conner Pin # Color 1 2 3 4 5 6 7 8 9 10 11	Function VERT+ VERT- LDIN END HS HEAT_GND DOWN HEAT- UH HL- UB	Head Down Switch Stylus Heating – Stylus Heating Power (+12V) Headlift Release Main Power (+24V)
12	GND	Main Ground (0V)
To Servo Motor Pin # 1 2 3 4	Function MOTOR GND TACHO T_GND	Description Servo Motor Drive Servo Motor Ground Servo Tacho Signal Servo Tacho Ground