

Introduction to ggplot

Federico Lopez

2015-10-23

Contents

1	Getting started with qplot	1
1.1	Using qplot to create scatterplots, histograms and boxplots	2
2	ggplot	13
2.1	Boxplots	14
2.2	Bargraphs	15
2.3	Line graphs and stacked area graphs	19
2.4	Histograms	26
3	More ggplot and an introduction to rOpenSci packages	30
4	ggplot and rgbif	32
4.1	Plot GBIF occurrences of a species	32
4.2	Plot GBIF occurrences of two or more species	34
4.3	Map environmental data	37
5	Other examples using morphological data for Darwin's finches	40

Install the necessary packages

```
install.packages("RCurl")
install.packages("ggplot2")
install.packages("ggpmap")
install.packages("maps")
install.packages("rdryad")
install.packages("rgbif")
install.packages("plyr")
install.packages("rWBclimate")
install.packages("cati")
```

1 Getting started with qplot

ggplot2 is a powerful plotting system for R. ggplot2 documentation is available at docs.ggplot2.org. qplot is the basic plotting function in the ggplot2 package. qplot is similar to the base R function plot; however, you cannot pass any type of R object to qplot.

Basic usage: `qplot(x, y, data...)`, where data is the data frame to use ... means other aesthetics passed for each layer.


1.1 Using qplot to create scatterplots, histograms and boxplots

1.1.1 Scatterplots


```
# Retrieve a published dataset
# Copy the file's raw GitHub URL
polistesdat.url <- "https://raw.githubusercontent.com/flopezo/atd/master/Tibbets_et_al_2015_data.csv"
polistesdat.url <- getURL(polistesdat.url)
polistes.data <- read.csv(textConnection(polistesdat.url))
# Show the variables included in the dataset
summary(polistes.data)
```

```
##      year      day.collected      weight      sfmf
## Min.   :2011    Min.   :-6.00    Min.   :0.05100    mf:106
## 1st Qu.:2011    1st Qu.: 1.00    1st Qu.:0.08400    sf:505
## Median :2011    Median :25.00    Median :0.09600
## Mean   :2011    Mean   :20.96    Mean   :0.09692
## 3rd Qu.:2012    3rd Qu.:31.00    3rd Qu.:0.10900
## Max.   :2012    Max.   :53.00    Max.   :0.15300
## nest.size      logface
## Min.   : 1.00    Min.   :0.0000
## 1st Qu.: 10.00    1st Qu.:0.3315
## Median : 19.00    Median :0.7270
## Mean   : 22.28    Mean   :0.6014
## 3rd Qu.: 27.00    3rd Qu.:0.8470
## Max.   :201.00    Max.   :1.0490
```


```
# Create a scatter diagram
qplot(logface, nest.size, data=polistes.data) + geom_point(size=4)
```



```
qplot(logface, nest.size, data=polistes.data, shape=sfmf) + geom_point(size=4)
```



```
# Add colors based on a categorical variable  
qplot(logface, nest.size, data=polistes.data, colour=sfmf) + geom_point(size=4)
```




In ggplot, geoms, short for geometric objects, describe the type of plot you will produce. For example, `geom_point` is used for scatterplots. `geom_point` is the default in `qplot` if `x` and `y` are specified. If only `x` is specified, `qplot` defaults to `geom_histogram`. In the scatter diagrams above, the `size` argument in `geom_point` controls the size of data points.


1.1.2 Fit a linear model

Add a smoothed line and fit linear models. `lm` is used to fit linear models and carry out regressions. A typical `lm` model has the form `response ~ terms` where `response` is the (numeric) response vector and `terms` specifies a linear predictor for response.

```
# Fit a linear model (by default includes 95% confidence region)
qplot(logface, nest.size, data=polistes.data, geom=c("point", "smooth"),
      method="lm") + geom_point(size=4)
```



```
# Create separate regressions for each factor and add labels
qplot(logface, nest.size, data=polistes.data, geom=c("point", "smooth"),
  method="lm", colour=sfml,
  main="Relationship between facial pattern brokenness and nest size",
  xlab="Facial Pattern Brokenness",
  ylab="Number of Nest Cells") + geom_point(size=4)
```



1.1.3 Boxplots and jittered points


```
# Load the ChickWeight dataset from the base R packages
# Results from an experiment on the effect of diet on early growth of chicks
cw <- ChickWeight
summary(cw)
```

```
##      weight      Time      Chick      Diet
## Min.   : 35.0   Min.   : 0.00   13      : 12   1:220
## 1st Qu.: 63.0   1st Qu.: 4.00    9       : 12   2:120
## Median :103.0   Median :10.00   20       : 12   3:120
## Mean   :121.8   Mean   :10.72   10       : 12   4:118
## 3rd Qu.:163.8   3rd Qu.:16.00   17       : 12
## Max.   :373.0   Max.   :21.00   19       : 12
##                                     (Other):506
```


```
tapply(cw$weight, cw$Diet, FUN=mean)
```

```
##      1      2      3      4
## 102.6455 122.6167 142.9500 135.2627
```


```
qplot(Diet, weight, data=cw, geom="boxplot", colour=Diet)
```




```
qplot(Diet, weight, data=cw, geom="jitter", colour=Diet)
```

```
# Use I() to manually set the aesthetics, e.g., colour = I("red") or size = I(3)
qplot(Time, weight, data=cw, geom="jitter", colour=Diet, size=I(3))
```




```
qplot(Diet, weight, data=cw, geom=c("boxplot","jitter"), colour=Diet)
```




1.1.4 Histograms and density plots

```
qplot(weight, data=cw, geom="histogram", fill=Diet)
```

```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```




```
qplot(weight, data=cw, geom="density", fill=Diet, alpha=I(0.5))
```



2 ggplot

qplot does not show the power of ggplot. ggplot2 functions can be chained with “+” signs. All the options that can be chained are available at docs.ggplot2.org. Let us remake the previous graphs using a few of the wide variety of options available in ggplot. ## Scatterplots


```
ggplot(polistes.data, aes(x=weight, y=nest.size, colour=nest.size)) +
  geom_point(size=5, alpha=.8) +
  # Add main and axis titles
  labs(title="Relationship between weight and nest size",
        x="Weight", y="Number of Cells") +
  # Add text to graph
  annotate("text", x=0.130, y=75, label="Group 1", size=10) +
  annotate("text", x=0.075, y=180, label="Group 2", size=10) +
  # Use a manually defined palette
  scale_colour_gradientn(colours=c("darkred", "orange", "yellow", "white"))
```



2.1 Boxplots


```
# The redundant legend can be removed with '+ guides(fill=FALSE)'
ggplot(cw, aes(x=Diet, y=weight, colour=Diet)) + geom_boxplot() +
  stat_summary(fun.y="mean", geom="point", shape=5, size=4) +
  labs(title="Relationship between diet and weight",
       x="Diet", y="Weight") +
  theme(plot.title=element_text(size=rel(2))) + # Title twice the base font size
  theme(axis.title.x=element_text(size=rel(1.5))) +
  theme(axis.title.y=element_text(size=rel(1.5))) +
  scale_fill_brewer(palette="Pastel1")
```

Relationship between diet and weight




2.2 Bargraphs

```
# Use stat="identity" if you want the heights of the bars to represent  
# values in the data  
ggplot(cw, aes(x=Diet, y=weight, fill=Diet)) +  
  geom_bar(stat="identity", width=0.6) +  
  scale_fill_grey()
```




```
ggplot(cw, aes(x=Diet, y=weight, fill=Diet)) +  
  geom_bar(stat="identity", width=0.6) +  
  scale_fill_brewer(palette="Blues")
```


```
# Add error bars
# Split data frame, apply function, and return results in a data frame
library(plyr)
cwse <- ddply(cw, "Diet", summarise,
  weightm=mean(weight, na.rm=TRUE),
  sd=sd(weight, na.rm=TRUE),
  n=sum(!is.na(weight)),
  se=sd/sqrt(n))
cwse
```

```
##   Diet weightm      sd    n      se
## 1    1 102.6455 56.65655 220 3.819784
## 2    2 122.6167 71.60749 120 6.536840
## 3    3 142.9500 86.54176 120 7.900146
## 4    4 135.2627 68.82871 118 6.336197
```

```
cwse$Diet <- as.factor(cwse$Diet)
ggplot(cwse, aes(x=Diet, y=weightm, fill=Diet)) +
  geom_bar(stat="identity") +
  geom_errorbar(aes(ymin=weightm-se, ymax=weightm+se), width=.2) +
  scale_fill_brewer(palette="Set3")
```




```
# Stacked bar graph  
ggplot(cw, aes(x=Time, y=weight, fill=Diet)) +  
  geom_bar(stat="identity")
```



2.3 Line graphs and stacked area graphs

```
# If your line graph looks wrong, specify the grouping variable with group.
# Problems occur with line graphs because ggplot() is unable to determine
# how to group the variables
# A sawtooth pattern results from improper grouping
ggplot(cw, aes(x=Time, y=weight, group=Chick, colour=Diet)) +
  geom_point(size=3) + geom_line(size=1)
```



```
cwd12 <- subset(cw, Diet==1:2)
cwd12
```

```
## Grouped Data: weight ~ Time | Chick
##      weight Time Chick Diet
## 1      42    0     1     1
## 3      59    4     1     1
## 5      76    8     1     1
## 7     106   12     1     1
## 9     149   16     1     1
## 11     199  20     1     1
## 13      40    0     2     1
## 15      58    4     2     1
## 17      84    8     2     1
## 19     122   12     2     1
## 21     162   16     2     1
## 23     209   20     2     1
## 25      43    0     3     1
## 27      55    4     3     1
## 29      84    8     3     1
## 31     115   12     3     1
## 33     163   16     3     1
## 35     198   20     3     1
## 37      42    0     4     1
## 39      56    4     4     1
## 41      74    8     4     1
```

## 43	102	12	4	1
## 45	136	16	4	1
## 47	160	20	4	1
## 49	41	0	5	1
## 51	48	4	5	1
## 53	79	8	5	1
## 55	141	12	5	1
## 57	197	16	5	1
## 59	220	20	5	1
## 61	41	0	6	1
## 63	59	4	6	1
## 65	97	8	6	1
## 67	141	12	6	1
## 69	155	16	6	1
## 71	160	20	6	1
## 73	41	0	7	1
## 75	57	4	7	1
## 77	89	8	7	1
## 79	146	12	7	1
## 81	218	16	7	1
## 83	288	20	7	1
## 85	42	0	8	1
## 87	61	4	8	1
## 89	84	8	8	1
## 91	110	12	8	1
## 93	126	16	8	1
## 95	125	20	8	1
## 97	51	2	9	1
## 99	68	6	9	1
## 101	96	10	9	1
## 103	92	14	9	1
## 105	100	18	9	1
## 107	98	21	9	1
## 109	44	2	10	1
## 111	63	6	10	1
## 113	81	10	10	1
## 115	96	14	10	1
## 117	112	18	10	1
## 119	124	21	10	1
## 121	51	2	11	1
## 123	84	6	11	1
## 125	139	10	11	1
## 127	177	14	11	1
## 129	184	18	11	1
## 131	175	21	11	1
## 133	49	2	12	1
## 135	62	6	12	1
## 137	88	10	12	1
## 139	135	14	12	1
## 141	185	18	12	1
## 143	205	21	12	1
## 145	48	2	13	1
## 147	60	6	13	1
## 149	67	10	13	1

## 151	70	14	13	1
## 153	81	18	13	1
## 155	96	21	13	1
## 157	49	2	14	1
## 159	79	6	14	1
## 161	128	10	14	1
## 163	192	14	14	1
## 165	248	18	14	1
## 167	266	21	14	1
## 169	49	2	15	1
## 171	64	6	15	1
## 173	68	10	15	1
## 175	68	14	15	1
## 177	45	2	16	1
## 179	51	6	16	1
## 181	51	10	16	1
## 183	42	0	17	1
## 185	61	4	17	1
## 187	83	8	17	1
## 189	98	12	17	1
## 191	113	16	17	1
## 193	133	20	17	1
## 195	39	0	18	1
## 197	43	0	19	1
## 199	55	4	19	1
## 201	65	8	19	1
## 203	82	12	19	1
## 205	106	16	19	1
## 207	144	20	19	1
## 209	41	0	20	1
## 211	54	4	20	1
## 213	65	8	20	1
## 215	77	12	20	1
## 217	98	16	20	1
## 219	115	20	20	1
## 222	50	2	21	2
## 224	86	6	21	2
## 226	163	10	21	2
## 228	240	14	21	2
## 230	307	18	21	2
## 232	331	21	21	2
## 234	55	2	22	2
## 236	77	6	22	2
## 238	95	10	22	2
## 240	111	14	22	2
## 242	148	18	22	2
## 244	167	21	22	2
## 246	52	2	23	2
## 248	73	6	23	2
## 250	103	10	23	2
## 252	135	14	23	2
## 254	163	18	23	2
## 256	175	21	23	2
## 258	52	2	24	2


```
## 260      74      6      24      2
## 262      68     10      24      2
## 264      71     14      24      2
## 266      72     18      24      2
## 268      74     21      24      2
## 270      49      2      25      2
## 272      78      6      25      2
## 274     124     10      25      2
## 276     164     14      25      2
## 278     231     18      25      2
## 280     265     21      25      2
## 282      48      2      26      2
## 284      74      6      26      2
## 286     114     10      26      2
## 288     147     14      26      2
## 290     205     18      26      2
## 292     251     21      26      2
## 294      46      2      27      2
## 296      73      6      27      2
## 298     100     10      27      2
## 300     123     14      27      2
## 302     163     18      27      2
## 304     192     21      27      2
## 306      46      2      28      2
## 308      73      6      28      2
## 310     114     10      28      2
## 312     156     14      28      2
## 314     207     18      28      2
## 316     233     21      28      2
## 318      48      2      29      2
## 320      74      6      29      2
## 322     106     10      29      2
## 324     150     14      29      2
## 326     230     18      29      2
## 328     309     21      29      2
## 330      48      2      30      2
## 332      72      6      30      2
## 334      98     10      30      2
## 336     122     14      30      2
## 338     151     18      30      2
## 340     150     21      30      2
```

```
cwse12 <- ddpoly(cwd12, c("Diet", "Time"), summarise,
  weightm=mean(weight, na.rm=TRUE),
  sd=sd(weight, na.rm=TRUE),
  n=sum(!is.na(weight)),
  se=sd/sqrt(n))
cwse12
```

```
##      Diet Time  weightm      sd  n      se
## 1      1    0  41.41667  1.164500 12 0.3361622
## 2      1    2  48.25000  2.549510  8 0.9013878
## 3      1    4  56.63636  3.722169 11 1.1222763
## 4      1    6  66.37500 10.595653  8 3.7461290
```

```
## 5      1      8 80.00000  9.643651 11  2.9076701
## 6      1     10 89.75000 30.471298  8 10.7732307
## 7      1     12 112.72727 23.242594 11  7.0079058
## 8      1     14 118.57143 50.345000  7 19.0286215
## 9      1     16 147.54545 37.264899 11 11.2357899
## 10     1     18 151.66667 64.301374  6 26.2509259
## 11     1     20 177.36364 51.252849 11 15.4533155
## 12     1     21 160.66667 67.408209  6 27.5192862
## 13     2      2 49.40000  2.875181 10  0.9092121
## 14     2      6 75.40000  4.168666 10  1.3182480
## 15     2     10 108.50000 24.295633 10  7.6829537
## 16     2     14 141.90000 43.697063 10 13.8182247
## 17     2     18 187.70000 63.331667 10 20.0272315
## 18     2     21 214.70000 78.138126 10 24.7094449
```


```
ggplot(cwse12, aes(x=Time, y=weightm, colour=Diet)) +
  geom_errorbar(aes(ymin=weightm-se, ymax=weightm+se), width=.4, size=0.8) +
  geom_line(size=1.5) +
  geom_point(size=3)
```




```
# Stacked area graph
# Area graphs represent cumulated totals over time
#tapply(cw$weight, cw$Diet, FUN=sum)
#cwd4 <- subset(cw, Diet==4)
#tapply(cwd4$weight, cwd4$Time, FUN=sum)
```



```
ggplot(cw, aes(x=Time, y=weight, group=Chick, fill=Diet)) +  
  geom_area(alpha=0.8)
```




```
ggplot(cw, aes(x=Time, y=weight, group=Chick, fill=Diet)) +  
  geom_area(colour="black", size=.2, alpha=.8) +  
  scale_fill_brewer(palette="Blues")
```



2.4 Histograms


```
ggplot(polistes.data, aes(x=weight, fill=sfmf)) + geom_histogram(alpha=.8)
```

stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.



```
ggplot(cw, aes(x=weight, fill=Diet)) + geom_histogram(alpha=.6)
```

```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```




```
# Find the mean of each group
library(plyr)
# For each subset of a data frame, ddply applies a function and then combines
# results into a data frame
mwt <- ddply(cw, "Diet", summarise, weight.mean=mean(weight))
mwt
```

```
##   Diet weight.mean
## 1    1    102.6455
## 2    2    122.6167
## 3    3    142.9500
## 4    4    135.2627
```


```
# Overlaid histograms with means
ggplot(cw, aes(x=weight, fill=Diet)) + geom_histogram(alpha=.5) +
  geom_vline(data=mwt, aes(xintercept=weight.mean, colour=Diet),
    linetype="dashed", size=1)
```

```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```



```
# Use facets to display subsets of the dataset in different panels
ggplot(cw, aes(x=weight, fill=Diet)) + geom_histogram(alpha=.5) +
  facet_grid(. ~ Diet)
```


```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```




3 More ggplot and an introduction to rOpenSci packages

rOpenSci is an initiative to create R packages for accessing data repositories. The full list of packages is available [here](#)

```
# Here we will use the 'rdryad' package to retrieve a dataset from Dryad
# Retrieve the data using the Dryad identifier '10255/dryad.34389'
# which is at the end of the URL where the dataset is found
# http://datadryad.org/handle/10255/dryad.34389
# the original publication is Kolbe et al. 2011, Evolution 65(12): 3608-3624
anolis.data <- download_url("10255/dryad.34389")
anolis.data <- dryad_getfile(anolis.data)
# create plot with discrete and continuous variables
anolis.scatter <- ggplot(anolis.data, aes(x=Ecomorph, y=Snout.vent.length,
  colour=Snout.vent.length)) + geom_point(size=4)
anolis.scatter
```



```
# create plot with continuous variables
anolis.scatter <- ggplot(anolis.data, aes(x=Head.length, y=Snout.vent.length,
  colour=Ecomorph)) + geom_point(size=4)
anolis.scatter
```



4 ggplot and rgbif

4.1 Plot GBIF occurrences of a species

```
# search for occurrences on GBIF
?occ_search
apicea.occ <- occ_search(scientificName="Aphaenogaster picea", limit=1000,
  return='data', hasCoordinate=TRUE)
# this dataset includes more than 100 columns
# show first 10 lines for columns 1 to 4
head(apicea.occ, n=10L)[,1:4]
```

##	name	key	decimalLatitude	decimalLongitude
## 1	Aphaenogaster picea	899067422	41.98968	-71.78827
## 2	Aphaenogaster picea	899067424	41.98968	-71.78827
## 3	Aphaenogaster picea	899067434	41.98968	-71.78827
## 4	Aphaenogaster picea	910640573	41.63587	-71.55863
## 5	Aphaenogaster picea	910640541	41.63587	-71.55863
## 6	Aphaenogaster picea	910640582	41.63587	-71.55863
## 7	Aphaenogaster picea	910640546	41.63587	-71.55863
## 8	Aphaenogaster picea	910640559	41.63587	-71.55863
## 9	Aphaenogaster picea	891147998	36.89260	-82.62960
## 10	Aphaenogaster picea	1142484688	34.76128	-84.70864


```
# select four columns from the complete data set
apicea.lat.lon <- apicea.occ[,c("name", "decimalLatitude", "decimalLongitude",
  "countryCode")]
# show the unique country codes in the data set
unique(apicea.lat.lon$countryCode)
```

```
## [1] "US" "MX"
```

```
# select only US occurrences
apicea.lat.lon <- subset(apicea.lat.lon, countryCode=="US")
summary(apicea.lat.lon)
```

```
##      name      decimalLatitude decimalLongitude countryCode
## Length:300    Min.   :33.49    Min.   :-94.25    Length:300
## Class :character 1st Qu.:38.23    1st Qu.: -88.51    Class :character
## Mode  :character Median :40.11    Median : -83.89    Mode  :character
##                Mean   :39.79    Mean   : -83.52
##                3rd Qu.:41.50    3rd Qu.: -79.32
##                Max.   :45.57    Max.   : -70.04
```


```
# get map data for world
#world_map <- map_data("world")

# show unique regions
#sort(unique(world_map$region))

# get map data for USA
states.map <- map_data("state")
head(states.map)
```

```
##      long      lat group order  region subregion
## 1 -87.46201 30.38968     1     1 alabama    <NA>
## 2 -87.48493 30.37249     1     2 alabama    <NA>
## 3 -87.52503 30.37249     1     3 alabama    <NA>
## 4 -87.53076 30.33239     1     4 alabama    <NA>
## 5 -87.57087 30.32665     1     5 alabama    <NA>
## 6 -87.58806 30.32665     1     6 alabama    <NA>
```

```
#states.map <- subset(states.map, long > -100 & lat < 50)
states.map <- ggplot(states.map, aes(x=long, y=lat, group=group)) +
  geom_polygon(fill="white", colour="black") + coord_map("mercator")
#states.map
states.map +
  geom_point(aes(x=decimalLongitude, y=decimalLatitude, group=name),
    colour="orange", size=4, data=apicea.lat.lon)
```



```
#gbifmap(apicea.lat.lon)
```

4.2 Plot GBIF occurrences of two or more species

```
splist <- c("Bombus fraternus", "Bombus perplexus")
# apply a function over a list or vector with sapply
bombus.keys <- sapply(splist, function(x) name_backbone(name=x)$speciesKey,
  USE.NAMES=FALSE)
bombus.occ <- occ_search(taxonKey=bombus.keys, limit=500, return="data",
  hasCoordinate=TRUE)
summary(bombus.occ)
```

```
##           Length Class      Mode
## 1340432 107      data.frame list
## 1340406 122      data.frame list
```

```
head(bombus.occ$`1340432`, n=10L)[,1:4]
```

```
##           name           key decimalLatitude decimalLongitude
## 1 Bombus fraternus 1098920735      33.72666      -95.68521
## 2 Bombus fraternus 1143521876      33.53094      -95.91432
## 3 Bombus fraternus  899954560      32.87881      -93.81990
```

```
## 4 Bombus fraternus 923923296      33.51451      -95.91873
## 5 Bombus fraternus 923923624      33.48436      -95.99989
## 6 Bombus fraternus 923923680      33.48885      -95.97723
## 7 Bombus fraternus 1065596357     33.69256      -96.76983
## 8 Bombus fraternus 1143569911     33.48602      -95.95263
## 9 Bombus fraternus 1024185501     33.55605      -95.92782
## 10 Bombus fraternus 1024191102     32.71433      -97.46752
```


```
bfraternus.lat.lon <- bombus.occ$`1340432`[,c("name", "decimalLatitude",
  "decimalLongitude", "countryCode")]
head(bombus.occ$`1340406`, n=10L)[,1:4]
```

```
##           name           key decimalLatitude decimalLongitude
## 1 Bombus perplexus 1143520430      46.64574      -60.95197
## 2 Bombus perplexus 1143520142      44.23823      -68.54755
## 3 Bombus perplexus 1143521611      43.70909      -73.03349
## 4 Bombus perplexus 1143532609      44.35068      -72.51181
## 5 Bombus perplexus 1122964996      44.69461      -73.34100
## 6 Bombus perplexus 1135213313      44.73630      -73.33179
## 7 Bombus perplexus 1143530758      44.69111      -73.34442
## 8 Bombus perplexus 1135350545      45.65765      -65.01472
## 9 Bombus perplexus 1143522783      46.71553      -60.39149
## 10 Bombus perplexus 1136227380      39.34410      -77.75340
```

```
bperplexus.lat.lon <- bombus.occ$`1340406`[,c("name", "decimalLatitude",
  "decimalLongitude", "countryCode")]
bperplexus.lat.lon <- subset(bperplexus.lat.lon, decimalLatitude < 50)
bombus.lat.lon <- rbind(bfraternus.lat.lon, bperplexus.lat.lon)
bombus.lat.lon <- subset(bombus.lat.lon, countryCode=="US")
states.map <- map_data("state")
#states.map <- subset(states.map, long > -120 & lat < 50)
states.map <- ggplot(states.map, aes(x=long, y=lat, group=group)) +
  geom_polygon(fill="white", colour="black") + coord_map("mercator")
#states.map

# create a title for ggplot that italicizes only the genus name
bombus.occ.title <- expression(paste(italic("Bombus"), " occurrences"))
bombus.map.occ <- geom_point(aes(x=decimalLongitude, y=decimalLatitude,
  group=name, colour=name, shape=name), size=4, data=bombus.lat.lon)
bombus.map.labels <- labs(title=bombus.occ.title, x="Longitude", y="Latitude",
  colour="Species", shape="Species")
bombus.map.legend <- theme(plot.title=element_text(face="italic",
  size=rel(1.8))) +
  theme(legend.title=element_text(size=rel(1.5))) +
  theme(legend.text=element_text(face="italic", size=rel(1.2))) +
  theme(axis.title.x=element_text(size=rel(1.2))) +
  theme(axis.title.y=element_text(size=rel(1.2)))

states.map + bombus.map.occ + bombus.map.labels + bombus.map.legend
```



```
bombus.map.den <- stat_density2d(aes(x=decimalLongitude, y=decimalLatitude,
  group=name, colour=name), size=1, data=bombus.lat.lon, geom="density2d")
bombus.den.title <- expression(paste(italic("Bombus"), " distribution"))
bombus.maplabels <- labs(title=bombus.den.title, x="Longitude", y="Latitude",
  colour="Species", shape="Species")
states.map + bombus.map.den + bombus.maplabels + bombus.maplegend
```



===	5%
=====	8%
=====	11%
=====	13%
=====	16%
=====	18%
=====	21%
=====	24%
=====	26%
=====	29%
=====	32%
=====	34%
=====	37%
=====	39%
=====	42%
=====	45%
=====	47%
=====	50%
=====	53%
=====	55%
=====	58%
=====	61%
=====	63%
=====	66%
=====	68%
=====	71%
=====	74%

=====	76%
=====	79%
=====	82%
=====	84%
=====	87%
=====	89%
=====	92%
=====	95%
=====	97%
=====	100%

```

# Retrieve historical precipitation data
temp.dat <- get_historical_temp(nam, "decade")
# Create a subset using only data from one year
temp.dat <- subset(temp.dat, temp.dat$year==2000)
# Create maps of climate data
nam.map <- climate_map(nam.basin, temp.dat, return_map=TRUE)
nam.map

```



5 Other examples using morphological data for Darwin's finches

```
data(finch.ind)
tr <- traits.finch; sp <- sp.finch; dist <- ind.plot.finch
tr$sp <- sp; tr$dist <- dist
head(tr)
```


```
##      WingL BeakH UBeakL N.UBkL      sp dist
## 165    69  10.8  15.2   10.6 Geospiza_fortis DMaj
## 166    65  10.3  14.2    9.8 Geospiza_fortis DMaj
## 167    65  10.0  13.6    9.9 Geospiza_fortis DMaj
## 168    68   9.5  13.5    9.9 Geospiza_fortis DMaj
## 169    66  11.0  15.0   10.7 Geospiza_fortis DMaj
## 170    68  10.4  15.0   10.2 Geospiza_fortis DMaj
```

```
ggplot(tr, aes(x=BeakH, y=UBeakL, colour=dist)) +
  geom_point(size=4, alpha=0.4) +
  stat_smooth(method=lm, colour="black", level=0.95) +
  scale_colour_brewer(palette="Set3")
```

```
## Warning: Removed 924 rows containing missing values (stat_smooth).
```



```
## Warning: Removed 924 rows containing missing values (geom_point).
```



```
mbh <- ddpby(tr, "dist", summarise, bh.mean=mean(BeakH, na.rm=TRUE))
mbh
```

```
##      dist  bh.mean
## 1   DMaj 10.286047
## 2   EspHd 11.711345
## 3 FlorChrl 9.715032
## 4 GnovTwr 10.447945
## 5 MrchBndl 11.663877
## 6 SCruInde 9.890248
```

```
ggplot(tr, aes(x=BeakH, fill=dist)) + geom_density(alpha=0.4) +
  scale_fill_brewer(palette="Set1") +
  geom_vline(data=mbh, aes(xintercept=bh.mean, colour=dist),
    linetype="dashed", size=1)
```

```
## Warning: Removed 7 rows containing non-finite values (stat_density).
```

```
## Warning: Removed 29 rows containing non-finite values (stat_density).
```

```
## Warning: Removed 196 rows containing non-finite values (stat_density).
```

Warning: Removed 39 rows containing non-finite values (stat_density).

Warning: Removed 43 rows containing non-finite values (stat_density).

Warning: Removed 82 rows containing non-finite values (stat_density).

