

Floxis Adapter Integration Guide

(Prebid Version v8.52.2–v10.29.1)

Integration of the current Floxis bid adapter into older Prebid.js wrappers, without upgrading the wrapper's Prebid version. Each listed Prebid version was verified end-to-end: bundle build, adapter present in the bundle, and the full adapter test suite passing with 0 failures.

Key Requirement: The adapter alone is not enough. The *libraries/floxisUtils/* folder is mandatory for functionality.

1. Required Files & Setup

- **Adapter Source:** Copy the following files into the same paths of your Prebid.js repository:
 - modules/floxisBidAdapter.js
 - modules/floxisBidAdapter.md
 - test/spec/modules/floxisBidAdapter_spec.js
- **Dependencies:** You must include the entire *libraries/floxisUtils/* folder. It contains a utility the adapter requires (event beaconing) that newer Prebid cores ship natively but older cores do not.
- **Installer:** alternatively run `./install.sh /path/to/your/Prebid.js` from the kit folder — it copies all four files for you.

Download: github.com/floxis-admin/Prebid.js — branch `floxis-adapter-backport`, folder `floxis-backport-kit/`

2. Building the Project

After moving the files into your Prebid repository, execute:

```
# Install dependencies
npm ci

# Build with the floxis module included (append your existing module list, comma-separated)
node_modules/.bin/gulp build --modules=floxisBidAdapter
```

- Use `node_modules/.bin/gulp` (the repo-local gulp). On older Prebid tags a bare `npx gulp` can resolve to a newer global gulp and fail with `Local modules not found`.
- macOS Apple Silicon, Prebid 10.x only: run `PUPPETEER_SKIP_DOWNLOAD=true npm ci`.

3. Ad Unit Implementation

Configure your ad units with the parameters required by the floxis bidder:

```
pbjs.addAdUnits([{\n  code: 'ad',\n  mediaTypes: {\n    banner: {\n      sizes: [[300, 250]]\n    }\n  },\n  bids: [{\n    bidder: 'floxis',\n    params: {\n      seat: 'SEAT',          // required – your Floxis seat ID\n      region: 'us-e',       // optional – defaults to us-e\n      bidFloor: 0.01        // optional bid floor\n    }\n  }]\n}]);
```

seat is the only required parameter. Banner, video (instream) and native are supported. GDPR/TCF, US Privacy, GPP and COPPA signals are handled by Prebid.js core and forwarded automatically.

4. Verified Prebid Versions

Prebid.js	Build	Adapter test suite	User sync / billing / telemetry
8.52.2	OK	98 passed, 0 failed	fully supported by core
9.27.0	OK	98 passed, 0 failed	fully supported by core
9.53.0	OK	0 failed	fully supported by core
10.6.0	OK	98 passed, 0 failed	fully supported by core
10.29.1	OK	98 passed, 0 failed	fully supported by core

Versions between these tags are expected to work as well — confirm yours in minutes by running the adapter test suite (section 5). Prebid.js 11+ does not need this kit: the Floxis adapter ships natively in current Prebid.js (`--modules=floxisBidAdapter`).

GDPR note: the adapter declares IAB Europe TCF Vendor ID **1609** (Floxis). Vendor 1609 is published in the Global Vendor List as of **June 11, 2026**. EU/GDPR traffic flows once publishers' CMPs have refreshed to a vendor-list version containing 1609 — schedule EU go-live from June 12 onward. Non-GDPR traffic is unaffected.

5. Verification & Troubleshooting

- **Enable Debugging:** Use `pbjs.setConfig({debug: true})` to monitor internal logs.
- **Module Check:** Verify the module is loaded via `pbjs.installedModules` (look for `floxisBidAdapter`).
- **Traffic Check:** Monitor network requests for POST `https://<region>.floxis.tech/pbjs?seat=...` and check bid responses using `pbjs.getBidResponses()`.
- **Common Errors:** If no requests are fired, check for the missing `libraries/floxisUtils/` folder. If errors occur during execution, ensure all files were copied to the exact paths listed in section 1.
- **Running validation tests** (needs Chrome; set `CHROME_BIN` if the launcher cannot find it):

```
node_modules/.bin/gulp test --nolint --file
test/spec/modules/floxisBidAdapter_spec.js
```

Support / maintainer: prebid@floxis.tech