```
--01 Retrieve all columns from the employees table.
SELECT *
FROM workspace.default.q_1_all_columns;
```

Add parameter

Table ⌄ +

	123 id	Ac first_name	Ac last_name	Ac department	123 salary	Ac hire_date	Ac city
1	1	Alice	Green	IT	70000	2020-01-10	Johannesburg
2	2	Brian	Lee	HR	45000	2019-03-22	Cape Town
3	3	Cathy	Zulu	Finance	65000	2018-07-18	Durban
4	4	David	Mokoena	Marketing	50000	2021-11-05	Pretoria
5	5	Eva	Naidoo	IT	72000	2017-09-30	Johannesburg

```
--02 Find all unique departments
SELECT DISTINCT department
FROM workspace.default.q_1_all_columns;
```

Add parameter

Table ⌄ +

	Ac department
1	IT
2	HR
3	Finance
4	Marketing

```
--03 Retrieve first and last names ordered by salary descending.
SELECT first_name, last_name
FROM workspace.default.q_1_all_columns
ORDER BY salary DESC;
```

Add parameter

Table ⌄ +

	Ac first_name	Ac last_name
1	Eva	Naidoo
2	Alice	Green
3	Cathy	Zulu
4	David	Mokoena
5	Brian	Lee

```
--04 Retrieve the top 3 highest-paid employees
SELECT id, first_name, last_name, salary
FROM workspace.default.q_1_all_columns
WHERE salary > 60000;
```

Table ⌄ +

id	first_name	last_name	salary
1	Alice	Green	70000
3	Cathy	Zulu	65000
5	Eva	Naidoo	72000

```
--05 Find employees in the IT department.
SELECT id, first_name, last_name, department
FROM workspace.default.q_1_all_columns
WHERE department = 'IT';
```

Table ⌄ +

id	first_name	last_name	department
1	Alice	Green	IT
5	Eva	Naidoo	IT

```
--06 Find employees in Finance with salary > 60000
SELECT id, first_name, last_name, department, salary
FROM workspace.default.q_1_all_columns
WHERE department = 'Finance';
```

Table ⌄ +

id	first_name	last_name	department	salary
3	Cathy	Zulu	Finance	65000

```
--07 Find employees in HR or Marketing.
SELECT id, first_name, last_name, department
FROM workspace.default.q_1_all_columns
WHERE department = 'HR' OR department = 'Marketing';
```

Table ⌄ +

id	first_name	last_name	department
2	Brian	Lee	HR
4	David	Mokoena	Marketing

```
-- 08 Find employees not in IT.
----- EXPECTED COLUMNS: id, first_name, last_name, department.
SELECT id, first_name, last_name, department
FROM `workspace`.`sql_output`.`q_1_all_columns`
WHERE department <> 'IT';
```

id	first_name	last_name	department
2	Brian	Lee	HR
3	Cathy	Zulu	Finance
4	David	Mokoena	Marketing

```
-- 09 Find employees in IT with salary > 65000 and city Johannesburg.
SELECT id, first_name, last_name, department, salary, city
FROM `workspace`.`sql_output`.`q_1_all_columns`
WHERE department IN ('IT')
AND salary > 65000
AND city = 'Johannesburg';
```

id	first_name	last_name	department	salary	city
1	Alice	Green	IT	70000	Johannesburg
5	Eva	Naidoo	IT	72000	Johannesburg

```
-- 10 Find employees in IT with salary > 65000 and city Johannesburg.
SELECT id, first_name, last_name, department, salary, city
FROM `workspace`.`sql_output`.`q_1_all_columns`
WHERE department IN ('IT')
AND salary > 65000
AND city = 'Johannesburg';
```

id	first_name	last_name	department	salary	city
1	Alice	Green	IT	70000	Johannesburg
5	Eva	Naidoo	IT	72000	Johannesburg