Rest Assured Cheat Sheet

Rest Assured Commands Cheat Sheet

```
# Setup & Imports
import io.restassured.RestAssured;                # Import RestAssured
import io.restassured.response.Response;          # Import Response class
import static io.restassured.RestAssured.*;       # Static import for fluent syntax
import static org.hamcrest.Matchers.*;            # For assertions

# Base Configuration
RestAssured.baseURI = "<base-url>";               # Set base URI
RestAssured.basePath = "<path>";                  # Set base path
RestAssured.port = <port-number>;                 # Set port (if needed)

# Basic HTTP Methods
given().get("<endpoint>");                         # GET request
given().post("<endpoint>");                        # POST request
given().put("<endpoint>");                         # PUT request
given().delete("<endpoint>");                      # DELETE request

# Sending Request with Body
given()
  .header("Content-Type", "application/json")
  .body("{ \"key\": \"value\" }")
  .post("<endpoint>");                             # POST with body

# Validations & Assertions
.then().statusCode(200);                           # Assert status code
.then().body("key", equalTo("value"));             # Assert response field

# Extracting Values
Response res = given().get("<endpoint>");          # Store response
String value = res.jsonPath().getString("key");    # Extract field from response

# Query Parameters & Headers
given()
  .queryParam("param", "value")                    # Add query parameter
  .header("key", "value")                          # Add header
  .get("<endpoint>");
```

Rest Assured Commands Cheat Sheet

```
# Path Parameters
given()
  .pathParam("id", 1)
  .get("/users/{id}");                          # Use path param

# Authentication
given()
  .auth().basic("user", "pass")                 # Basic auth
  .get("<endpoint>");

given()
  .auth().oauth2("token")                       # Bearer token
  .get("<endpoint>");

# Logging
given()
  .log().all()                                  # Log request
  .get("<endpoint>");

.then()
  .log().body();                                # Log response body

# Serialization / Deserialization
.post().as(MyClass.class);                      # Deserialize to class
```

BHAVIN THUMAR