

ITI 1120

Lab # 6

while loops, lists ...

Starting Lab 6

- Open a browser and log into Blackboard Learn
- On the left hand side under Labs tab, find lab6 material contained in [lab6-students.zip](#) file
- Download that file to the Desktop and unzip it.

Before starting, always make sure you are running Python 3

This slide is applicable to all labs, exercises, assignments ... etc

ALWAYS MAKE SURE FIRST that you are running **Python 3.4** (3.5 is fine too)

That is, when you click on IDLE (or start python any other way) look at the first line that the Python shell displays. It should say Python 3.4 or 3.5 (and then some extra digits)

If you do not know how to do this, read the material provided with Lab 1. It explains it step by step

Do all the exercises labeled as
Task in your head i.e. on a
paper

Later on if you wish, you can type them
into a computer (or copy/paste from the
solutions once I poste them)

Task 1

Go to the page below in your interactive textbook

- read through
- click Forward until reaching the end on the Python Visualizing example (to understand it)
- and answer the two questions and the end:

<http://interactivepython.org/runestone/static/thinkcspy/MoreAboutIteration/ThewhileStatement.html>

Study of **while** vs **for** ... in some elementary functions:

Problem: sum of positive odd integers smaller than **n**

A solution with for loop

```
def sum_odd_for(n):
    odd_sum = 0
    for num in range(n):
        if num % 2 == 1:
            odd_sum = odd_sum + num
    return odd_sum
```

A solution with a while loop

```
def sum_odd_while(n):
    odd_sum = 0
    i=1
    while i < n:
        if i % 2 == 1:
            odd_sum = odd_sum + i
        i=i+1
    return odd_sum
```

Problem: Sum of odd numbers in a given list **a**

A solution with for loop

```
def sum_list_for(a):
    ''' (list)->num '''
    list_sum = 0
    for i in range(len(a)):
        if a[i] % 2 == 1:
            list_sum = list_sum + a[i]
    return list_sum
```

A solution with a while loop

```
def sum_list_while(a):
    ''' (list)->num '''
    list_sum = 0
    i=0
    while i < len(a):
        if a[i] % 2 == 1:
            list_sum = list_sum + a[i]
        i=i+1
    return list_sum
```

Study of **while** vs **for** ... in another important elementary functions:

Problem:

find a minimum element in a list (of length at least 1)

Two solutions with for loop
(over elements and over indices)

```
def minimum_for_v1(a):  
    ''' (list)->num '''  
    minimum = a[0]  
    for element in a:  
        if element < minimum:  
            minimum = element  
  
    return minimum
```

```
def minimum_for_v2(a):  
    ''' (list)->num '''  
    minimum = a[0]  
    for i in range(len(a)):  
        if a[i] < minimum:  
            minimum = a[i]  
  
    return minimum
```

A solution with a while loop

```
def minimum_while(a):  
    ''' (list)->num'''  
    minimum = a[0]  
    i=0  
    while i < len(a):  
        if a[i] < minimum:  
            minimum = a[i]  
            i=i+1  
    return minimum
```

Task 2 and Programming Exercise 1

After studying the previous four functions

1. Open the file called `seven_functions.py` Copy/paste, one by one, the three solutions labeled with “# with while loop” into Python visualizer. Run through each example and understand how the solutions work and how the variables change in the loops. Play by changing what variable `i` is initialized to and how it is incremented (do for example `i=i+3`) and see what happens. As always, you can find python visualizer here (make sure you choose Python 3)

<http://www.pythontutor.com/visualize.html#mode=edit>

- 2. Programming exercise 1:** Open file called `prog-ex-1.py` Complete there the function `sum_odd_while_v2` that takes an integer `n` as input and computes the sum of all odd integers between 5 and `n`. Use **WHILE LOOP only** and **NO IF STATEMENT**.

```
>>> sum_odd_while_v2(10)
21
>>> sum_odd_while_v2(-7)
0
```


Programming Exercise 2

(Here is a problem that in Python CANNOT be solved with FOR LOOP)

Write a program that

- asks the user for two integers (one by one or at the same time if you know how to handle it). Then it adds them and displays the sum.

Then the user is asked to enter 'yes' if she wishes to perform the operation again, and otherwise if she enters anything other than 'yes' the program terminates. The operation (the bullet above) is repeated, as long as the user enters 'yes'.

Task 3

Question 1. What does the program below print if the input user entered was:

1 5 -3 0

Question 2. Can you tell what the program does? Write one sentence explaining it in plane English.

```
number=int(input("Enter an integer: "))
apple=number

while(number!=0):
    number=int(input("Enter an integer: "))
    if(number > apple):
        apple=number
print("apple is", apple)
```

Task 4

Question 1. How many times does the code on the right print `aha`?

```
x = 10
y = 100 % 90
i = 0
while i < 10000:
    if(x!=y):
        print("aha")
    i=i+1
```

Task 5

Question 1. What does the code on the write print?

ps. sometimes I say code, sometimes I say program. I mean the same thing.

```
def is_apple(x):  
    if x%4 == 0:  
        appleFlag = True  
    else:  
        appleFlag = False  
    appleFlag = appleFlag and is_pear(-200)  
    return appleFlag
```

```
def is_pear(x):  
    if (x < -101):  
        pearFlag = True  
    else:  
        pearFlag = False  
    return pearFlag
```

```
flag1 = is_apple(44)  
flag2 = is_pear(-101)  
print(str(flag1)+" "+str(flag2))  
if (flag1 and flag2):  
    print("ding!")  
if (flag1 or flag2):  
    print("dong!")
```

Programming Exercise 3

Write a function `first_neg` that takes a (possibly empty) list of numbers as input, finds the first occurrence of a negative number, and returns its index (i.e. position in the list) of that number. If there is no negative number or the list is empty, the program should return `None`. Use while loop (and not for loop) and your while loop should stop looping once the first negative number is found.

Test your function with at least the examples below

```
>>> first_neg([2, 3, -1, 4, -2])
2
>>> first_neg([2, 3, 1, 4, 2])
>>> first_neg([])
```

Programming Exercise 4

Write a function `sum_5_consecutive` that takes a list of numbers as input and returns True if there are 5 consecutive numbers in the list that sum to zero. Otherwise it returns False. You may assume that the list has at least 5 elements

Solve this in two ways:

1. for loop (over indices of the list)
2. while loop (over indices of the list)

In both cases need to think about “stopping condition” in order to avoid “`IndexError: list index out of range`”

3. Test your function with at least the examples below

```
>>> sum_5_consecutive([2, 3, -3, 2, 4, -6])
True
>>> sum_5_consecutive ([-10, 1, 1, 4, 2, 10, 13])
False
>>> sum_5_consecutive([2, 1, -3, -3, -3, 2, 7, 4, -6])
True
>>> sum_5_consecutive ([])
False
>>> sum_5_consecutive ([1, -1, 0])
False
```

Programming Exercise 5 :

Different ways to create useful lists

Recall, for example, that

`a=[2]` creates a list (refer to by variable `a`) with one element, a number 2 in this case

`b=[None]` creates a list of length 1, but where, for now, we do not want to specify a value so we might as well put `None`

`c=[]` creates an empty list of length zero

Recall further that multiplying a list by an integer `n`, creates a new list that repeats the given list `n` times. Or that "adding" two lists creates a new lists that concatenates the given two lists.

For example

`[7,2]*3` creates a list `[7,2,7,2,7,2]`

`[1,2]+[10,20,0]` creates a list `[1,2,10,20,0]`

Finally recall the slicing ... for example, if `a=[2,3,4,1]`, `a[:]` returns the new list with the same elements as `a`.

Open the file called `creating_various_lists.py`. The first line is given to you. It asks the user to enter a positive even integer `n`. Those bullets that are green below, try to find at least two solutions: one using eg. multiplication and another using a loop with accumulator pattern.

1. Create a list `a` (i.e referred to by variable `a`) of length `n` filled with zeros
2. Create a list `b` of length `n` filled with random numbers between 1 and 100
3. Create a variable `c` that is an alias of `b`
4. Set first half of the elements of `c` to zero, and then print both `b` and `c`
5. Copy list `b` into a list `d`
6. Create a new list `e` that has every 2nd element of `b`

Programming Exercise 6: Fibonacci Numbers

Write a function called `fib(n)` that takes as input an integer `n` (greater than 1) and creates a list containing `n` values such that

$$a[0] = 1$$

$$a[1] = 1$$

$$a[i] = a[i-1] + a[i-2] \text{ for all } i \text{ in the range } 1 < i < n$$

and it prints that list once it creates it

```
>>> fib(7)
[1  1  2  3  5  8 13]
```

Once you are done, trace your program on paper and then Python visualizer to see what the values in the list will be for `n=5`.

Programming Exercise 7:

Write a function `inner_product` that takes as input two lists (of same length) of integers and then computes and returns the *inner product* of the two lists of integers. The inner product of two lists $x = [x_1, x_2, \dots, x_n]$ and $y = [y_1, y_2, \dots, y_n]$ is the value $x_1 y_1 + x_2 y_2 + \dots + x_n y_n$.

```
>>> inner_product([2,3,4], [1,0,2])  
10
```

More programming Exercises:

Do everything in the first 13 exercises here

<http://interactivepython.org/courselib/static/thinkcspy/Lists/Exercises.html>

and if you need more exercises

go to the web site below, for some more practice programming questions but **be aware** that the web site is in **Python 2**, thus if you do these exercises do them on your own computer **AND NOT** in the little browser window of the web site.

<http://codingbat.com/python>