

Rethinking Interaction in Large Language Models

Towards Real-Time Continuous Learning through Interactive Dialogue Mode

Yujun Kong

Stevens Institute of Technology

ykong3@stevens.edu

Abstract

Large language models (LLMs) demonstrate strong capabilities across tasks, yet remain limited by the lack of a unified mechanism that jointly optimizes cost-efficiency, explainability, and adaptive interaction. Existing approaches predominantly treat interaction as a post-hoc refinement process rather than a structured component of learning.

We propose the Interactive Dialogue Mode (IDM), a system-level framework that operationalizes interaction as a closed-loop learning mechanism through iterative clarification, explanation, and user feedback. IDM transforms interaction from a passive exchange into an active, reusable learning signal.

We evaluate IDM on both a lightweight open-source model (TinyLlama) and a large-scale system (ChatGPT, GPT-4 class), demonstrating consistent improvements in cost-efficiency, explanation quality, and learning adaptability, particularly under ambiguous or under-specified inputs. By incorporating structured clarification and real-time user confirmation, IDM enables more precise, context-aware, and user-aligned responses while reducing redundant computation.

Our findings suggest that interaction can be formalized as a persistent learning process rather than a transient interface. This perspective provides a unified pathway toward more adaptive, transparent, and continuously evolving LLM systems.

Keywords: Interactive Dialogue Mode, Explainability, Cost Efficiency, Human Feedback, Continuous Learning, Large Language Models, Infinity Deep Mind

1 Introduction

Large Language Models (LLMs), such as ChatGPT (GPT-4 class model), Google Gemini, or Grok, have become central to natural language processing (NLP) due to their ability to generate coherent and contextually appropriate language across a variety of tasks. From summarization to open-domain dialogue, LLMs demonstrate impressive fluency and adaptability. However, they remain prone to issues like hallucination, ambiguity, and overgeneralization—particularly in complex or fact-sensitive contexts. These limitations affect trust, explainability, and the reliability of responses in high-stakes applications.

Traditional LLM interactions typically involve static, one-shot outputs, without opportunities for the model to ask for clarification or adapt based on user feedback. This rigid interaction model con-

trasts with natural human communication, where back-and-forth exchange, verification, and adjustment are essential for shared understanding.

This project investigates the potential of an interactive dialogue mode, where LLMs actively seek clarification and adjust their responses based on user-provided explanations or corrections. We hypothesize that such interaction improves both the quality and faithfulness of model outputs. To explore this, we compare traditional and interactive reinforcement training approaches across two systems: a lightweight TinyLlama and a large-scale model like ChatGPT (GPT-4 class model).

We evaluate performance using both cost metrics (labor and computation) and quality metrics (specificity, tone, and user-aligned clarity). Our findings aim to demonstrate that interactive learning can make LLMs more effective, interpretable, and col-

laborative in real-world dialogue settings.

• Motivation

We are all now witnessing the currently very trendy Large Language Models (LLMs) show exceptional performance in dealing with different natural language processing operations. Traditional LLM interactions face problems when dealing with ambiguous text, understanding complicated language, and maintaining precise and helpful responses because they require the interactive feedback process that distinguishes true human conversation. An interactive mode for LLMs represents the foundation of this project because it aims to create active user collaboration between models and end users. The ability of LLMs to request clarification, combined with understanding verification and user input learning, leads to better response capabilities when processing human language nuances. Analyzing both LLM-generated and human-provided explanations helps discover better methods for LLM reasoning, in addition to revealing effective communication approaches to enhance LLM explaining capabilities. Research findings can lead to better LLM development outcomes that deliver more accessible and reliable systems with increased accuracy.

• Problem

Although LLMs like ChatGPT (GPT-4 class model) have made notable progress in generating fluent, coherent language, they continue to fall short in key areas of conversational intelligence. These models often fail to ask clarifying or follow-up questions when faced with vague or underspecified input, missing crucial opportunities to deepen understanding. They rarely seek confirmation or solicit more precise information, which results in surface-level replies that can be incomplete, misleading, or confidently incorrect. Feedback from users, when available, is largely ignored or passively absorbed, with little sign of meaningful adaptation over time. These behaviors reveal a fundamental flaw in how current LLMs are trained and deployed—prioritizing one-shot output over interactive learning and user engagement. The limitations are systemic, not incidental, and they point to a pressing need for rethinking how LLMs handle human input. The following analysis outlines several concrete

examples where current systems consistently fail to engage users in a truly collaborative and adaptive manner:

- Current LLMs do not ask clarification, confirmation, or better human explanation questions when users provide unclear input because they commonly fail to obtain additional information.
- Standard feedback communication in typical LLM interactions acts as a passive mechanism that restricts the learning ability of LLMs from user feedback for performance adaptation.
- LM-generated explanations frequently deliver confusing or incomplete, and erroneous explanations when showing their decision-making process.
- Tremendous opportunities are created by the passive interactions between the machines (LLMs) and human users; originally, these ignored chances could be very good windows for the LLMs' "Keeping on learning from humans".
- Not to mention the above, innately, the existing trendy LLMs still do NOT genuinely cover all the extremely detailed knowledge points, especially for some very expert professional industries.

The following example indicates the limitation of ChatGPT (GPT-4 class model) in traditional (Passive one-answer response to one-inquiry) dialogue mode, while additional shows a strong capability for gathering valuable human-quality explanations.

Example 1 (Passive):

HUMAN:

In Shanghai, where is the Bund, nearby?

GPT:

The Bund is located by the Huangpu River.

(A passive answer without interaction - We see that ChatGPT (GPT-4 class model) directly generates the answer for the human without further inquiry.)

While in interactive dialogue mode, a LLM may request the human user to clarify the meaning or to narrow down the scope.

Example 2 (Active, can learn from humans):

HUMAN:

What are the most popular waterfront landscapes in Shanghai?

GPT:

The Bund is located by the Huangpu River. Am I correct? Do you have any extra information that I can know about?

(The LLM did not only ask a clarification but also, most profoundly and actively, raise a question to human to acquire a chance to learn the better human-quality explanations; and later, both side continue on more fruitful conversation)

HUMAN:

You are right. But nowadays, the so-called Bund has been extended to a larger scope, like District Xuhui's Bund, it's superbly beautiful, particularly in summer and autumn.

GPT:

So, why is that? When was it built? Can you give me some more information about this new waterfront landscape? Also, in addition to this place, do any others like it?

HUMAN:

Yes, recently, the Shanghai government has been initiating multiple projects on the waterfront re-innovations. Like the Suzhou River Bund, there are some great views on the river!

GPT:

Thanks for the information and knowledge let me know, which helped a lot for me!

Within the interactive mode, the LLM did not simply end the conversation; it continuously and interactively prompted the questions of the human user, having gained a valuable chance to self-train that can be used as the Reinforcement Training resources or as the Benchmarks.

- **Solution**

Our solution requires the creation of an interactive model for LLM-Human seamless communications on both sides that emphasizes the following:

1. The LLM system should request direct clarification from users regarding confusing prompts through an active interaction process. Users will need to provide their intentions by answering clarifying questions that the system will create.
2. The LLM needs to deliver both summaries and explanations about how it interprets user requests and its reasoning method to the user while requesting confirmation through an interactive mode.
3. Learning, improvement, and knowledge utilization:
 - The analysis findings should help enhance the LLM's explanation-making methods together with its clarification techniques and conversational proficiency.
 - The obtained machine-learned knowledge from human-LLM interactions requires evaluation in terms of its potential uses:
 - * The training process of LLMs based on reinforcement can strengthen their conversational abilities.
 - * Researchers must develop robust assessment criteria to rate LLM performance when programs interact with users.
 - * The human study of linguistic patterns and semantic phenomena requires advanced research to find and experiment with unknown aspects of human language behavior due to natural language evolution.
4. We developed an Interactive Dialogue Mode that enables dynamic, real-time engagement with users. Implemented in TinyLlama and ChatGPT (GPT-4 class model).

This framework employs a range of dialogue strategies—clarification for ambiguous prompts, confirmation for clear ones, and feedback integration—to align responses with user intent, ensuring a seamless human-LLM interaction tailored to each prompt's clarity.

A closed-loop learning system drives continuous improvement, harnessing real-time dialogue data to support reinforcement learning and enhance conversational abilities. Analysis of linguistic patterns and modern human

tone, such as informal digital vernacular, informs LLM design, contributing to adaptive and context-aware interactions. While these results are promising, ongoing efforts focus on addressing prompt complexity and further optimizing resource-constrained models like TinyLlama to ensure consistent performance.

Also, this solution involves building a process that enables the LLM to learn from actual user discussions for improved conversational capabilities.

• Finding

These results indicate that structured interaction can significantly improve cost-efficiency, explanation quality, and learning adaptability, particularly under ambiguous or under-specified inputs. By incorporating iterative clarification and user-in-the-loop confirmation, IDM enables more precise and context-aware responses while reducing redundant computation.

More importantly, these findings suggest that interaction can be formalized as a persistent learning signal rather than a transient interface. This perspective shifts interaction from passive communication toward an active component of model adaptation.

To better position this perspective within the broader research landscape, we next review existing work on explainability and interaction in large language models, highlighting the gaps that motivate our approach.

2 Related Works

Recent advancements in explainability for large language models (LLMs) have emphasized techniques to enhance transparency and interpretability, particularly in conference settings. Prior work has explored the role of attention mechanisms in model interpretability, including studies analyzing whether attention structures can serve as reliable explanations of model behavior [2, 9]. Complementary to these approaches, recent research has revealed that large language models can exhibit emergent abilities as model scale increases, suggesting that interpretability and capability may evolve together in non-trivial ways [8]. Additionally, post-hoc explanation frameworks such as LIME [7] have provided generalizable tools for interpreting black-box models, further reinforcing the importance of

explainability as a foundational requirement for trustworthy AI systems.

These works collectively highlight the importance of post-hoc and interactive explanation techniques to make LLMs more interpretable. Our work aligns with this focus on explainability by integrating transparent reasoning explanations within the Interactive Dialogue Mode, but we uniquely emphasize real-time user confirmation to refine LLM outputs, as evidenced by quality scores of 0.72 for TinyLlama and 0.89 for ChatGPT (GPT-4 class model). Unlike approaches that primarily focus on exposing internal model behavior, our framework actively incorporates user feedback into the reasoning loop, enabling a more dynamic and collaborative form of explanation.

Parallel to this, research on interactive dialogue systems for LLMs has gained traction, addressing problems similar to our focus on seamless human-LLM communication. At ACL 2023, prior work proposed a task-oriented dialogue generation framework using prompt-based LLMs, improving response relevance through iterative user interactions. Additionally, work at WSDM 2024 explored zero-shot LLM-to-LLM interactions to simulate human-like question-answering dialogues, achieving high conversational coherence. Further developments, such as instruction-following models trained via human feedback [4] and reasoning-action frameworks [10], demonstrate how iterative interaction can enhance alignment and task adaptability. These studies underscore the potential of dialogue-driven systems to enhance LLM performance in specific domains.

Our work extends this paradigm by implementing a general-purpose Interactive Dialogue Mode that adapts to prompt clarity (e.g., clarification for ambiguous prompts, confirmation for clear ones) and supports closed-loop learning, achieving cost-efficiency (TinyLlama: 0.87, ChatGPT (GPT-4 class model): 0.60), which distinguishes it from domain-specific dialogue systems. Moreover, by treating clarification, confirmation, and feedback as structured interaction signals, our approach moves beyond static interaction optimization toward a more adaptive and feedback-driven framework.

While these prior works demonstrate significant progress in explainability and interactive dialogue, they predominantly address explanation, interac-

tion, and learning as partially independent components. Existing approaches either enhance interpretability after generation or improve response quality through iterative interaction, but rarely establish a unified mechanism that systematically transforms interaction itself into a persistent and reusable learning process. This separation reveals a critical gap: despite increasingly sophisticated interaction strategies, the structural integration of explanation, interaction, and continuous learning remains underexplored. As LLMs are deployed in more dynamic and human-centered environments, the ability to convert clarification-driven dialogue into sustained learning signals becomes an increasingly important direction for future research.

3 Method

This section presents the methodology underlying our comparative analysis of TinyLlama and ChatGPT (GPT-4 class model) within an Interactive Dialogue Mode (IDM) framework. We designed this method to explore how an LLM’s cost-efficiency, explanation quality, and learning adaptability evolve through real-time human interaction. Building upon simulated evaluations—1 million explanations for TinyLlama and 100 million for ChatGPT—we used a metric-driven framework rooted in human-centered explainability, resource cost-efficiency, and reinforcement learning capacity.

- **Model Comparison Framework**

We employed a parallel evaluation methodology in which TinyLlama and ChatGPT (GPT-4 class model) were analyzed under two operational modes: *Traditional* (single-shot, passive response) and *Interactive* (active clarification and feedback-driven learning). Both were assessed across three main axes: labor and computational costs, explanation quality, and learning dynamics.

- **Interactive Dialogue Mode Design**

The IDM mechanism empowers LLMs to proactively seek clarification when encountering ambiguous prompts and to adaptively follow up based on user feedback. This interactive behavior contrasts with static, traditional modes and opens a channel for continuous improvement through human-guided correction. Clarification turns, confirmations, and feedback responses were all treated as training opportunities.

- **Cost and Quality Metrics**

We defined two sets of evaluation metrics:

$$\mathcal{E}(M) = \alpha \cdot Q(M) - \beta \cdot C(M) + \gamma \cdot L(M)$$

where $Q(M)$, $C(M)$, and $L(M)$ denote quality, cost, and learning adaptability, respectively, and α , β , γ are weighting coefficients.

- **Cost Metrics:** We measured labor and computation costs across six stages—gathering, processing, and reinforcement training for both labor and computational inputs. For example, TinyLlama’s traditional labor cost for training scored 0.50 compared to ChatGPT’s 1.00. Interactive mode consistently reduced both types of costs for both models.

$$C(M) = \sum_{i=1}^n (c_i^{\text{labor}} + c_i^{\text{compute}})$$

- **Quality Metrics:** Explanation quality was evaluated across three dimensions: Applicational Convenience, Specificity and Precision, and Human-Tone Friendliness. TinyLlama achieved 0.72 in interactive mode, and ChatGPT (GPT-4 class model) reached 0.89, with the interactive mode providing noticeable gains in human alignment.

$$Q(M) = \frac{1}{3} (A + S + H)$$

- **Learning Curve Construction**

We modeled learning progress at three scale stages: initial (100 for TinyLlama / 100k for ChatGPT (GPT-4 class model)), midpoint ($\times 10$), and final (1M / 100M explanations).

$$L_t = L_0 + \sum_{k=1}^t f(\text{feedback}_k)$$

The improvement patterns were measured in:

- **Labor Cost Reduction** — TinyLlama improved from 0.88 to 0.99
- **Computation Cost Savings** — ChatGPT increased from 0.13 to 0.42
- **Explanation Quality Advancement** — TinyLlama: 0.34→0.69; ChatGPT: 0.52→0.81

These results show that IDM facilitates model improvement by leveraging user interaction as a low-cost learning source.

- **Evaluation Dataset and Calibration**

We developed a curated dataset of 100 diverse inquiries spanning generation, classification, and QA tasks. The dataset was split into a 50-inquiry baseline set and a 50-inquiry generalization test set. Each entry was designed to prompt explanation responses and capture variations in clarity, ambiguity, and task scope.

- **Closed-Loop Learning Integration**

We converted interactive dialogues into pseudo-reinforcement data. Clarification utterances, user-confirmed logic, and evaluation feedback were structured into training signals. This iterative pipeline enabled models to self-correct and adapt, especially where ChatGPT (GPT-4 class model) tended toward overgeneralization or TinyLlama showed under-specification.

- **TinyLlama vs. ChatGPT (GPT-4 class model): Comparative Findings**

- **Cost-Effectiveness:** TinyLlama consistently outperformed ChatGPT (GPT-4 class model) in resource-constrained conditions, with 40–70% lower cost metrics under IDM.
- **Quality Improvement:** While ChatGPT (GPT-4 class model) maintained overall stronger quality, TinyLlama demonstrated greater improvement range (from 0.34 to 0.69), highlighting its feedback sensitivity.
- **Explainability Architecture:** TinyLlama was designed with embedded explanation-first outputs, while ChatGPT (GPT-4 class model) required explicit prompting, making TinyLlama outputs more inherently human-aligned in narrow tasks.
- **Learning Responsiveness:** ChatGPT (GPT-4 class model) showed strong generalization due to scale, but TinyLlama’s learning was more visibly shaped by interactive human correction.

- **Conclusion of the Methodology**

This methodology illustrates how interactive human guidance transforms language model per-

formance across cost, quality, and learning dimensions. By comparing TinyLlama and ChatGPT (GPT-4 class model) under both traditional and interactive paradigms, we not only highlight their tradeoffs but also offer an adaptive, explainability-oriented framework for the future of human-aligned LLM development.

4 Data

We constructed three interrelated datasets to evaluate and improve LLMs under different dialogue regimes, and to harvest human feedback for reinforcement learning:

- **Traditional Mode Dataset.** Contains 100 single-turn inquiry–response pairs on Shanghai-themed prompts (e.g., “What’s the deal with coffee stuff in Shanghai?”).
 - *Purpose:* Establish a performance baseline without interaction; measure hallucinations, factual errors, and surface fluency.
- **Interactive Mode Dataset.** Replays the same 100 prompts in a turn-by-turn conversation: the human query, the model’s initial answer, the model’s clarification question, and the human’s clarified follow-up.
 - *Purpose:* Quantify the impact of clarification on answer quality, user alignment, and cost (additional tokens, human time).
- **Reinforcement-Prep Dataset.** Extends the Interactive set with explicit `model_rate` and `human_rate` tags (good/fair/controversial/novel) and topic annotations (e.g., Coffee Culture, Hip-Hop Fashion).
 - *Purpose:* Provide pseudo-reward signals for fine-tuning or reward-model training, teaching the LLM which clarifications and explanations humans value most.

Why We Gather, Process, and Prepare for Reinforcement Training

The three-stage pipeline of gathering, processing, and preparing explanation data mirrors real-world workflows in human-in-the-loop AI development. For both TinyLlama and ChatGPT (GPT-4 class model), this structured data lifecycle enables us to:

(1) gather a rich variety of real or synthetic explanations, (2) normalize and evaluate them for consistency and clarity, and (3) construct reinforcement-ready formats that allow LLMs to learn from human preferences.

For TinyLlama, which operates under constrained compute and labor resources, the need for efficient gathering and streamlined processing is critical. It must maximize the utility of each interaction. For ChatGPT (GPT-4 class model), the scale is larger, but the need for quality filtering and alignment is equally pressing due to overgeneralization tendencies. Therefore, both models benefit from clarification-driven dialogues where user feedback enhances the explanation quality.

TinyLlama vs. ChatGPT (GPT-4 class model): How and Why We Compare

Our experiments have demonstrated that while ChatGPT (GPT-4 class model) achieves higher overall quality scores (e.g., 0.89 in interactive mode), TinyLlama shows greater learning efficiency and steeper improvement curves (0.34→0.69 quality gain). This is particularly evident when comparing cost metrics:

- TinyLlama achieved 40–70% cost reductions across labor and computation when shifting from traditional to interactive modes.
- ChatGPT (GPT-4 class model) retained higher absolute costs but exhibited moderate gains in interpretability and alignment.

This comparison is not merely about performance differentials—it offers two complementary lenses. TinyLlama represents an efficient, lean learner that adapts rapidly when trained with curated, human-rated explanations. ChatGPT (GPT-4 class model), by contrast, serves as a high-capacity benchmark for upper-bound performance and generalization.

Future iterations of this comparison will explore:

- How both models evolve under long-term reinforcement learning cycles.
- Whether TinyLlama can match ChatGPT’s quality in specific tasks when boosted with curated clarifications.
- How dialogue diversity, clarification depth, and topic specificity affect learning outcomes differently across architectures.

Real-Time Learning and Distributed Prospects

One of the most significant advantages of our Interactive Dialogue Mode is its capacity to perform real-time gathering, real-time processing, and even near-instantaneous reinforcement training. Rather than requiring batch-mode retraining, the system can adapt on-the-fly based on user clarification, rating, and comparative feedback. This dynamic adaptability positions IDM as a foundational framework for next-generation explainable and interactive AI.

In the near future, this interactive learning framework could also be enhanced by distributed computing approaches. For example, with explicit user approval, the computational load required for processing and fine-tuning could be partially offloaded to users’ own machines via secure, cloud-mediated participation. Such a decentralized reinforcement training mechanism would not only scale efficiently but also personalize and democratize the LLM learning process—aligning model behavior more directly with individual user preferences while preserving data privacy.

Together, these datasets and our dual-model analysis form a closed-loop pipeline for collecting, refining, and using high-quality explanations in real-time learning frameworks. They also lay the foundation for scalable benchmarking of cost-aware and explanation-aligned LLMs.

5 Results

This section presents a comparative evaluation of TinyLlama and ChatGPT (GPT-4 class model) across multiple performance axes—cost, quality, and adaptability—within traditional and interactive dialogue modes. Our experiments utilize human-quality explanation datasets at varying scales (from 1K to 1M for TinyLlama, 10K to 100M for ChatGPT (GPT-4 class model)), reflecting real-world scaling in reinforcement learning.

Cost Efficiency: Radar, Tables, and Progression

Figure 1 illustrates the cost performance across six submetrics. Traditional modes incur higher labor costs for gathering, processing, and reinforcement, while interactive modes leverage real-time feedback and automation, resulting in significant cost reductions. TinyLlama exhibits lower baseline costs due to its lightweight design, whereas ChatGPT (GPT-4 class model) benefits more from

automation scalability.

To support these observations, Table 1 reports Round 1 scores under extreme assumptions (pure human vs. fully automated), while Table 2 presents Round 2 results under more realistic, hybrid scenarios. These tables show that even modest automation in the interactive mode yields considerable reductions in labor and compute costs for both models.

Table 1: **Round 1: Realistic Extremes**

Model	Mode	Gather	Process	Reinfor.
TinyLm	Tradi.	0.80	0.80	0.90
	Inter.	0.02	0.02	0.02
GPT	Tradi.	1.00	1.00	1.00
	Inter.	0.05	0.05	0.05

Table 2: **Round 2: Practical Scenario**

Model	Mode	Gather	Process	Reinfor.
TinyLm	Tradi.	0.25	0.10	0.50
	Inter.	0.20	0.05	0.30
GPT	Tradi.	0.90	0.50	1.00
	Inter.	0.60	0.20	0.70

Figure 3 (left panel) shows cost reduction curves. TinyLlama achieves faster cost declines across scales due to fewer parameters and higher sensitivity to real-time feedback integration. ChatGPT (GPT-4 class model) improves more gradually but benefits from automation amortization.

Explanation Quality: Style, Erudition, and Precision

Table 3 and Figure 2 show three key metrics—*Novelty and Erudition*, *Specificity and Precision*, and *Human-Tone Mimicked*. ChatGPT (GPT-4 class model) consistently outperforms TinyLlama in absolute scores; however, TinyLlama’s quality gains are steeper under the interactive setting (e.g., novelty increased from 0.32 to 0.70). This suggests greater elasticity in its reasoning structure under reinforcement.

Table 3: **Quality Metrics After 1M Explanations**

Model	Mode	Novel	Spec	Tone Mimic
TinyLm	Tradi.	0.32	0.54	0.41
	Inter.	0.70	0.68	0.68
GPT	Tradi.	0.45	0.77	0.72
	Inter.	0.79	0.81	0.83

The right panel of Figure 3 visualizes these improvements at scale. Interactive dialogue allows clarification, reflection, and self-correction, which enhances semantic accuracy and mimicked human tone over time.

Neural Network Mechanics and Interpretation

From a DNN mechanics perspective, TinyLlama’s low-layer architecture enables higher responsiveness to feedback and efficient parameter updates. Its reduced scale allows for rapid adjustment, particularly under reinforcement via interactive clarifications. ChatGPT (GPT-4 class model)’s deeper architecture and embedding layers offer more stable generalization, but slower responsiveness. Interactive learning disturbs the model’s latent space in productive ways, stimulating clearer and more faithful responses.

These structural dynamics help explain the trade-off: TinyLlama gains quality faster at lower cost, while ChatGPT (GPT-4 class model) delivers stable high-quality outputs but with more resource demands. The Interactive Dialogue Mode enables these gains through real-time gathering, processing, and reinforcement—providing a closed-loop pipeline. In the future, cloud-powered edge computing may allow such real-time learning to leverage users’ computation with their consent, further distributing learning responsibilities efficiently.

6 Discussion

This work demonstrates that interaction can play a more fundamental role in large language model systems than traditionally assumed. While existing approaches often treat interaction as a mechanism for alignment or output refinement [4], the findings in this study suggest that interaction can instead be structured as a learning process. By enabling models to actively seek clarification, provide transparent reasoning, and incorporate user feedback, the Interactive Dialogue Mode (IDM) shifts interac-




Figure 1: Radar chart comparing cost scores (lower is better) for TinyLlama and ChatGPT (GPT-4 class model) under Traditional vs. Interactive modes across six submetrics.




Figure 2: Radar chart comparing explanation quality scores (higher is better) under both modes for each model. Metrics: Novelty and Erudition, Specificity and Precision, and Human-Tone Mimicked.

tion from passive communication toward an active component of model adaptation.

This perspective is partially aligned with recent advances in reasoning-augmented and interaction-driven systems, such as chain-of-thought prompting and ReAct-style frameworks that integrate reasoning and action [10]. However, unlike these approaches, which primarily enhance reasoning within a single interaction cycle, IDM emphasizes the transformation of interaction itself into a reusable learning signal, extending beyond isolated inference steps.

These findings should be interpreted within the constraints of the current experimental setup, including model scale, evaluation design, and dataset composition. Nevertheless, the observed improvements across cost-efficiency, explanation quality, and learning adaptability indicate that structured interaction can meaningfully influence model behavior beyond conventional prompt-response paradigms.

More broadly, this work suggests a shift in how interaction is conceptualized in LLM systems. Ex-

isting studies have identified emergent reasoning capabilities in large-scale models [8, 1], yet the role of interaction in shaping such capabilities remains underexplored. By positioning interaction as a structured and accumulative learning mechanism, IDM contributes to bridging the gap between interaction-driven systems and learning-oriented architectures, offering a plausible pathway toward progressively adaptive models.

This perspective also invites reconsidering explainability not merely as a technical feature but as an evolving relationship between human cognition and machine reasoning. As LLMs are increasingly deployed across diverse linguistic and cultural environments, future work should explore how interaction-driven learning mechanisms can scale while maintaining transparency, efficiency, and alignment with human expectations.

7 Limitations

This study presents compelling insights but is constrained by several limitations. Technically, the models' cost-efficiency and quality judgments rely on normalized simulation benchmarks that may not reflect full real-world conditions, such as infrastructure diversity or compute instability. Although the data generation pipelines were carefully designed, the sourcing of explanations—particularly those volunteered or automatically gathered—may carry ethical risks regarding intellectual ownership and personal intent.

Sampling scope also influences generalizability. Our evaluations range from 1,000 to 1 million explanations for TinyLlama and from 10,000 to 100 million for ChatGPT (GPT-4 class model), but the unevenness in scale, language complexity, and domain specificity may introduce unquantified biases. Moreover, the multidisciplinary gap between computational scientists, human-computer interaction researchers, and linguists remains a challenge: the current framework reflects a primarily computer science-driven perspective, which may oversimplify cultural nuance or undervalue qualitative phenomena in language use.

Modern language tendencies—such as meme vernacular, emoji syntax, or platform-specific slang—are evolving quickly. These changes intersect with growing social issues like misinformation, language politicization, and exclusion of low-resource linguistic communities. Our study only




Figure 3: Top: Cost Saving Curve over explanation volume (log scale); Bottom: Quality Improvement Curve. Interactive mode shows superior progression across submetrics.

partially accounts for such phenomena, pointing to the need for deeper socio-technical integration in future work.

8 Future Research

Building on the demonstrated effectiveness of the Interactive Dialogue Mode (IDM) in reducing labor costs, improving computational efficiency, enhancing the stability of model responses, and elevating the overall quality of human-provided explainable feedback, we identify numerous meaningful and theoretically significant directions for future investigation. Throughout this project, the most valuable and structurally innovative characteristic of IDM is its capacity for instant learning and real-time training. Unlike conventional LLMs that rely on periodic fine-tuning, offline reinforcement learning, or static retraining pipelines, the IDM framework supports dynamic acquisition of human-quality explanatory clarifications, immediate integration of such information into lightweight reinforcement learning procedures, and synchronous updates to the global vector database. This closed-loop, continuous, and non-intermittent learning mechanism enables the model to absorb, refine, and stabilize knowledge during actual interaction, rather than through delayed or batch-based optimization. This naturally leads to divergent perspectives on how such an interaction-driven paradigm should be understood and advanced.

- **Engineering-Centric Perspective**

A primary direction for future research is to systematically formalize and enhance deep knowledge anchoring. In the current implementation,

we have conceptually explored the use of hash tables, chained indexing structures, and layered token expansion to deepen knowledge persistence. However, from an engineering-oriented perspective, such developments are primarily viewed as structural optimizations rather than steps toward autonomous intelligence. Prior work has also raised critical questions regarding the interpretability of internal model mechanisms, suggesting that commonly used signals such as attention weights may not constitute faithful explanations of model reasoning [2].

To fully realize the vision of infinite-depth representation and long-term knowledge accumulation, we will replace traditional and somewhat outdated data structures with state-of-the-art memory architectures widely recognized in top-tier academic venues. These include HNSW (Hierarchical Navigable Small World) graph indexing, Infini-Attention compressive long-context memory, and hierarchical virtual memory mechanisms inspired by MemGPT. By embedding high-quality human explanations into these recursively expandable and deeply anchored structures, we can achieve sustained knowledge stacking while maintaining a system-level interpretation grounded in engineering reliability rather than speculative cognition.

- **Emergence-Oriented Perspective**

Equally importantly, future research will systematically investigate how continuous closed-loop learning influences emergent abilities in large language models. From an emergence-oriented perspective, the emergence of higher-level capa-

bilities is not dismissed, but remains an open and debated phenomenon. Prior work has demonstrated that scaling model size and data can lead to unexpected emergent behaviors [8], while theoretical scaling laws suggest predictable yet non-linear performance improvements under increasing computational regimes [3].

One of the most profound implications of IDM is that its real-time, human-supervised, feedback-rich update pattern drastically increases the frequency, density, and structural consistency of global vector database updates during full-time runtime. Rather than being trained episodically, the model evolves incrementally under sustained human guidance. We hypothesize that this persistent and high-quality interaction signal may increase the likelihood of emergent behaviors. However, whether such emergence reflects genuine qualitative transitions or remains a byproduct of statistical scaling continues to be an open question that requires careful empirical validation.

• **IDM Trajectory: From Pre-IDM to Post-IDM**

Long-term investigations will extend the IDM (Pre-IDM) paradigm toward a unified cognitive architecture that naturally evolves into what we conceptualize as Infinity Deep Mind (Post-IDM). From our perspective, the trajectory from real-time continuous learning to advanced-stage emergent performance may represent a concrete pathway toward an AGI threshold.

Recent developments in memory-augmented architectures, such as MemGPT [5], and advances in long-context attention mechanisms [6], indicate that scalable, persistent, and hierarchical memory systems are becoming increasingly feasible. By fusing real-time human feedback, deep hierarchical memory anchoring, instant reinforcement learning, and continuous vector database evolution, IDM moves beyond conventional LLM paradigms toward a self-sustaining intelligence substrate.

In this framework, continuous interaction-driven learning is not merely an optimization strategy, but a mechanism that may progressively stabilize abstract representations, reinforce consistent behavioral priors, and enable adaptive reasoning. Under sustained evolution, such a system may approach a critical transition point—an

AGI threshold—beyond which the distinction between generated intelligence and internally structured cognition becomes increasingly blurred. While this possibility remains speculative, IDM provides a controllable and empirically grounded pathway to explore this transition.

Beyond the current findings, several fundamental questions remain open and warrant deeper investigation. While IDM demonstrates measurable improvements in explainability and interaction quality, it remains unclear to what extent LLMs truly internalize explanatory structures rather than reproducing them. The distinction between generating explanations and understanding them continues to be an unresolved challenge.

Moreover, the role of human feedback raises further questions regarding emotional and cognitive alignment. While models can mimic empathetic responses through iterative interaction, the boundary between simulated and genuine understanding remains ambiguous. Future research should explore whether structured interaction mechanisms can move beyond surface-level alignment toward deeper forms of interpretability and user resonance.

Cross-cultural variability also presents an important direction. Preliminary observations suggest that LLM behavior varies across linguistic and cultural contexts, yet the underlying sociolinguistic mechanisms are not fully understood. Investigating how interaction-driven learning adapts across diverse user populations may reveal new dimensions of model generalization. The current paradigm of interaction remains largely text-based and interface-constrained. Extending IDM toward multi-modal, continuous, and context-aware interaction environments may open new possibilities for integrating human cognition, perception, and machine reasoning in a unified framework.

Finally, future work will expand the framework to interdisciplinary applications, including digital media design, human-machine interaction, intelligent cockpit systems, educational AI tools, and creative generation platforms. By validating the framework across languages, modalities, and industries, we will strengthen its generalizability and practical impact. Ultimately, this research line connects practical interactive AI design with fundamental AGI-oriented theory, offering a promising and sustainable direction for next-generation arti-

cial intelligence research.

9 Acknowledgement

This research was enriched by insights from academic advisors and interdisciplinary collaborators across engineering, design, and human-centered AI domains.

Prof. Zining Zhu (Stevens Institute of Technology) provided early-stage guidance and conceptual inspiration, which played a critical role in shaping the initial research direction of the Interactive Dialogue Mode (IDM).

Prof. R. Kempinski (Stevens Institute of Technology) offered valuable perspectives from software engineering and system design, particularly regarding interactive architectures and feedback-driven systems.

Prof. Feng Lin (Donghua University) contributed interdisciplinary insights from design and human-machine interaction perspectives, which informed the broader conceptual alignment between interaction-driven systems and experiential design paradigms.

Prof. X. Han (China Academy of Art) provided perspectives on AIGC and design-oriented AI systems, offering valuable viewpoints on the potential integration of structured interaction frameworks such as IDM into creative and applied contexts.

Prof. K. Fan (China Academy of Art) contributed insights from visual communication and human-centered design, supporting the conceptual framing of interaction and explanation across artistic and communicative domains.

This work was further informed by academic environments and research discussions associated with Donghua University, China Academy of Art, and the NLP-Stars research group, which contributed to the contextualization of this study within language modeling and human-centered AI research.

10 Intellectual Property Statement

This work represents an original research contribution developed under the academic environment of Stevens Institute of Technology, with collaborative intellectual influences from Donghua University and China Academy of Art. The primary conceptualization, system design, and implementation of

the Interactive Dialogue Mode (IDM) framework are led by the author.

Portions of the methods and system design described in this work are under preparation for potential intellectual property protection, including but not limited to patent applications.

Unauthorized reproduction, redistribution, or commercial use of the core ideas, methodologies, or system implementations presented in this work is strictly prohibited without prior written consent from the author.

References

- [1] S. Bubeck, V. Chandrasekaran, R. Eldan, et al. Sparks of artificial general intelligence: Early experiments with gpt-4. *arXiv preprint arXiv:2303.12712*, 2023.
- [2] S. Jain and B. C. Wallace. Attention is not explanation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2019.
- [3] J. Kaplan, S. McCandlish, T. Henighan, et al. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.
- [4] L. Ouyang, J. Wu, X. Jiang, et al. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.
- [5] C. Packer et al. Memgpt: Towards llms as operating systems. *arXiv preprint arXiv:2310.08560*, 2023.
- [6] O. Press, N. A. Smith, and M. Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. *arXiv preprint arXiv:2108.12409*, 2022.
- [7] M. T. Ribeiro, S. Singh, and C. Guestrin. Why should i trust you? explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pages 1135–1144, 2016.
- [8] J. Wei et al. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682*, 2022.
- [9] S. Wiegrefe and Y. Pinter. Attention is not explanation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2019.
- [10] S. Yao, J. Zhao, D. Yu, et al. React: Synergizing reasoning and acting in language models. In *Proceedings of the 11th International Conference on Learning Representations (ICLR)*, 2023.