Electrical Rules Check Report

Class	Document	Message
Warning	Solens.SchDoc	Nets Wire FUEL_AL_L has multiple names (Sheet Entry Z1-FUEL_AL_L(I/O),Sheet Entry Z4-PERIPH_ALERT(I/O),Sheet Entry Z5-A\L\E\R\T\(I/O))
Warning	Solens.SchDoc	Nets Wire I2C2_ALERT has multiple names (Net Label I2C2_ALERT,Net Label PERIPH_ALERT,Sheet Entry Z1-FUEL_AL_L(I/O),Sheet Entry Z4-PERIPH_ALERT(I/O),Sheet Entry Z5-A\L\E\R\T\(I/O))
Warning	Solens.SchDoc	Nets Wire I2C2_SCL has multiple names (Net Label I2C2_SCL,Net Label PERIPH_SCL,Sheet Entry Z1-SCL(I/O),Sheet Entry Z4-PERIPH_SCL(I/O),Sheet Entry Z5-SCL(I/O))
Warning	Solens.SchDoc	Nets Wire I2C2_SDA has multiple names (Net Label I2C2_SDA,Net Label PERIPH_SDA,Sheet Entry Z1-SDA(I/O),Sheet Entry Z4-PERIPH_SDA(I/O),Sheet Entry Z5-SDA(I/O))
Warning	Solens.SchDoc	Nets Wire PWR_CHRG_L has multiple names (Net Label PWR_CHRG_L,Sheet Entry Z1-PV_CHRG_L(Output),Sheet Entry Z4-PV_CHRG_L(Input))
Warning	Solens.SchDoc	Nets Wire PWR_FAULT_L has multiple names (Net Label PWR_FAULT_L,Sheet Entry Z1-PV_FAULT_L(Output),Sheet Entry Z4-PV_FAULT_L(Input))
Warning	Solens.SchDoc	Nets Wire SCL has multiple names (Sheet Entry Z1-SCL(I/O),Sheet Entry Z4-PERIPH_SCL(I/O),Sheet Entry Z5-SCL(I/O))
Warning	Solens.SchDoc	Nets Wire SDA has multiple names (Sheet Entry Z1-SDA(I/O),Sheet Entry Z4-PERIPH_SDA(I/O),Sheet Entry Z5-SDA(I/O))

Design Rules Verification Report

Filename : C:\Users\qux\projects\solenshardware\Altium\Solens\Solens.PcbDoc

Warnings	
Your board contains 2 shelved polygons - copper connectivity will not be reported correctly. Unshelve polygons and	2
Unplated multi-layer pad(s) detected	4
Total	6

Rule Violations	
Width Constraint (Min=8mil) (Max=120mil) (Preferred=8mil) (InComponent('MTGH*'))	0
Short-Circuit Constraint (Allowed=Yes) (InComponent('MTGH*') And (IsFill Or IsPad Or IsTrack)),(InComponent('MTG*')	0
Room Z6 (Bounding Region = (6641.339mil, 5696.457mil, 7468.11mil, 7035.039mil) (InComponentClass('Z6'))	0
Short-Circuit Constraint (Allowed=Yes) (InComponent('SJ*') And (IsFill Or IsPad Or IsTrack)),(InComponent('SJ*') And	0
Clearance Constraint (Gap=0mil) (InComponent('SJ*') And (IsFill Or IsPad Or IsTrack)),(InComponent('SJ*') And (IsFill	0
Modified Polygon (Allow modified: No), (Allow shelved: No)	0
Net Antennae (Tolerance=0mil) (All)	0
Silk to Silk (Clearance=8mil) (All),(All)	1
Silk To Solder Mask (Clearance=8mil) (IsPad),(All)	417
Minimum Solder Mask Sliver (Gap=6mil) (All),(All)	82
Hole To Hole Clearance (Gap=10mil) (All),(All)	0
Hole Size Constraint (Min=12mil) (Max=250mil) (All)	0
Height Constraint (Min=0mil) (Max=1000mil) (Prefered=500mil) (All)	0
Width Constraint (Min=7mil) (Max=12mil) (Preferred=8mil) (All)	0
Power Plane Connect Rule(Relief Connect)(Expansion=20mil) (Conductor Width=10mil) (Air Gap=10mil) (Entries=4)	0
Clearance Constraint (Gap=8mil) (All),(All)	0
Un-Routed Net Constraint ((All))	0
Short-Circuit Constraint (Allowed=No) (All),(All)	0
Room Z2 (Bounding Region = (5302.756mil, 7468.11mil, 6680.709mil, 8688.583mil) (InComponentClass('Z2'))	0
Width Constraint (Min=8mil) (Max=64mil) (Preferred=8mil) (InNetClass('PWR'))	0
Width Constraint (Min=8mil) (Max=64mil) (Preferred=8mil) (InNetClass('HVY'))	0
Room Z1 (Bounding Region = (2350mil, 6975.984mil, 5224.016mil, 8688.583mil) (InComponentClass('Z1'))	0
Room Z7 (Bounding Region = (6779.134mil, 7172.835mil, 9042.913mil, 8688.583mil) (InComponentClass('Z7'))	0
Total	500

Your board contains 2 shelved polygons - copper connectivity will not be reported correctly. Unshelve polygons and re
Polygon named: 3V3 Plane 1 In net 3V3 On Signal Layer 2
Polygon named: GND Plane In net GND On Signal Layer 1

Unplated multi-layer pad(s) detected
Pad MTGH3-1(6496.063mil,3543.307mil) on Multi-Layer on Net GND
Pad MTGH2-1(196.85mil,3543.307mil) on Multi-Layer on Net GND
Pad MTGH1-1(196.85mil,196.85mil) on Multi-Layer on Net GND
Pad MTGH4-1(6496.063mil,196.85mil) on Multi-Layer on Net GND

Silk to Silk (Clearance=8mil) (All),(All)
Silk To Silk Clearance Constraint: (5.151mil < 8mil) Between Text "C304" (4481.299mil,387.795mil) on Top Overlay And Arc (4476.378mil,455.709mil) on

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)
Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Arc (1507.874mil,3592.52mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (5.905mil < 8mil) Between Arc (1368.11mil,3077.756mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Arc (740.157mil,2980.315mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (3.74mil < 8mil) Between Arc (1073.819mil,3553.347mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2327.756mil,1374.016mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (3074.803mil,556.102mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2877.953mil,556.102mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2327.756mil,1570.866mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2682.087mil,2062.992mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (5.905mil < 8mil) Between Arc (4842.52mil,2978.346mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (5.905mil < 8mil) Between Arc (4842.52mil,3135.827mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2327.756mil,1500mil) on Bottom Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2327.756mil,1696.851mil) on Bottom Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2396.653mil,1137.795mil) on Bottom Overlay And Pad
Silk To Solder Mask Clearance Constraint: (6.102mil < 8mil) Between Arc (2327.756mil,791.339mil) on Bottom Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3816.929mil,1773.622mil)(3816.929mil,1795.276mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3816.929mil,1795.276mil)(3816.929mil,1816.929mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1773.622mil)(3816.929mil,1773.622mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1816.929mil)(3816.929mil,1816.929mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1773.622mil)(3714.567mil,1816.929mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1773.622mil)(3816.929mil,1773.622mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1816.929mil)(3816.929mil,1816.929mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.5mil < 8mil) Between Track (5729.545mil,2756.811mil)(5729.545mil,2786.811mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4169.291mil,2633.858mil)(4169.291mil,2667.323mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4169.291mil,2600.394mil)(4169.291mil,2633.858mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4027.559mil,2600.394mil)(4169.291mil,2600.394mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4027.559mil,2667.323mil)(4169.291mil,2667.323mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4027.559mil,2600.394mil)(4027.559mil,2667.323mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4027.559mil,2600.394mil)(4169.291mil,2600.394mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4027.559mil,2667.323mil)(4169.291mil,2667.323mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4192.913mil,2683.071mil)(4192.913mil,2757.874mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2683.071mil)(4192.913mil,2683.071mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2757.874mil)(4192.913mil,2757.874mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2720.472mil)(4003.937mil,2757.874mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2683.071mil)(4003.937mil,2720.472mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2683.071mil)(4192.913mil,2683.071mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4003.937mil,2757.874mil)(4192.913mil,2757.874mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3560.039mil,2779.528mil)(3560.039mil,2823.819mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3560.039mil,2735.236mil)(3560.039mil,2779.528mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3382.874mil,2735.236mil)(3560.039mil,2735.236mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3382.874mil,2823.819mil)(3560.039mil,2823.819mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3382.874mil,2735.236mil)(3382.874mil,2823.819mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3382.874mil,2735.236mil)(3560.039mil,2735.236mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3382.874mil,2823.819mil)(3560.039mil,2823.819mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3045.276mil,2673.228mil)(3078.74mil,2673.228mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3045.276mil,2673.228mil)(3045.276mil,2814.961mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3112.205mil,2673.228mil)(3112.205mil,2814.961mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3078.74mil,2673.228mil)(3112.205mil,2673.228mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3045.276mil,2673.228mil)(3045.276mil,2814.961mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3112.205mil,2673.228mil)(3112.205mil,2814.961mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3045.276mil,2814.961mil)(3112.205mil,2814.961mil) on Top Overlay And Pad
Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2869.095mil)(2411.417mil,2913.386mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2913.386mil)(2411.417mil,2957.677mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2869.095mil)(2588.583mil,2869.095mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2957.677mil)(2588.583mil,2957.677mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2588.583mil,2869.095mil)(2588.583mil,2957.677mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2869.095mil)(2588.583mil,2869.095mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2411.417mil,2957.677mil)(2588.583mil,2957.677mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.126mil < 8mil) Between Track (2436.024mil,2726.378mil)(2563.976mil,2726.378mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.126mil < 8mil) Between Track (2458.661mil,2844.488mil)(2563.976mil,2844.488mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2594.488mil,3053.15mil)(2594.488mil,3127.953mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3053.15mil)(2594.488mil,3053.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3127.953mil)(2594.488mil,3127.953mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3053.15mil)(2405.512mil,3090.551mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3090.551mil)(2405.512mil,3127.953mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3053.15mil)(2594.488mil,3053.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2405.512mil,3127.953mil)(2594.488mil,3127.953mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2679.134mil)(1051.181mil,2753.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2679.134mil)(1183.071mil,2679.134mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2753.937mil)(1183.071mil,2753.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,2716.535mil)(1183.071mil,2753.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,2679.134mil)(1183.071mil,2716.535mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2679.134mil)(1183.071mil,2679.134mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2753.937mil)(1183.071mil,2753.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,2618.11mil)(1183.071mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,2580.709mil)(1183.071mil,2618.11mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2580.709mil)(1183.071mil,2580.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2655.512mil)(1183.071mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2580.709mil)(1051.181mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2580.709mil)(1183.071mil,2580.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2655.512mil)(1183.071mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,2777.559mil)(1183.071mil,2852.362mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2777.559mil)(1183.071mil,2777.559mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2852.362mil)(1183.071mil,2852.362mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2777.559mil)(1051.181mil,2814.961mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2814.961mil)(1051.181mil,2852.362mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2777.559mil)(1183.071mil,2777.559mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1051.181mil,2852.362mil)(1183.071mil,2852.362mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1045.276mil,2867.126mil)(1045.276mil,2999.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1120.079mil,2867.126mil)(1120.079mil,2999.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1045.276mil,2999.016mil)(1120.079mil,2999.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1045.276mil,2867.126mil)(1082.677mil,2867.126mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1045.276mil,2867.126mil)(1045.276mil,2999.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1120.079mil,2867.126mil)(1120.079mil,2999.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1082.677mil,2867.126mil)(1120.079mil,2867.126mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1181.102mil,2984.252mil)(1202.756mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1159.449mil,2881.89mil)(1159.449mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1202.756mil,2881.89mil)(1202.756mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1159.449mil,2984.252mil)(1181.102mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1159.449mil,2881.89mil)(1159.449mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1202.756mil,2881.89mil)(1202.756mil,2984.252mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1159.449mil,2881.89mil)(1202.756mil,2881.89mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (2.675mil < 8mil) Between Text "C200" (1358.268mil,3307.087mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3214.567mil)(1364.173mil,3248.032mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3248.032mil)(1364.173mil,3281.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3214.567mil)(1505.906mil,3214.567mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3281.496mil)(1505.906mil,3281.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1505.906mil,3214.567mil)(1505.906mil,3281.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3214.567mil)(1505.906mil,3214.567mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1364.173mil,3281.496mil)(1505.906mil,3281.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,2928.15mil)(1427.165mil,2928.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,3016.732mil)(1427.165mil,3016.732mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,2972.441mil)(1250mil,3016.732mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,2928.15mil)(1250mil,2972.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1427.165mil,2928.15mil)(1427.165mil,3016.732mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,2928.15mil)(1427.165mil,2928.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1250mil,3016.732mil)(1427.165mil,3016.732mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1437.008mil,2836.614mil)(1437.008mil,2911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2836.614mil)(1437.008mil,2836.614mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2911.417mil)(1437.008mil,2911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2836.614mil)(1437.008mil,2836.614mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2911.417mil)(1437.008mil,2911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2874.016mil)(1248.032mil,2911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1248.032mil,2836.614mil)(1248.032mil,2874.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.596mil < 8mil) Between Text "SJ200" (767.716mil,2559.055mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (848.425mil,2722.441mil)(848.425mil,2789.37mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (848.425mil,2722.441mil)(972.441mil,2722.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (848.425mil,2789.37mil)(972.441mil,2789.37mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (972.441mil,2722.441mil)(972.441mil,2789.37mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (848.425mil,2722.441mil)(972.441mil,2722.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (848.425mil,2789.37mil)(972.441mil,2789.37mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (700.787mil,2541.339mil)(700.787mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2541.339mil)(700.787mil,2541.339mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2655.512mil)(700.787mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2541.339mil)(511.811mil,2598.425mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2598.425mil)(511.811mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2541.339mil)(700.787mil,2541.339mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2655.512mil)(700.787mil,2655.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (700.787mil,2679.134mil)(700.787mil,2793.307mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2679.134mil)(700.787mil,2679.134mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2793.307mil)(700.787mil,2793.307mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2679.134mil)(511.811mil,2736.22mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2736.22mil)(511.811mil,2793.307mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2679.134mil)(700.787mil,2679.134mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2793.307mil)(700.787mil,2793.307mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (700.787mil,2816.929mil)(700.787mil,2931.102mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2816.929mil)(700.787mil,2816.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2931.102mil)(700.787mil,2931.102mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2816.929mil)(511.811mil,2874.016mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2874.016mil)(511.811mil,2931.102mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2816.929mil)(700.787mil,2816.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (511.811mil,2931.102mil)(700.787mil,2931.102mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (6.399mil < 8mil) Between Text "TP200" (78.74mil,3267.717mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,2935.039mil)(976.378mil,3009.843mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,2935.039mil)(976.378mil,2935.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3009.843mil)(976.378mil,3009.843mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,2935.039mil)(844.488mil,2972.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,2972.441mil)(844.488mil,3009.843mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,2935.039mil)(976.378mil,2935.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3009.843mil)(976.378mil,3009.843mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,3033.465mil)(976.378mil,3108.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3033.465mil)(976.378mil,3033.465mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3108.268mil)(976.378mil,3108.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3033.465mil)(844.488mil,3070.866mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3070.866mil)(844.488mil,3108.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3033.465mil)(976.378mil,3033.465mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3108.268mil)(976.378mil,3108.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3131.89mil)(844.488mil,3206.693mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3131.89mil)(976.378mil,3131.89mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3206.693mil)(976.378mil,3206.693mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,3169.291mil)(976.378mil,3206.693mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,3131.89mil)(976.378mil,3169.291mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3131.89mil)(976.378mil,3131.89mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3206.693mil)(976.378mil,3206.693mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3230.315mil)(844.488mil,3305.118mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3230.315mil)(976.378mil,3230.315mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3305.118mil)(976.378mil,3305.118mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,3267.717mil)(976.378mil,3305.118mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (976.378mil,3230.315mil)(976.378mil,3267.717mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3230.315mil)(976.378mil,3230.315mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (844.488mil,3305.118mil)(976.378mil,3305.118mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (5070.866mil,1911.417mil)(5070.866mil,1986.22mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1911.417mil)(5070.866mil,1911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1986.22mil)(5070.866mil,1986.22mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1911.417mil)(4881.89mil,1948.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1948.819mil)(4881.89mil,1986.22mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1911.417mil)(5070.866mil,1911.417mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,1986.22mil)(5070.866mil,1986.22mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (5070.866mil,2009.842mil)(5070.866mil,2084.646mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2009.842mil)(5070.866mil,2009.842mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2084.646mil)(5070.866mil,2084.646mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2009.842mil)(4881.89mil,2047.244mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2047.244mil)(4881.89mil,2084.646mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2009.842mil)(5070.866mil,2009.842mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4881.89mil,2084.646mil)(5070.866mil,2084.646mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4736.22mil,1823.819mil)(4736.22mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4811.024mil,1823.819mil)(4811.024mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4736.22mil,1823.819mil)(4811.024mil,1823.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4773.622mil,1955.709mil)(4811.024mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4736.22mil,1823.819mil)(4736.22mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4811.024mil,1823.819mil)(4811.024mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4736.22mil,1955.709mil)(4773.622mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4647.638mil,1823.819mil)(4647.638mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4722.441mil,1823.819mil)(4722.441mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4647.638mil,1823.819mil)(4722.441mil,1823.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4647.638mil,1955.709mil)(4685.039mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4647.638mil,1823.819mil)(4647.638mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4722.441mil,1823.819mil)(4722.441mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,1955.709mil)(4722.441mil,1955.709mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4658.465mil,1438.976mil)(4658.465mil,1513.78mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4658.465mil,1438.976mil)(4790.354mil,1438.976mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4658.465mil,1513.78mil)(4790.354mil,1513.78mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4790.354mil,1438.976mil)(4790.354mil,1476.378mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4790.354mil,1476.378mil)(4790.354mil,1513.78mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4658.465mil,1438.976mil)(4790.354mil,1438.976mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4658.465mil,1513.78mil)(4790.354mil,1513.78mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1541.339mil)(4662.401mil,1608.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1541.339mil)(4786.417mil,1541.339mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1608.268mil)(4786.417mil,1608.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4786.417mil,1541.339mil)(4786.417mil,1608.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1541.339mil)(4786.417mil,1541.339mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1608.268mil)(4786.417mil,1608.268mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,899.606mil)(4670.276mil,948.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,899.606mil)(4776.575mil,899.606mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,948.819mil)(4776.575mil,948.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,899.606mil)(4776.575mil,948.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,899.606mil)(4776.575mil,899.606mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,948.819mil)(4776.575mil,948.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,958.661mil)(4670.276mil,1007.874mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1007.874mil)(4776.575mil,1007.874mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,958.661mil)(4776.575mil,958.661mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,958.661mil)(4776.575mil,1007.874mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1007.874mil)(4776.575mil,1007.874mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,958.661mil)(4776.575mil,958.661mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1017.716mil)(4670.276mil,1066.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1066.929mil)(4776.575mil,1066.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1017.716mil)(4776.575mil,1017.716mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1017.716mil)(4776.575mil,1066.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1066.929mil)(4776.575mil,1066.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1017.716mil)(4776.575mil,1017.716mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1076.772mil)(4670.276mil,1125.984mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1076.772mil)(4776.575mil,1076.772mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1125.984mil)(4776.575mil,1125.984mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1076.772mil)(4776.575mil,1125.984mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1076.772mil)(4776.575mil,1076.772mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1125.984mil)(4776.575mil,1125.984mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4786.417mil,1698.819mil)(4786.417mil,1765.748mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1698.819mil)(4786.417mil,1698.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1765.748mil)(4786.417mil,1765.748mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1698.819mil)(4662.401mil,1765.748mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1698.819mil)(4786.417mil,1698.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1765.748mil)(4786.417mil,1765.748mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1135.827mil)(4670.276mil,1185.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1135.827mil)(4776.575mil,1135.827mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1185.039mil)(4776.575mil,1185.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1135.827mil)(4776.575mil,1185.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1135.827mil)(4776.575mil,1135.827mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1185.039mil)(4776.575mil,1185.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1620.079mil)(4662.401mil,1687.008mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1620.079mil)(4786.417mil,1620.079mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1687.008mil)(4786.417mil,1687.008mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4786.417mil,1620.079mil)(4786.417mil,1687.008mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1620.079mil)(4786.417mil,1620.079mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4662.401mil,1687.008mil)(4786.417mil,1687.008mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1194.882mil)(4670.276mil,1244.094mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1244.094mil)(4776.575mil,1244.094mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1194.882mil)(4776.575mil,1194.882mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1194.882mil)(4776.575mil,1244.094mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1244.094mil)(4776.575mil,1244.094mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1194.882mil)(4776.575mil,1194.882mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1253.937mil)(4670.276mil,1303.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1303.15mil)(4776.575mil,1303.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1253.937mil)(4776.575mil,1253.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1253.937mil)(4776.575mil,1303.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1303.15mil)(4776.575mil,1303.15mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1253.937mil)(4776.575mil,1253.937mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.276mil,1312.992mil)(4670.276mil,1362.205mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1312.992mil)(4776.575mil,1312.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1362.205mil)(4776.575mil,1362.205mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4776.575mil,1312.992mil)(4776.575mil,1362.205mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1312.992mil)(4776.575mil,1312.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4670.275mil,1362.205mil)(4776.575mil,1362.205mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3816.929mil,1208.661mil)(3816.929mil,1230.315mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3816.929mil,1230.315mil)(3816.929mil,1251.968mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1208.661mil)(3816.929mil,1208.661mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1251.968mil)(3816.929mil,1251.968mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1208.661mil)(3714.567mil,1251.968mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1208.661mil)(3816.929mil,1208.661mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3714.567mil,1251.968mil)(3816.929mil,1251.968mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2805.118mil,656.496mil)(2842.52mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2767.716mil,524.606mil)(2767.716mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2842.52mil,524.606mil)(2842.52mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2767.716mil,656.496mil)(2805.118mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2767.716mil,524.606mil)(2767.716mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2842.52mil,524.606mil)(2842.52mil,656.496mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2767.716mil,524.606mil)(2842.52mil,524.606mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1285.433mil,883.858mil)(1285.433mil,905.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1285.433mil,905.512mil)(1285.433mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,883.858mil)(1285.433mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,927.165mil)(1285.433mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,883.858mil)(1183.071mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,883.858mil)(1285.433mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1183.071mil,927.165mil)(1285.433mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1448.819mil,883.858mil)(1448.819mil,905.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1448.819mil,905.512mil)(1448.819mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1346.457mil,883.858mil)(1448.819mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1346.457mil,927.165mil)(1448.819mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1346.457mil,883.858mil)(1346.457mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1346.457mil,883.858mil)(1448.819mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1346.457mil,927.165mil)(1448.819mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1612.205mil,883.858mil)(1612.205mil,905.512mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1612.205mil,905.512mil)(1612.205mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1509.842mil,883.858mil)(1612.205mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1509.842mil,927.165mil)(1612.205mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1509.842mil,883.858mil)(1509.842mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1509.842mil,883.858mil)(1612.205mil,883.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (1509.842mil,927.165mil)(1612.205mil,927.165mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4684.055mil,698.819mil)(4684.055mil,740.158mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4684.055mil,740.158mil)(4760.827mil,740.158mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4684.055mil,698.819mil)(4760.827mil,698.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4760.827mil,719.488mil)(4760.827mil,740.158mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4760.827mil,698.819mil)(4760.827mil,719.488mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4684.055mil,740.158mil)(4760.827mil,740.158mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4684.055mil,698.819mil)(4760.827mil,698.819mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.858mil < 8mil) Between Track (4510.827mil,569.882mil)(4510.827mil,599.41mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4561.024mil,559.055mil)(4561.024mil,610.236mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,559.055mil)(4561.024mil,559.055mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,610.236mil)(4561.024mil,610.236mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,559.055mil)(4450.787mil,584.646mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,559.055mil)(4561.024mil,559.055mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,610.236mil)(4561.024mil,610.236mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,584.646mil)(4450.787mil,610.236mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.858mil < 8mil) Between Track (4510.827mil,483.268mil)(4510.827mil,512.795mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4561.024mil,472.441mil)(4561.024mil,523.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,472.441mil)(4561.024mil,472.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,523.622mil)(4561.024mil,523.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,472.441mil)(4450.787mil,498.032mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,472.441mil)(4561.024mil,472.441mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,523.622mil)(4561.024mil,523.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (5.906mil < 8mil) Between Track (4450.787mil,498.032mil)(4450.787mil,523.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4876.968mil,512.795mil)(4876.968mil,579.725mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4876.968mil,512.795mil)(5000.984mil,512.795mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4876.968mil,579.725mil)(5000.984mil,579.725mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (5000.984mil,512.795mil)(5000.984mil,579.725mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4876.968mil,512.795mil)(5000.984mil,512.795mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (3.937mil < 8mil) Between Track (4876.968mil,579.725mil)(5000.984mil,579.725mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4761.811mil,342.52mil)(4761.811mil,383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,342.52mil)(4761.811mil,342.52mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,383.858mil)(4761.811mil,383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,342.52mil)(4685.039mil,363.189mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,363.189mil)(4685.039mil,383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,342.52mil)(4761.811mil,342.52mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4685.039mil,383.858mil)(4761.811mil,383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,413.386mil)(4672.244mil,435.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,391.733mil)(4672.244mil,413.386mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,435.039mil)(4774.606mil,435.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,391.733mil)(4774.606mil,391.733mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4774.606mil,391.733mil)(4774.606mil,435.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,435.039mil)(4774.606mil,435.039mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4672.244mil,391.733mil)(4774.606mil,391.733mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4773.622mil,648.622mil)(4773.622mil,670.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4773.622mil,670.276mil)(4773.622mil,691.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4671.26mil,648.622mil)(4773.622mil,648.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4671.26mil,691.929mil)(4773.622mil,691.929mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4671.26mil,648.622mil)(4671.26mil,691.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4671.26mil,648.622mil)(4773.622mil,648.622mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (4671.26mil,691.929mil)(4773.622mil,691.929mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3267.716mil,2045.276mil)(3289.37mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3246.063mil,1942.914mil)(3246.063mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3289.37mil,1942.914mil)(3289.37mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3246.063mil,2045.276mil)(3267.716mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3246.063mil,1942.914mil)(3246.063mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3289.37mil,1942.914mil)(3289.37mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3246.063mil,1942.914mil)(3289.37mil,1942.914mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3059.055mil,2045.276mil)(3080.709mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3059.055mil,1942.914mil)(3059.055mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3102.362mil,1942.914mil)(3102.362mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3080.709mil,2045.276mil)(3102.362mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3059.055mil,1942.914mil)(3059.055mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3102.362mil,1942.914mil)(3102.362mil,2045.276mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3059.055mil,1942.914mil)(3102.362mil,1942.914mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3275.591mil,710.63mil)(3297.244mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3297.244mil,710.63mil)(3318.898mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3275.591mil,710.63mil)(3275.591mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3318.898mil,710.63mil)(3318.898mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3275.591mil,812.992mil)(3318.898mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3275.591mil,710.63mil)(3275.591mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3318.898mil,710.63mil)(3318.898mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3068.898mil,710.63mil)(3068.898mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3112.205mil,710.63mil)(3112.205mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3068.898mil,710.63mil)(3090.551mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3090.551mil,710.63mil)(3112.205mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3068.898mil,710.63mil)(3068.898mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3112.205mil,710.63mil)(3112.205mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3068.898mil,812.992mil)(3112.205mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2812.992mil,710.63mil)(2834.646mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2812.992mil,710.63mil)(2812.992mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2856.299mil,710.63mil)(2856.299mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2834.646mil,710.63mil)(2856.299mil,710.63mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2812.992mil,710.63mil)(2812.992mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2856.299mil,710.63mil)(2856.299mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2812.992mil,812.992mil)(2856.299mil,812.992mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2629.921mil,1828.74mil)(2629.921mil,1850.394mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2629.921mil,1850.394mil)(2629.921mil,1872.047mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2527.559mil,1828.74mil)(2629.921mil,1828.74mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2527.559mil,1872.047mil)(2629.921mil,1872.047mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2527.559mil,1828.74mil)(2527.559mil,1872.047mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2527.559mil,1828.74mil)(2629.921mil,1828.74mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (2527.559mil,1872.047mil)(2629.921mil,1872.047mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3638.78mil,2383.858mil)(3638.78mil,2458.662mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2383.858mil)(3638.78mil,2383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2458.662mil)(3638.78mil,2458.662mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2383.858mil)(3506.89mil,2421.26mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2421.26mil)(3506.89mil,2458.662mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2383.858mil)(3638.78mil,2383.858mil) on Top Overlay And Pad

Silk To Solder Mask Clearance Constraint: (7.874mil < 8mil) Between Track (3506.89mil,2458.662mil)(3638.78mil,2458.662mil) on Top Overlay And Pad

Silk To Solder Mask (Clearance=8mil) (IsPad),(All)

Silk To Solder Mask Clearance Constraint: (Collision < 8mil) Between Text "U100" (2696.85mil,1771.654mil) on Top Overlay And Pad

Minimum Solder Mask Sliver (Gap=6mil) (All),(All)
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-7(2555.118mil,2796.26mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-6(2555.118mil,2776.575mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-5(2555.118mil,2756.89mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-4(2444.882mil,2756.89mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-2(2444.882mil,2796.26mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad U203-1(2444.882mil,2815.945mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.858mil < 6mil) Between Pad U203-9(2500mil,2785.433mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-2(1093.504mil,3187.992mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-3(1093.504mil,3162.402mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-4(1093.504mil,3136.811mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-5(1093.504mil,3111.22mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-6(1093.504mil,3085.63mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-11(1268.701mil,3187.992mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-10(1268.701mil,3162.402mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-9(1268.701mil,3136.811mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-8(1268.701mil,3111.22mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U200-7(1268.701mil,3085.63mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad R308-1(4739.173mil,719.488mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (3.843mil < 6mil) Between Pad R303-1(4706.693mil,363.189mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-2(4635.827mil,555.118mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-3(4635.827mil,529.528mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-4(4635.827mil,503.937mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-7(4809.055mil,555.118mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-6(4809.055mil,529.528mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.662mil < 6mil) Between Pad U302-5(4809.055mil,503.937mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-143(2824.803mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-142(2844.488mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-141(2864.173mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-140(2883.858mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-139(2903.543mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-138(2923.228mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-137(2942.913mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-136(2962.598mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-135(2982.284mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-134(3001.968mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-133(3021.653mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-132(3041.339mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-131(3061.024mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-130(3080.709mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-129(3100.394mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-128(3120.079mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-127(3139.764mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-126(3159.449mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-125(3179.134mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-124(3198.819mil,1804.134mil) on Top Layer And Pad

Minimum Solder Mask Sliver (Gap=6mil) (All),(All)

Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-123(3218.504mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-122(3238.189mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-121(3257.874mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-120(3277.559mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-119(3297.244mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-118(3316.929mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-117(3336.614mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-116(3356.299mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-115(3375.984mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-114(3395.669mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-113(3415.354mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-112(3435.039mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-111(3454.724mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-110(3474.41mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-109(3494.095mil,1804.134mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-107(3575.787mil,1702.756mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-106(3575.787mil,1683.071mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-105(3575.787mil,1663.386mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-104(3575.787mil,1643.701mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-103(3575.787mil,1624.016mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-102(3575.787mil,1604.331mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-101(3575.787mil,1584.646mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-100(3575.787mil,1564.961mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-99(3575.787mil,1545.276mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-98(3575.787mil,1525.591mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-97(3575.787mil,1505.906mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-96(3575.787mil,1486.22mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-95(3575.787mil,1466.535mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-94(3575.787mil,1446.85mil) on Top Layer And Pad
Minimum Solder Mask Sliver Constraint: (2.071mil < 6mil) Between Pad U100-93(3575.787mil,1427.165mil) on Top Layer And Pad