```
--LG11 View1
create or replace view find total
select c.cid, custname, custsurname, sum(quantity) "#of items bought"
from cust c, receipt r, receipt_details rd
where c.CID = r.cid and r.rid = rd.rid
group by c.cid, custname, custsurname;
select *
from find_total;
--LG11 View2
create or replace view product_report
select p.pid, pname, sum(quantity) "#ofSold"
from product p, receipt r, receipt_details rd
where rd.pid = p.pid and r.rid = rd.rid
group by p.pid, pname
order by p.pid, pname;
select *
from product_report;
--LG11 Function
create or replace function market_coupon
RETURN NUMBER
IS
 CURSOR market_cursor IS
  select c.cid, custname, custsurname, sum(total) TotalAmount
  from cust c, receipt r
 where c.CID = r.cid
 group by c.cid, custname, custsurname;
 m_rec market_cursor%ROWTYPE;
  coupon number(6,2);
 noOfCoupons number(3) := 0;
  FOR m_rec IN market_cursor LOOP
   CASE
   WHEN m_rec.totalamount >= 300 THEN
    coupon := m_rec.totalamount * 0.20;
    noOfCoupons := noOfCoupons+1;
   WHEN m_rec.totalamount >= 200 THEN
    coupon := m_rec.totalamount * 0.10;
    noOfCoupons := noOfCoupons+1;
   WHEN m_rec.totalamount >= 100 THEN
    coupon := m_rec.totalamount * 0.05;
    noOfCoupons := noOfCoupons+1;
   ELSE
      coupon := 0;
    END CASE;
    DBMS_OUTPUT_PUT_LINE(m_rec.cid||' '||m_rec.custname||' '||m_rec.custsurname||': your total shopping
amount is: '||m_rec.totalamount);
    --you may display a new line using CHR(10) in DBMS_OUTPUT.PUT_LINE function
    IF coupon = 0 THEN
      DBMS_OUTPUT.PUT_LINE('Your total shopping amount is < 100, sorry!'||CHR(10));
    ELSE
      DBMS_OUTPUT.PUT_LINE('YOU WON '||coupon||' TL MARKET COUPON :)'||CHR(10));
    END IF;
  END LOOP;
 RETURN noOfCoupons;
END;
SET SERVEROUTPUT ON;
BEGIN
 DBMS_OUTPUT.PUT_LINE('Total number of coupons: '||market_coupon());
END;
/
```