

User Requirements Specification - T-101

Document No.	URS-T101-001	Revision	01
System	Solution Preparation Tank T-101	Status	Approved - Training
Project	Otrivin Nasal Spray Facility - Synthetic Case	Purpose	RAG/C&Q Training

Training disclaimer: This is a fictional, simplified document set created solely for education. It does not describe or reproduce the actual manufacturing process, specifications, or controlled records for Otrivin.

1. Objective

Define the user requirements to be verified through design review, FAT, IQ and OQ.

Requirements

ID	Topic	Requirement	Class
URS-001	Working volume	T-101 shall provide a nominal working volume of 1,000 L.	Critical
URS-002	Product contact material	Product-contact metallic surfaces shall be 316L stainless steel.	Critical
URS-003	Surface finish	Product-contact stainless-steel surfaces shall have Ra <= 0.8 µm.	Critical
URS-004	Agitator speed	Agitator operating range shall be 50-300 rpm.	Critical
URS-005	Temperature	Product temperature shall be monitored over 15-30 °C.	Critical
URS-006	Temperature accuracy	TT-101 measurement accuracy shall be +/-0.5 °C or better.	Critical
URS-007	Level indication	Tank shall provide continuous level indication from 0-100%.	Major
URS-008	High-level alarm	A high-level alarm shall activate at 90% level.	Critical
URS-009	Drainability	Tank and product outlet shall be designed for complete gravity drainability.	Critical
URS-010	CIP	Tank shall support an automated CIP cycle.	Critical
URS-011	Recipe control	PLC shall provide controlled mixing recipe steps and setpoints.	Major
URS-012	Audit trail	Changes to GMP-relevant recipe parameters shall be attributable and recorded.	Critical
URS-013	Emergency stop	Local emergency stop shall stop agitator operation.	Critical
URS-014	Calibration	Critical instruments shall have current calibration before qualification execution.	Critical
URS-015	Documentation	Approved drawings, manuals and material certificates shall be available before IQ completion.	Major