

```
mit-macbookpro2:f mit$ git log -p
commit 26f32f6510e44b5c395febcd5b142476e4cd4497
Author: Michael Thomsen <mit@google.com>
Date: Wed Oct 5 14:20:33 2016 +0200
```

Files changes when creating a Flutter run/debug config

```
diff --git a/.idea/workspace.xml b/.idea/workspace.xml
index 274d952..2a239a4 100644
--- a/.idea/workspace.xml
+++ b/.idea/workspace.xml
@@ -1,9 +1,7 @@
<?xml version="1.0" encoding="UTF-8"?>
<project version="4">
  <component name="ChangeListManager">
-   <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="">
-     <change type="MODIFICATION" beforePath="$PROJECT_DIR$/.idea/f.iml" afterPath="$PROJECT_DIR$/.idea/f.iml" />
-   </list>
+   <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="" />
+   <ignored path="f.iws" />
+   <ignored path=".idea/workspace.xml" />
+   <ignored path=".idea/dataSources.local.xml" />
@@ -26,8 +24,8 @@
  <file leaf-file-name="main.dart" pinned="false" current-in-tab="true">
    <entry file="file://$PROJECT_DIR$/lib/main.dart">
      <provider selected="true" editor-type-id="text-editor">
-       <state relative-caret-position="0">
-         <caret line="0" column="0" selection-start-line="0" selection-start-column="0" selection-end-line="0" selection-end-column="0" />
+       <state relative-caret-position="170">
+         <caret line="10" column="6" selection-start-line="10" selection-start-column="6" selection-end-line="10" selection-end-
column="6" />
        <folding />
      </state>
    </provider>
@@ -127,7 +125,7 @@
    <property name="WebServerToolWindowFactoryState" value="false" />
    <property name="dart.analysis.tool.window.force.activate" value="false" />
  </component>
- <component name="RunManager">
+ <component name="RunManager" selected="Flutter.Flutter">
  <configuration default="true" type="#org.jetbrains.idea.devkit.run.PluginConfigurationType" factoryName="Plugin">
    <module name="" />
    <option name="VM_PARAMETERS" value="-Xmx512m -Xms256m -XX:MaxPermSize=250m -ea" />
@@ -157,6 +155,9 @@
```

```
<envs />
<method />
</configuration>
+ <configuration default="true" type="FlutterRunConfigurationType" factoryName="Flutter">
+   <method />
+ </configuration>
<configuration default="true" type="JUnit" factoryName="JUnit">
  <extension name="coverage" enabled="false" merge="false" sample_coverage="true" runner="idea" />
  <module name="" />
@@ -214,6 +215,13 @@
  <listeners />
  <method />
</configuration>
+ <configuration default="false" name="Flutter" type="FlutterRunConfigurationType" factoryName="Flutter">
+   <option name="filePath" value="$PROJECT_DIR$/lib/main.dart" />
+   <method />
+ </configuration>
+ <list size="1">
+   <item index="0" class="java.lang.String" itemvalue="Flutter.Flutter" />
+ </list>
</component>
<component name="ShelveChangesManager" show_recycled="false">
  <option name="remove_strategy" value="false" />
@@ -226,12 +234,12 @@
  <option name="presentableId" value="Default" />
  <updated>1475669512810</updated>
  <workItem from="1475669514038" duration="13000" />
-   <workItem from="1475669682548" duration="125000" />
+   <workItem from="1475669682548" duration="321000" />
</task>
<servers />
</component>
<component name="TimeTrackingManager">
-   <option name="totallyTimeSpent" value="138000" />
+   <option name="totallyTimeSpent" value="334000" />
</component>
<component name="ToolWindowManager">
  <frame x="1213" y="23" width="1280" height="1573" extended-state="0" />
@@ -282,8 +290,8 @@
<component name="editorHistoryManager">
  <entry file="file://$PROJECT_DIR$/lib/main.dart">
    <provider selected="true" editor-type-id="text-editor">
-     <state relative-caret-position="0">
-     <caret line="0" column="0" selection-start-line="0" selection-start-column="0" selection-end-line="0" selection-end-column="0" />
```

```
+     <state relative-caret-position="170">
+       <caret line="10" column="6" selection-start-line="10" selection-start-column="6" selection-end-line="10" selection-end-column="6" />
+       <folding />
+     </state>
+   </provider>
```

commit 3d57d36a4efe2ceca9a777662bb5e58c34cf22eb

Author: Michael Thomsen <mit@google.com>

Date: Wed Oct 5 14:17:41 2016 +0200

Files changes when enabling Dart support

```
diff --git a/.idea/f.iml b/.idea/f.iml
```

```
index 2bc162d..57cb72d 100644
```

```
--- a/.idea/f.iml
```

```
+++ b/.idea/f.iml
```

```
@@ -7,5 +7,7 @@
```

```
    </content>
```

```
    <orderEntry type="inheritedJdk" />
```

```
    <orderEntry type="sourceFolder" forTests="false" />
```

```
+    <orderEntry type="library" name="Dart SDK" level="application" />
```

```
+    <orderEntry type="library" name="Dart Packages" level="project" />
```

```
  </component>
```

```
</module>
```

```
\ No newline at end of file
```

```
diff --git a/.idea/libraries/Dart_Packages.xml b/.idea/libraries/Dart_Packages.xml
```

```
new file mode 100644
```

```
index 0000000..cb102dc
```

```
--- /dev/null
```

```
+++ b/.idea/libraries/Dart_Packages.xml
```

```
@@ -0,0 +1,148 @@
```

```
+<component name="libraryTable">
```

```
+  <library name="Dart Packages" type="DartPackagesLibraryType">
```

```
+    <properties>
```

```
+      <option name="packageNameToDirsMap">
```

```
+        <entry key="async">
```

```
+          <value>
```

```
+            <list>
```

```
+              <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/async-1.11.2/lib" />
```

```
+            </list>
```

```
+          </value>
```

```
+        </entry>
```

```
+        <entry key="charcode">
```

```
+          <value>
```

```
+      <list>
+        <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/charcode-1.1.0/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="collection">
+    <value>
+      <list>
+        <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/collection-1.9.1/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="flutter">
+    <value>
+      <list>
+        <option value="$USER_HOME$/dev/github/flutter/packages/flutter/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="flutter_services">
+    <value>
+      <list>
+        <option value="$USER_HOME$/dev/github/flutter/bin/cache/pkg/flutter_services/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="http_parser">
+    <value>
+      <list>
+        <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/http_parser-3.0.2/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="intl">
+    <value>
+      <list>
+        <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/intl-0.14.0/lib" />
+      </list>
+    </value>
+  </entry>
+  <entry key="meta">
+    <value>
+      <list>
+        <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/meta-1.0.4/lib" />
+      </list>
+    </value>
+  </entry>
```

```
+     </list>
+   </value>
+ </entry>
+ <entry key="mojo">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo-0.4.27/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="mojo_sdk">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo_sdk-0.2.31/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="mojo_services">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo_services-0.4.34/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="path">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/path-1.3.9/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="sky_engine">
+   <value>
+     <list>
+       <option value="$USER_HOME$/dev/github/flutter/bin/cache/pkg/sky_engine/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="sky_services">
+   <value>
+     <list>
+       <option value="$USER_HOME$/dev/github/flutter/bin/cache/pkg/sky_services/lib" />
+     </list>
+   </value>
+ </entry>
```

```
+ </entry>
+ <entry key="source_span">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/source_span-1.2.3/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="string_scanner">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/string_scanner-1.0.0/lib" />
+     </list>
+   </value>
+ </entry>
+ <entry key="vector_math">
+   <value>
+     <list>
+       <option value="$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/vector_math-2.0.3/lib" />
+     </list>
+   </value>
+ </entry>
+ </option>
+ </properties>
+ <CLASSES>
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/async-1.11.2/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/charcode-1.1.0/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/collection-1.9.1/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/http_parser-3.0.2/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/intl-0.14.0/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/meta-1.0.4/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo-0.4.27/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo_sdk-0.2.31/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/mojo_services-0.4.34/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/path-1.3.9/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/source_span-1.2.3/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/string_scanner-1.0.0/lib" />
+   <root url="file://$USER_HOME$/.pub-cache/hosted/pub.dartlang.org/vector_math-2.0.3/lib" />
+   <root url="file://$USER_HOME$/dev/github/flutter/bin/cache/pkg/flutter_services/lib" />
+   <root url="file://$USER_HOME$/dev/github/flutter/bin/cache/pkg/sky_engine/lib" />
+   <root url="file://$USER_HOME$/dev/github/flutter/bin/cache/pkg/sky_services/lib" />
+   <root url="file://$USER_HOME$/dev/github/flutter/packages/flutter/lib" />
+ </CLASSES>
+ <JAVADOC />
```

```
+ <SOURCES />
+ </library>
+</component>
\ No newline at end of file
diff --git a/.idea/workspace.xml b/.idea/workspace.xml
index 1cafc3a..274d952 100644
--- a/.idea/workspace.xml
+++ b/.idea/workspace.xml
@@ -1,7 +1,9 @@
<?xml version="1.0" encoding="UTF-8"?>
<project version="4">
  <component name="ChangeListManager">
-   <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="" />
+   <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="">
+     <change type="MODIFICATION" beforePath="$PROJECT_DIR$/.idea/f.iml" afterPath="$PROJECT_DIR$/.idea/f.iml" />
+   </list>
    <ignored path="f.iws" />
    <ignored path=".idea/workspace.xml" />
    <ignored path=".idea/dataSources.local.xml" />
@@ -24,8 +26,8 @@
    <file leaf-file-name="main.dart" pinned="false" current-in-tab="true">
      <entry file="file://$PROJECT_DIR$/lib/main.dart">
        <provider selected="true" editor-type-id="text-editor">
-         <state relative-caret-position="153">
-           <caret line="9" column="30" selection-start-line="9" selection-start-column="30" selection-end-line="9" selection-end-
column="30" />
+         <state relative-caret-position="0">
+           <caret line="0" column="0" selection-start-line="0" selection-start-column="0" selection-end-line="0" selection-end-column="0" />
          <folding />
        </state>
      </provider>
@@ -123,6 +125,7 @@
    <property name="aspect.path.notification.shown" value="true" />
    <property name="last_opened_file_path" value="$PROJECT_DIR$" />
    <property name="WebServerToolWindowFactoryState" value="false" />
+   <property name="dart.analysis.tool.window.force.activate" value="false" />
  </component>
  <component name="RunManager">
    <configuration default="true" type="#org.jetbrains.idea.devkit.run.PluginConfigurationType" factoryName="Plugin">
@@ -223,12 +226,12 @@
    <option name="presentableId" value="Default" />
    <updated>1475669512810</updated>
    <workItem from="1475669514038" duration="13000" />
-   <workItem from="1475669682548" duration="50000" />
```

```

+   <workItem from="1475669682548" duration="125000" />
  </task>
  <servers />
</component>
<component name="TimeTrackingManager">
-   <option name="totallyTimeSpent" value="63000" />
+   <option name="totallyTimeSpent" value="138000" />
</component>
<component name="ToolWindowManager">
  <frame x="1213" y="23" width="1280" height="1573" extended-state="0" />
@@ -240,6 +243,7 @@
  <window_info id="Capture Analysis" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
  <window_info id="Event Log" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="7" side_tool="true" content_ui="tabs" />
  <window_info id="Maven Projects" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
+   <window_info id="Dart Analysis" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="true"
show_stripe_button="true" weight="0.32978722" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
  <window_info id="Run" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="2" side_tool="false" content_ui="tabs" />
  <window_info id="Version Control" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="7" side_tool="false" content_ui="tabs" />
  <window_info id="Terminal" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="7" side_tool="false" content_ui="tabs" />
@@ -278,8 +282,8 @@
  <component name="editorHistoryManager">
    <entry file="file://$PROJECT_DIR$/lib/main.dart">
      <provider selected="true" editor-type-id="text-editor">
-        <state relative-caret-position="153">
-          <caret line="9" column="30" selection-start-line="9" selection-start-column="30" selection-end-line="9" selection-end-column="30" />
+        <state relative-caret-position="0">
+          <caret line="0" column="0" selection-start-line="0" selection-start-column="0" selection-end-line="0" selection-end-column="0" />
        <folding />
      </state>
    </provider>

```

commit 818c8ad6e1f945009bcab7d5937464d3ef7a6930

Author: Michael Thomsen <mit@google.com>

Date: Wed Oct 5 14:16:25 2016 +0200

Files changes when opening lib/main.dart

diff --git a/.idea/workspace.xml b/.idea/workspace.xml


```
index 1a73fa8..1cafc3a 100644
--- a/.idea/workspace.xml
+++ b/.idea/workspace.xml
@@ -4,6 +4,7 @@
   <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="" />
   <ignored path="f.iws" />
   <ignored path=".idea/workspace.xml" />
+  <ignored path=".idea/dataSources.local.xml" />
   <option name="EXCLUDED_CONVERTED_TO_IGNORED" value="true" />
   <option name="TRACKING_ENABLED" value="true" />
   <option name="SHOW_DIALOG" value="false" />
@@ -18,6 +19,20 @@
 <component name="FavoritesManager">
   <favorites_list name="f" />
 </component>
+ <component name="FileEditorManager">
+   <leaf>
+     <file leaf-file-name="main.dart" pinned="false" current-in-tab="true">
+       <entry file="file://$PROJECT_DIR$/lib/main.dart">
+         <provider selected="true" editor-type-id="text-editor">
+           <state relative-caret-position="153">
+             <caret line="9" column="30" selection-start-line="9" selection-start-column="30" selection-end-
column="30" />
+           <folding />
+         </state>
+       </provider>
+     </entry>
+   </file>
+ </leaf>
+ </component>
 <component name="Git.Settings">
   <option name="RECENT_GIT_ROOT_PATH" value="$PROJECT_DIR$" />
 </component>
@@ -73,6 +88,30 @@
   <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.ProjectViewProjectNode" />
 </PATH_ELEMENT>
 </PATH>
+ <PATH>
+   <PATH_ELEMENT>
+     <option name="myItemId" value="f" />
+     <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.ProjectViewProjectNode" />
+   </PATH_ELEMENT>
+   <PATH_ELEMENT>
+     <option name="myItemId" value="f" />
```

```

+         <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.PsiDirectoryNode" />
+     </PATH_ELEMENT>
+ </PATH>
+ <PATH>
+     <PATH_ELEMENT>
+         <option name="myItemId" value="f" />
+         <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.ProjectViewProjectNode" />
+     </PATH_ELEMENT>
+     <PATH_ELEMENT>
+         <option name="myItemId" value="f" />
+         <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.PsiDirectoryNode" />
+     </PATH_ELEMENT>
+     <PATH_ELEMENT>
+         <option name="myItemId" value="lib" />
+         <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.PsiDirectoryNode" />
+     </PATH_ELEMENT>
+ </PATH>
+ </subPane>
+ </pane>
+ <pane id="Scratches" />
@@ -184,16 +223,16 @@
+     <option name="presentableId" value="Default" />
+     <updated>1475669512810</updated>
+     <workItem from="1475669514038" duration="13000" />
-     <workItem from="1475669682548" duration="2000" />
+     <workItem from="1475669682548" duration="50000" />
+ </task>
+ <servers />
+ </component>
+ <component name="TimeTrackingManager">
-     <option name="totallyTimeSpent" value="15000" />
+     <option name="totallyTimeSpent" value="63000" />
+ </component>
+ <component name="ToolWindowManager">
+     <frame x="1213" y="23" width="1280" height="1573" extended-state="0" />
-     <editor active="false" />
+     <editor active="true" />
+     <layout>
+         <window_info id="Palette" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
+         <window_info id="TODO" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="6" side_tool="false" content_ui="tabs" />
@@ -206,7 +245,7 @@
+     <window_info id="Terminal" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"

```

```
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="7" side_tool="false" content_ui="tabs" />
  <window_info id="Capture Tool" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="2" side_tool="false" content_ui="tabs" />
  <window_info id="Designer" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
-   <window_info id="Project" active="true" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="true"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="0" side_tool="false" content_ui="combo" />
+   <window_info id="Project" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="true"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="0" side_tool="false" content_ui="combo" />
  <window_info id="Database" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
  <window_info id="Structure" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
  <window_info id="Ant Build" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
@@ -236,4 +275,14 @@
  <breakpoint-manager />
  <watches-manager />
</component>
+ <component name="editorHistoryManager">
+   <entry file="file://$PROJECT_DIR$/lib/main.dart">
+     <provider selected="true" editor-type-id="text-editor">
+       <state relative-caret-position="153">
+         <caret line="9" column="30" selection-start-line="9" selection-start-column="30" selection-end-line="9" selection-end-column="30" />
+       <folding />
+     </state>
+   </provider>
+ </entry>
+ </component>
</project>
\ No newline at end of file

commit 02d5a80188a719e5c7083fc73ee2fe0a408cb08a
Author: Michael Thomsen <mit@google.com>
Date:   Wed Oct 5 14:15:21 2016 +0200

    Files changes on second IJ open

diff --git a/.idea/workspace.xml b/.idea/workspace.xml
index 2a0d915..1a73fa8 100644
--- a/.idea/workspace.xml
+++ b/.idea/workspace.xml
@@ -34,7 +34,7 @@
</component>
```

```
<component name="ProjectFrameBounds">
  <option name="x" value="1213" />
-  <option name="y" value="119" />
+  <option name="y" value="23" />
  <option name="width" value="1280" />
  <option name="height" value="1573" />
</component>
@@ -63,7 +63,6 @@
  <foldersAlwaysOnTop value="true" />
</navigator>
<panes>
-  <pane id="Scratches" />
  <pane id="Scope" />
  <pane id="PackagesPane" />
  <pane id="ProjectPane">
@@ -76,6 +75,7 @@
    </PATH>
  </subPane>
</pane>
+  <pane id="Scratches" />
</panes>
</component>
<component name="PropertiesComponent">
@@ -184,40 +184,41 @@
  <option name="presentableId" value="Default" />
  <updated>1475669512810</updated>
  <workItem from="1475669514038" duration="13000" />
+  <workItem from="1475669682548" duration="2000" />
</task>
<servers />
</component>
<component name="TimeTrackingManager">
-  <option name="totallyTimeSpent" value="13000" />
+  <option name="totallyTimeSpent" value="15000" />
</component>
<component name="ToolWindowManager">
-  <frame x="1213" y="119" width="1280" height="1573" extended-state="0" />
+  <frame x="1213" y="23" width="1280" height="1573" extended-state="0" />
  <editor active="false" />
  <layout>
-  <window_info id="Palette" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+  <window_info id="Palette" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
```



```
<window_info id="Ant Build" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
- <window_info id="UI Designer" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="UI Designer" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="2" side_tool="false" content_ui="tabs" />
<window_info id="Debug" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
- <window_info id="Favorites" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="true" content_ui="tabs" />
+ <window_info id="Favorites" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="2" side_tool="true" content_ui="tabs" />
<window_info id="Cvs" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="4" side_tool="false" content_ui="tabs" />
- <window_info id="Hierarchy" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="2" side_tool="false" content_ui="combo" />
<window_info id="Message" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="0" side_tool="false" content_ui="tabs" />
<window_info id="Commander" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="0" side_tool="false" content_ui="tabs" />
- <window_info id="Find" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
<window_info id="Inspection" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="5" side_tool="false" content_ui="tabs" />
+ <window_info id="Hierarchy" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="2" side_tool="false" content_ui="combo" />
+ <window_info id="Find" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
</layout>
</component>
<component name="Vcs.Log.UiProperties">
```

commit 0e8e7a4fda5a41a3701a0c0415336fb232ed424c

Author: Michael Thomsen <mit@google.com>

Date: Wed Oct 5 14:13:05 2016 +0200

Files created on first IJ open

```
diff --git a/.idea/compiler.xml b/.idea/compiler.xml
```

```
new file mode 100644
```

```
index 0000000..96cc43e
```

```
--- /dev/null
```

```
+++ b/.idea/compiler.xml
```

```
@@ -0,0 +1,22 @@
```

```
+<?xml version="1.0" encoding="UTF-8"?>
+<project version="4">
+  <component name="CompilerConfiguration">
+    <resourceExtensions />
+    <wildcardResourcePatterns>
+      <entry name="!*.*.java" />
+      <entry name="!*.*.form" />
+      <entry name="!*.*.class" />
+      <entry name="!*.*.groovy" />
+      <entry name="!*.*.scala" />
+      <entry name="!*.*.flex" />
+      <entry name="!*.*.kt" />
+      <entry name="!*.*.clj" />
+      <entry name="!*.*.aj" />
+    </wildcardResourcePatterns>
+    <annotationProcessing>
+      <profile default="true" name="Default" enabled="false">
+        <processorPath useClasspath="true" />
+      </profile>
+    </annotationProcessing>
+  </component>
+</project>
\ No newline at end of file
diff --git a/.idea/copyright/profiles_settings.xml b/.idea/copyright/profiles_settings.xml
new file mode 100644
index 0000000..e7bedf3
--- /dev/null
+++ b/.idea/copyright/profiles_settings.xml
@@ -0,0 +1,3 @@
+<component name="CopyrightManager">
+  <settings default="" />
+</component>
\ No newline at end of file
diff --git a/.idea/f.iml b/.idea/f.iml
new file mode 100644
index 0000000..2bc162d
--- /dev/null
+++ b/.idea/f.iml
@@ -0,0 +1,11 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<module type="JAVA_MODULE" version="4">
+  <component name="NewModuleRootManager" inherit-compiler-output="true">
+    <exclude-output />
+    <content url="file://$MODULE_DIR$">
```



```
+     <excludeFolder url="file://$MODULE_DIR$/packages" />
+   </content>
+   <orderEntry type="inheritedJdk" />
+   <orderEntry type="sourceFolder" forTests="false" />
+ </component>
+</module>
\ No newline at end of file
diff --git a/.idea/misc.xml b/.idea/misc.xml
new file mode 100644
index 0000000..6f95f4b
--- /dev/null
+++ b/.idea/misc.xml
@@ -0,0 +1,36 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<project version="4">
+  <component name="MavenImportPreferences">
+    <option name="generalSettings">
+      <MavenGeneralSettings>
+        <option name="mavenHome" value="Bundled (Maven 3)" />
+      </MavenGeneralSettings>
+    </option>
+  </component>
+  <component name="ProjectLevelVcsManager" settingsEditedManually="false">
+    <OptionsSetting value="true" id="Add" />
+    <OptionsSetting value="true" id="Remove" />
+    <OptionsSetting value="true" id="Checkout" />
+    <OptionsSetting value="true" id="Update" />
+    <OptionsSetting value="true" id="Status" />
+    <OptionsSetting value="true" id="Edit" />
+    <ConfirmationsSetting value="0" id="Add" />
+    <ConfirmationsSetting value="0" id="Remove" />
+  </component>
+  <component name="ProjectRootManager" version="2" languageLevel="JDK_1_3" default="true" assert-keyword="false" jdk-15="false" />
+  <component name="masterDetails">
+    <states>
+      <state key="ProjectJDKs.UI">
+        <settings>
+          <splitter-proportions>
+            <option name="proportions">
+              <list>
+                <option value="0.2" />
+              </list>
+            </option>
+          </splitter-proportions>

```



```
+     </settings>
+     </state>
+   </states>
+ </component>
+</project>
\ No newline at end of file
diff --git a/.idea/modules.xml b/.idea/modules.xml
new file mode 100644
index 0000000..3b5e351
--- /dev/null
+++ b/.idea/modules.xml
@@ -0,0 +1,8 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<project version="4">
+  <component name="ProjectModuleManager">
+    <modules>
+      <module fileurl="file://$PROJECT_DIR$/.idea/f.iml" filepath="$PROJECT_DIR$/.idea/f.iml" />
+    </modules>
+  </component>
+</project>
\ No newline at end of file
diff --git a/.idea/vcs.xml b/.idea/vcs.xml
new file mode 100644
index 0000000..35eb1dd
--- /dev/null
+++ b/.idea/vcs.xml
@@ -0,0 +1,6 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<project version="4">
+  <component name="VcsDirectoryMappings">
+    <mapping directory="" vcs="Git" />
+  </component>
+</project>
\ No newline at end of file
diff --git a/.idea/workspace.xml b/.idea/workspace.xml
new file mode 100644
index 0000000..2a0d915
--- /dev/null
+++ b/.idea/workspace.xml
@@ -0,0 +1,238 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<project version="4">
+  <component name="ChangeListManager">
+    <list default="true" id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="" />

```

```
+ <ignored path="f.iws" />
+ <ignored path=".idea/workspace.xml" />
+ <option name="EXCLUDED_CONVERTED_TO_IGNORED" value="true" />
+ <option name="TRACKING_ENABLED" value="true" />
+ <option name="SHOW_DIALOG" value="false" />
+ <option name="HIGHLIGHT_CONFLICTS" value="true" />
+ <option name="HIGHLIGHT_NON_ACTIVE_CHANGELIST" value="false" />
+ <option name="LAST_RESOLUTION" value="IGNORE" />
+ </component>
+ <component name="CreatePatchCommitExecutor">
+   <option name="PATCH_PATH" value="" />
+ </component>
+ <component name="ExecutionTargetManager" SELECTED_TARGET="default_target" />
+ <component name="FavoritesManager">
+   <favorites_list name="f" />
+ </component>
+ <component name="Git.Settings">
+   <option name="RECENT_GIT_ROOT_PATH" value="$PROJECT_DIR$" />
+ </component>
+ <component name="GradleLocalSettings">
+   <option name="externalProjectsViewState">
+     <projects_view />
+   </option>
+ </component>
+ <component name="JsBuildToolGruntFileManager" detection-done="true" sorting="DEFINITION_ORDER" />
+ <component name="JsBuildToolPackageJson" detection-done="true" sorting="DEFINITION_ORDER" />
+ <component name="JsGulpfileManager">
+   <detection-done>true</detection-done>
+   <sorting>DEFINITION_ORDER</sorting>
+ </component>
+ <component name="ProjectFrameBounds">
+   <option name="x" value="1213" />
+   <option name="y" value="119" />
+   <option name="width" value="1280" />
+   <option name="height" value="1573" />
+ </component>
+ <component name="ProjectLevelVcsManager" settingsEditedManually="false">
+   <OptionsSetting value="true" id="Add" />
+   <OptionsSetting value="true" id="Remove" />
+   <OptionsSetting value="true" id="Checkout" />
+   <OptionsSetting value="true" id="Update" />
+   <OptionsSetting value="true" id="Status" />
+   <OptionsSetting value="true" id="Edit" />
+   <ConfirmationsSetting value="0" id="Add" />

```

```
+ <ConfirmationsSetting value="0" id="Remove" />
+ </component>
+ <component name="ProjectView">
+   <navigator currentView="ProjectPane" proportions="" version="1">
+     <flattenPackages />
+     <showMembers />
+     <showModules />
+     <showLibraryContents />
+     <hideEmptyPackages />
+     <abbreviatePackageNames />
+     <autoscrollToSource />
+     <autoscrollFromSource />
+     <sortByType />
+     <manualOrder />
+     <foldersAlwaysOnTop value="true" />
+   </navigator>
+   <panes>
+     <pane id="Scratches" />
+     <pane id="Scope" />
+     <pane id="PackagesPane" />
+     <pane id="ProjectPane">
+       <subPane>
+         <PATH>
+           <PATH_ELEMENT>
+             <option name="myItemId" value="f" />
+             <option name="myItemType" value="com.intellij.ide.projectView.impl.nodes.ProjectViewProjectNode" />
+           </PATH_ELEMENT>
+         </PATH>
+       </subPane>
+     </pane>
+   </panes>
+ </component>
+ <component name="PropertiesComponent">
+   <property name="settings.editor.selected.configurable" value="flutter.settings" />
+   <property name="settings.editor.splitter.proportion" value="0.2" />
+   <property name="aspect.path.notification.shown" value="true" />
+   <property name="last_opened_file_path" value="$PROJECT_DIR$" />
+   <property name="WebServerToolWindowFactoryState" value="false" />
+ </component>
+ <component name="RunManager">
+   <configuration default="true" type="#org.jetbrains.idea.devkit.run.PluginConfigurationType" factoryName="Plugin">
+     <module name="" />
+     <option name="VM_PARAMETERS" value="-Xmx512m -Xms256m -XX:MaxPermSize=250m -ea" />
+     <option name="PROGRAM_PARAMETERS" />
+   </configuration>
+ </component>
```

```
+ <method />
+ </configuration>
+ <configuration default="true" type="Applet" factoryName="Applet">
+   <option name="HTML_USED" value="false" />
+   <option name="WIDTH" value="400" />
+   <option name="HEIGHT" value="300" />
+   <option name="POLICY_FILE" value="$APPLICATION_HOME_DIR$/bin/appletviewer.policy" />
+   <module />
+   <method />
+ </configuration>
+ <configuration default="true" type="Application" factoryName="Application">
+   <extension name="coverage" enabled="false" merge="false" sample_coverage="true" runner="idea" />
+   <option name="MAIN_CLASS_NAME" />
+   <option name="VM_PARAMETERS" />
+   <option name="PROGRAM_PARAMETERS" />
+   <option name="WORKING_DIRECTORY" value="$PROJECT_DIR$" />
+   <option name="ALTERNATIVE_JRE_PATH_ENABLED" value="false" />
+   <option name="ALTERNATIVE_JRE_PATH" />
+   <option name="ENABLE_SWING_INSPECTOR" value="false" />
+   <option name="ENV_VARIABLES" />
+   <option name="PASS_PARENT_ENVS" value="true" />
+   <module name="" />
+   <envs />
+   <method />
+ </configuration>
+ <configuration default="true" type="JUnit" factoryName="JUnit">
+   <extension name="coverage" enabled="false" merge="false" sample_coverage="true" runner="idea" />
+   <module name="" />
+   <option name="ALTERNATIVE_JRE_PATH_ENABLED" value="false" />
+   <option name="ALTERNATIVE_JRE_PATH" />
+   <option name="PACKAGE_NAME" />
+   <option name="MAIN_CLASS_NAME" />
+   <option name="METHOD_NAME" />
+   <option name="TEST_OBJECT" value="class" />
+   <option name="VM_PARAMETERS" value="-ea" />
+   <option name="PARAMETERS" />
+   <option name="WORKING_DIRECTORY" value="$MODULE_DIR$" />
+   <option name="ENV_VARIABLES" />
+   <option name="PASS_PARENT_ENVS" value="true" />
+   <option name="TEST_SEARCH_SCOPE">
+     <value defaultName="singleModule" />
+   </option>
+   <envs />
+   <patterns />
```

```
+ <method />
+ </configuration>
+ <configuration default="true" type="Remote" factoryName="Remote">
+   <option name="USE_SOCKET_TRANSPORT" value="true" />
+   <option name="SERVER_MODE" value="false" />
+   <option name="SHMEM_ADDRESS" value="javadebug" />
+   <option name="HOST" value="localhost" />
+   <option name="PORT" value="5005" />
+   <method />
+ </configuration>
+ <configuration default="true" type="TestNG" factoryName="TestNG">
+   <extension name="coverage" enabled="false" merge="false" sample_coverage="true" runner="idea" />
+   <module name="" />
+   <option name="ALTERNATIVE_JRE_PATH_ENABLED" value="false" />
+   <option name="ALTERNATIVE_JRE_PATH" />
+   <option name="SUITE_NAME" />
+   <option name="PACKAGE_NAME" />
+   <option name="MAIN_CLASS_NAME" />
+   <option name="METHOD_NAME" />
+   <option name="GROUP_NAME" />
+   <option name="TEST_OBJECT" value="CLASS" />
+   <option name="VM_PARAMETERS" value="-ea" />
+   <option name="PARAMETERS" />
+   <option name="WORKING_DIRECTORY" value="$MODULE_DIR$" />
+   <option name="OUTPUT_DIRECTORY" />
+   <option name="ANNOTATION_TYPE" />
+   <option name="ENV_VARIABLES" />
+   <option name="PASS_PARENT_ENVS" value="true" />
+   <option name="TEST_SEARCH_SCOPE">
+     <value defaultName="singleModule" />
+   </option>
+   <option name="USE_DEFAULT_REPORTERS" value="false" />
+   <option name="PROPERTIES_FILE" />
+   <envs />
+   <properties />
+   <listeners />
+   <method />
+ </configuration>
+ </component>
+ <component name="ShelveChangesManager" show_recycled="false">
+   <option name="remove_strategy" value="false" />
+ </component>
+ <component name="TaskManager">
+   <task active="true" id="Default" summary="Default task">
```

```
+ <changelist id="20d0b268-3a27-43b7-b6f2-8f57f3a51737" name="Default" comment="" />
+ <created>1475669512810</created>
+ <option name="number" value="Default" />
+ <option name="presentableId" value="Default" />
+ <updated>1475669512810</updated>
+ <workItem from="1475669514038" duration="13000" />
+ </task>
+ <servers />
+ </component>
+ <component name="TimeTrackingManager">
+ <option name="totallyTimeSpent" value="13000" />
+ </component>
+ <component name="ToolWindowManager">
+ <frame x="1213" y="119" width="1280" height="1573" extended-state="0" />
+ <editor active="false" />
+ <layout>
+ <window_info id="Palette" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="TODO" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="6" side_tool="false" content_ui="tabs" />
+ <window_info id="Palette#" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Capture Analysis" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Event Log" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="true" content_ui="tabs" />
+ <window_info id="Maven Projects" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Run" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="2" side_tool="false" content_ui="tabs" />
+ <window_info id="Version Control" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Terminal" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Capture Tool" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Designer" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Project" active="true" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="true"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="0" side_tool="false" content_ui="combo" />
+ <window_info id="Database" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Structure" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
```

```
+ <window_info id="Ant Build" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
+ <window_info id="UI Designer" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="false" content_ui="tabs" />
+ <window_info id="Debug" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="3" side_tool="false" content_ui="tabs" />
+ <window_info id="Favorites" active="false" anchor="left" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="-1" side_tool="true" content_ui="tabs" />
+ <window_info id="Cvs" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="4" side_tool="false" content_ui="tabs" />
+ <window_info id="Hierarchy" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.25" sideWeight="0.5" order="2" side_tool="false" content_ui="combo" />
+ <window_info id="Message" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="0" side_tool="false" content_ui="tabs" />
+ <window_info id="Commander" active="false" anchor="right" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="0" side_tool="false" content_ui="tabs" />
+ <window_info id="Find" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.33" sideWeight="0.5" order="1" side_tool="false" content_ui="tabs" />
+ <window_info id="Inspection" active="false" anchor="bottom" auto_hide="false" internal_type="DOCKED" type="DOCKED" visible="false"
show_stripe_button="true" weight="0.4" sideWeight="0.5" order="5" side_tool="false" content_ui="tabs" />
+ </layout>
+ </component>
+ <component name="Vcs.Log.UiProperties">
+ <option name="RECENTLY_FILTERED_USER_GROUPS">
+ <collection />
+ </option>
+ <option name="RECENTLY_FILTERED_BRANCH_GROUPS">
+ <collection />
+ </option>
+ </component>
+ <component name="VcsContentAnnotationSettings">
+ <option name="myLimit" value="2678400000" />
+ </component>
+ <component name="XDebuggerManager">
+ <breakpoint-manager />
+ <watches-manager />
+ </component>
+</project>
\ No newline at end of file

commit 28fb74807b1a9e25d0a4495916f714c02e9c2591
Author: Michael Thomsen <mit@google.com>
Date: Wed Oct 5 14:10:51 2016 +0200
```

```
gitignore
```

```
diff --git a/.gitignore b/.gitignore
```

```
new file mode 100644
```

```
index 0000000..14c7d4c
```

```
--- /dev/null
```

```
+++ b/.gitignore
```

```
@@ -0,0 +1,9 @@
```

```
+.DS_Store
```

```
+.atom/
```

```
+.idea
```

```
+.packages
```

```
+.pub/
```

```
+build/
```

```
+ios/.generated/
```

```
+packages
```

```
+pubspec.lock
```

```
commit a4c54289186152bee59d1de0b34c32b926365083
```

```
Author: Michael Thomsen <mit@google.com>
```

```
Date: Wed Oct 5 14:10:24 2016 +0200
```

```
Files created by flutter create
```

```
diff --git a/README.md b/README.md
```

```
new file mode 100644
```

```
index 0000000..436646d
```

```
--- /dev/null
```

```
+++ b/README.md
```

```
@@ -0,0 +1,8 @@
```

```
+# f
```

```
+
```

```
+A new flutter project.
```

```
+
```

```
### Getting Started
```

```
+
```

```
+For help getting started with Flutter, view our online
```

```
+documentation(http://flutter.io/).
```

```
diff --git a/android/AndroidManifest.xml b/android/AndroidManifest.xml
```

```
new file mode 100644
```

```
index 0000000..6b1b619
```

```
--- /dev/null
```

```
+++ b/android/AndroidManifest.xml
```

```
@@ -0,0 +1,22 @@
```



```
+<manifest xmlns:android="http://schemas.android.com/apk/res/android"
+  package="com.yourcompany.f"
+  android:versionCode="1"
+  android:versionName="0.0.1">
+
+  <uses-sdk android:minSdkVersion="16" android:targetSdkVersion="21" />
+  <uses-permission android:name="android.permission.INTERNET"/>
+
+  <application android:name="org.domokit.sky.shell.SkyApplication" android:label="f" android:icon="@mipmap/ic_launcher">
+    <activity android:name="org.domokit.sky.shell.SkyActivity"
+      android:launchMode="singleTop"
+      android:theme="@android:style/Theme.Black.NoTitleBar"
+      android:configChanges="orientation|keyboardHidden|keyboard|screenSize|locale|layoutDirection"
+      android:hardwareAccelerated="true"
+      android:windowSoftInputMode="adjustResize">
+      <intent-filter>
+        <action android:name="android.intent.action.MAIN"/>
+        <category android:name="android.intent.category.LAUNCHER"/>
+      </intent-filter>
+    </activity>
+  </application>
+</manifest>
```

```
diff --git a/android/res/mipmap-hdpi/ic_launcher.png b/android/res/mipmap-hdpi/ic_launcher.png
```

```
new file mode 100644
```

```
index 0000000..db77bb4
```

```
Binary files /dev/null and b/android/res/mipmap-hdpi/ic_launcher.png differ
```

```
diff --git a/android/res/mipmap-mdpi/ic_launcher.png b/android/res/mipmap-mdpi/ic_launcher.png
```

```
new file mode 100644
```

```
index 0000000..17987b7
```

```
Binary files /dev/null and b/android/res/mipmap-mdpi/ic_launcher.png differ
```

```
diff --git a/android/res/mipmap-xhdpi/ic_launcher.png b/android/res/mipmap-xhdpi/ic_launcher.png
```

```
new file mode 100644
```

```
index 0000000..09d4391
```

```
Binary files /dev/null and b/android/res/mipmap-xhdpi/ic_launcher.png differ
```

```
diff --git a/android/res/mipmap-xxhdpi/ic_launcher.png b/android/res/mipmap-xxhdpi/ic_launcher.png
```

```
new file mode 100644
```

```
index 0000000..d5f1c8d
```

```
Binary files /dev/null and b/android/res/mipmap-xxhdpi/ic_launcher.png differ
```

```
diff --git a/android/res/mipmap-xxxhdpi/ic_launcher.png b/android/res/mipmap-xxxhdpi/ic_launcher.png
```

```
new file mode 100644
```

```
index 0000000..4d6372e
```

```
Binary files /dev/null and b/android/res/mipmap-xxxhdpi/ic_launcher.png differ
```

```
diff --git a/flutter.yaml b/flutter.yaml
```

```
new file mode 100644
```

```
index 0000000..1bd028d
--- /dev/null
+++ b/flutter.yaml
@@ -0,0 +1,2 @@
+name: f
+uses-material-design: true
diff --git a/ios/.gitignore b/ios/.gitignore
new file mode 100644
index 0000000..fc39465
--- /dev/null
+++ b/ios/.gitignore
@@ -0,0 +1,38 @@
+.idea/
+.vagrant/
+.sconsign.dblite
+.svn/
+
+.DS_Store
+*.swp
+*.lock
+profile
+
+DerivedData/
+build/
+
+*.pbxuser
+*.mode1v3
+*.mode2v3
+*.perspectivev3
+
+!default.pbxuser
+!default.mode1v3
+!default.mode2v3
+!default.perspectivev3
+
+xcuserdata
+
+*.moved-aside
+
+*.pyc
+*sync/
+Icon?
+.tags*
+
```

```
+Flutter/app.flx
+Flutter/app.dylib
+Flutter/app.zip
+Flutter/Flutter.framework
+Flutter/Generated.xcconfig
+ServiceDefinitions.json
diff --git a/ios/Flutter/Debug.xcconfig b/ios/Flutter/Debug.xcconfig
new file mode 100644
index 0000000..9803018
--- /dev/null
+++ b/ios/Flutter/Debug.xcconfig
@@ -0,0 +1,2 @@
+#include "Generated.xcconfig"
+#include "Pods/Target Support Files/Pods-Runner/Pods-Runner.debug.xcconfig"
diff --git a/ios/Flutter/Release.xcconfig b/ios/Flutter/Release.xcconfig
new file mode 100644
index 0000000..a4a8c60
--- /dev/null
+++ b/ios/Flutter/Release.xcconfig
@@ -0,0 +1,2 @@
+#include "Generated.xcconfig"
+#include "Pods/Target Support Files/Pods-Runner/Pods-Runner.release.xcconfig"
diff --git a/ios/Podfile b/ios/Podfile
new file mode 100644
index 0000000..b6f1c98
--- /dev/null
+++ b/ios/Podfile
@@ -0,0 +1,10 @@
+# Uncomment this line to define a global platform for your project
+# platform :ios, '9.0'
+
+target 'Runner' do
+ # Uncomment this line if you're using Swift or would like to use dynamic frameworks
+ # use_frameworks!
+
+ # Pods for Runner
+
+end
diff --git a/ios/Pods/Pods.xcodeproj/project.pbxproj b/ios/Pods/Pods.xcodeproj/project.pbxproj
new file mode 100644
index 0000000..01ec225
--- /dev/null
+++ b/ios/Pods/Pods.xcodeproj/project.pbxproj
@@ -0,0 +1,299 @@
```

```
+// !*$UTF8*$!  
+{  
+    archiveVersion = 1;  
+    classes = {  
+    };  
+    objectVersion = 46;  
+    objects = {  
+  
+/* Begin PBXBuildFile section */  
+    08F011DBD88D0920DE96F3C5A69A26E8 /* Foundation.framework in Frameworks */ = {isa = PBXBuildFile; fileRef =  
CEC22C73C1608DFA5D5D78BDCB218219 /* Foundation.framework */; };  
+    D3926DFAF385F0A3878A1536D134FB40 /* Pods-Runner-dummy.m in Sources */ = {isa = PBXBuildFile; fileRef =  
468664057D17C890473F3825BE8B6822 /* Pods-Runner-dummy.m */; };  
+/* End PBXBuildFile section */  
+  
+/* Begin PBXFileReference section */  
+    027D05C3C28CE1BD46A8707666A9C5F8 /* libPods-Runner.a */ = {isa = PBXFileReference; explicitFileType = archive.ar; includeInIndex  
= 0; path = "libPods-Runner.a"; sourceTree = BUILT_PRODUCTS_DIR; };  
+    14E58FE88BDE74696DA18D71709505C9 /* Pods-Runner-acknowledgements.plist */ = {isa = PBXFileReference; includeInIndex = 1;  
lastKnownFileType = text.plist.xml; path = "Pods-Runner-acknowledgements.plist"; sourceTree = "<group>"; };  
+    1B4CEFB7A7C39037B5DFAFCE375062E1 /* Pods-Runner.debug.xcconfig */ = {isa = PBXFileReference; includeInIndex = 1;  
lastKnownFileType = text.xcconfig; path = "Pods-Runner.debug.xcconfig"; sourceTree = "<group>"; };  
+    468664057D17C890473F3825BE8B6822 /* Pods-Runner-dummy.m */ = {isa = PBXFileReference; includeInIndex = 1; lastKnownFileType =  
sourcecode.c.objc; path = "Pods-Runner-dummy.m"; sourceTree = "<group>"; };  
+    5C42D986846F74B4DB78535F7182D117 /* Pods-Runner.release.xcconfig */ = {isa = PBXFileReference; includeInIndex = 1;  
lastKnownFileType = text.xcconfig; path = "Pods-Runner.release.xcconfig"; sourceTree = "<group>"; };  
+    7AD2F72BE79A2D928E85F9EB9FB613FA /* Pods-Runner-acknowledgements.markdown */ = {isa = PBXFileReference; includeInIndex = 1;  
lastKnownFileType = text; path = "Pods-Runner-acknowledgements.markdown"; sourceTree = "<group>"; };  
+    93A4A3777CF96A4AAC1D13BA6DCCEA73 /* Podfile */ = {isa = PBXFileReference; explicitFileType = text.script.ruby; includeInIndex =  
1; name = Podfile; path = ../Podfile; sourceTree = SOURCE_ROOT; xclangLanguageSpecificationIdentifier = xcode.lang.ruby; };  
+    A1153EC5FE504BE5C724E20E9B411E90 /* Pods-Runner-frameworks.sh */ = {isa = PBXFileReference; includeInIndex = 1; lastKnownFileType  
= text.script.sh; path = "Pods-Runner-frameworks.sh"; sourceTree = "<group>"; };  
+    A84633CB40E489EF4DD77D43434D3024 /* Pods-Runner-resources.sh */ = {isa = PBXFileReference; includeInIndex = 1; lastKnownFileType  
= text.script.sh; path = "Pods-Runner-resources.sh"; sourceTree = "<group>"; };  
+    CEC22C73C1608DFA5D5D78BDCB218219 /* Foundation.framework */ = {isa = PBXFileReference; lastKnownFileType = wrapper.framework;  
name = Foundation.framework; path = Platforms/iPhoneOS.platform/Developer/SDKs/iPhoneOS9.3.sdk/System/Library/Frameworks/Foundation.framework;  
sourceTree = DEVELOPER_DIR; };  
+/* End PBXFileReference section */  
+  
+/* Begin PBXFrameworksBuildPhase section */  
+    08266C2F1E6679346D9D748BD3A7915D /* Frameworks */ = {  
+        isa = PBXFrameworksBuildPhase;  
+        buildActionMask = 2147483647;  
+        files = (  

```

```

+         08F011DBD88D0920DE96F3C5A69A26E8 /* Foundation.framework in Frameworks */,
+     );
+     runOnlyForDeploymentPostprocessing = 0;
+ };
+ /* End PBXFrameworksBuildPhase section */
+
+ /* Begin PBXGroup section */
+     1C79DB53CD07E661221493B5C6E0CF0B /* Pods-Runner */ = {
+         isa = PBXGroup;
+         children = (
+             7AD2F72BE79A2D928E85F9EB9FB613FA /* Pods-Runner-acknowledgements.markdown */,
+             14E58FE88BDE74696DA18D71709505C9 /* Pods-Runner-acknowledgements.plist */,
+             468664057D17C890473F3825BE8B6822 /* Pods-Runner-dummy.m */,
+             A1153EC5FE504BE5C724E20E9B411E90 /* Pods-Runner-frameworks.sh */,
+             A84633CB40E489EF4DD77D43434D3024 /* Pods-Runner-resources.sh */,
+             1B4CEFB7A7C39037B5DFAFCE375062E1 /* Pods-Runner.debug.xcconfig */,
+             5C42D986846F74B4DB78535F7182D117 /* Pods-Runner.release.xcconfig */,
+         );
+         name = "Pods-Runner";
+         path = "Target Support Files/Pods-Runner";
+         sourceTree = "<group>";
+     };
+     3DCAB2B7CDE207B3958B6CB957FCC758 /* iOS */ = {
+         isa = PBXGroup;
+         children = (
+             CEC22C73C1608DFA5D5D78BDCB218219 /* Foundation.framework */,
+         );
+         name = iOS;
+         sourceTree = "<group>";
+     };
+     6276BDF4AEEBE7163429CDB73B6980D7 /* Targets Support Files */ = {
+         isa = PBXGroup;
+         children = (
+             1C79DB53CD07E661221493B5C6E0CF0B /* Pods-Runner */,
+         );
+         name = "Targets Support Files";
+         sourceTree = "<group>";
+     };
+     7DB346D0F39D3F0E887471402A8071AB = {
+         isa = PBXGroup;
+         children = (
+             93A4A3777CF96A4AAC1D13BA6DCCEA73 /* Podfile */,
+             BC3CA7F9E30CC8F7E2DD044DD34432FC /* Frameworks */,
+             9A3A7EACADA9417D2516CD83C5B1027A /* Products */,

```

```

+         6276BDF4AE7E7163429CDB73B6980D7 /* Targets Support Files */,
+     );
+     sourceTree = "<group>";
+ };
+ 9A3A7EACADA9417D2516CD83C5B1027A /* Products */ = {
+     isa = PBXGroup;
+     children = (
+         027D05C3C28CE1BD46A8707666A9C5F8 /* libPods-Runner.a */,
+     );
+     name = Products;
+     sourceTree = "<group>";
+ };
+ BC3CA7F9E30CC8F7E2DD044DD34432FC /* Frameworks */ = {
+     isa = PBXGroup;
+     children = (
+         3DCAB2B7CDE207B3958B6CB957FCC758 /* iOS */,
+     );
+     name = Frameworks;
+     sourceTree = "<group>";
+ };
+ /* End PBXGroup section */
+
+ /* Begin PBXNativeTarget section */
+ B0B211B0FA111CE20F29C3A6B3CED356 /* Pods-Runner */ = {
+     isa = PBXNativeTarget;
+     buildConfigurationList = BBD992B4B5EA046F3BF6DB62624D0AF0 /* Build configuration list for PBXNativeTarget "Pods-Runner"
+ */;
+     buildPhases = (
+         83AF969EC59378C6BB28D1C7AFE23E7D /* Sources */,
+         08266C2F1E6679346D9D748BD3A7915D /* Frameworks */,
+     );
+     buildRules = (
+     );
+     dependencies = (
+     );
+     name = "Pods-Runner";
+     productName = "Pods-Runner";
+     productReference = 027D05C3C28CE1BD46A8707666A9C5F8 /* libPods-Runner.a */;
+     productType = "com.apple.product-type.library.static";
+ };
+ /* End PBXNativeTarget section */
+
+ /* Begin PBXProject section */
+ D41D8CD98F00B204E9800998ECF8427E /* Project object */ = {

```

```
+ isa = PBXProject;
+ attributes = {
+     LastSwiftUpdateCheck = 0730;
+     LastUpgradeCheck = 0700;
+ };
+ buildConfigurationList = 2D8E8EC45A3A1A1D94AE762CB5028504 /* Build configuration list for PBXProject "Pods" */;
+ compatibilityVersion = "Xcode 3.2";
+ developmentRegion = English;
+ hasScannedForEncodings = 0;
+ knownRegions = (
+     en,
+ );
+ mainGroup = 7DB346D0F39D3F0E887471402A8071AB;
+ productRefGroup = 9A3A7EACADA9417D2516CD83C5B1027A /* Products */;
+ projectDirPath = "";
+ projectRoot = "";
+ targets = (
+     B0B211B0FA111CE20F29C3A6B3CED356 /* Pods-Runner */;
+ );
+ };
+/* End PBXProject section */
+
+/* Begin PBXSourcesBuildPhase section */
+     83AF969EC59378C6BB28D1C7AFE23E7D /* Sources */ = {
+         isa = PBXSourcesBuildPhase;
+         buildActionMask = 2147483647;
+         files = (
+             D3926DFAF385F0A3878A1536D134FB40 /* Pods-Runner-dummy.m in Sources */;
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+     };
+/* End PBXSourcesBuildPhase section */
+
+/* Begin XCBuildConfiguration section */
+     309EF1F5E327BE758428CD2A22E8B8BD /* Debug */ = {
+         isa = XCBuildConfiguration;
+         baseConfigurationReference = 1B4CEFB7A7C39037B5DFAFCE375062E1 /* Pods-Runner.debug.xcconfig */;
+         buildSettings = {
+             "CODE_SIGN_IDENTITY[sdk=iphones*]" = "iPhone Developer";
+             DEBUG_INFORMATION_FORMAT = dwarf;
+             ENABLE_STRICT_OBJC_MSGSEND = YES;
+             GCC_NO_COMMON_BLOCKS = YES;
+             IPHONEOS_DEPLOYMENT_TARGET = 9.3;
+             MACH_O_TYPE = staticlib;
+         };
+     };
+/* End XCBuildConfiguration section */
```

```

+         MTL_ENABLE_DEBUG_INFO = YES;
+         OTHER_LDFLAGS = "";
+         OTHER_LIBTOOLFLAGS = "";
+         PODS_ROOT = "$(SRCROOT)";
+         PRODUCT_BUNDLE_IDENTIFIER = "org.cocoapods.${PRODUCT_NAME:rfc1034identifier}";
+         PRODUCT_NAME = "$(TARGET_NAME)";
+         SDKROOT = iphoneos;
+         SKIP_INSTALL = YES;
+     };
+     name = Debug;
+ };
+ 3FA451D268613890FA8A5A03801E11D5 /* Release */ = {
+     isa = XCBuildConfiguration;
+     buildSettings = {
+         ALWAYS_SEARCH_USER_PATHS = NO;
+         CLANG_ANALYZER_NONNULL = YES;
+         CLANG_CXX_LANGUAGE_STANDARD = "gnu++0x";
+         CLANG_CXX_LIBRARY = "libc++";
+         CLANG_ENABLE_MODULES = YES;
+         CLANG_ENABLE_OBJC_ARC = YES;
+         CLANG_WARN_BOOL_CONVERSION = YES;
+         CLANG_WARN_CONSTANT_CONVERSION = YES;
+         CLANG_WARN_DIRECT_OBJC_ISA_USAGE = YES;
+         CLANG_WARN_EMPTY_BODY = YES;
+         CLANG_WARN_ENUM_CONVERSION = YES;
+         CLANG_WARN_INT_CONVERSION = YES;
+         CLANG_WARN_OBJC_ROOT_CLASS = YES;
+         CLANG_WARN_UNREACHABLE_CODE = YES;
+         CLANG_WARN__DUPLICATE_METHOD_MATCH = YES;
+         COPY_PHASE_STRIP = YES;
+         ENABLE_NS_ASSERTIONS = NO;
+         GCC_C_LANGUAGE_STANDARD = gnu99;
+         GCC_PREPROCESSOR_DEFINITIONS = (
+             "POD_CONFIGURATION_RELEASE=1",
+             "$(inherited)",
+         );
+         GCC_WARN_64_TO_32_BIT_CONVERSION = YES;
+         GCC_WARN_ABOUT_RETURN_TYPE = YES;
+         GCC_WARN_UNDECLARED_SELECTOR = YES;
+         GCC_WARN_UNINITIALIZED_AUTOS = YES;
+         GCC_WARN_UNUSED_FUNCTION = YES;
+         GCC_WARN_UNUSED_VARIABLE = YES;
+         IPHONEOS_DEPLOYMENT_TARGET = 8.0;
+         STRIP_INSTALLED_PRODUCT = NO;

```



```

+         SYMROOT = "${SRCROOT}/../build";
+         VALIDATE_PRODUCT = YES;
+     };
+     name = Release;
+ };
+ 5E62115DE8C09934BF8D2FE5D15FED1E /* Debug */ = {
+     isa = XCBuildConfiguration;
+     buildSettings = {
+         ALWAYS_SEARCH_USER_PATHS = NO;
+         CLANG_ANALYZER_NONNULL = YES;
+         CLANG_CXX_LANGUAGE_STANDARD = "gnu++0x";
+         CLANG_CXX_LIBRARY = "libc++";
+         CLANG_ENABLE_MODULES = YES;
+         CLANG_ENABLE_OBJC_ARC = YES;
+         CLANG_WARN_BOOL_CONVERSION = YES;
+         CLANG_WARN_CONSTANT_CONVERSION = YES;
+         CLANG_WARN_DIRECT_OBJC_ISA_USAGE = YES;
+         CLANG_WARN_EMPTY_BODY = YES;
+         CLANG_WARN_ENUM_CONVERSION = YES;
+         CLANG_WARN_INT_CONVERSION = YES;
+         CLANG_WARN_OBJC_ROOT_CLASS = YES;
+         CLANG_WARN_UNREACHABLE_CODE = YES;
+         CLANG_WARN__DUPLICATE_METHOD_MATCH = YES;
+         COPY_PHASE_STRIP = NO;
+         ENABLE_TESTABILITY = YES;
+         GCC_C_LANGUAGE_STANDARD = gnu99;
+         GCC_DYNAMIC_NO_PIC = NO;
+         GCC_OPTIMIZATION_LEVEL = 0;
+         GCC_PREPROCESSOR_DEFINITIONS = (
+             "POD_CONFIGURATION_DEBUG=1",
+             "DEBUG=1",
+             "$(inherited)",
+         );
+         GCC_SYMBOLS_PRIVATE_EXTERN = NO;
+         GCC_WARN_64_TO_32_BIT_CONVERSION = YES;
+         GCC_WARN_ABOUT_RETURN_TYPE = YES;
+         GCC_WARN_UNDECLARED_SELECTOR = YES;
+         GCC_WARN_UNINITIALIZED_AUTOS = YES;
+         GCC_WARN_UNUSED_FUNCTION = YES;
+         GCC_WARN_UNUSED_VARIABLE = YES;
+         IPHONEOS_DEPLOYMENT_TARGET = 8.0;
+         ONLY_ACTIVE_ARCH = YES;
+         STRIP_INSTALLED_PRODUCT = NO;
+         SYMROOT = "${SRCROOT}/../build";

```

```

+         };
+         name = Debug;
+     };
+     A73609B65BD0880FA9B2FE021CB0D23D /* Release */ = {
+         isa = XCBuildConfiguration;
+         baseConfigurationReference = 5C42D986846F74B4DB78535F7182D117 /* Pods-Runner.release.xcconfig */;
+         buildSettings = {
+             "CODE_SIGN_IDENTITY[sdk=iphoneos*]" = "iPhone Developer";
+             DEBUG_INFORMATION_FORMAT = "dwarf-with-dsym";
+             ENABLE_STRICT_OBJC_MSGSEND = YES;
+             GCC_NO_COMMON_BLOCKS = YES;
+             IPHONEOS_DEPLOYMENT_TARGET = 9.3;
+             MACH_O_TYPE = staticlib;
+             MTL_ENABLE_DEBUG_INFO = NO;
+             OTHER_LDFLAGS = "";
+             OTHER_LIBTOOLFLAGS = "";
+             PODS_ROOT = "${SRCROOT}";
+             PRODUCT_BUNDLE_IDENTIFIER = "org.cocoapods.${PRODUCT_NAME:rfc1034identifier}";
+             PRODUCT_NAME = "${TARGET_NAME}";
+             SDKROOT = iphoneos;
+             SKIP_INSTALL = YES;
+         };
+         name = Release;
+     };
+ /* End XCBuildConfiguration section */
+
+ /* Begin XCConfigurationList section */
+     2D8E8EC45A3A1A1D94AE762CB5028504 /* Build configuration list for PBXProject "Pods" */ = {
+         isa = XCConfigurationList;
+         buildConfigurations = (
+             5E62115DE8C09934BF8D2FE5D15FED1E /* Debug */,
+             3FA451D268613890FA8A5A03801E11D5 /* Release */,
+         );
+         defaultConfigurationIsVisible = 0;
+         defaultConfigurationName = Release;
+     };
+     BBD992B4B5EA046F3BF6DB62624D0AF0 /* Build configuration list for PBXNativeTarget "Pods-Runner" */ = {
+         isa = XCConfigurationList;
+         buildConfigurations = (
+             309EF1F5E327BE758428CD2A22E8B8BD /* Debug */,
+             A73609B65BD0880FA9B2FE021CB0D23D /* Release */,
+         );
+         defaultConfigurationIsVisible = 0;
+         defaultConfigurationName = Release;
+     };

```

```
+      };
+/* End XCConfigurationList section */
+      };
+      rootObject = D41D8CD98F00B204E9800998ECF8427E /* Project object */;
+}
diff --git a/ios/Pods/Pods.xcodeproj/xcsreddata/xcschemes/Pods-Runner.xcscheme b/ios/Pods/Pods.xcodeproj/xcsreddata/xcschemes/Pods-Runner.xcscheme
new file mode 100644
index 0000000..c7e2d72
--- /dev/null
+++ b/ios/Pods/Pods.xcodeproj/xcsreddata/xcschemes/Pods-Runner.xcscheme
@@ -0,0 +1,80 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<Scheme
+  LastUpgradeVersion = "0730"
+  version = "1.3">
+  <BuildAction
+    parallelizeBuildables = "YES"
+    buildImplicitDependencies = "YES">
+    <BuildActionEntries>
+      <BuildActionEntry
+        buildForTesting = "YES"
+        buildForRunning = "YES"
+        buildForProfiling = "YES"
+        buildForArchiving = "YES"
+        buildForAnalyzing = "YES">
+        <BuildableReference
+          BuildableIdentifier = "primary"
+          BlueprintIdentifier = "B0B211B0FA111CE20F29C3A6B3CED356"
+          BuildableName = "libPods-Runner.a"
+          BlueprintName = "Pods-Runner"
+          ReferencedContainer = "container:Pods.xcodeproj">
+        </BuildableReference>
+      </BuildActionEntry>
+    </BuildActionEntries>
+  </BuildAction>
+  <TestAction
+    buildConfiguration = "Debug"
+    selectedDebuggerIdentifier = "Xcode.DebuggerFoundation.Debugger.LLDB"
+    selectedLauncherIdentifier = "Xcode.DebuggerFoundation.Launcher.LLDB"
+    shouldUseLaunchSchemeArgsEnv = "YES">
+    <Testables>
+    </Testables>
+    <AdditionalOptions>
```

```
+   </AdditionalOptions>
+ </TestAction>
+ <LaunchAction
+   buildConfiguration = "Debug"
+   selectedDebuggerIdentifier = "Xcode.DebuggerFoundation.Debugger.LLDB"
+   selectedLauncherIdentifier = "Xcode.DebuggerFoundation.Launcher.LLDB"
+   launchStyle = "0"
+   useCustomWorkingDirectory = "NO"
+   ignoresPersistentStateOnLaunch = "NO"
+   debugDocumentVersioning = "YES"
+   debugServiceExtension = "internal"
+   allowLocationSimulation = "YES">
+   <MacroExpansion>
+     <BuildableReference
+       BuildableIdentifier = "primary"
+       BlueprintIdentifier = "B0B211B0FA111CE20F29C3A6B3CED356"
+       BuildableName = "libPods-Runner.a"
+       BlueprintName = "Pods-Runner"
+       ReferencedContainer = "container:Pods.xcodeproj">
+     </BuildableReference>
+   </MacroExpansion>
+   <AdditionalOptions>
+   </AdditionalOptions>
+ </LaunchAction>
+ <ProfileAction
+   buildConfiguration = "Release"
+   shouldUseLaunchSchemeArgsEnv = "YES"
+   savedToolIdentifier = ""
+   useCustomWorkingDirectory = "NO"
+   debugDocumentVersioning = "YES">
+   <MacroExpansion>
+     <BuildableReference
+       BuildableIdentifier = "primary"
+       BlueprintIdentifier = "B0B211B0FA111CE20F29C3A6B3CED356"
+       BuildableName = "libPods-Runner.a"
+       BlueprintName = "Pods-Runner"
+       ReferencedContainer = "container:Pods.xcodeproj">
+     </BuildableReference>
+   </MacroExpansion>
+ </ProfileAction>
+ <AnalyzeAction
+   buildConfiguration = "Debug">
+ </AnalyzeAction>
+ <ArchiveAction
```

```
+     buildConfiguration = "Release"
+     revealArchiveInOrganizer = "YES">
+ </ArchiveAction>
+</Scheme>
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.markdown b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.markdown
new file mode 100644
index 0000000..102af75
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.markdown
@@ -0,0 +1,3 @@
+# Acknowledgements
+This application makes use of the following third party libraries:
+Generated by CocoaPods - https://cocoapods.org
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.plist b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.plist
new file mode 100644
index 0000000..7acbad1
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-acknowledgements.plist
@@ -0,0 +1,29 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN" "http://www.apple.com/DTDs/PropertyList-1.0.dtd">
+<plist version="1.0">
+<dict>
+  <key>PreferenceSpecifiers</key>
+  <array>
+    <dict>
+      <key>FooterText</key>
+      <string>This application makes use of the following third party libraries:</string>
+      <key>Title</key>
+      <string>Acknowledgements</string>
+      <key>Type</key>
+      <string>PSGroupSpecifier</string>
+    </dict>
+    <dict>
+      <key>FooterText</key>
+      <string>Generated by CocoaPods - https://cocoapods.org</string>
+      <key>Title</key>
+      <string></string>
+      <key>Type</key>
+      <string>PSGroupSpecifier</string>
+    </dict>
+  </array>
```

```
+     <key>StringsTable</key>
+     <string>Acknowledgements</string>
+     <key>Title</key>
+     <string>Acknowledgements</string>
+</dict>
+</plist>
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-dummy.m b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-dummy.m
new file mode 100644
index 0000000..0b73bc1
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-dummy.m
@@ -0,0 +1,5 @@
+#import <Foundation/Foundation.h>
+@interface PodsDummy_Pods_Runner : NSObject
+@end
+@implementation PodsDummy_Pods_Runner
+@end
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-frameworks.sh b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-
frameworks.sh
new file mode 100755
index 0000000..893c16a
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-frameworks.sh
@@ -0,0 +1,84 @@
+#!/bin/sh
+set -e
+
+echo "mkdir -p ${CONFIGURATION_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+mkdir -p "${CONFIGURATION_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+
+SWIFT_STDLIB_PATH="${DT_TOOLCHAIN_DIR}/usr/lib/swift/${PLATFORM_NAME}"
+
+install_framework()
+{
+  if [ -r "${BUILT_PRODUCTS_DIR}/${1}" ]; then
+    local source="${BUILT_PRODUCTS_DIR}/${1}"
+  elif [ -r "${BUILT_PRODUCTS_DIR}/$(basename "$1")" ]; then
+    local source="${BUILT_PRODUCTS_DIR}/$(basename "$1")"
+  elif [ -r "$1" ]; then
+    local source="$1"
+  fi
+
+  local destination="${TARGET_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+}
```

```

+ if [ -L "${source}" ]; then
+     echo "Symlinked..."
+     source="$(readlink "${source}")"
+ fi
+
+ # use filter instead of exclude so missing patterns dont' throw errors
+ echo "rsync -av --filter \"- CVS/\ " --filter \"- .svn/\ " --filter \"- .git/\ " --filter \"- .hg/\ " --filter \"- Headers\ " --filter \"-
PrivateHeaders\ " --filter \"- Modules\ " \ "${source}\ " \ "${destination}\ "
+ rsync -av --filter "- CVS/" --filter "- .svn/" --filter "- .git/" --filter "- .hg/" --filter "- Headers" --filter "- PrivateHeaders" --filter
"- Modules" "${source}" "${destination}"
+
+ local basename
+ basename="$(basename -s .framework "$1")"
+ binary="${destination}/${basename}.framework/${basename}"
+ if ! [ -r "$binary" ]; then
+     binary="${destination}/${basename}"
+ fi
+
+ # Strip invalid architectures so "fat" simulator / device frameworks work on device
+ if [[ "$(file "$binary")" == *"dynamically linked shared library"* ]]; then
+     strip_invalid_archs "$binary"
+ fi
+
+ # Resign the code if required by the build settings to avoid unstable apps
+ code_sign_if_enabled "${destination}/$(basename "$1")"
+
+ # Embed linked Swift runtime libraries. No longer necessary as of Xcode 7.
+ if [ "${XCODE_VERSION_MAJOR}" -lt 7 ]; then
+     local swift_runtime_libs
+     swift_runtime_libs=$(xcrun otool -LX "$binary" | grep --color=never @rpath/libswift | sed -E s/@rpath\\/\(.+dylib\).*/\1/g | uniq -u &&
exit ${PIPESTATUS[0]})
+     for lib in $swift_runtime_libs; do
+         echo "rsync -auv \ "${SWIFT_STDLIB_PATH}/${lib}\ " \ "${destination}\ "
+         rsync -auv "${SWIFT_STDLIB_PATH}/${lib}" "${destination}"
+         code_sign_if_enabled "${destination}/${lib}"
+     done
+ fi
+}
+
+# Signs a framework with the provided identity
+code_sign_if_enabled() {
+ if [ -n "${EXPANDED_CODE_SIGN_IDENTITY}" -a "${CODE_SIGNING_REQUIRED}" != "NO" -a "${CODE_SIGNING_ALLOWED}" != "NO" ]; then
+     # Use the current code_sign_identity
+     echo "Code Signing $1 with Identity ${EXPANDED_CODE_SIGN_IDENTITY_NAME}"

```

```
+ echo "/usr/bin/codesign --force --sign ${EXPANDED_CODE_SIGN_IDENTITY} ${OTHER_CODE_SIGN_FLAGS} --preserve-metadata=identifier,entitlements\n\"$1\""\n+\n+ /usr/bin/codesign --force --sign ${EXPANDED_CODE_SIGN_IDENTITY} ${OTHER_CODE_SIGN_FLAGS} --preserve-metadata=identifier,entitlements "$1"\n+ fi\n+}\n+\n+# Strip invalid architectures\n+strip_invalid_archs() {\n+ binary="$1"\n+ # Get architectures for current file\n+ archs="$(lipo -info "$binary" | rev | cut -d ':' -f1 | rev)"\n+ stripped=""\n+ for arch in $archs; do\n+   if ! [[ "${VALID_ARCHS}" == *"$arch"* ]]; then\n+     # Strip non-valid architectures in-place\n+     lipo -remove "$arch" -output "$binary" "$binary" || exit 1\n+     stripped="$stripped $arch"\n+   fi\n+ done\n+ if [[ "$stripped" ]]; then\n+   echo "Stripped $binary of architectures:$stripped"\n+ fi\n+}\n+\ndiff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-resources.sh b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-resources.sh\nnew file mode 100755\nindex 0000000..0a15615\n--- /dev/null\n+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner-resources.sh\n@@ -0,0 +1,102 @@\n+#!/bin/sh\n+set -e\n+\n+mkdir -p "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}"\n+\n+RESOURCES_TO_COPY=${PODS_ROOT}/resources-to-copy-${TARGETNAME}.txt\n+> "$RESOURCES_TO_COPY"\n+\n+XCASSET_FILES=()\n+\n+case "${TARGETED_DEVICE_FAMILY}" in\n+ 1,2)\n+   TARGET_DEVICE_ARGS="--target-device ipad --target-device iphone"
```



```

+ ;;
+ 1)
+   TARGET_DEVICE_ARGS="--target-device iphone"
+   ;;
+ 2)
+   TARGET_DEVICE_ARGS="--target-device ipad"
+   ;;
+ *)
+   TARGET_DEVICE_ARGS="--target-device mac"
+   ;;
+esac
+
+realpath() {
+  DIRECTORY="$(cd "${1%/*}" && pwd)"
+  FILENAME="${1##*/}"
+  echo "$DIRECTORY/$FILENAME"
+}
+
+install_resource()
+{
+  if [[ "$1" = /* ]] ; then
+    RESOURCE_PATH="$1"
+  else
+    RESOURCE_PATH="${PODS_ROOT}/${1}"
+  fi
+  if [[ ! -e "$RESOURCE_PATH" ]] ; then
+    cat << EOM
+error: Resource "$RESOURCE_PATH" not found. Run 'pod install' to update the copy resources script.
+EOM
+    exit 1
+  fi
+  case $RESOURCE_PATH in
+    *.storyboard)
+      echo "ibtool --reference-external-strings-file --errors --warnings --notices --minimum-deployment-target ${!
DEPLOYMENT_TARGET_SETTING_NAME} --output-format human-readable-text --compile ${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename
\"$RESOURCE_PATH\" .storyboard`.storyboardc $RESOURCE_PATH --sdk ${SDKROOT} ${TARGET_DEVICE_ARGS}"
+      ibtool --reference-external-strings-file --errors --warnings --notices --minimum-deployment-target ${!DEPLOYMENT_TARGET_SETTING_NAME} --
output-format human-readable-text --compile "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH
\" .storyboard`.storyboardc" "$RESOURCE_PATH" --sdk "${SDKROOT}" ${TARGET_DEVICE_ARGS}
+      ;;
+    *.xib)
+      echo "ibtool --reference-external-strings-file --errors --warnings --notices --minimum-deployment-target ${!
DEPLOYMENT_TARGET_SETTING_NAME} --output-format human-readable-text --compile ${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename
\"$RESOURCE_PATH\" .xib`.nib $RESOURCE_PATH --sdk ${SDKROOT} ${TARGET_DEVICE_ARGS}"

```

```

+   ibtool --reference-external-strings-file --errors --warnings --notices --minimum-deployment-target ${!DEPLOYMENT_TARGET_SETTING_NAME} --
output-format human-readable-text --compile "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH\" .xib`.nib"
"$RESOURCE_PATH" --sdk "${SDKROOT}" ${TARGET_DEVICE_ARGS}
+   ;;
+ *.framework)
+   echo "mkdir -p ${TARGET_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+   mkdir -p "${TARGET_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+   echo "rsync -av $RESOURCE_PATH ${TARGET_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+   rsync -av "$RESOURCE_PATH" "${TARGET_BUILD_DIR}/${FRAMEWORKS_FOLDER_PATH}"
+   ;;
+ *.xcdatamodel)
+   echo "xcrun momc \"$RESOURCE_PATH\" \"${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH\" .mom\"`"
+   xcrun momc "$RESOURCE_PATH" "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH\" .xcdatamodel`.mom"
+   ;;
+ *.xcdatamodeld)
+   echo "xcrun momc \"$RESOURCE_PATH\" \"${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename
"$RESOURCE_PATH\" .xcdatamodeld`.momd\"`"
+   xcrun momc "$RESOURCE_PATH" "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH\" .xcdatamodeld`.momd"
+   ;;
+ *.xcmappingmodel)
+   echo "xcrun mapc \"$RESOURCE_PATH\" \"${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename
"$RESOURCE_PATH\" .xcmappingmodel`.cdm\"`"
+   xcrun mapc "$RESOURCE_PATH" "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}/`basename \"$RESOURCE_PATH\" .xcmappingmodel`.cdm"
+   ;;
+ *.xcassets)
+   ABSOLUTE_XCASSET_FILE=$(realpath "$RESOURCE_PATH")
+   XCASSET_FILES+=("$ABSOLUTE_XCASSET_FILE")
+   ;;
+ *)
+   echo "$RESOURCE_PATH"
+   echo "$RESOURCE_PATH" >> "$RESOURCES_TO_COPY"
+   ;;
+ esac
+}
+
+mkdir -p "${TARGET_BUILD_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}"
+rsync -avr --copy-links --no-relative --exclude '*/.svn/*' --files-from="$RESOURCES_TO_COPY" / "${TARGET_BUILD_DIR}/${
UNLOCALIZED_RESOURCES_FOLDER_PATH}"
+if [[ "${ACTION}" == "install" ]] && [[ "${SKIP_INSTALL}" == "NO" ]]; then
+   mkdir -p "${INSTALL_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}"
+   rsync -avr --copy-links --no-relative --exclude '*/.svn/*' --files-from="$RESOURCES_TO_COPY" / "${INSTALL_DIR}/${
UNLOCALIZED_RESOURCES_FOLDER_PATH}"
+fi
+rm -f "$RESOURCES_TO_COPY"

```

```

+
+if [[ -n "${WRAPPER_EXTENSION}" ]] && [ "`xcrun --find actool`" ] && [ -n "$XCASSET_FILES" ]
+then
+ # Find all other xcassets (this unfortunately includes those of path pods and other targets).
+ OTHER_XCASSETS=$(find "$PWD" -iname "*.xcassets" -type d)
+ while read line; do
+   if [[ $line != "`realpath $PODS_ROOT`*" ]]; then
+     XCASSET_FILES+=("$line")
+   fi
+ done <<<"$OTHER_XCASSETS"
+
+ printf "%s\n" "${XCASSET_FILES[@]}" | xargs -0 xcrun actool --output-format human-readable-text --notices --warnings --platform "${
{PLATFORM_NAME}" --minimum-deployment-target "${!DEPLOYMENT_TARGET_SETTING_NAME}" ${TARGET_DEVICE_ARGS} --compress-pngs --compile "$
{BUILT_PRODUCTS_DIR}/${UNLOCALIZED_RESOURCES_FOLDER_PATH}"
+fi
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner.debug.xcconfig b/ios/Pods/Target Support Files/Pods-Runner/Pods-
Runner.debug.xcconfig
new file mode 100644
index 0000000..f1c5b33
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner.debug.xcconfig
@@ -0,0 +1,7 @@
+GCC_PREPROCESSOR_DEFINITIONS = $(inherited) COCOAPODS=1
+HEADER_SEARCH_PATHS = $(inherited) "${PODS_ROOT}/Headers/Public"
+OTHER_CFLAGS = $(inherited) -isystem "${PODS_ROOT}/Headers/Public"
+OTHER_LDFLAGS = $(inherited) -ObjC
+PODS_BUILD_DIR = $BUILD_DIR
+PODS_CONFIGURATION_BUILD_DIR = $PODS_BUILD_DIR/${CONFIGURATION}${EFFECTIVE_PLATFORM_NAME}
+PODS_ROOT = ${SRCROOT}/Pods
diff --git a/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner.release.xcconfig b/ios/Pods/Target Support Files/Pods-Runner/Pods-
Runner.release.xcconfig
new file mode 100644
index 0000000..f1c5b33
--- /dev/null
+++ b/ios/Pods/Target Support Files/Pods-Runner/Pods-Runner.release.xcconfig
@@ -0,0 +1,7 @@
+GCC_PREPROCESSOR_DEFINITIONS = $(inherited) COCOAPODS=1
+HEADER_SEARCH_PATHS = $(inherited) "${PODS_ROOT}/Headers/Public"
+OTHER_CFLAGS = $(inherited) -isystem "${PODS_ROOT}/Headers/Public"
+OTHER_LDFLAGS = $(inherited) -ObjC
+PODS_BUILD_DIR = $BUILD_DIR
+PODS_CONFIGURATION_BUILD_DIR = $PODS_BUILD_DIR/${CONFIGURATION}${EFFECTIVE_PLATFORM_NAME}
+PODS_ROOT = ${SRCROOT}/Pods
diff --git a/ios/Runner.xcodeproj/project.pbxproj b/ios/Runner.xcodeproj/project.pbxproj

```

```
new file mode 100644
index 0000000..b32f4d3
--- /dev/null
+++ b/ios/Runner.xcodeproj/project.pbxproj
@@ -0,0 +1,455 @@
+// !$*UTF8*$!
+{
+    archiveVersion = 1;
+    classes = {
+    };
+    objectVersion = 46;
+    objects = {
+
+/* Begin PBXBuildFile section */
+        9705A1C51CF9049000538489 /* app.dylib in Embed Frameworks */ = {isa = PBXBuildFile; fileRef = 9740EEB81CF902C7004384FC /*
app.dylib */; settings = {ATTRIBUTES = (CodeSignOnCopy, ); }; };
+        9705A1C61CF904A100538489 /* Flutter.framework in Frameworks */ = {isa = PBXBuildFile; fileRef = 9740EEBA1CF902C7004384FC /*
Flutter.framework */; };
+        9705A1C71CF904A300538489 /* Flutter.framework in Embed Frameworks */ = {isa = PBXBuildFile; fileRef = 9740EEBA1CF902C7004384FC /*
Flutter.framework */; settings = {ATTRIBUTES = (CodeSignOnCopy, RemoveHeadersOnCopy, ); }; };
+        9740EEB41CF90195004384FC /* Debug.xcconfig in Resources */ = {isa = PBXBuildFile; fileRef = 9740EEB21CF90195004384FC /*
Debug.xcconfig */; };
+        9740EEB51CF90195004384FC /* Generated.xcconfig in Resources */ = {isa = PBXBuildFile; fileRef = 9740EEB31CF90195004384FC /*
Generated.xcconfig */; };
+        9740EEB1CF902C7004384FC /* app.flx in Resources */ = {isa = PBXBuildFile; fileRef = 9740EEB71CF902C7004384FC /* app.flx */; };
+        978B8F6F1D3862AE00F588F7 /* AppDelegate.m in Sources */ = {isa = PBXBuildFile; fileRef = 7AFFD8EE1D35381100E5BB4D /*
AppDelegate.m */; };
+        97C146F31CF9000F007C117D /* main.m in Sources */ = {isa = PBXBuildFile; fileRef = 97C146F21CF9000F007C117D /* main.m */; };
+        97C146FC1CF9000F007C117D /* Main.storyboard in Resources */ = {isa = PBXBuildFile; fileRef = 97C146FA1CF9000F007C117D /*
Main.storyboard */; };
+        97C146FE1CF9000F007C117D /* Assets.xcassets in Resources */ = {isa = PBXBuildFile; fileRef = 97C146FD1CF9000F007C117D /*
Assets.xcassets */; };
+        97C147011CF9000F007C117D /* LaunchScreen.storyboard in Resources */ = {isa = PBXBuildFile; fileRef = 97C146FF1CF9000F007C117D /*
LaunchScreen.storyboard */; };
+        B1F3D14E8117A6C9F65810E0 /* libPods-Runner.a in Frameworks */ = {isa = PBXBuildFile; fileRef = 4D558BB7489B1C82B42A9097 /*
libPods-Runner.a */; };
+/* End PBXBuildFile section */
+
+/* Begin PBXCopyFilesBuildPhase section */
+        9705A1C41CF9048500538489 /* Embed Frameworks */ = {
+            isa = PBXCopyFilesBuildPhase;
+            buildActionMask = 2147483647;
+            dstPath = "";
+            dstSubfolderSpec = 10;

```

```

+         files = (
+             9705A1C51CF9049000538489 /* app.dylib in Embed Frameworks */,
+             9705A1C71CF904A300538489 /* Flutter.framework in Embed Frameworks */,
+         );
+         name = "Embed Frameworks";
+         runOnlyForDeploymentPostprocessing = 0;
+     };
+ /* End PBXCopyFilesBuildPhase section */
+
+ /* Begin PBXFileReference section */
+     4D558BB7489B1C82B42A9097 /* libPods-Runner.a */ = {isa = PBXFileReference; explicitFileType = archive.ar; includeInIndex = 0;
path = "libPods-Runner.a"; sourceTree = BUILT_PRODUCTS_DIR; };
+     7AFA3C8E1D35360C0083082E /* Release.xcconfig */ = {isa = PBXFileReference; lastKnownFileType = text.xcconfig; name =
Release.xcconfig; path = Flutter/Release.xcconfig; sourceTree = "<group>"; };
+     7AFFD8ED1D35381100E5BB4D /* AppDelegate.h */ = {isa = PBXFileReference; fileEncoding = 4; lastKnownFileType = sourcecode.c.h;
path = AppDelegate.h; sourceTree = "<group>"; };
+     7AFFD8EE1D35381100E5BB4D /* AppDelegate.m */ = {isa = PBXFileReference; fileEncoding = 4; lastKnownFileType = sourcecode.c.objc;
path = AppDelegate.m; sourceTree = "<group>"; };
+     9740EEB21CF90195004384FC /* Debug.xcconfig */ = {isa = PBXFileReference; fileEncoding = 4; lastKnownFileType = text.xcconfig;
name = Debug.xcconfig; path = Flutter/Debug.xcconfig; sourceTree = "<group>"; };
+     9740EEB31CF90195004384FC /* Generated.xcconfig */ = {isa = PBXFileReference; fileEncoding = 4; lastKnownFileType = text.xcconfig;
name = Generated.xcconfig; path = Flutter/Generated.xcconfig; sourceTree = "<group>"; };
+     9740EEB71CF902C7004384FC /* app.flx */ = {isa = PBXFileReference; lastKnownFileType = file; name = app.flx; path = Flutter/
app.flx; sourceTree = "<group>"; };
+     9740EEB81CF902C7004384FC /* app.dylib */ = {isa = PBXFileReference; lastKnownFileType = "compiled.mach-o.dylib"; name =
app.dylib; path = Flutter/app.dylib; sourceTree = "<group>"; };
+     9740EEBA1CF902C7004384FC /* Flutter.framework */ = {isa = PBXFileReference; lastKnownFileType = wrapper.framework; name =
Flutter.framework; path = Flutter/Flutter.framework; sourceTree = "<group>"; };
+     97C146EE1CF9000F007C117D /* Runner.app */ = {isa = PBXFileReference; explicitFileType = wrapper.application; includeInIndex = 0;
path = Runner.app; sourceTree = BUILT_PRODUCTS_DIR; };
+     97C146F21CF9000F007C117D /* main.m */ = {isa = PBXFileReference; lastKnownFileType = sourcecode.c.objc; path = main.m; sourceTree
= "<group>"; };
+     97C146FB1CF9000F007C117D /* Base */ = {isa = PBXFileReference; lastKnownFileType = file.storyboard; name = Base; path =
Base.lproj/Main.storyboard; sourceTree = "<group>"; };
+     97C146FD1CF9000F007C117D /* Assets.xcassets */ = {isa = PBXFileReference; lastKnownFileType = folder.assetcatalog; path =
Assets.xcassets; sourceTree = "<group>"; };
+     97C147001CF9000F007C117D /* Base */ = {isa = PBXFileReference; lastKnownFileType = file.storyboard; name = Base; path =
Base.lproj/LaunchScreen.storyboard; sourceTree = "<group>"; };
+     97C147021CF9000F007C117D /* Info.plist */ = {isa = PBXFileReference; lastKnownFileType = text.plist.xml; path = Info.plist;
sourceTree = "<group>"; };
+ /* End PBXFileReference section */
+
+ /* Begin PBXFrameworksBuildPhase section */
+     97C146EB1CF9000F007C117D /* Frameworks */ = {

```

```

+         isa = PBXFrameworksBuildPhase;
+         buildActionMask = 2147483647;
+         files = (
+             9705A1C61CF904A100538489 /* Flutter.framework in Frameworks */,
+             B1F3D14E8117A6C9F65810E0 /* libPods-Runner.a in Frameworks */,
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+     };
+ /* End PBXFrameworksBuildPhase section */
+
+ /* Begin PBXGroup section */
+     840012C8B5EDBCF56B0E4AC1 /* Pods */ = {
+         isa = PBXGroup;
+         children = (
+         );
+         name = Pods;
+         sourceTree = "<group>";
+     };
+     9740EEB11CF90186004384FC /* Flutter */ = {
+         isa = PBXGroup;
+         children = (
+             9740EEB71CF902C7004384FC /* app.flx */,
+             9740EEB81CF902C7004384FC /* app.dylib */,
+             9740EEBA1CF902C7004384FC /* Flutter.framework */,
+             9740EEB21CF90195004384FC /* Debug.xcconfig */,
+             7AFA3C8E1D35360C0083082E /* Release.xcconfig */,
+             9740EEB31CF90195004384FC /* Generated.xcconfig */,
+         );
+         name = Flutter;
+         sourceTree = "<group>";
+     };
+     97C146E51CF9000F007C117D = {
+         isa = PBXGroup;
+         children = (
+             9740EEB11CF90186004384FC /* Flutter */,
+             97C146F01CF9000F007C117D /* Runner */,
+             97C146EF1CF9000F007C117D /* Products */,
+             840012C8B5EDBCF56B0E4AC1 /* Pods */,
+             CF3B75C9A7D2FA2A4C99F110 /* Frameworks */,
+         );
+         sourceTree = "<group>";
+     };
+     97C146EF1CF9000F007C117D /* Products */ = {
+         isa = PBXGroup;

```

```

+         children = (
+             97C146EE1CF9000F007C117D /* Runner.app */,
+         );
+         name = Products;
+         sourceTree = "<group>";
+     };
+ 97C146F01CF9000F007C117D /* Runner */ = {
+     isa = PBXGroup;
+     children = (
+         7AFFD8ED1D35381100E5BB4D /* AppDelegate.h */,
+         7AFFD8EE1D35381100E5BB4D /* AppDelegate.m */,
+         97C146FA1CF9000F007C117D /* Main.storyboard */,
+         97C146FD1CF9000F007C117D /* Assets.xcassets */,
+         97C146FF1CF9000F007C117D /* LaunchScreen.storyboard */,
+         97C147021CF9000F007C117D /* Info.plist */,
+         97C146F11CF9000F007C117D /* Supporting Files */,
+     );
+     path = Runner;
+     sourceTree = "<group>";
+ };
+ 97C146F11CF9000F007C117D /* Supporting Files */ = {
+     isa = PBXGroup;
+     children = (
+         97C146F21CF9000F007C117D /* main.m */,
+     );
+     name = "Supporting Files";
+     sourceTree = "<group>";
+ };
+ CF3B75C9A7D2FA2A4C99F110 /* Frameworks */ = {
+     isa = PBXGroup;
+     children = (
+         4D558BB7489B1C82B42A9097 /* libPods-Runner.a */,
+     );
+     name = Frameworks;
+     sourceTree = "<group>";
+ };
+ /* End PBXGroup section */
+
+ /* Begin PBXNativeTarget section */
+ 97C146ED1CF9000F007C117D /* Runner */ = {
+     isa = PBXNativeTarget;
+     buildConfigurationList = 97C147051CF9000F007C117D /* Build configuration list for PBXNativeTarget "Runner" */;
+     buildPhases = (
+         AB1344B0443C71CD721E1BB7 /* [CP] Check Pods Manifest.lock */,

```

```

+           9740EEB61CF901F6004384FC /* ShellScript */,
+           97C146EA1CF9000F007C117D /* Sources */,
+           97C146EB1CF9000F007C117D /* Frameworks */,
+           97C146EC1CF9000F007C117D /* Resources */,
+           9705A1C41CF9048500538489 /* Embed Frameworks */,
+           95BB15E9E1769C0D146AA592 /* [CP] Embed Pods Frameworks */,
+           532EA9D341340B1DCD08293D /* [CP] Copy Pods Resources */,
+       );
+       buildRules = (
+       );
+       dependencies = (
+       );
+       name = Runner;
+       productName = Runner;
+       productReference = 97C146EE1CF9000F007C117D /* Runner.app */;
+       productType = "com.apple.product-type.application";
+   };
+/* End PBXNativeTarget section */
+
+/* Begin PBXProject section */
+   97C146E61CF9000F007C117D /* Project object */ = {
+       isa = PBXProject;
+       attributes = {
+           LastUpgradeCheck = 0730;
+           ORGANIZATIONNAME = "The Chromium Authors";
+           TargetAttributes = {
+               97C146ED1CF9000F007C117D = {
+                   CreatedOnToolsVersion = 7.3.1;
+               };
+           };
+       };
+       buildConfigurationList = 97C146E91CF9000F007C117D /* Build configuration list for PBXProject "Runner" */;
+       compatibilityVersion = "Xcode 3.2";
+       developmentRegion = English;
+       hasScannedForEncodings = 0;
+       knownRegions = (
+           en,
+           Base,
+       );
+       mainGroup = 97C146E51CF9000F007C117D;
+       productRefGroup = 97C146EF1CF9000F007C117D /* Products */;
+       projectDirPath = "";
+       projectRoot = "";
+       targets = (

```



```

+           97C146ED1CF9000F007C117D /* Runner */,
+       );
+   };
+/* End PBXProject section */
+
+/* Begin PBXResourcesBuildPhase section */
+   97C146EC1CF9000F007C117D /* Resources */ = {
+       isa = PBXResourcesBuildPhase;
+       buildActionMask = 2147483647;
+       files = (
+           9740EEBB1CF902C7004384FC /* app.flx in Resources */,
+           97C147011CF9000F007C117D /* LaunchScreen.storyboard in Resources */,
+           9740EEB51CF90195004384FC /* Generated.xcconfig in Resources */,
+           9740EEB41CF90195004384FC /* Debug.xcconfig in Resources */,
+           97C146FE1CF9000F007C117D /* Assets.xcassets in Resources */,
+           97C146FC1CF9000F007C117D /* Main.storyboard in Resources */,
+       );
+       runOnlyForDeploymentPostprocessing = 0;
+   };
+/* End PBXResourcesBuildPhase section */
+
+/* Begin PBXShellScriptBuildPhase section */
+   532EA9D341340B1DCD08293D /* [CP] Copy Pods Resources */ = {
+       isa = PBXShellScriptBuildPhase;
+       buildActionMask = 2147483647;
+       files = (
+       );
+       inputPaths = (
+       );
+       name = "[CP] Copy Pods Resources";
+       outputPaths = (
+       );
+       runOnlyForDeploymentPostprocessing = 0;
+       shellPath = /bin/sh;
+       shellScript = "\"${SRCROOT}/Pods/Target Support Files/Pods-Runner/Pods-Runner-resources.sh\"";
+       showEnvVarsInLog = 0;
+   };
+   95BB15E9E1769C0D146AA592 /* [CP] Embed Pods Frameworks */ = {
+       isa = PBXShellScriptBuildPhase;
+       buildActionMask = 2147483647;
+       files = (
+       );
+       inputPaths = (
+       );

```

```

+         name = "[CP] Embed Pods Frameworks";
+         outputPaths = (
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+         shellPath = /bin/sh;
+         shellScript = "\"${SRCROOT}/Pods/Target Support Files/Pods-Runner/Pods-Runner-frameworks.sh\"";
+         showEnvVarsInLog = 0;
+     };
+     9740EEB61CF901F6004384FC /* ShellScript */ = {
+         isa = PBXShellScriptBuildPhase;
+         buildActionMask = 2147483647;
+         files = (
+         );
+         inputPaths = (
+         );
+         outputPaths = (
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+         shellPath = /bin/sh;
+         shellScript = "/bin/sh $FLUTTER_ROOT/packages/flutter_tools/bin/xcode_backend.sh";
+     };
+     AB1344B0443C71CD721E1BB7 /* [CP] Check Pods Manifest.lock */ = {
+         isa = PBXShellScriptBuildPhase;
+         buildActionMask = 2147483647;
+         files = (
+         );
+         inputPaths = (
+         );
+         name = "[CP] Check Pods Manifest.lock";
+         outputPaths = (
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+         shellPath = /bin/sh;
+         shellScript = "diff \"${PODS_ROOT}/../Podfile.lock\" \"${PODS_ROOT}/Manifest.lock\" > /dev/null\nif [[ $? != 0 ]] ; then
\n      cat << EOM\nerror: The sandbox is not in sync with the Podfile.lock. Run 'pod install' or update your CocoaPods installation.\nEOM\n
exit 1\nfi\n";
+         showEnvVarsInLog = 0;
+     };
+ /* End PBXShellScriptBuildPhase section */
+
+ /* Begin PBXSourcesBuildPhase section */
+     97C146EA1CF9000F007C117D /* Sources */ = {
+         isa = PBXSourcesBuildPhase;
+         buildActionMask = 2147483647;

```

```

+         files = (
+             978B8F6F1D3862AE00F588F7 /* AppDelegate.m in Sources */,
+             97C146F31CF9000F007C117D /* main.m in Sources */,
+         );
+         runOnlyForDeploymentPostprocessing = 0;
+     };
+ /* End PBXSourcesBuildPhase section */
+
+ /* Begin PBXVariantGroup section */
+     97C146FA1CF9000F007C117D /* Main.storyboard */ = {
+         isa = PBXVariantGroup;
+         children = (
+             97C146FB1CF9000F007C117D /* Base */,
+         );
+         name = Main.storyboard;
+         sourceTree = "<group>";
+     };
+     97C146FF1CF9000F007C117D /* LaunchScreen.storyboard */ = {
+         isa = PBXVariantGroup;
+         children = (
+             97C147001CF9000F007C117D /* Base */,
+         );
+         name = LaunchScreen.storyboard;
+         sourceTree = "<group>";
+     };
+ /* End PBXVariantGroup section */
+
+ /* Begin XCBuildConfiguration section */
+     97C147031CF9000F007C117D /* Debug */ = {
+         isa = XCBuildConfiguration;
+         baseConfigurationReference = 9740EEB21CF90195004384FC /* Debug.xcconfig */;
+         buildSettings = {
+             ALWAYS_SEARCH_USER_PATHS = NO;
+             CLANG_ANALYZER_NONNULL = YES;
+             CLANG_CXX_LANGUAGE_STANDARD = "gnu++0x";
+             CLANG_CXX_LIBRARY = "libc++";
+             CLANG_ENABLE_MODULES = YES;
+             CLANG_ENABLE_OBJC_ARC = YES;
+             CLANG_WARN_BOOL_CONVERSION = YES;
+             CLANG_WARN_CONSTANT_CONVERSION = YES;
+             CLANG_WARN_DIRECT_OBJC_ISA_USAGE = YES_ERROR;
+             CLANG_WARN_EMPTY_BODY = YES;
+             CLANG_WARN_ENUM_CONVERSION = YES;
+             CLANG_WARN_INT_CONVERSION = YES;

```

```

+         CLANG_WARN_OBJC_ROOT_CLASS = YES_ERROR;
+         CLANG_WARN_UNREACHABLE_CODE = YES;
+         CLANG_WARN__DUPLICATE_METHOD_MATCH = YES;
+         "CODE_SIGN_IDENTITY[sdk=iphoneos*]" = "iPhone Developer";
+         COPY_PHASE_STRIP = NO;
+         DEBUG_INFORMATION_FORMAT = dwarf;
+         ENABLE_STRICT_OBJC_MSGSEND = YES;
+         ENABLE_TESTABILITY = YES;
+         GCC_C_LANGUAGE_STANDARD = gnu99;
+         GCC_DYNAMIC_NO_PIC = NO;
+         GCC_NO_COMMON_BLOCKS = YES;
+         GCC_OPTIMIZATION_LEVEL = 0;
+         GCC_PREPROCESSOR_DEFINITIONS = (
+             "DEBUG=1",
+             "$(inherited)",
+         );
+         GCC_WARN_64_TO_32_BIT_CONVERSION = YES;
+         GCC_WARN_ABOUT_RETURN_TYPE = YES_ERROR;
+         GCC_WARN_UNDECLARED_SELECTOR = YES;
+         GCC_WARN_UNINITIALIZED_AUTOS = YES_AGGRESSIVE;
+         GCC_WARN_UNUSED_FUNCTION = YES;
+         GCC_WARN_UNUSED_VARIABLE = YES;
+         IPHONEOS_DEPLOYMENT_TARGET = 8.0;
+         MTL_ENABLE_DEBUG_INFO = YES;
+         ONLY_ACTIVE_ARCH = YES;
+         SDKROOT = iphoneos;
+         TARGETED_DEVICE_FAMILY = "1,2";
+     };
+     name = Debug;
+ };
+ 97C147041CF9000F007C117D /* Release */ = {
+     isa = XCBuildConfiguration;
+     baseConfigurationReference = 7AFA3C8E1D35360C0083082E /* Release.xcconfig */;
+     buildSettings = {
+         ALWAYS_SEARCH_USER_PATHS = NO;
+         CLANG_ANALYZER_NONNULL = YES;
+         CLANG_CXX_LANGUAGE_STANDARD = "gnu++0x";
+         CLANG_CXX_LIBRARY = "libc++";
+         CLANG_ENABLE_MODULES = YES;
+         CLANG_ENABLE_OBJC_ARC = YES;
+         CLANG_WARN_BOOL_CONVERSION = YES;
+         CLANG_WARN_CONSTANT_CONVERSION = YES;
+         CLANG_WARN_DIRECT_OBJC_ISA_USAGE = YES_ERROR;
+         CLANG_WARN_EMPTY_BODY = YES;

```

```

+         CLANG_WARN_ENUM_CONVERSION = YES;
+         CLANG_WARN_INT_CONVERSION = YES;
+         CLANG_WARN_OBJC_ROOT_CLASS = YES_ERROR;
+         CLANG_WARN_UNREACHABLE_CODE = YES;
+         CLANG_WARN__DUPLICATE_METHOD_MATCH = YES;
+         "CODE_SIGN_IDENTITY[sdk=iphoneos*]" = "iPhone Developer";
+         COPY_PHASE_STRIP = NO;
+         DEBUG_INFORMATION_FORMAT = "dwarf-with-dsym";
+         ENABLE_NS_ASSERTIONS = NO;
+         ENABLE_STRICT_OBJC_MSGSEND = YES;
+         GCC_C_LANGUAGE_STANDARD = gnu99;
+         GCC_NO_COMMON_BLOCKS = YES;
+         GCC_WARN_64_TO_32_BIT_CONVERSION = YES;
+         GCC_WARN_ABOUT_RETURN_TYPE = YES_ERROR;
+         GCC_WARN_UNDECLARED_SELECTOR = YES;
+         GCC_WARN_UNINITIALIZED_AUTOS = YES_AGGRESSIVE;
+         GCC_WARN_UNUSED_FUNCTION = YES;
+         GCC_WARN_UNUSED_VARIABLE = YES;
+         IPHONEOS_DEPLOYMENT_TARGET = 8.0;
+         MTL_ENABLE_DEBUG_INFO = NO;
+         SDKROOT = iphoneos;
+         TARGETED_DEVICE_FAMILY = "1,2";
+         VALIDATE_PRODUCT = YES;
+     };
+     name = Release;
+ };
+ 97C147061CF9000F007C117D /* Debug */ = {
+     isa = XCBuildConfiguration;
+     baseConfigurationReference = 9740EEB21CF90195004384FC /* Debug.xcconfig */;
+     buildSettings = {
+         ASSETCATALOG_COMPILER_APPICON_NAME = AppIcon;
+         ENABLE_BITCODE = NO;
+         FRAMEWORK_SEARCH_PATHS = (
+             "$(inherited)",
+             "$(PROJECT_DIR)/Flutter",
+         );
+         INFOPLIST_FILE = Runner/Info.plist;
+         LD_RUNPATH_SEARCH_PATHS = "$(inherited) @executable_path/Frameworks";
+         LIBRARY_SEARCH_PATHS = (
+             "$(inherited)",
+             "$(PROJECT_DIR)/Flutter",
+         );
+         PRODUCT_NAME = "$(TARGET_NAME)";
+     };
+ };

```

```

+         name = Debug;
+     };
+     97C147071CF9000F007C117D /* Release */ = {
+         isa = XCBuildConfiguration;
+         baseConfigurationReference = 7AFA3C8E1D35360C0083082E /* Release.xcconfig */;
+         buildSettings = {
+             ASSETCATALOG_COMPILER_APPICON_NAME = AppIcon;
+             ENABLE_BITCODE = NO;
+             FRAMEWORK_SEARCH_PATHS = (
+                 "$(inherited)",
+                 "$(PROJECT_DIR)/Flutter",
+             );
+             INFOPLIST_FILE = Runner/Info.plist;
+             LD_RUNPATH_SEARCH_PATHS = "$(inherited) @executable_path/Frameworks";
+             LIBRARY_SEARCH_PATHS = (
+                 "$(inherited)",
+                 "$(PROJECT_DIR)/Flutter",
+             );
+             PRODUCT_NAME = "$(TARGET_NAME)";
+         };
+     name = Release;
+ };
+ /* End XCBuildConfiguration section */
+
+ /* Begin XCConfigurationList section */
+     97C146E91CF9000F007C117D /* Build configuration list for PBXProject "Runner" */ = {
+         isa = XCConfigurationList;
+         buildConfigurations = (
+             97C147031CF9000F007C117D /* Debug */,
+             97C147041CF9000F007C117D /* Release */,
+         );
+         defaultConfigurationIsVisible = 0;
+         defaultConfigurationName = Release;
+     };
+     97C147051CF9000F007C117D /* Build configuration list for PBXNativeTarget "Runner" */ = {
+         isa = XCConfigurationList;
+         buildConfigurations = (
+             97C147061CF9000F007C117D /* Debug */,
+             97C147071CF9000F007C117D /* Release */,
+         );
+         defaultConfigurationIsVisible = 0;
+         defaultConfigurationName = Release;
+     };
+ /* End XCConfigurationList section */

```

```
+     };
+     rootObject = 97C146E61CF9000F007C117D /* Project object */;
+}
diff --git a/ios/Runner.xcodeproj/project.xcworkspace/contents.xcworkspacedata b/ios/Runner.xcodeproj/project.xcworkspace/
contents.xcworkspacedata
new file mode 100644
index 0000000..21a3cc1
--- /dev/null
+++ b/ios/Runner.xcodeproj/project.xcworkspace/contents.xcworkspacedata
@@ -0,0 +1,10 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<Workspace
+  version = "1.0">
+  <FileRef
+    location = "group:Runner.xcodeproj">
+  </FileRef>
+  <FileRef
+    location = "group:Pods/Pods.xcodeproj">
+  </FileRef>
+</Workspace>
diff --git a/ios/Runner.xcodeproj/xcsourcedata/xcschemes/Runner.xcscheme b/ios/Runner.xcodeproj/xcsourcedata/xcschemes/Runner.xcscheme
new file mode 100644
index 0000000..89550f6
--- /dev/null
+++ b/ios/Runner.xcodeproj/xcsourcedata/xcschemes/Runner.xcscheme
@@ -0,0 +1,91 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<Scheme
+  LastUpgradeVersion = "0730"
+  version = "1.3">
+  <BuildAction
+    parallelizeBuildables = "YES"
+    buildImplicitDependencies = "YES">
+    <BuildActionEntries>
+      <BuildActionEntry
+        buildForTesting = "YES"
+        buildForRunning = "YES"
+        buildForProfiling = "YES"
+        buildForArchiving = "YES"
+        buildForAnalyzing = "YES">
+        <BuildableReference
+          BuildableIdentifier = "primary"
+          BlueprintIdentifier = "97C146ED1CF9000F007C117D"
+          BuildableName = "Runner.app"
```

```
+         BlueprintName = "Runner"
+         ReferencedContainer = "container:Runner.xcodeproj">
+     </BuildableReference>
+ </BuildActionEntry>
+ </BuildActionEntries>
+ </BuildAction>
+ <TestAction
+     buildConfiguration = "Debug"
+     selectedDebuggerIdentifier = "Xcode.DebuggerFoundation.Debugger.LLDB"
+     selectedLauncherIdentifier = "Xcode.DebuggerFoundation.Launcher.LLDB"
+     shouldUseLaunchSchemeArgsEnv = "YES">
+     <Testables>
+     </Testables>
+     <MacroExpansion>
+         <BuildableReference
+             BuildableIdentifier = "primary"
+             BlueprintIdentifier = "97C146ED1CF9000F007C117D"
+             BuildableName = "Runner.app"
+             BlueprintName = "Runner"
+             ReferencedContainer = "container:Runner.xcodeproj">
+         </BuildableReference>
+     </MacroExpansion>
+     <AdditionalOptions>
+     </AdditionalOptions>
+ </TestAction>
+ <LaunchAction
+     buildConfiguration = "Debug"
+     selectedDebuggerIdentifier = "Xcode.DebuggerFoundation.Debugger.LLDB"
+     selectedLauncherIdentifier = "Xcode.DebuggerFoundation.Launcher.LLDB"
+     launchStyle = "0"
+     useCustomWorkingDirectory = "NO"
+     ignoresPersistentStateOnLaunch = "NO"
+     debugDocumentVersioning = "YES"
+     debugServiceExtension = "internal"
+     allowLocationSimulation = "YES">
+     <BuildableProductRunnable
+         runnableDebuggingMode = "0">
+         <BuildableReference
+             BuildableIdentifier = "primary"
+             BlueprintIdentifier = "97C146ED1CF9000F007C117D"
+             BuildableName = "Runner.app"
+             BlueprintName = "Runner"
+             ReferencedContainer = "container:Runner.xcodeproj">
+         </BuildableReference>
```



```

+     </BuildableProductRunnable>
+     <AdditionalOptions>
+     </AdditionalOptions>
+ </LaunchAction>
+ <ProfileAction
+   buildConfiguration = "Release"
+   shouldUseLaunchSchemeArgsEnv = "YES"
+   savedToolIdentifier = ""
+   useCustomWorkingDirectory = "NO"
+   debugDocumentVersioning = "YES">
+   <BuildableProductRunnable
+     runnableDebuggingMode = "0">
+     <BuildableReference
+       BuildableIdentifier = "primary"
+       BlueprintIdentifier = "97C146ED1CF9000F007C117D"
+       BuildableName = "Runner.app"
+       BlueprintName = "Runner"
+       ReferencedContainer = "container:Runner.xcodeproj">
+     </BuildableReference>
+   </BuildableProductRunnable>
+ </ProfileAction>
+ <AnalyzeAction
+   buildConfiguration = "Debug">
+ </AnalyzeAction>
+ <ArchiveAction
+   buildConfiguration = "Release"
+   revealArchiveInOrganizer = "YES">
+ </ArchiveAction>
+</Scheme>
diff --git a/ios/Runner.xcworkspace/contents.xcworkspacedata b/ios/Runner.xcworkspace/contents.xcworkspacedata
new file mode 100644
index 0000000..21a3cc1
--- /dev/null
+++ b/ios/Runner.xcworkspace/contents.xcworkspacedata
@@ -0,0 +1,10 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<Workspace
+  version = "1.0">
+  <FileRef
+    location = "group:Runner.xcodeproj">
+  </FileRef>
+  <FileRef
+    location = "group:Pods/Pods.xcodeproj">
+  </FileRef>

```

```
+</Workspace>
diff --git a/ios/Runner/AppDelegate.h b/ios/Runner/AppDelegate.h
new file mode 100644
index 0000000..a5a8b38
--- /dev/null
+++ b/ios/Runner/AppDelegate.h
@@ -0,0 +1,7 @@
+#import <UIKit/UIKit.h>
+
+@interface AppDelegate : UIResponder <UIApplicationDelegate>
+
+@property (strong, nonatomic) UIWindow *window;
+
+@end
diff --git a/ios/Runner/AppDelegate.m b/ios/Runner/AppDelegate.m
new file mode 100644
index 0000000..d4cfa3a
--- /dev/null
+++ b/ios/Runner/AppDelegate.m
@@ -0,0 +1,33 @@
+#import <Flutter/Flutter.h>
+#include "AppDelegate.h"
+
+@implementation AppDelegate
+
+- (BOOL)application:(UIApplication *)application didFinishLaunchingWithOptions:(NSDictionary *)launchOptions {
+    // Override point for customization after application launch.
+    return YES;
+}
+
+- (void)applicationWillResignActive:(UIApplication *)application {
+    // Sent when the application is about to move from active to inactive state. This can occur for certain types of temporary interruptions
+    (such as an incoming phone call or SMS message) or when the user quits the application and it begins the transition to the background state.
+    // Use this method to pause ongoing tasks, disable timers, and throttle down OpenGL ES frame rates. Games should use this method to pause
+    the game.
+}
+
+- (void)applicationDidEnterBackground:(UIApplication *)application {
+    // Use this method to release shared resources, save user data, invalidate timers, and store enough application state information to restore
+    your application to its current state in case it is terminated later.
+    // If your application supports background execution, this method is called instead of applicationWillTerminate: when the user quits.
+}
+
+- (void)applicationWillEnterForeground:(UIApplication *)application {
```

```
+ // Called as part of the transition from the background to the inactive state; here you can undo many of the changes made on entering the
background.
+}
+
+- (void)applicationDidBecomeActive:(UIApplication *)application {
+ // Restart any tasks that were paused (or not yet started) while the application was inactive. If the application was previously in the
background, optionally refresh the user interface.
+}
+
+- (void)applicationWillTerminate:(UIApplication *)application {
+ // Called when the application is about to terminate. Save data if appropriate. See also applicationDidEnterBackground:.
+}
+
+@end
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json
new file mode 100644
index 0000000..87cdfb9
--- /dev/null
+++ b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json
@@ -0,0 +1,110 @@
+{
+  "images": [
+    {
+      "idiom": "iphone",
+      "size": "29x29",
+      "scale": "1x",
+      "filename": "Icon-App-29x29@1x.png"
+    },
+    {
+      "idiom": "iphone",
+      "size": "29x29",
+      "scale": "2x",
+      "filename": "Icon-App-29x29@2x.png"
+    },
+    {
+      "idiom": "iphone",
+      "size": "29x29",
+      "scale": "3x",
+      "filename": "Icon-App-29x29@3x.png"
+    },
+    {
+      "idiom": "iphone",
+      "size": "40x40",
+      "scale": "1x",
```

```
+      "filename": "Icon-App-40x40@1x.png"
+      ,
+      "idiom": "iphone",
+      "size": "40x40",
+      "scale": "2x",
+      "filename": "Icon-App-40x40@2x.png"
+      ,
+      "idiom": "iphone",
+      "size": "40x40",
+      "scale": "3x",
+      "filename": "Icon-App-40x40@3x.png"
+      ,
+      "idiom": "iphone",
+      "size": "60x60",
+      "scale": "1x",
+      "filename": "Icon-App-60x60@1x.png"
+      ,
+      "idiom": "iphone",
+      "size": "60x60",
+      "scale": "2x",
+      "filename": "Icon-App-60x60@2x.png"
+      ,
+      "idiom": "iphone",
+      "size": "60x60",
+      "scale": "3x",
+      "filename": "Icon-App-60x60@3x.png"
+      ,
+      "idiom": "ipad",
+      "size": "29x29",
+      "scale": "1x",
+      "filename": "Icon-App-29x29@1x.png"
+      ,
+      "idiom": "ipad",
+      "size": "29x29",
+      "scale": "2x",
+      "filename": "Icon-App-29x29@2x.png"
+      ,
```

```

+     {
+       "idiom":"ipad",
+       "size":"40x40",
+       "scale":"1x",
+       "filename":"Icon-App-40x40@1x.png"
+     },
+     {
+       "idiom":"ipad",
+       "size":"40x40",
+       "scale":"2x",
+       "filename":"Icon-App-40x40@2x.png"
+     },
+     {
+       "idiom":"ipad",
+       "size":"76x76",
+       "scale":"1x",
+       "filename":"Icon-App-76x76@1x.png"
+     },
+     {
+       "idiom":"ipad",
+       "size":"76x76",
+       "scale":"2x",
+       "filename":"Icon-App-76x76@2x.png"
+     },
+     {
+       "idiom":"ipad",
+       "size":"76x76",
+       "scale":"3x",
+       "filename":"Icon-App-76x76@3x.png"
+     },
+     {
+       "idiom":"ipad",
+       "size":"83.5x83.5",
+       "scale":"2x",
+       "filename":"Icon-App-83.5x83.5@2x.png"
+   }
+ ],
+ "info":{
+   "version":1,
+   "author":"makeappicon"
+ }
+}

```

```

diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@1x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@1x.png

```

```
new file mode 100644
index 0000000..4cde121
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@1x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@2x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@2x.png
new file mode 100644
index 0000000..d0ef06e
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@2x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@3x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@3x.png
new file mode 100644
index 0000000..dcdc230
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@3x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@1x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@1x.png
new file mode 100644
index 0000000..2ccbfd9
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@1x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@2x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@2x.png
new file mode 100644
index 0000000..c8f9ed8
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@2x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@3x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@3x.png
new file mode 100644
index 0000000..a6d6b86
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@3x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@1x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@1x.png
new file mode 100644
index 0000000..f091b6b
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@1x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@2x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@2x.png
new file mode 100644
index 0000000..a6d6b86
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@2x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@3x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@3x.png
new file mode 100644
index 0000000..75b2d16
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@3x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@1x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-
```

```
App-76x76@1x.png
new file mode 100644
index 0000000..c4df70d
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@1x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@2x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@2x.png
new file mode 100644
index 0000000..6a84f41
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@2x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@3x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@3x.png
new file mode 100644
index 0000000..5d2bad8
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@3x.png differ
diff --git a/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-83.5x83.5@2x.png b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-83.5x83.5@2x.png
new file mode 100644
index 0000000..d0e1f58
Binary files /dev/null and b/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-83.5x83.5@2x.png differ
diff --git a/ios/Runner/Base.lproj/LaunchScreen.storyboard b/ios/Runner/Base.lproj/LaunchScreen.storyboard
new file mode 100644
index 0000000..ebf48f6
--- /dev/null
+++ b/ios/Runner/Base.lproj/LaunchScreen.storyboard
@@ -0,0 +1,27 @@
+<?xml version="1.0" encoding="UTF-8" standalone="no"?>
+<document type="com.apple.InterfaceBuilder3.CocoaTouch.Storyboard.XIB" version="3.0" toolsVersion="10117" systemVersion="15F34"
targetRuntime="iOS.CocoaTouch" propertyAccessControl="none" useAutolayout="YES" launchScreen="YES" useTraitCollections="YES"
initialViewController="01J-lp-oVM">
+  <dependencies>
+    <deployment identifier="iOS"/>
+    <plugIn identifier="com.apple.InterfaceBuilder.IBCocoaTouchPlugin" version="10085"/>
+  </dependencies>
+  <scenes>
+    <!--View Controller-->
+    <scene sceneID="EHf-IW-A2E">
+      <objects>
+        <viewController id="01J-lp-oVM" sceneMemberID="viewController">
+          <layoutGuides>
+            <viewControllerLayoutGuide type="top" id="Llm-lL-Icb"/>
+            <viewControllerLayoutGuide type="bottom" id="xb3-a0-Qok"/>
+          </layoutGuides>
+          <view key="view" contentMode="scaleToFill" id="Ze5-6b-2t3">
+            <rect key="frame" x="0.0" y="0.0" width="600" height="600"/>

```

```

+         <autoresizingMask key="autoresizingMask" widthSizable="YES" heightSizable="YES"/>
+         <color key="backgroundColor" white="1" alpha="1" colorSpace="custom" customColorSpace="calibratedWhite"/>
+     </view>
+ </viewController>
+ <placeholder placeholderIdentifier="IBFirstResponder" id="iYj-Kq-Ea1" userLabel="First Responder"
sceneMemberID="firstResponder"/>
+ </objects>
+ <point key="canvasLocation" x="53" y="375"/>
+ </scene>
+ </scenes>
+</document>
diff --git a/ios/Runner/Base.lproj/Main.storyboard b/ios/Runner/Base.lproj/Main.storyboard
new file mode 100644
index 0000000..f3c2851
--- /dev/null
+++ b/ios/Runner/Base.lproj/Main.storyboard
@@ -0,0 +1,26 @@
+<?xml version="1.0" encoding="UTF-8" standalone="no"?>
+<document type="com.apple.InterfaceBuilder3.CocoaTouch.Storyboard.XIB" version="3.0" toolsVersion="10117" systemVersion="15F34"
targetRuntime="iOS.CocoaTouch" propertyAccessControl="none" useAutolayout="YES" useTraitCollections="YES" initialViewController="BYZ-38-t0r">
+ <dependencies>
+ <deployment identifier="iOS"/>
+ <plugIn identifier="com.apple.InterfaceBuilder.IBCocoaTouchPlugin" version="10085"/>
+ </dependencies>
+ <scenes>
+ <!--Flutter View Controller-->
+ <scene sceneID="tne-QT-ifu">
+ <objects>
+ <viewController id="BYZ-38-t0r" customClass="FlutterViewController" sceneMemberID="viewController">
+ <layoutGuides>
+ <viewControllerLayoutGuide type="top" id="y3c-jy-aDJ"/>
+ <viewControllerLayoutGuide type="bottom" id="wfy-db-euE"/>
+ </layoutGuides>
+ <view key="view" contentMode="scaleToFill" id="8bC-Xf-vdC">
+ <rect key="frame" x="0.0" y="0.0" width="600" height="600"/>
+ <autoresizingMask key="autoresizingMask" widthSizable="YES" heightSizable="YES"/>
+ <color key="backgroundColor" white="1" alpha="1" colorSpace="custom" customColorSpace="calibratedWhite"/>
+ </view>
+ </viewController>
+ <placeholder placeholderIdentifier="IBFirstResponder" id="dkx-z0-nzr" sceneMemberID="firstResponder"/>
+ </objects>
+ </scene>
+ </scenes>
+</document>

```



```
diff --git a/ios/Runner/Info.plist b/ios/Runner/Info.plist
new file mode 100644
index 0000000..fbc0886
--- /dev/null
+++ b/ios/Runner/Info.plist
@@ -0,0 +1,49 @@
+<?xml version="1.0" encoding="UTF-8"?>
+<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN" "http://www.apple.com/DTDs/PropertyList-1.0.dtd">
+<plist version="1.0">
+<dict>
+  <key>CFBundleDevelopmentRegion</key>
+  <string>en</string>
+  <key>CFBundleExecutable</key>
+  <string>$(EXECUTABLE_NAME)</string>
+  <key>CFBundleIdentifier</key>
+  <string>com.yourcompany.f</string>
+  <key>CFBundleInfoDictionaryVersion</key>
+  <string>6.0</string>
+  <key>CFBundleName</key>
+  <string>f</string>
+  <key>CFBundlePackageType</key>
+  <string>APPL</string>
+  <key>CFBundleShortVersionString</key>
+  <string>1.0</string>
+  <key>CFBundleSignature</key>
+  <string>????</string>
+  <key>CFBundleVersion</key>
+  <string>1</string>
+  <key>LSRequiresIPhoneOS</key>
+  <true/>
+  <key>UILaunchStoryboardName</key>
+  <string>LaunchScreen</string>
+  <key>UIMainStoryboardFile</key>
+  <string>Main</string>
+  <key>UIRequiredDeviceCapabilities</key>
+  <array>
+    <string>arm64</string>
+  </array>
+  <key>UISupportedInterfaceOrientations</key>
+  <array>
+    <string>UIInterfaceOrientationPortrait</string>
+    <string>UIInterfaceOrientationLandscapeLeft</string>
+    <string>UIInterfaceOrientationLandscapeRight</string>
+  </array>
+</dict>
```

```
+ <key>UISupportedInterfaceOrientations~ipad</key>
+ <array>
+   <string>UIInterfaceOrientationPortrait</string>
+   <string>UIInterfaceOrientationPortraitUpsideDown</string>
+   <string>UIInterfaceOrientationLandscapeLeft</string>
+   <string>UIInterfaceOrientationLandscapeRight</string>
+ </array>
+ <key>UIViewControllerBasedStatusBarAppearance</key>
+ <false/>
+</dict>
+</plist>
```

```
diff --git a/ios/Runner/main.m b/ios/Runner/main.m
```

```
new file mode 100644
```

```
index 0000000..7e0fe2c
```

```
--- /dev/null
```

```
+++ b/ios/Runner/main.m
```

```
@@ -0,0 +1,11 @@
```

```
+#import <UIKit/UIKit.h>
```

```
+#import <Flutter/Flutter.h>
```

```
+#import "AppDelegate.h"
```

```
+
```

```
+int main(int argc, char * argv[]) {
```

```
+  FlutterInit(argc, (const char**)argv);
```

```
+  @autoreleasepool {
```

```
+    return UIApplicationMain(argc, argv, nil,
```

```
+                               NSStringFromClass([AppDelegate class]));
```

```
+  }
```

```
+}
```

```
diff --git a/lib/main.dart b/lib/main.dart
```

```
new file mode 100644
```

```
index 0000000..b45cce8
```

```
--- /dev/null
```

```
+++ b/lib/main.dart
```

```
@@ -0,0 +1,48 @@
```

```
+import 'package:flutter/material.dart';
```

```
+
```

```
+void main() {
```

```
+  runApp(
```

```
+    new MaterialApp(
```

```
+      title: 'Flutter Demo',
```

```
+      theme: new ThemeData(
```

```
+        primarySwatch: Colors.blue,
```

```
+      ),
```

```
+      home: new FlutterDemo(),
```

```
+   ),
+ );
+}
+
+class FlutterDemo extends StatefulWidget {
+  FlutterDemo({Key key}) : super(key: key);
+
+  @override
+  _FlutterDemoState createState() => new _FlutterDemoState();
+}
+
+class _FlutterDemoState extends State<FlutterDemo> {
+  int _counter = 0;
+
+  void _incrementCounter() {
+    setState(() {
+      _counter++;
+    });
+  }
+
+  @override
+  Widget build(BuildContext context) {
+    return new Scaffold(
+      appBar: new AppBar(
+        title: new Text('Flutter Demo'),
+      ),
+      body: new Center(
+        child: new Text(
+          'Button tapped $_counter time${ _counter == 1 ? '' : 's' }.'),
+        ),
+      floatingActionButton: new FloatingActionButton(
+        onPressed: _incrementCounter,
+        tooltip: 'Increment',
+        child: new Icon(Icons.add),
+      ),
+    ),
+  );
+ }
+}
diff --git a/pubspec.yaml b/pubspec.yaml
new file mode 100644
index 0000000..de4835f
--- /dev/null
+++ b/pubspec.yaml
@@ -0,0 +1,5 @@
```

```
+name: f
+description: A new flutter project.
+dependencies:
+  flutter:
+    sdk: flutter
mit-macbookpro2:f mit$
```