GM ASEP / A2 / CLASS FINAL / VERSION 1.0

CLASS FINAL PREP

Units 1 and 2, weighted by priority and your quiz misses.

Prepared 2026-10-13 **Scope** Instructor scope (class notes), not the ASE task list

CONTENTS

01 How to Use This (read first)

02 Tier A: Planetary Gears (your Unit 1 misses)

03 Tier A: Torque Converter (Unit 2)

04 Tier A/B: Hydraulics and Pressure

05 Tier B: Fluid, Heat and Diagnosis (Ch 15)

06 Tier B: Electronics

07 Tier C: Recognition

08 Night Before

01 HOW TO USE THIS (READ FIRST)

Built for the **class final on 2026-10-14**, assuming it covers **Unit 1 and Unit 2** (instructor scope: your class notes, not the ASE task list). It is a compression of the Unit 1 guide, the Unit 2 guide and your own quiz misses. Version 1: **no Unit 2 test feedback yet.** Send what you missed and I'll rebuild it as v2.

Weighting. Time goes where the points are likely and where you have already missed:

TIER	WHAT	WHY IT'S WEIGHTED THIS WAY
A: lock in	Planetary parts and rules; reaction clutch; converter and stall logic; line pressure high/low	You missed planetary items on the Unit 1 quiz; Unit 2 is converter/hydraulic heavy
B: know cold	TCC apply/release; pressure test logic; fluid level and condition; sensors and solenoids	Straight recall from your notes
C: recognize	10-speed chart pattern; gear set families; shift types; accumulators	The instructor said recognize, don't memorize

02 TIER A: PLANETARY GEARS (YOUR UNIT 1 MISSES)

2.1 THE FOUR NAMES

PART	MEMORY HOOK
Sun	Small gear in the **center**. External teeth
Planets / pinions	Orbit the sun, mesh with sun **and** ring
Carrier	**Holds the planets.** It is not the big outer gear
Ring (annulus, internal gear)	**Big outer gear, teeth on the inside**

> **WRONG DIRECTION** "Sun gear is also called the internal gear" is **false**. Internal gear = **ring**. Carrier ≠ ring.

2.2 THE RULES

RESULT	CONDITION
Neutral	No driving member or no reaction (held) member: nothing connects input to output
Direct drive 1:1	**Any two members driven together**
Reduction (forward)	**Carrier is the output**
Overdrive (forward)	**Carrier is the input**
Reverse	**Carrier is held**, always reversed
Sun input → reduction	Sun output → overdrive

One member **driven**, one **held**, one **output**. Extra pinions add strength, not ratio. Planetary ratios from sun/ring: 30-tooth sun, 70-tooth ring, ring held and sun driven = (30+70)/30 = **3.33:1**.

2.3 GEAR SETS

- **Simpson:** one sun, two carriers, two rings (4–5 speed).
- **Ravigneaux: two suns, two planet sets, one carrier, one ring.**
- **LePelletier:** a **simple planetary + a Ravigneaux** (6–8 speed; 6L80E).
- **Total ratio of stages in series: multiply, don't add.** A big number is not a reason to reject it. (2:1 then 3:1 = 6:1.)

2.4 CLUTCHES AND HOLDING DEVICES

- **Reaction (holding) multi-disc clutch:** the unlined **steel plates are splined to the transmission case**. Not a drum, not a carrier.
- **Band** wraps a drum; a **servo** applies it.
- **One-way clutches:** roller, sprag (hourglass), mechanical diode (strongest, like a ratchet). Holds one way, freewheels the other.

- **Synchronous** shifts (clutch-to-clutch): timed, **no one-way clutch**; mistimed = harsh/tie-up or flare. **Nonsynchronous:** one-way clutch self-releases.
- **Garage shift:** at rest, static friction. **Power shift:** under load, dynamic friction.

---

03 TIER A: TORQUE CONVERTER (UNIT 2)

PART	CONNECTED TO	RULE
Impeller (pump)	**Engine**	Engine rpm = impeller speed
Turbine	**Input shaft**	Input speed sensor = turbine speed
Stator	One-way clutch (reaction)	Redirects fluid back to the impeller

	STALL / LAUNCH	COUPLING
Stator	**Locked** by the one-way clutch	**Freewheels**
Flow	Vortex	Rotary
Multiplication	**Yes**	**None**

- **Stator freewheels both ways:** poor launch, good highway, **low stall**.
- **Stator locked both ways:** good launch, poor highway, overheating.
- **High stall = the transmission is slipping.** Nothing inside the converter raises stall.
- **Most transmission heat comes from the converter**, especially at stall. Limit stall tests. Cool it with the parking brake and idle.
- **Creep** with brakes released is normal. A non-lockup converter always slips.

TCC

- **TCC slip = engine rpm − turbine rpm.** Applied: ~200 → **0**. PWM solenoid. Damper springs cushion the apply.
- **Release oil** (stator shaft/turbine shaft passage) pushes the plate **off**. **Apply oil** (converter hub/stator shaft passage) **clamps** it.
- **No TCC apply:** electrical (connector, harness, solenoid), internal converter damage, TCC control or regulator valve worn or sticking, cut turbine-shaft O-ring.
- **Overdrive transmission that won't lock the converter overheats.**

---

04 TIER A/B: HYDRAULICS AND PRESSURE

- **Pascal's law:** equal everywhere; **pressure = force ÷ area** (10 lb on 1 sq in = 10 psi; 4 sq in at 10 psi = 40 lb).
- **Pump creates flow. Resistance creates pressure.** Internal pump, always. Gear/crescent, gerotor, vane. **Variable displacement: vane housing pivots.**
- **Valves:** switch (routes), servo (moves a valve), regulator (pressure). **Spool valves.** Manual valve = mechanical. Every unit has a pressure regulator.
- **TV pressure** = throttle position.

LINE PRESSURE: HIGH OR LOW

READING	CAUSE
Low in every range	Low fluid, foamy/aerated fluid, clogged filter or suction air leak, worn pump, weak regulator, big common leak
Low in one range	Leak in **that** circuit: piston seal, sealing ring, servo seal
Fails with all valves closed (P/N)	**Upstream:** pump, filter, regulator
OK until a range is selected, then drops	That range's circuit leaks
High	Stuck regulator; EPC/pressure solenoid failsafe (**no current = max** on classic design); TV cable too tight; modulator vacuum lost
High/low in neutral	Throttle valve, converter or cooler circuits

- **Reverse reads higher by design** (textbook example 150–250 psi; P/N/D idle 50–60).
- Mainline test gauge: **0–300 psi**. Electronic gauge on a scope shows small changes. If line pressure is low, **don't stall test**.

---

05 TIER B: FLUID, HEAT AND DIAGNOSIS (CH 15)

CONDITION	RESULT
Underfilled	Air at the filter and pump intake: mushy, may go to neutral, slip, TCC won't lock or unlock right
Overfilled	Fluid reaches the spinning gear sets and **foams**: slip, mushy, fluid out the **vent or filler pipe**
Milkshake fluid	Water/coolant, usually a **failed transmission cooler** in the radiator
Overheating signs	Fluid out the vent, **purple converter**, burned clutches

- **Cold slip or flare while cornering, fine warm → low fluid level**.
- A poorly running **engine** can feel like a shift problem. **Wrong fluid** causes shift problems.
- **Cooler flow** is measured as **flow rate**.
- **Cracked flexplate or case** = **alignment**. Alignment dowels stay in the engine; reinstall them if they come out with the old transmission.
- Shift terms: **flare** = rpm rises (released early); **tie-up** = rpm pulled down (overlap); **slide-bump** = accumulator bottoms out (smooth start, harsh finish). **Accumulator** smooths pressure rise and doesn't store backup pressure.

---

06 TIER B: ELECTRONICS

ITEM	REMEMBER
ISS = TSS	Input/turbine speed. Also gives TCC slip

ITEM	REMEMBER
OSS = VS	Output/vehicle speed
Both	**Hall-effect**, can use a clutch drum as reluctor, share **8.3-9.3 V** from the TCM
TR / MLP switch	Tells the TCM the selected range
Pressure switches	On/off; read as a **pattern** to confirm the gear
TFT sensor	NTC thermistor: resistance **drops** as fluid warms
EPC / PCS	Normally closed, PWM, **more current = lower pressure**
GM line PC	Normally high: ~0.1 A max pressure, ~1.0 A min
TCC PC solenoid	PWM; controls and ramps TCC apply
Shift solenoids	On/off combination picks the gear
Adapts (TAP)	Reset after transmission replacement or clutch-to-clutch work

> **RULE** the scan tool shows the **command**, not the pressure. Only a gauge shows actual pressure.

---

07 TIER C: RECOGNITION

- **10-speed pattern:** high reduction (1st ~4.70:1) → direct at **7th (1.000:1)** → overdrive through 10th (~0.64:1). One-way clutch holds 1st–2nd, overruns 3rd–7th, unused 8th–10th. **Neutral has three clutches applied but no output path.**
- 8/9/10-speed sets combine more than one compound set; check SI for the real design.
- Governor pressure (road speed) opposes throttle valve pressure; the TCM replaced that logic.

---

08 NIGHT BEFORE

- Say aloud: **engine → impeller, transmission → turbine; carrier holds planets; ring = internal gear; two members driven = direct; carrier held = reverse.**
- Redo the tier A tables from memory, then check this sheet.
- Stop early. You know hydraulics and diagnosis from the shop; the points you lose are the **naming and direction** ones.

*Source: class notes, **`unit1_study_guide.md`**, **`unit2_study_guide.md`**, and your Unit 1 quiz misses. Not ASE content.*