



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

# Database Management Systems

## Module 06: Introduction to Relational Model/1

Partha Pratim Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*ppd@cse.iitkgp.ac.in*



## Module 06

Partha Pratim  
Das

### Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- The proliferation of DBMS in wide range of applications provide motivation to study the subject
- Know Your Course provided information about prerequisites, outline and text book
- The specific need for a DBMS discussed in contrast to a file system based application using a programming language like Python
- Basic notions of a DBMS are introduced



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- To understand attributes and their types
- To understand the mathematical structure of relational model
  - Schema
  - Instance
  - Keys
- To familiarize with different types of relational query languages



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- Attribute Types
- Relation Schema and Instance
- Keys
- Relational Query Languages



# Example of a Relation

## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

**Attributes**

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

# Attributes



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- Consider  
*Students = Roll#, First Name, Last Name, DoB, Passport#, Aadhaar#, Department*  
relation
- The set of allowed values for each attribute is called the **domain** of the attribute
  - **Roll #**: Alphanumeric string
  - **First Name, Last Name**: Alpha String
  - **DoB**: Date
  - **Passport #**: String (Letter followed by 7 digits) – nullable (optional)
  - **Aadhaar #**: 12-digit number
  - **Department**: Alpha String
- Attribute values are (normally) required to be **atomic**; that is, indivisible
- The special value **null** is a member of every domain. Indicates that the value is **unknown**
- The null value may cause complications in the definition of many operations



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- For  
*Students = Roll#, First Name, Last Name, DoB, Passport#, Aadhaar#, Department*
- And **domain** of the attributes as:
  - **Roll #**: Alphanumeric string
  - **First Name, Last Name**: Alpha String
  - **DoB**: Date
  - **Passport #**: String (Letter followed by 7 digits) – nullable (optional)
  - **Aadhaar #**: 12-digit number
  - **Department**: Alpha String

Roll #	First Name	Last Name	DoB	Passport #	Aadhaar #	Department
15CS10026	Lalit	Dubey	27-Mar-1997	L4032464	1728-6174-9239	Computer
16EE30029	Jatin	Chopra	17-Nov-1996	null	3917-1836-3816	Electrical





## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

**Schema and  
Instance**

Keys

Relational Query  
Languages

Module Summary

# Schema and Instance



# Relation Schema and Instance

## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- $A_1, A_2, \dots, A_n$  are *attributes*
- $R = (A_1, A_2, \dots, A_n)$  is a *relation schema*  
Example: *instructor* = (*ID*, *name*, *dept\_name*, *salary*)
- Formally, given sets  $D_1, D_2, \dots, D_n$  a **relation**  $r$  is a subset of

$$D_1 \times D_2 \times \dots \times D_n$$

Thus, a relation is a set of  $n$ -tuples  $(a_1, a_2, \dots, a_n)$  where each  $a_i \in D_i$

- The current values (**relation instance**) of a relation are specified by a table
- An element  $t$  of  $r$  is a tuple, represented by a row in a table
- Example:  
 $\text{instructor} \equiv (\text{String}(5) \times \text{String} \times \text{String} \times \text{Number}^+)$ , where  $ID \in \text{String}(5)$ ,  
 $\text{name} \in \text{String}$ ,  $\text{dept\_name} \in \text{String}$ , and  $\text{salary} \in \text{Number}^+$



# Relations are Unordered with Unique Tuples

Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- **Order of tuples / rows is irrelevant** (tuples may be stored in an arbitrary order)
- **No two tuples / rows may be identical**
- Example: *instructor* relation with unordered tuples

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

**Keys**

Relational Query  
Languages

Module Summary

# Keys



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- Let  $K \subseteq R$ , where  $R$  is the set of attributes in the relation
- $K$  is a **superkey** of  $R$  if values for  $K$  are sufficient to identify a unique tuple of each possible relation  $r(R)$ 
  - Example:  $\{ID\}$  and  $\{ID, name\}$  are both superkeys of *instructor*
- Superkey  $K$  is a **candidate key** if  $K$  is minimal
  - Example:  $\{ID\}$  is a candidate key for *instructor*
- One of the candidate keys is selected to be the **primary key**
  - Which one?
- A **surrogate key** (or synthetic key) in a database is a unique identifier for either an *entity* in the modeled world or an *object* in the database
  - The surrogate key is *not* derived from application data, unlike a *natural* (or *business*) key which is derived from application data



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- *Students = Roll#, First Name, Last Name, DoB, Passport#, Aadhaar#, Department*
- **Super Key:** Roll #, {Roll #, DoB}
- **Candidate Keys:** Roll #, {First Name, Last Name}, Aadhaar#
  - Passport # cannot be a key. Why?
  - Null values are allowed for Passport # (a student may not have a passport)
- **Primary Key:** Roll #
  - Can Aadhaar# be a key?
  - It may suffice for unique identification. But Roll# may have additional useful information. For example: 14CS92P01
    - ▷ Read 14CS92P01 as 14-CS-92-P-01
    - ▷ 14: Admission in 2014
    - ▷ CS: Department = CS
    - ▷ 92: Category of Student
    - ▷ P: Type of admission: *Project*
    - ▷ 01: Serial Number



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- **Secondary / Alternate Key:** {First Name, Last Name}, Aadhaar #
- **Simple Key:** Consists of a *single attribute*
- **Composite Key:** {First Name, Last Name}
  - Consists of more than one attribute to uniquely identify an entity occurrence
  - One or more of the attributes, which make up the key, are not simple keys in their own right

<u>Roll #</u>	<b>First Name</b>	<b>Last Name</b>	<b>DoB</b>	<b>Passport #</b>	<b>Aadhaar #</b>	<b>Department</b>
15CS10026	Lalit	Dubey	27-Mar-1997	L4032464	1728-6174-9239	Computer
16EE30029	Jatin	Chopra	17-Nov-1996	null	3917-1836-3816	Electrical
15EC10016	Smriti	Mongra	23-Dec-1996	G5432849	2045-9271-0914	Electronics
16CE10038	Dipti	Dutta	02-Feb-1997	null	5719-1948-2918	Civil
15CS30021	Ramdin	Minz	10-Jan-1997	X8811623	4928-4927-5924	Computer



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
OutlineExample of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- **Foreign key constraint:** Value in one relation must appear in another
  - **Referencing** relation
    - ▷ Enrolment: Foreign Keys – Roll #, Course #
  - **Referenced** relation
    - ▷ Students, Courses
- A **compound key** consists of *more than one attribute* to uniquely identify an entity occurrence
  - Each attribute, which makes up the key, is a simple key in its own right
  - {Roll #, Course #}

Students

<u>Roll #</u>	First Name	Last Name	DoB	Passport #	Aadhaar #	Department
---------------	------------	-----------	-----	------------	-----------	------------

Courses

<u>Course #</u>	Course Name	Credits	L-T-P	Department
-----------------	-------------	---------	-------	------------

Enrolment

<u>Roll #</u>	<u>Course #</u>	Instructor ID
---------------	-----------------	---------------





# Schema Diagram for University Database

## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation


Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary



# Relational Query Languages

## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

# Relational Query Languages



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

## Procedural viz-a-viz Non-procedural or Declarative Paradigms

- **Procedural programming** requires that the programmer tell the computer what to do
  - That is, *how* to get the output for the range of required inputs
  - The programmer must know an appropriate algorithm
- **Declarative programming** requires a more descriptive style
  - The programmer must know *what* relationships hold between various entities



Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

## Procedural vs. Non-procedural or Declarative Paradigms

- **Example: Square root of  $n$** 
  - Procedural
    - a) Guess  $x_0$  (close to root of  $n$ )
    - b)  $i \leftarrow 0$
    - c)  $x_{i+1} \leftarrow (x_i + n/x_i)/2$
    - d) Repeat Step 2 if  $|x_{i+1} - x_i| > \textit{delta}$
  - Declarative
    - ▷ Root of  $n$  is  $m$  such that  $m^2 = n$



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- “Pure” languages:
  - Relational algebra
  - Tuple relational calculus
  - Domain relational calculus
- The above 3 pure languages are equivalent in computing power
- We will concentrate on relational algebra
  - Not Turing-machine equivalent
    - ▷ Not all algorithms can be expressed in RA
  - Consists of 6 basic operations



## Module 06

Partha Pratim  
Das

Week Recap

Objectives &  
Outline

Example of a  
Relation

Attributes

Schema and  
Instance

Keys

Relational Query  
Languages

Module Summary

- Introduced the notion of attributes and their types
- Taken an overview of the mathematical structure of relational model – schema and instance
- Introduced the notion of keys – primary as well as foreign

**Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.**

**Edited and new slides are marked with “PPD”.**



Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

# Database Management Systems

## Module 07: Introduction to Relational Model/2

Partha Pratim Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*ppd@cse.iitkgp.ac.in*



## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Basic notions of modeling introduced
  - Attributes and their Types
  - Schema and Instance
  - Keys and their Categorization
- Languages for Relation Model introduced





# Module Objectives

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- To understand relational algebra
- To familiarize with the operators of relational algebra



## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Operations
  - Select
  - Project
  - Union
  - Difference
  - Intersection
  - Cartesian Product
  - Natural Join
- Aggregate Operations



Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

## Relational Operators



# Basic Properties of Relations

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- **A relation is set.** Hence,
- **Ordering of rows / tuples is inconsequential**

A	B
a1	b1
a1	b2
a2	b1
a2	b2

is same as:

A	B
a1	b1
a2	b1
a2	b2
a1	b2

- **All rows / tuples must be distinct**

A	B
a1	b1
a1	b2
a1	b2
a1	b1

is not valid

A	B
a1	b1
a1	b2

is



# Select Operation – selection of rows (tuples)

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Relation  $r$

$A$	$B$	$C$	$D$
$\alpha$	$\alpha$	1	7
$\alpha$	$\beta$	5	7
$\beta$	$\beta$	12	3
$\beta$	$\beta$	23	10

- $\sigma_{A=B \wedge D > 5}(r)$

$A$	$B$	$C$	$D$
$\alpha$	$\alpha$	1	7
$\beta$	$\beta$	23	10



# Project Operation – selection of columns (Attributes)

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Relation  $r$

A	B	C
$\alpha$	10	1
$\alpha$	20	1
$\beta$	30	1
$\beta$	40	2

- $\pi_{A,C}(r)$

A	C
$\alpha$	1
$\alpha$	1
$\beta$	1
$\beta$	2

 $=$ 

A	C
$\alpha$	1
$\beta$	1
$\beta$	2



# Union of two relations

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Relation  $r, s$

A	B
$\alpha$	1
$\alpha$	2
$\beta$	1

$r$

A	B
$\alpha$	2
$\beta$	3

$s$

- $r \cup s$

A	B
$\alpha$	1
$\alpha$	2
$\beta$	1
$\beta$	3



# Set difference of two relations

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Relation  $r, s$

A	B
$\alpha$	1
$\alpha$	2
$\beta$	1

$r$

A	B
$\alpha$	2
$\beta$	3

$s$

- $r - s$

A	B
$\alpha$	1
$\beta$	1





# Set intersection of two relations

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Relation  $r, s$

A	B
$\alpha$	1
$\alpha$	2
$\beta$	1

$r$

A	B
$\alpha$	2
$\beta$	3

$s$

- $r \cap s$

A	B
$\alpha$	2

**Note:**  $r \cap s = r - (r - s)$



# Joining two relations – Cartesian-product

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- Relation  $r, s$

A	B
$\alpha$	1
$\beta$	2

$r$

C	D	E
$\alpha$	10	a
$\beta$	10	a
$\beta$	20	b
$\gamma$	10	b

$s$

- $r \times s$

A	B	C	D	E
$\alpha$	1	$\alpha$	10	a
$\alpha$	1	$\beta$	10	a
$\alpha$	1	$\beta$	20	b
$\alpha$	1	$\gamma$	10	b
$\beta$	2	$\alpha$	10	a
$\beta$	2	$\beta$	10	a
$\beta$	2	$\beta$	20	b
$\beta$	2	$\gamma$	10	b



# Cartesian-product – naming issue

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- Relation  $r, s$

$A$	$B$
$\alpha$	1
$\beta$	2

$r$

$B$	$D$	$E$
$\alpha$	10	a
$\beta$	10	a
$\beta$	20	b
$\gamma$	10	b

$s$

- $r \times s$

$A$	$r.B$	$s.B$	$D$	$E$
$\alpha$	1	$\alpha$	10	a
$\alpha$	1	$\beta$	10	a
$\alpha$	1	$\beta$	20	b
$\alpha$	1	$\gamma$	10	b
$\beta$	2	$\alpha$	10	a
$\beta$	2	$\beta$	10	a
$\beta$	2	$\beta$	20	b
$\beta$	2	$\gamma$	10	b



# Renaming a Table

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- Allows us to refer to a relation, (say  $E$ ) by more than one name.

$$\rho_X(E)$$

returns the expression  $E$  under the name  $X$

- Relations  $r$

$A$	$B$
$\alpha$	1
$\beta$	2

$r$

- $r \times \rho_s(r)$

$r.A$	$r.B$	$s.A$	$s.B$
$\alpha$	1	$\alpha$	1
$\alpha$	1	$\beta$	2
$\beta$	2	$\alpha$	1
$\beta$	2	$\beta$	2



# Composition of Operations

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- Can build expressions using multiple operations
- Example:  $\sigma_{A=C}(r \times s)$
- $r \times s$

A	B	C	D	E
$\alpha$	1	$\alpha$	10	a
$\alpha$	1	$\beta$	10	a
$\alpha$	1	$\beta$	20	b
$\alpha$	1	$\gamma$	10	b
$\beta$	2	$\alpha$	10	a
$\beta$	2	$\beta$	10	a
$\beta$	2	$\beta$	20	b
$\beta$	2	$\gamma$	10	b

- $\sigma_{A=C}(r \times s)$

A	B	C	D	E
$\alpha$	1	$\alpha$	10	a
$\beta$	2	$\beta$	10	a
$\beta$	2	$\beta$	20	b



# Joining two relations – Natural Join

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Let  $r$  and  $s$  be relations on schemas  $R$  and  $S$  respectively. Then, the “natural join” of relations  $R$  and  $S$  is a relation on schema  $R \cup S$  obtained as follows:
  - Consider each pair of tuples  $t_r$  from  $r$  and  $t_s$  from  $s$ .
  - If  $t_r$  and  $t_s$  have the same value on each of the attributes in  $R \cap S$ , add a tuple  $t$  to the result, where
    - ▷  $t$  has the same value as  $t_r$  on  $r$
    - ▷  $t$  has the same value as  $t_s$  on  $s$



# Natural Join Example

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

- Relations  $r, s$  :

A	B	C	D
$\alpha$	1	$\alpha$	a
$\beta$	2	$\gamma$	a
$\gamma$	4	$\beta$	b
$\alpha$	1	$\gamma$	a
$\delta$	2	$\beta$	b

$r$

B	D	E
1	a	$\alpha$
3	a	$\beta$
1	a	$\gamma$
2	b	$\delta$
3	b	$\epsilon$

$s$

- Natural Join

$$\circ r \bowtie s$$

A	B	C	D	E
$\alpha$	1	$\alpha$	a	$\alpha$
$\alpha$	1	$\alpha$	a	$\gamma$
$\alpha$	1	$\gamma$	a	$\alpha$
$\alpha$	1	$\gamma$	a	$\gamma$
$\delta$	2	$\beta$	b	$\delta$

$$\pi_{A,r.B,C,r.D,E}(\sigma_{r.B=s.B \wedge r.D=s.D}(r \times s))$$

**Module 07**Partha Pratim  
DasObjectives &  
OutlineRelational  
Operators**Aggregation  
Operators**

Module Summary

## Aggregation Operators





Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Can we compute:
  - SUM
  - AVG
  - MAX
  - MIN



# Notes about Relational Languages

## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Each query input is a table (or set of tables)
- Each query output is a table
- All data in the output table appears in one of the input tables
- Relational Algebra is not Turing complete



# Summary of Relational Algebra Operators

## Module 07

Partha Pratim  
DasObjectives &  
OutlineRelational  
OperatorsAggregation  
Operators

Module Summary

Symbol (Name)	Example of Use
$\sigma$ (Selection)	$\sigma \text{ salary} > 85000 \text{ (instructor)}$ Return rows of the input relation that satisfy the predicate.
$\Pi$ (Projection)	$\Pi ID, salary \text{ (instructor)}$ Output specified attributes from all rows of the input relation. Remove duplicate tuples from the output.
$\times$ (Cartesian Product)	$instructor \times department$ Output pairs of rows from the two input relations that have the same value on all attributes that have the same name.
$\cup$ (Union)	$\Pi name \text{ (instructor)} \cup \Pi name \text{ (student)}$ Output the union of tuples from the two input relations.
$-$ (Set Difference)	$\Pi name \text{ (instructor)} - \Pi name \text{ (student)}$ Output the set difference of tuples from the two input relations.
$\bowtie$ (Natural Join)	$instructor \bowtie department$ Output pairs of rows from the two input relations that have the same value on all attributes that have the same name.



## Module 07

Partha Pratim  
Das

Objectives &  
Outline

Relational  
Operators

Aggregation  
Operators

Module Summary

- Introduced relational algebra
- Familiarized with the operators of relational algebra

**Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.**

**Edited and new slides are marked with “PPD”.**



Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

# Database Management Systems

## Module 08: Introduction to SQL/1

Partha Pratim Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*ppd@cse.iitkgp.ac.in*



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- Introduced relational algebra
- Familiarized with the operators of relational algebra



## Module 08

Partha Pratim  
Das

### Objectives & Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- To understand relational query language
- To understand data definition and basic query structure



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- History of SQL
- Data Definition Language (DDL)
- Data Manipulation Language (DML): Query Structure





## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

# History of SQL



## Module 08

Partha Pratim  
DasObjectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- IBM developed *Structured English Query Language* (**SEQUEL**) as part of System R project. Renamed Structured Query Language (SQL: *pronounced still as SEQUEL*)
- ANSI and ISO standard SQL:

<b>SQL-86</b>	First formalized by <b>ANSI</b>
<b>SQL-89</b>	+ <b>Integrity Constraints</b>
<b>SQL-92</b>	Major revision ( <b>ISO/IEC 9075 standard</b> ), <b>De-facto Industry Standard</b>
<b>SQL:1999</b>	+ <b>Regular Expression Matching, Recursive Queries, Triggers, Support for Procedural and Control Flow Statements</b> , Nonscalar types (Arrays), and Some OO features (structured types), <b>Embedding SQL in Java (SQL/OLB)</b> , and <b>Embedding Java in SQL (SQL/JRT)</b>
<b>SQL:2003</b>	+ <b>XML features (SQL/XML)</b> , Window Functions, Standardized Sequences, and Columns with Auto-generated Values (identity columns)
<b>SQL:2006</b>	+ Ways of <b>importing and storing XML data</b> in an SQL database, <b>manipulating</b> it within the database, and <b>publishing both XML and conventional SQL-data in XML form</b>
<b>SQL:2008</b>	Legalizes <b>ORDER BY</b> outside Cursor Definitions + <b>INSTEAD OF Triggers, TRUNCATE Statement, and FETCH Clause</b>
<b>SQL:2011</b>	+ <b>Temporal Data (PERIOD FOR)</b> Enhancements for <b>Window Functions</b> and <b>FETCH Clause</b>
<b>SQL:2016</b>	+ <b>Row Pattern Matching, Polymorphic Table Functions, and JSON</b>
<b>SQL:2019</b>	+ <b>Multidimensional Arrays (MDarray type and operators)</b>



# History of Query Language (2): Compliance

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- SQL is the de facto industry standard today for relational or structured data systems
- Commercial systems as well as open systems may be fully or partially compliant to one or more standards from SQL-92 onward
- Not all examples here may work on your particular system. Check your system's SQL documentation



# History of Query Language (3): Alternatives

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- There aren't any alternatives to SQL for speaking to relational databases (that is, SQL as a protocol), but there are many alternatives to writing SQL in the applications
- These alternatives have been implemented in the form of frontends for working with relational databases. Some examples of a frontend include (for a section of languages):
  - [SchemeQL](#) and [CLSQL](#), which are probably the most flexible, owing to their Lisp heritage, but they also look like a lot more like SQL than other frontends
  - [LINQ](#) (in .Net)
  - [ScalaQL](#) and [ScalaQuery](#) (in [Scala](#))
  - [SqlStatement](#), [ActiveRecord](#) and many others in [Ruby](#)
  - [HaskellDB](#)
  - ...the list goes on for many other languages.

**Source:** [What are good alternatives to SQL \(the language\)?](#)



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- There are several query languages that are derived from or inspired by SQL. Of these, the most popular and effective is SPARQL.
  - **SPARQL** (pronounced *sparkle*, a recursive acronym for *SPARQL Protocol and RDF Query Language*) is an RDF query language
    - ▷ A semantic query language for databases - able to retrieve and manipulate data stored in **Resource Description Framework** (RDF) format.
    - ▷ It has been standardized by the W3C Consortium as key technology of the semantic web
    - ▷ Versions:
      - **SPARQL 1.0** (January 2008)
      - **SPARQL 1.1** (March, 2013)
    - ▷ Used as the query languages for several NoSQL systems - particularly the Graph Databases that use RDF as store



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

**Data Definition  
Language (DDL)**

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

# Data Definition Language (DDL)



# Data Definition Language (DDL)

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation

Language (DML):

Query Structure

Select Clause

Where Clause

From Clause

Module Summary

The SQL data-definition language (DDL) allows the specification of information about relations, including:

- The *Schema* for each *Relation*
- The *Domain* of values associated with each *Attribute*
- *Integrity Constraints*
- And, as we will see later, also other information such as
  - The set of *Indices* to be maintained for each relations
  - *Security and Authorization* information for each relation
  - The *Physical Storage Structure* of each relation on disk



# Domain Types in SQL

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- **char( $n$ )**. Fixed length character string, with user-specified length  $n$
- **varchar( $n$ )**. Variable length character strings, with user-specified maximum length  $n$
- **int**. Integer (a finite subset of the integers that is machine-dependent)
- **smallint( $n$ )**. Small integer (a machine-dependent subset of the integer domain type)
- **numeric( $p, d$ )**. Fixed point number, with user-specified precision of  $p$  digits, with  $d$  digits to the right of decimal point. (ex., **numeric**(3, 1), allows 44.5 to be stores exactly, but not 444.5 or 0.32)
- **real, double precision**. Floating point and double-precision floating point numbers, with machine-dependent precision
- **float( $n$ )**. Floating point number, with user-specified precision of at least  $n$  digits
- More are covered in Chapter 4





# Schema Diagram for University Database

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data


Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary





Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation

Language (DML):

Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- An SQL relation is defined using the **create table** command:

**create table**  $r$  ( $A_1D_1, A_2D_2, \dots, A_nD_n$ ),  
                  (*integrity-constraint*<sub>1</sub>),  
                  ...  
                  (*integrity-constraint* <sub>$k$</sub> ));

- $r$  is the name of the relation
- each  $A_i$  is an attribute name in the schema of relation  $r$
- $D_i$  is the data type of values in the domain of attribute  $A_i$



# Create Table Construct (2)

## Module 08

Partha Pratim  
DasObjectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure


Select Clause

Where Clause

From Clause

Module Summary

```
create table instructor (
    ID char(5),
    name varchar(20)
    dept_name varchar(20)
    salary numeric(8, 2));
```





# Create Table Construct (3): Integrity Constraints

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- **not null**
- **primary key** ( $A_1, \dots, A_n$ )
- **foreign key** ( $A_m, \dots, A_n$ ) **references**  $r$

```
create table instructor (  
    ID char(5),  
    name varchar(20)  
    dept_name varchar(20)  
    salary numeric(8,2));
```

```
create table instructor (  
    ID char(5),  
    name varchar(20) not null,  
    dept_name varchar(20),  
    salary numeric(8,2),  
    primary key (ID),  
    foreign key (dept_name) references department));
```

**primary key** declaration on an attribute automatically ensures **not null**



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table


Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary





# Create Table Construct (4): More Relations

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

```
create table student (  
    ID varchar(5),  
    name varchar(20) not null,  
    dept_name varchar(20),  
    tot_cred numeric(3, 0),  
    primary key (ID),  
    foreign key (dept_name)  
    references department);
```

```
create table course (  
    course_id varchar(8),  
    title varchar(50),  
    dept_name varchar(20),  
    credits numeric(2, 0),  
    primary key (course_id),  
    foreign key (dept_name)  
    references department);
```

```
create table takes (  
    ID varchar(5),  
    course_id varchar(8), sec_id varchar(8),  
    semester varchar(6), year numeric(4, 0),  
    grade varchar(2),  
    primary key (ID, course_id, sec_id, semester, year),  
    foreign key (ID) references student  
    foreign key (course_id, sec_id, semester, year)  
    references section);
```

- **Note:** *sec\_id* can be dropped from primary key above, to ensure a student cannot be registered for two sections of the same course in the same semester



# Update Tables

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation

Language (DML):

Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- **Insert (DML command)**

- **insert into** *instructor* **values** ('10211', 'Smith', 'Biology', 66000);

- **Delete (DML command)**

- Remove all tuples from the *student* relation

**delete from** *student*

- **Drop Table (DDL command)**

- **drop table** *r*

- **Alter (DDL command)**

- **alter table** *r* **add** *A D*

- ▷ Where *A* is the name of the attribute to be added to relation *r* and *D* is the domain of *A*
- ▷ All existing tuples in the relation are assigned *null* as the value for the new attribute

- **alter table** *r* **drop** *A*

- ▷ Where *A* is the name of an attribute of relation *r*
- ▷ Dropping of attributes not supported by many databases



## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

# Data Manipulation Language (DML): Query Structure





# Basic Query Structure

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- A typical SQL query has the form:  
**select**  $A_1, A_2, \dots, A_n$ ,  
**from**  $r_1, r_2, \dots, r_m$   
**where**  $P$ 
  - $A_i$  represents an attribute from  $r_i$ 's
  - $r_i$  represents a relation
  - $P$  is a predicate
- The result of an SQL query is a relation



# Select Clause

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- The **select** clause lists the attributes desired in the result of a query
  - Corresponds to the projection operation of the relational algebra
- Example: find the names of all instructors:  
**select** *name*,  
**from** *instructor*
- NOTE: SQL names are case insensitive (that is, you may use upper-case or lower-case letters)
  - *Name*  $\equiv$  *NAME*  $\equiv$  *name*
  - Some people use upper case wherever we use bold font



# Select Clause (2)

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- **SQL allows duplicates in relations as well as in query results!!!**
- To force the elimination of duplicates, insert the keyword **distinct** after select
- Find the department names of all instructors, and remove duplicates  
**select distinct dept\_name**  
**from instructor**
- The keyword **all** specifies that duplicates should not be removed  
**select all dept\_name**  
**from instructor**



# Select Clause (3)

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- An asterisk in the select clause denotes *all attributes*  
**select \***  
**from instructor**
- An attribute can be a literal with no **from** clause  
**select '437'**
  - Results is a table with one column and a single row with value '437'
  - Can give the column a name using:  
**select '437' as FOO**
- An attribute can be a literal with **from** clause  
**select 'A'**  
**from instructor**
  - Result is a table with one column and N rows (number of tuples in the instructors table), each row with value 'A'



# Select Clause (4)

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation

Language (DML):

Query Structure

Select Clause

Where Clause

From Clause

Module Summary

The **select** clause can contain arithmetic expressions involving the operation,  $+$ ,  $-$ ,  $*$ , and  $/$ , and operating on constants or attributes of tuples

- The query:

```
select ID, name, salary/12  
from instructor
```

- Would return a relation that is the same as the *instructor* relation, except that the value of the attribute *salary* is divided by 12
- Can rename “*salary/12*” using the **as** clause:

```
select ID, name, salary/12 as monthly_salary
```



# Where Clause

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation

Language (DML):

Query Structure

Select Clause

**Where Clause**

From Clause

Module Summary

- The **where** clause specifies conditions that the result must satisfy
  - Corresponds to the selection predicate of the relational algebra
- To find all instructors in Comp. Sci. dept

```
select name
from instructor
where dept_name = 'Comp. Sci.'
```
- Comparison results can be combined using the logical connectives **and**, **or**, and **not**
  - To find all instructors in Comp. Sci. dept with salary > 80000

```
select name
from instructor
where dept_name = 'Comp. Sci.' and salary > 80000
```
- Comparisons can be applied to results of arithmetic expressions



# From Clause

## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

**From Clause**

Module Summary

- The **from** clause lists the relations involved in the query
  - Corresponds to the Cartesian product operation of the relational algebra
- Find the Cartesian product *instructor X teaches*  
**select \***  
**from** *instructor, teaches*
  - Generates every possible instructor-teaches pair, with all attributes from both relations
  - For common attributes (for example, *ID*), the attributes in the resulting table are renamed using the relation name (for example, *instructor.ID*)
- Cartesian product not very useful directly, but useful combined with where-clause condition (selection operation in relational algebra)



# Cartesian Product

## Module 08

Partha Pratim  
DasObjectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data  
Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

*instructor*

ID	name	dept_name	salary
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821			
98345			

*teaches*

ID	course_id	sec_id	semester	year
10101	CS-101	1	Fall	2009
10101	CS-315	1	Spring	2010
10101	CS-347	1	Fall	2009
12121	FIN-201	1	Spring	2010
15151	MU-199	1	Spring	2010
22222	PHY-101	1	Fall	2009
32343	HIS-351	1	Spring	2010
45565	CS-101	1	Spring	2010
45565	CS-319	1	Spring	2010
76766	BIO-101	1	Summer	2009
				2010
				2009
				2009
				2010
				2009

Inst.ID	name	dept_name	salary	teaches.ID	course_id	sec_id	semester	year
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2009
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2009
10101	Srinivasan	Comp. Sci.	65000	12121	FIN-201	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	15151	MU-199	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	22222	PHY-101	1	Fall	2009
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...
12121	Wu	Finance	90000	10101	CS-101	1	Fall	2009
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2010
12121	Wu	Pinance	90000	10101	CS-347	1	Fall	2009
12121	Wu	Pinance	90000	12121	FIN-201	1	Spring	2010
12121	Wu	Finance	90000	15151	MU-199	1	Spring	2010
12121	Wu	Pinance	90000	22222	PHY-101	1	Fall	2009
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...





## Module 08

Partha Pratim  
Das

Objectives &  
Outline

Outline

History of SQL

Data Definition  
Language (DDL)

Create Table

Integrity Constraints

Update Table

Data

Manipulation  
Language (DML):  
Query Structure

Select Clause

Where Clause

From Clause

Module Summary

- Introduced relational query language
- Familiarized with data definition and basic query structure

**Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.**

**Edited and new slides are marked with “PPD”.**



Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

# Database Management Systems

## Module 09: Introduction to SQL/2

Partha Pratim Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*ppd@cse.iitkgp.ac.in*



## Module 09

Partha Pratim  
Das

### Objectives & Outline

#### Additional Basic Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

#### Module Summary

- Introduced relational query language
- Familiarized with data definition and basic query structure



## Module 09

Partha Pratim  
Das

### Objectives & Outline

#### Additional Basic Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

#### Module Summary

- To complete the understanding of basic query structure



## Module 09

Partha Pratim  
Das

### Objectives & Outline

#### Additional Basic Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

#### Module Summary

- Additional Basic Operations
  - Cartesian Product
  - Rename AS Operation
  - String Values
  - Order By
  - Select Top / Fetch
  - Where Clause Predicate
  - Duplicates



## Module 09

Partha Pratim  
Das

Objectives &  
Outline

**Additional Basic  
Operations**

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

# Additional Basic Operations



# Cartesian Product

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- Find the Cartesian product *instructor X teaches*  
**select \***  
**from** *instructor, teaches*
  - generates every possible instructor-teaches pair, with all attributes from both relations
  - For common attributes (for example, *ID*), the attributes in the resulting table are renamed using the relation name (for example, *instructor.ID*)
- Cartesian product not very useful directly, but useful combined with where-clause condition (selection operation in relational algebra)



# Cartesian Product

## Module 09

Partha Pratim  
DasObjectives &  
OutlineAdditional Basic  
Operations

Cartesian Product

Rename AS

Operation

String Values

Order By Clause

Select Top / Fetch  
ClauseWhere Clause  
Predicates

Duplicates

Module Summary

*instructor*

ID	name	dept_name	salary
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821			
98345			

*teaches*

ID	course_id	sec_id	semester	year
10101	CS-101	1	Fall	2009
10101	CS-315	1	Spring	2010
10101	CS-347	1	Fall	2009
12121	FIN-201	1	Spring	2010
15151	MU-199	1	Spring	2010
22222	PHY-101	1	Fall	2009
32343	HIS-351	1	Spring	2010
45565	CS-101	1	Spring	2010
45565	CS-319	1	Spring	2010
76766	BIO-101	1	Summer	2009

Inst.ID	name	dept_name	salary	teaches.ID	course_id	sec_id	semester	year
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2009
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2009
10101	Srinivasan	Comp. Sci.	65000	12121	FIN-201	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	15151	MU-199	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	22222	PHY-101	1	Fall	2009
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...
12121	Wu	Finance	90000	10101	CS-101	1	Fall	2009
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2010
12121	Wu	Finance	90000	10101	CS-347	1	Fall	2009
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2010
12121	Wu	Finance	90000	15151	MU-199	1	Spring	2010
12121	Wu	Finance	90000	22222	PHY-101	1	Fall	2009
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...





## Module 09

Partha Pratim  
DasObjectives &  
OutlineAdditional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
ClauseWhere Clause  
Predicates

Duplicates

Module Summary

- Find the names of all instructors who have taught some course and the course\_id
  - select** *name, course\_id*
  - from** *instructor, teaches*
  - where** *instructor.ID = teaches.ID*
  - Equi-Join, Natural Join

instructor				teaches					
ID	name	dept_name	salary	ID	course_id	sec_id	semester	year	
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2009	
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2010	
15151	Mozart	Music	40000	10101	CS-347	1	Fall	2009	
22222	Einstein	Physics	95000	12121	FIN-201	1	Spring	2010	
32343	El Said	History	60000	15151	MU-199	1	Spring	2010	
33456	Gold	Physics	87000	22222	PHY-101	1	Fall	2009	
45565	Katz	Comp. Sci.	75000	32343	HIS-351	1	Spring	2010	
58583	Califieri	History	62000	45565	CS-101	1	Spring	2010	
76543	Singh	Finance	80000	45565	CS-319	1	Spring	2010	
76766	Crick	Biology	72000	76766	BIO-101	1	Summer	2009	
83821								2010	
98345								2009	
inst.ID	name	dept_name	salary	teaches.ID	course_id	sec_id	semester	year	
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2009	
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2010	
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2009	
10101	Srinivasan	Comp. Sci.	65000	12121	FIN-201	1	Spring	2010	
10101	Srinivasan	Comp. Sci.	65000	15151	MU-199	1	Spring	2010	
10101	Srinivasan	Comp. Sci.	65000	22222	PHY-101	1	Fall	2009	
...	...	...	...	...	...	...	...	...	
...	...	...	...	...	...	...	...	...	
12121	Wu	Finance	90000	10101	CS-101	1	Fall	2009	
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2010	
12121	Wu	Finance	90000	10101	CS-347	1	Fall	2009	
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2010	
12121	Wu	Finance	90000	15151	MU-199	1	Spring	2010	
12121	Wu	Finance	90000	22222	PHY-101	1	Fall	2009	
...	...	...	...	...	...	...	...	...	
...	...	...	...	...	...	...	...	...	



## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- Find the names of all instructors in the Art department who have taught some course and the course\_id

```
select name, course_id  
from instructor, teaches  
where instructor.ID = teaches.ID and instructor.dept_name = 'Art'
```



# Rename AS Operation

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- The SQL allows renaming relations and attributes using the **as** clause:  
*old\_name as new\_name*
- Find the names of all instructors who have a higher salary than some instructor in 'Comp. Sci'.  
**select distinct** *T.name*  
**from** *instructor as T, instructor as S,*  
**where** *T.salary > S.salary and S.dept\_name = 'Comp. Sci'*
- Keyword **as** is optional and may be omitted  
*instructor as T*  $\equiv$  *instructor T*



# Cartesian Product Example

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- Relation *emp\_super*

<i>person</i>	<i>supervisor</i>
Bob	Alice
Mary	Susan
Alice	David
David	Mary

- Find the supervisor of “Bob”
- Find the supervisor of the supervisor of “Bob”
- Find ALL the supervisors (direct and indirect) of “Bob”



# String Operations

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- SQL includes a string-matching operator for comparisons on character strings. The operator **like** uses patterns that are described using two special characters:
  - percent ( % ). The % character matches any substring
  - underscore ( \_ ). The \_ character matches any character
- Find the names of all instructors whose name includes the substring “dar”  

```
select name  
from instructor  
where name like '%dar%'
```
- Match the string “100%”  

```
like '100%' escape '\'
```
- in that above we use backslash ( \ ) as the escape character



# String Operations (2)

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- Patterns are case sensitive
- Pattern matching examples:
  - 'Intro%' matches any string beginning with "Intro"
  - '%Comp%' matches any string containing "Comp" as a substring
  - '\_ \_ \_' matches any string of exactly three characters
  - '\_ \_ \_ %' matches any string of at least three characters
- SQL supports a variety of string operations such as
  - concatenation (using "||")
  - converting from upper to lower case (and vice versa)
  - finding string length, extracting substrings, etc.



# Ordering the Display of Tuples

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- List in alphabetic order the names of all instructors

```
select distinct name  
from instructor  
order by name
```

- We may specify **desc** for descending order or **asc** for ascending order, for each attribute; ascending order is the default.
  - Example: **order by** *name desc*
- Can sort on multiple attributes
  - Example: **order by** *dept\_name, name*



# Selecting Number of Tuples in Output

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- The **Select Top** clause is used to specify the number of records to return
- The **Select Top** clause is useful on large tables with thousands of records. Returning a large number of records can impact performance

```
select top 10 distinct name  
from instructor
```

- Not all database systems support the SELECT TOP clause.
  - SQL Server & MS Access support **select top**
  - MySQL supports the **limit** clause
  - Oracle uses **fetch first n rows only** and **rownum**

```
select distinct name  
from instructor  
order by name  
fetch first 10 rows only
```





# Where Clause Predicates

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- SQL includes a **between** comparison operator
- Example: Find the names of all instructors with salary between \$90,000 and \$100,000 (that is,  $\geq$  \$90,000 and  $\leq$  \$100,000)

```
select name  
from instructor  
where salary between 90000 and 100000
```

- Tuple comparison

```
select name, course_id  
from instructor, teaches  
where (instructor.ID, dept_name) = (teaches.ID, 'Biology');
```



# In Operator

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- The **in** operator allows you to specify multiple values in a **where** clause
- The **in** operator is a shorthand for multiple **or** conditions  
**select** *name*  
**from** *instructor*  
**where** *dept\_name* **in** ('Comp. Sci.', 'Biology')



# Duplicates

## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- In relations with duplicates, SQL can define how many copies of tuples appear in the result
- **Multiset** versions of some of the relational algebra operators – given multiset relations  $r_1$  and  $r_2$ :
  - a)  $\sigma_\theta(r_1)$ : If there are  $c_1$  copies of tuple  $t_1$  in  $r_1$ , and  $t_1$  satisfies selections  $\sigma_\theta$ , then there are  $c_1$  copies of  $t_1$  in  $\sigma_\theta(r_1)$
  - b)  $\Pi_A(r)$ : For each copy of tuple  $t_1$  in  $r_1$ , there is a copy of tuple  $\Pi_A(t_1)$  in  $\Pi_A(r_1)$  where  $\Pi_A(t_1)$  denotes the projection of the single tuple  $t_1$
  - c)  $r_1 \times r_2$ : If there are  $c_1$  copies of tuple  $t_1$  in  $r_1$  and  $c_2$  copies of tuple  $t_2$  in  $r_2$ , there are  $c_1 \times c_2$  copies of the tuple  $t_1.t_2$  in  $r_1 \times r_2$



# Duplicates (2)

## Module 09

Partha Pratim  
DasObjectives &  
OutlineAdditional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
ClauseWhere Clause  
Predicates

Duplicates

Module Summary

- Example: Suppose multiset relations  $r_1(A, B)$  and  $r_2(C)$  are as follows:

$$r_1 = \{(1, a)(2, a)\} \quad r_2 = \{(2), (3), (3)\}$$

- Then  $\Pi_B(r_1)$  would be  $\{(a), (a)\}$ , while  $\Pi_B(r_1) \times r_2$  would be  $\{(a, 2), (a, 2), (a, 3), (a, 3), (a, 3), (a, 3)\}$

- SQL duplicate semantics:

**select**  $A_1, A_2, \dots, A_n$

**from**  $r_1, r_2, \dots, r_m$

**where**  $P$

is equivalent to the *multiset* version of the expression:

$$\Pi_{A_1, A_2, \dots, A_n}(\sigma_P(r_1 \times r_2 \times \dots \times r_m))$$



## Module 09

Partha Pratim  
Das

Objectives &  
Outline

Additional Basic  
Operations

Cartesian Product

Rename AS  
Operation

String Values

Order By Clause

Select Top / Fetch  
Clause

Where Clause  
Predicates

Duplicates

Module Summary

- Completed the understanding of basic query structure

**Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.**

**Edited and new slides are marked with “PPD”.**



Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

# Database Management Systems

## Module 10: Introduction to SQL/3

Partha Pratim Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*ppd@cse.iitkgp.ac.in*



## Module 10

Partha Pratim  
Das

### Objectives & Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Completed the understanding of basic query structure



## Module 10

Partha Pratim  
Das

### Objectives & Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- To familiarize with set operations, null values and aggregation





## Module 10

Partha Pratim  
Das

### Objectives & Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Set Operations: union, intersect, except
- Null Values
- Aggregate Functions: avg, min, max, sum, and count
  - Group By
  - Having
  - Null Values



## Module 10

Partha Pratim  
Das

Objectives &  
Outline

**Set Operations**

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

# Set Operations



# Set Operations

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Find courses that ran in Fall 2009 or in Spring 2010  
(**select** *course\_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2009)  
**union**  
(**select** *course\_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2010)
- Find courses that ran in Fall 2009 and in Spring 2010  
(**select** *course\_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2009)  
**intersect**  
(**select** *course\_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2010)
- Find courses that ran in Fall 2009 but not in Spring 2010  
(**select** *course\_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2009)  
**except**  
(**select** *course\_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2010)



# Set Operations (2)

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Find the salaries of all instructors that are less than the largest salary

```
select distinct T.salary  
from instructor as T, instructor as S  
where T.salary < S.salary
```

- Find all the salaries of all instructors

```
select distinct salary  
from instructor
```

- Find the largest salary of all instructors

```
(select "second query" )  
except  
(select "first query")
```



# Set Operations (3)

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Set operations **union**, **intersect**, and **except**
  - Each of the above operations automatically eliminates duplicates
- To retain all duplicates use the corresponding multiset versions **union all**, **intersect all**, and **except all**.
- Suppose a tuple occurs  $m$  times in  $r$  and  $n$  times in  $s$ , then, it occurs:
  - $m + n$  times in  $r$  **union all**  $s$
  - $\min(m, n)$  times in  $r$  **intersect all**  $s$
  - $\max(0, m - n)$  times in  $r$  **except all**  $s$



## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

**Null Values**

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

# Null Values



# Null Values

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- It is possible for tuples to have a null value, denoted by *null*, for some of their attributes
- *null* signifies an unknown value or that a value does not exist
- The result of any arithmetic expression involving *null* is *null*
  - Example:  $5 + \text{null}$  returns null
- The predicate **is null** can be used to check for null values
  - Example: Find all instructors whose salary is null  

```
select name
from instructor
where salary is null
```
- It is not possible to test for **null** values with comparison operators, such as  $=$ ,  $<$ , or  $<>$   
We need to use the **is null** and **is not null** operators instead



# Null Values (2): Three Valued Logic

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Three values – **true**, **false**, **unknown**
- Any comparison with *null* returns *unknown*
  - Example:  $5 < null$  or  $null <> null$  or  $null = null$
- Three-valued logic using the value unknown:
  - OR: (*unknown* **or** *true*) = *true*,  
(*unknown* **or** *false*) = *unknown*  
(*unknown* **or** *unknown*) = *unknown*
  - AND: (*true* **and** *unknown*) = *unknown*,  
(*false* **and** *unknown*) = *false*,  
(*unknown* **and** *unknown*) = *unknown*
  - NOT: (**not** *unknown*) = *unknown*
  - “*P* is **unknown**” evaluates to *true* if predicate *P* evaluates to *unknown*
- Result of **where** clause predicate is treated as *false* if it evaluates to *unknown*





## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

**Aggregate  
Functions**

Group By

Having

Null Values

Module Summary

# Aggregate Functions



# Aggregate Functions

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- These functions operate on the multiset of values of a column of a relation, and return a value

**avg**: average value

**min**: minimum value

**max**: maximum value

**sum**: sum of values

**count**: number of values



# Aggregate Functions (2)

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Find the average salary of instructors in the Computer Science department  
**select avg (salary)**  
**from instructor**  
**where dept\_name = 'Comp. Sci';**
- Find the total number of instructors who teach a course in the Spring 2010 semester  
**select count (distinct ID)**  
**from teaches**  
**where semester = 'Spring' and year = 2010;**
- Find the number of tuples in the *course* relation  
**select count (\*)**  
**from courses;**



# Aggregate Functions (3): Group By

## Module 10

Partha Pratim  
DasObjectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Find the average salary of instructors in each department

```
select dept_name, avg(salary) as avg_salary  
from instructor  
group by dept_name;
```

ID	name	dept_name	salary
76766	Crick	Biology	72000
45565	Katz	Comp. Sci.	75000
10101	Srinivasan	Comp. Sci.	65000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000
12121	Wu	Finance	90000
76543	Singh	Finance	80000
32343	El Said	History	60000
58583	Califieri	History	62000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
22222	Einstein	Physics	95000

dept_name	avg_salary
Biology	72000
Comp. Sci.	77333
Elec. Eng.	80000
Finance	85000
History	61000
Music	40000
Physics	91000



# Aggregate Functions (4): Group By

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Attributes in **select** clause outside of aggregate functions must appear in **group by** list  
*/\* erroneous query \*/*  
**select** *dept\_name, ID, avg(salary)*  
**from** *instructor*  
**group by** *dept\_name;*



# Aggregate Functions (5): Having Clause

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

**Having**

Null Values

Module Summary

- Find the names and average salaries of all departments whose average salary is greater than 42000

```
select dept_name, ID, avg(salary)
from instructor
group by dept_name
having avg(salary) > 42000;
```

Note: predicates in the **having** clause are applied after the formation of groups whereas predicates in the **where** clause are applied before forming groups



# Null Values and Aggregates

## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Total all salaries  
**select sum (salary)**  
**from instructor;**
  - Above statement ignores null amounts
  - Result is *null* if there is no non-null amount
- All aggregate operations except **count(\*)** ignore tuples with null values on the aggregated attributes
- What if collection has only null values?
  - count returns 0
  - all other aggregates return null



## Module 10

Partha Pratim  
Das

Objectives &  
Outline

Set Operations

Null Values

Three Valued Logic

Aggregate  
Functions

Group By

Having

Null Values

Module Summary

- Completed the understanding of set operations, null values, and aggregation

**Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.  
Edited and new slides are marked with “PPD”.**