

# Analysis of algorithms

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Measuring performance

- Example of validating SIM cards against Aadhaar data
  - Naive approach takes thousands of years
  - Smarter solution takes a few minutes

# Measuring performance

- Example of validating SIM cards against Aadhaar data
  - Naive approach takes thousands of years
  - Smarter solution takes a few minutes
- Two main resources of interest
  - Running time — how long the algorithm takes
  - Space — memory requirement

# Measuring performance

- Example of validating SIM cards against Aadhaar data
  - Naive approach takes thousands of years
  - Smarter solution takes a few minutes
- Two main resources of interest
  - Running time — how long the algorithm takes
  - Space — memory requirement
- Time depends on processing power
  - Impossible to change for given hardware
  - Enhancing hardware has only a limited impact at a practical level

# Measuring performance

- Example of validating SIM cards against Aadhaar data
  - Naive approach takes thousands of years
  - Smarter solution takes a few minutes
- Two main resources of interest
  - Running time — how long the algorithm takes
  - Space — memory requirement
- Time depends on processing power
  - Impossible to change for given hardware
  - Enhancing hardware has only a limited impact at a practical level
- Storage is limited by available memory
  - Easier to configure, augment

# Measuring performance

- Example of validating SIM cards against Aadhaar data
  - Naive approach takes thousands of years
  - Smarter solution takes a few minutes
- Two main resources of interest
  - Running time — how long the algorithm takes
  - Space — memory requirement
- Time depends on processing power
  - Impossible to change for given hardware
  - Enhancing hardware has only a limited impact at a practical level
- Storage is limited by available memory
  - Easier to configure, augment
- Typically, we focus on time rather than space

# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort

# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
  - Input size  $n$
  - Running time  $t(n)$



# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
  - Input size  $n$
  - Running time  $t(n)$
- Different inputs of size  $n$  may take different amounts of time
  - We will return to this point later

# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
  - Input size  $n$
  - Running time  $t(n)$
- Different inputs of size  $n$  may take different amounts of time
  - We will return to this point later

Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$  — number of cards

# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
  - Input size  $n$
  - Running time  $t(n)$
- Different inputs of size  $n$  may take different amounts of time
  - We will return to this point later

## Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$  — number of cards
- Naive algorithm:  $t(n) \approx n^2$

# Input size

- Running time depends on input size
  - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
  - Input size  $n$
  - Running time  $t(n)$
- Different inputs of size  $n$  may take different amounts of time
  - We will return to this point later

## Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$  — number of cards
- Naive algorithm:  $t(n) \approx n^2$
- Clever algorithm:  $t(n) \approx n \log_2 n$ 
  - $\log_2 n$  — number of times you need to divide  $n$  by 2 to reach 1
  - $\log_2(n) = k \Rightarrow n = 2^k$

## Example 2 Video game

- Several objects on screen

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs
- There is a clever algorithm that takes time  $n \log_2 n$



## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs
- There is a clever algorithm that takes time  $n \log_2 n$
- High resolution gaming console may have 4000x2000 pixels
  - $8 \times 10^6$  points — 8 million

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs
- There is a clever algorithm that takes time  $n \log_2 n$
- High resolution gaming console may have  $4000 \times 2000$  pixels
  - $8 \times 10^6$  points — 8 million
- Suppose we have  $100,000 = 1 \times 10^5$  objects

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs
- There is a clever algorithm that takes time  $n \log_2 n$
- High resolution gaming console may have  $4000 \times 2000$  pixels
  - $8 \times 10^6$  points — 8 million
- Suppose we have  $100,000 = 1 \times 10^5$  objects
- Naive algorithm takes  $10^{10}$  steps
  - 1000 seconds, or 16.7 minutes in Python
  - Unacceptable response time!

## Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- $n$  objects — naive algorithm is  $n^2$ 
  - For each pair of objects, compute their distance
  - Report minimum distance across all pairs
- There is a clever algorithm that takes time  $n \log_2 n$
- High resolution gaming console may have  $4000 \times 2000$  pixels
  - $8 \times 10^6$  points — 8 million
- Suppose we have  $100,000 = 1 \times 10^5$  objects
- Naive algorithm takes  $10^{10}$  steps
  - 1000 seconds, or 16.7 minutes in Python
  - Unacceptable response time!
- $\log_2 100,000$  is under 20, so  $n \log_2 n$  takes a fraction of a second

# Orders of magnitude

- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors

# Orders of magnitude

- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors
- $f(n) = n^3$  eventually grows faster than  $g(n) = 5000n^2$ 
  - For small values of  $n$ ,  $f(n) < g(n)$
  - After  $n = 5000$ ,  $f(n)$  overtakes  $g(n)$

# Orders of magnitude

- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors
- $f(n) = n^3$  eventually grows faster than  $g(n) = 5000n^2$ 
  - For small values of  $n$ ,  $f(n) < g(n)$
  - After  $n = 5000$ ,  $f(n)$  overtakes  $g(n)$
- Asymptotic complexity
  - What happens in the limit, as  $n$  becomes large

# Orders of magnitude

- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors
- $f(n) = n^3$  eventually grows faster than  $g(n) = 5000n^2$ 
  - For small values of  $n$ ,  $f(n) < g(n)$
  - After  $n = 5000$ ,  $f(n)$  overtakes  $g(n)$
- Asymptotic complexity
  - What happens in the limit, as  $n$  becomes large
- Typical growth functions
  - Is  $t(n)$  proportional to  $\log n, \dots, n^2, n^3, \dots, 2^n$ ?
    - Note:  $\log n$  means  $\log_2 n$  by default
  - Logarithmic, polynomial, exponential, ...



# Orders of magnitude

Input size	Values of $t(n)$						
	$\log n$	$n$	$n \log n$	$n^2$	$n^3$	$2^n$	$n!$
10	3.3	10	33	100	1000	1000	$10^6$
100	6.6	100	66	$10^4$	$10^6$	$10^{30}$	$10^{157}$
1000	10	1000	$10^4$	$10^6$	$10^9$		
$10^4$	13	$10^4$	$10^5$	$10^8$	$10^{12}$		
$10^5$	17	$10^5$	$10^6$	$10^{10}$			
$10^6$	20	$10^6$	$10^7$	$10^{12}$			
$10^7$	23	$10^7$	$10^8$				
$10^8$	27	$10^8$	$10^9$				
$10^9$	30	$10^9$	$10^{10}$				
$10^{10}$	33	$10^{10}$	$10^{11}$				

# Measuring running time

- Analysis should be independent of the underlying hardware
  - Don't use actual time
  - Measure in terms of **basic operations**

# Measuring running time

- Analysis should be independent of the underlying hardware
  - Don't use actual time
  - Measure in terms of **basic operations**
- Typical basic operations
  - Compare two values
  - Assign a value to a variable

# Measuring running time

- Analysis should be independent of the underlying hardware
  - Don't use actual time
  - Measure in terms of **basic operations**

- Typical basic operations

- Compare two values
  - Assign a value to a variable

- Exchange a pair of values?

```
(x,y) = (y,x)      t = x
                   x = y
                   y = t
```

- If we ignore constants, focus on orders of magnitude, both are within a factor of 3
  - Need not be very precise about defining basic operations

# What is the input size

- Typically a natural parameter
  - Size of a list/array that we want to search or sort
  - Number of objects we want to rearrange
  - Number of vertices and number edges in a graph
    - We shall see why these are separate parameters

# What is the input size

- Typically a natural parameter
  - Size of a list/array that we want to search or sort
  - Number of objects we want to rearrange
  - Number of vertices and number edges in a graph
    - We shall see why these are separate parameters
- What about numeric problems? Is  $n$  a prime?

# What is the input size

- Typically a natural parameter
  - Size of a list/array that we want to search or sort
  - Number of objects we want to rearrange
  - Number of vertices and number edges in a graph
    - We shall see why these are separate parameters
- What about numeric problems? Is  $n$  a prime?
  - Magnitude of  $n$  is not the correct measure

# What is the input size

- Typically a natural parameter
  - Size of a list/array that we want to search or sort
  - Number of objects we want to rearrange
  - Number of vertices and number edges in a graph
    - We shall see why these are separate parameters
- What about numeric problems? Is  $n$  a prime?
  - Magnitude of  $n$  is not the correct measure
  - Arithmetic operations are performed digit by digit
    - Addition with carry, subtraction with borrow, multiplication, long division ...



# What is the input size

- Typically a natural parameter
  - Size of a list/array that we want to search or sort
  - Number of objects we want to rearrange
  - Number of vertices and number edges in a graph
    - We shall see why these are separate parameters
- What about numeric problems? Is  $n$  a prime?
  - Magnitude of  $n$  is not the correct measure
  - Arithmetic operations are performed digit by digit
    - Addition with carry, subtraction with borrow, multiplication, long division ...
  - Number of digits is a natural measure of input size
    - Same as  $\log_b n$ , when we write  $n$  in base  $b$

# Which inputs should we consider?

- Performance varies across input instances
  - By luck, the value we are searching for is the first element we examine in an array

# Which inputs should we consider?

- Performance varies across input instances
  - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
  - Difficult to compute
  - Average over what? Are all inputs equally likely?
  - Need a probability distribution over inputs

# Which inputs should we consider?

- Performance varies across input instances
  - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
  - Difficult to compute
  - Average over what? Are all inputs equally likely?
  - Need a probability distribution over inputs
- Instead, **worst case** input
  - Input that forces algorithm to take longest possible time
    - Search for a value that is not present in an unsorted list
    - Must scan all elements

# Which inputs should we consider?

- Performance varies across input instances
  - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
  - Difficult to compute
  - Average over what? Are all inputs equally likely?
  - Need a probability distribution over inputs
- Instead, **worst case** input
  - Input that forces algorithm to take longest possible time
    - Search for a value that is not present in an unsorted list
    - Must scan all elements
  - Pessimistic — worst case may be rare

# Which inputs should we consider?

- Performance varies across input instances
  - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
  - Difficult to compute
  - Average over what? Are all inputs equally likely?
  - Need a probability distribution over inputs
- Instead, **worst case** input
  - Input that forces algorithm to take longest possible time
    - Search for a value that is not present in an unsorted list
    - Must scan all elements
  - Pessimistic — worst case may be rare
  - Upper bound for worst case **guarantees** good performance

# Summary

- Two important parameters when measuring algorithm performance
  - Running time, memory requirement (space)
  - We mainly focus on time

# Summary

- Two important parameters when measuring algorithm performance
  - Running time, memory requirement (space)
  - We mainly focus on time
- Running time  $t(n)$  is a function of input size  $n$ 
  - Interested in orders of magnitude
  - Asymptotic complexity, as  $n$  becomes large



# Summary

- Two important parameters when measuring algorithm performance
  - Running time, memory requirement (space)
  - We mainly focus on time
- Running time  $t(n)$  is a function of input size  $n$ 
  - Interested in orders of magnitude
  - Asymptotic complexity, as  $n$  becomes large
- From running time, we can estimate feasible input sizes

# Summary

- Two important parameters when measuring algorithm performance
  - Running time, memory requirement (space)
  - We mainly focus on time
- Running time  $t(n)$  is a function of input size  $n$ 
  - Interested in orders of magnitude
  - Asymptotic complexity, as  $n$  becomes large
- From running time, we can estimate feasible input sizes
- We focus on worst case inputs
  - Pessimistic, but easier to calculate than average case
  - Upper bound on worst case gives us an overall guarantee on performance

# Comparing orders of magnitude

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Orders of magnitude

- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors
- $f(n) = n^3$  eventually grows faster than  $g(n) = 5000n^2$

# Orders of magnitude


- When comparing  $t(n)$ , focus on orders of magnitude
  - Ignore constant factors
- $f(n) = n^3$  eventually grows faster than  $g(n) = 5000n^2$
- How do we compare functions with respect to orders of magnitude?

# Upper bounds

- $f(x)$  is said to be  $O(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $c \cdot g(x)$  is an upper bound for  $f(x)$  for  $x$  beyond  $x_0$


# Upper bounds

- $f(x)$  is said to be  $O(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $c \cdot g(x)$  is an upper bound for  $f(x)$  for  $x$  beyond  $x_0$
- $f(x) \leq cg(x)$  for every  $x \geq x_0$



# Upper bounds


- $f(x)$  is said to be  $O(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $c \cdot g(x)$  is an upper bound for  $f(x)$  for  $x$  beyond  $x_0$
- $f(x) \leq cg(x)$  for every  $x \geq x_0$
- Graphs of typical functions we have seen





# Examples

- $100n + 5$  is  $O(n^2)$ 
  - $100n + 5 \leq 100n + n = 101n$ , for  $n \geq 5$
  - $101n \leq 101n^2$
  - Choose  $n_0 = 5$ ,  $c = 101$



# Examples

- $100n + 5$  is  $O(n^2)$

- $100n + 5 \leq 100n + n = 101n$ , for  $n \geq 5$

- $101n \leq 101n^2$


- Choose  $n_0 = 5$ ,  $c = 101$

- Alternatively

- $100n + 5 \leq 100n + 5n = 105n$ , for  $n \geq 1$


- $105n \leq 105n^2$

- Choose  $n_0 = 1$ ,  $c = 105$




# Examples

- $100n + 5$  is  $O(n^2)$ 
  - $100n + 5 \leq 100n + n = 101n$ , for  $n \geq 5$
  - $101n \leq 101n^2$
  - Choose  $n_0 = 5$ ,  $c = 101$
- Alternatively
  - $100n + 5 \leq 100n + 5n = 105n$ , for  $n \geq 1$
  - $105n \leq 105n^2$
  - Choose  $n_0 = 1$ ,  $c = 105$
- Choice of  $n_0$ ,  $c$  not unique




# Examples ...

- $100n^2 + 20n + 5$  is  $O(n^2)$ 
  - $100n^2 + 20n + 5 \leq 100n^2 + 20n^2 + 5n^2$ , for  $n \geq 1$
  - $100n^2 + 20n + 5 \leq 125n^2$ , for  $n \geq 1$
  - Choose  $n_0 = 1$ ,  $c = 125$




# Examples ...

- $100n^2 + 20n + 5$  is  $O(n^2)$ 
  - $100n^2 + 20n + 5 \leq 100n^2 + 20n^2 + 5n^2$ , for  $n \geq 1$
  - $100n^2 + 20n + 5 \leq 125n^2$ , for  $n \geq 1$
  - Choose  $n_0 = 1$ ,  $c = 125$
- What matters is the highest term
  - $20n + 5$  is dominated by  $100n^2$



# Examples ...

- $100n^2 + 20n + 5$  is  $O(n^2)$ 
  - $100n^2 + 20n + 5 \leq 100n^2 + 20n^2 + 5n^2$ , for  $n \geq 1$
  - $100n^2 + 20n + 5 \leq 125n^2$ , for  $n \geq 1$
  - Choose  $n_0 = 1$ ,  $c = 125$
- What matters is the highest term
  - $20n + 5$  is dominated by  $100n^2$
- $n^3$  is not  $O(n^2)$ 
  - No matter what  $c$  we choose,  $cn^2$  will be dominated by  $n^3$  for  $n \geq c$



# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$
- Proof
  - $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
  - $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$



# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$
- Proof
  - $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
  - $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
  - Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$
- Proof
  - $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
  - $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
  - Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
  - For  $n \geq n_3$ ,  $f_1(n) + f_2(n) \leq c_1 g_1(n) + c_2 g_2(n)$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$

- Proof

- $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
- $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
- Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
- For  $n \geq n_3$ ,  $f_1(n) + f_2(n)$ 
  - $\leq c_1 g_1(n) + c_2 g_2(n)$
  - $\leq c_3(g_1(n) + g_2(n))$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$

- Proof

- $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
- $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
- Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
- For  $n \geq n_3$ ,  $f_1(n) + f_2(n)$ 
  - $\leq c_1 g_1(n) + c_2 g_2(n)$
  - $\leq c_3(g_1(n) + g_2(n))$
  - $\leq 2c_3(\max(g_1(n), g_2(n)))$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$

- Proof

- $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
- $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
- Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
- For  $n \geq n_3$ ,  $f_1(n) + f_2(n)$ 
  - $\leq c_1 g_1(n) + c_2 g_2(n)$
  - $\leq c_3 (g_1(n) + g_2(n))$
  - $\leq 2c_3 (\max(g_1(n), g_2(n)))$

- Algorithm has two phases

- Phase A takes time  $O(g_A(n))$
- Phase B takes time  $O(g_B(n))$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$
- Proof
  - $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
  - $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
  - Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
  - For  $n \geq n_3$ ,  $f_1(n) + f_2(n)$ 
    - $\leq c_1 g_1(n) + c_2 g_2(n)$
    - $\leq c_3(g_1(n) + g_2(n))$
    - $\leq 2c_3(\max(g_1(n), g_2(n)))$
- Algorithm has two phases
  - Phase A takes time  $O(g_A(n))$
  - Phase B takes time  $O(g_B(n))$
- Algorithm as a whole takes time  $\max(O(g_A(n), g_B(n)))$

# Useful properties

- If  $f_1(n)$  is  $O(g_1(n))$  and  $f_2(n)$  is  $O(g_2(n))$ , then  $f_1(n) + f_2(n)$  is  $O(\max(g_1(n), g_2(n)))$

- Proof

- $f_1(n) \leq c_1 g_1(n)$  for  $n > n_1$
- $f_2(n) \leq c_2 g_2(n)$  for  $n > n_2$
- Let  $c_3 = \max(c_1, c_2)$ ,  $n_3 = \max(n_1, n_2)$
- For  $n \geq n_3$ ,  $f_1(n) + f_2(n)$ 
  - $\leq c_1 g_1(n) + c_2 g_2(n)$
  - $\leq c_3(g_1(n) + g_2(n))$
  - $\leq 2c_3(\max(g_1(n), g_2(n)))$

- Algorithm has two phases
  - Phase A takes time  $O(g_A(n))$
  - Phase B takes time  $O(g_B(n))$
- Algorithm as a whole takes time  $\max(O(g_A(n), g_B(n)))$
- Least efficient phase is the upper bound for the whole algorithm

# Lower bounds

- $f(x)$  is said to be  $\Omega(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $cg(x)$  is a lower bound for  $f(x)$  for  $x$  beyond  $x_0$ 
  - $f(x) \geq cg(x)$  for every  $x \geq x_0$



# Lower bounds

- $f(x)$  is said to be  $\Omega(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $cg(x)$  is a lower bound for  $f(x)$  for  $x$  beyond  $x_0$ 
  - $f(x) \geq cg(x)$  for every  $x \geq x_0$
- $n^3$  is  $\Omega(n^2)$ 
  - $n^3 > n^2$  for all  $n$ , so  $n_0 = 1$ ,  $c = 1$

# Lower bounds

- $f(x)$  is said to be  $\Omega(g(x))$  if we can find constants  $c$  and  $x_0$  such that  $cg(x)$  is a lower bound for  $f(x)$  for  $x$  beyond  $x_0$ 
  - $f(x) \geq cg(x)$  for every  $x \geq x_0$
- $n^3$  is  $\Omega(n^2)$ 
  - $n^3 > n^2$  for all  $n$ , so  $n_0 = 1$ ,  $c = 1$
- Typically we establish lower bounds for a problem rather than an individual algorithm
  - If we sort a list by comparing elements and swapping them, we require  $\Omega(n \log n)$  comparisons
  - This is **independent** of the algorithm we use for sorting

# Tight bounds

- $f(x)$  is said to be  $\Theta(g(x))$  if it is both  $O(g(x))$  and  $\Omega(g(x))$ 
  - Find constants  $c_1, c_2, x_0$  such that  $c_1g(x) \leq f(x) \leq c_2g(x)$  for every  $x \geq x_0$

# Tight bounds

- $f(x)$  is said to be  $\Theta(g(x))$  if it is both  $O(g(x))$  and  $\Omega(g(x))$ 
  - Find constants  $c_1, c_2, x_0$  such that  $c_1g(x) \leq f(x) \leq c_2g(x)$  for every  $x \geq x_0$
- $n(n-1)/2$  is  $\Theta(n^2)$

# Tight bounds

- $f(x)$  is said to be  $\Theta(g(x))$  if it is both  $O(g(x))$  and  $\Omega(g(x))$ 
  - Find constants  $c_1, c_2, x_0$  such that  $c_1g(x) \leq f(x) \leq c_2g(x)$  for every  $x \geq x_0$
- $n(n-1)/2$  is  $\Theta(n^2)$ 
  - Upper bound
    - $n(n-1)/2 = n^2/2 - n/2 \leq n^2/2$  for all  $n \geq 0$

# Tight bounds

- $f(x)$  is said to be  $\Theta(g(x))$  if it is both  $O(g(x))$  and  $\Omega(g(x))$ 
  - Find constants  $c_1, c_2, x_0$  such that  $c_1g(x) \leq f(x) \leq c_2g(x)$  for every  $x \geq x_0$
- $n(n-1)/2$  is  $\Theta(n^2)$ 
  - Upper bound
    - $n(n-1)/2 = n^2/2 - n/2 \leq n^2/2$  for all  $n \geq 0$
  - Lower bound
    - $n(n-1)/2 = n^2/2 - n/2 \geq n^2/2 - (n/2 \times n/2) \geq n^2/4$  for  $n \geq 2$

# Tight bounds

- $f(x)$  is said to be  $\Theta(g(x))$  if it is both  $O(g(x))$  and  $\Omega(g(x))$ 
  - Find constants  $c_1, c_2, x_0$  such that  $c_1g(x) \leq f(x) \leq c_2g(x)$  for every  $x \geq x_0$
- $n(n-1)/2$  is  $\Theta(n^2)$ 
  - Upper bound
    - $n(n-1)/2 = n^2/2 - n/2 \leq n^2/2$  for all  $n \geq 0$
  - Lower bound
    - $n(n-1)/2 = n^2/2 - n/2 \geq n^2/2 - (n/2 \times n/2) \geq n^2/4$  for  $n \geq 2$
  - Choose  $n_0 = 2$ ,  $c_1 = 1/4$ ,  $c_2 = 1/2$

# Summary

- $f(n)$  is  $O(g(n))$  means  $g(n)$  is an upper bound for  $f(n)$ 
  - Useful to describe asymptotic worst case running time



# Summary

- $f(n)$  is  $O(g(n))$  means  $g(n)$  is an upper bound for  $f(n)$ 
  - Useful to describe asymptotic worst case running time
- $f(n)$  is  $\Omega(g(n))$  means  $g(n)$  is a lower bound for  $f(n)$ 
  - Typically used for a problem as a whole, rather than an individual algorithm

# Summary

- $f(n)$  is  $O(g(n))$  means  $g(n)$  is an upper bound for  $f(n)$ 
  - Useful to describe asymptotic worst case running time
- $f(n)$  is  $\Omega(g(n))$  means  $g(n)$  is a lower bound for  $f(n)$ 
  - Typically used for a problem as a whole, rather than an individual algorithm
- $f(n)$  is  $\Theta(g(n))$ : matching upper and lower bounds
  - We have found an optimal algorithm for a problem

# Calculating complexity — Examples

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Calculating complexity

- Iterative programs
- Recursive programs

# Example 1

## Find the maximum element in a list

- Input size is length of the list
- Single loop scans all elements
- Always takes  $n$  steps
- Overall time is  $O(n)$

```
def maxElement(L):  
    maxval = L[0]  
    for i in range(len(L)):  
        if L[i] > maxval:  
            maxval = L[i]  
    return(maxval)
```

## Example 2

### Check whether a list contains duplicates

- Input size is length of the list
- Nested loop scans all pairs of elements
- A duplicate may be found in the very first iteration
- Worst case — no duplicates, both loops run fully
- Time is  $(n-1) + (n-2) + \dots + 1 = n(n-1)/2$
- Overall time is  $O(n^2)$

```
def noDuplicates(L):  
    for i in range(len(L)):  
        for j in range(i+1, len(L)):  
            if L[i] == L[j]:  
                return(False)  
    return(True)
```

# Example 3

## Matrix multiplication

- Matrix is represented as list of lists

- $\begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \end{pmatrix}$

- $[[1,2,3],[4,5,6]]$

- Input matrices have size  $m \times n$ ,  $n \times p$

- Output matrix is  $m \times p$

- Three nested loops

- Overall time is  $O(mnp)$  —  $O(n^3)$  if both are  $n \times n$

```
def matrixMultiply(A,B):  
    (m,n,p) = (len(A),len(B),len(B[0]))  
  
    C = [[ 0 for i in range(p) ]  
          for j in range(m) ]  
  
    for i in range(m):  
        for j in range(p):  
            for k in range(n):  
                C[i][j] = C[i][j] + A[i][k]*B[k][j]  
  
    return(C)
```

# Example 4

## Number of bits in binary representation of $n$

- $\log n$  steps for  $n$  to reach 1
- For number theoretic problems, input size is number of digits
- This algorithm is linear in input size


```
def numberOfBits(n):  
  
    count = 1  
  
    while n > 1:  
        count = count + 1  
        n = n // 2  
  
    return(count)
```



# Example 5

## Towers of Hanoi


- Three pegs A,B,C
- Move  $n$  disks from A to B, use C as transit peg
- Never put a larger disk on a smaller one



# Example 5

## Towers of Hanoi

- Three pegs A,B,C
- Move  $n$  disks from A to B, use C as transit peg
- Never put a larger disk on a smaller one



## Recursive solution

- Move  $n - 1$  disks from A to C, use B as transit peg
- Move largest disk from A to B
- Move  $n - 1$  disks from C to B, use A as transit peg

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$M(n) = 2M(n-1) + 1$$

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$\begin{aligned} M(n) &= 2M(n-1) + 1 \\ &= 2(2M(n-2) + 1) + 1 = 2^2M(n-2) + (2 + 1) \end{aligned}$$

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$\begin{aligned}M(n) &= 2M(n-1) + 1 \\&= 2(2M(n-2) + 1) + 1 = 2^2M(n-2) + (2 + 1) \\&= 2^2(2M(n-3) + 1) + (2 + 1) = 2^3M(n-3) + (4 + 2 + 1)\end{aligned}$$

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$\begin{aligned}M(n) &= 2M(n-1) + 1 \\&= 2(2M(n-2) + 1) + 1 = 2^2M(n-2) + (2 + 1) \\&= 2^2(2M(n-3) + 1) + (2 + 1) = 2^3M(n-3) + (4 + 2 + 1) \\&\quad \dots \\&= 2^kM(n-k) + (2^k - 1)\end{aligned}$$

# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$\begin{aligned}M(n) &= 2M(n-1) + 1 \\&= 2(2M(n-2) + 1) + 1 = 2^2M(n-2) + (2 + 1) \\&= 2^2(2M(n-3) + 1) + (2 + 1) = 2^3M(n-3) + (4 + 2 + 1) \\&\quad \dots \\&= 2^k M(n-k) + (2^k - 1) \\&\quad \dots \\&= 2^{n-1} M(1) + (2^{n-1} - 1)\end{aligned}$$



# Example 5

## Recurrence

- $M(n)$  — number of moves to transfer  $n$  disks
- $M(1) = 1$
- $M(n) = M(n-1) + 1 + M(n-1) = 2M(n-1) + 1$

## Unwind and solve

$$\begin{aligned}M(n) &= 2M(n-1) + 1 \\&= 2(2M(n-2) + 1) + 1 = 2^2M(n-2) + (2 + 1) \\&= 2^2(2M(n-3) + 1) + (2 + 1) = 2^3M(n-3) + (4 + 2 + 1) \\&\quad \dots \\&= 2^k M(n-k) + (2^k - 1) \\&\quad \dots \\&= 2^{n-1} M(1) + (2^{n-1} - 1) \\&= 2^{n-1} + 2^{n-1} - 1 = 2^n - 1\end{aligned}$$

# Summary

- Iterative programs
  - Focus on loops

# Summary

- Iterative programs
  - Focus on loops
- Recursive programs
  - Write and solve a recurrence

# Summary

- Iterative programs
  - Focus on loops
- Recursive programs
  - Write and solve a recurrence
- Need to be clear about accounting for “basic” operations

# Searching in a List

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Search problem

- Is value  $v$  present in list  $l$ ?

# Search problem

- Is value  $v$  present in list  $l$ ?
- Naive solution scans the list

```
def naivesearch(v,l):  
    for x in l:  
        if v == x:  
            return(True)  
    return(False)
```

# Search problem

- Is value  $v$  present in list  $l$ ?
- Naive solution scans the list
- Input size  $n$ , the length of the list

```
def naivesearch(v,l):  
    for x in l:  
        if v == x:  
            return(True)  
    return(False)
```



# Search problem

- Is value  $v$  present in list  $l$ ?
- Naive solution scans the list
- Input size  $n$ , the length of the list
- Worst case is when  $v$  is not present in  $l$

```
def naivesearch(v,l):  
    for x in l:  
        if v == x:  
            return(True)  
    return(False)
```

# Search problem

- Is value  $v$  present in list  $l$ ?
- Naive solution scans the list
- Input size  $n$ , the length of the list
- Worst case is when  $v$  is not present in  $l$
- Worst case complexity is  $O(n)$

```
def naivesearch(v,l):  
    for x in l:  
        if v == x:  
            return(True)  
    return(False)
```

# Searching a sorted list

- What if 1 is sorted in ascending order?

# Searching a sorted list

- What if  $l$  is sorted in ascending order?
- Compare  $v$  with the midpoint of  $l$

# Searching a sorted list

- What if `l` is sorted in ascending order?
- Compare `v` with the midpoint of `l`
  - If midpoint is `v`, the value is found
  - If `v` less than midpoint, search the first half
  - If `v` greater than midpoint, search the second half
  - Stop when the interval to search becomes empty

```
def binarysearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(binarysearch(v,l[:m]))  
    else:  
        return(binarysearch(v,l[m+1:]))
```

# Searching a sorted list

- What if `l` is sorted in ascending order?
- Compare `v` with the midpoint of `l`
  - If midpoint is `v`, the value is found
  - If `v` less than midpoint, search the first half
  - If `v` greater than midpoint, search the second half
  - Stop when the interval to search becomes empty

## ■ Binary search

```
def binarysearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(binarysearch(v,l[:m]))  
    else:  
        return(binarysearch(v,l[m+1:]))
```

# Binary search

- How long does this take?

```
def binarysearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(binarysearch(v,l[:m]))  
    else:  
        return(binarysearch(v,l[m+1:]))
```

# Binary search

- How long does this take?
  - Each call halves the interval to search
  - Stop when the interval become empty
- $\log n$  — number of times to divide  $n$  by 2 to reach 1
  - $1 // 2 = 0$ , so next call reaches empty interval

```
def binarysearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(binarysearch(v,l[:m]))  
    else:  
        return(binarysearch(v,l[m+1:]))
```



# Binary search

- How long does this take?
  - Each call halves the interval to search
  - Stop when the interval become empty
- $\log n$  — number of times to divide  $n$  by 2 to reach 1
  - $1 // 2 = 0$ , so next call reaches empty interval
- $O(\log n)$  steps

```
def binarysearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(binarysearch(v,l[:m]))  
    else:  
        return(binarysearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$ 
  - If  $n = 0$ , we exit, so  $T(n) = 1$
  - If  $n > 0$ ,  $T(n) = T(n // 2) + 1$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$ 
  - If  $n = 0$ , we exit, so  $T(n) = 1$
  - If  $n > 0$ ,  $T(n) = T(n // 2) + 1$
- Recurrence for  $T(n)$ 
  - $T(0) = 1$
  - $T(n) = T(n // 2) + 1, n > 0$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$ 
  - If  $n = 0$ , we exit, so  $T(n) = 1$
  - If  $n > 0$ ,  $T(n) = T(n // 2) + 1$
- Recurrence for  $T(n)$ 
  - $T(0) = 1$
  - $T(n) = T(n // 2) + 1, n > 0$
- Solve by “unwinding”

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$ 
  - If  $n = 0$ , we exit, so  $T(n) = 1$
  - If  $n > 0$ ,  $T(n) = T(n // 2) + 1$
- Recurrence for  $T(n)$ 
  - $T(0) = 1$
  - $T(n) = T(n // 2) + 1, n > 0$
- Solve by “unwinding”
- $T(n) = T(n // 2) + 1$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$

- If  $n = 0$ , we exit, so  $T(n) = 1$
- If  $n > 0$ ,  $T(n) = T(n // 2) + 1$

- Recurrence for  $T(n)$

- $T(0) = 1$
- $T(n) = T(n // 2) + 1, n > 0$

- Solve by “unwinding”

- $$\begin{aligned} T(n) &= T(n // 2) + 1 \\ &= (T(n // 4) + 1) + 1 \end{aligned}$$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$ 
  - If  $n = 0$ , we exit, so  $T(n) = 1$
  - If  $n > 0$ ,  $T(n) = T(n // 2) + 1$
- Recurrence for  $T(n)$ 
  - $T(0) = 1$
  - $T(n) = T(n // 2) + 1, n > 0$
- Solve by “unwinding”
- $$\begin{aligned} T(n) &= T(n // 2) + 1 \\ &= (T(n // 4) + 1) + 1 = T(n // 2^2) + \underbrace{1 + 1}_2 \end{aligned}$$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$

- If  $n = 0$ , we exit, so  $T(n) = 1$
- If  $n > 0$ ,  $T(n) = T(n // 2) + 1$

- Recurrence for  $T(n)$

- $T(0) = 1$
- $T(n) = T(n // 2) + 1, n > 0$

- Solve by “unwinding”

- $$\begin{aligned} T(n) &= T(n // 2) + 1 \\ &= (T(n // 4) + 1) + 1 = T(n // 2^2) + \underbrace{1 + 1}_2 \\ &= \dots \\ &= T(n // 2^k) + \underbrace{1 + \dots + 1}_k \end{aligned}$$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```



# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$

- If  $n = 0$ , we exit, so  $T(n) = 1$
- If  $n > 0$ ,  $T(n) = T(n // 2) + 1$

- Recurrence for  $T(n)$

- $T(0) = 1$
- $T(n) = T(n // 2) + 1, n > 0$

- Solve by “unwinding”

- $$\begin{aligned} T(n) &= T(n // 2) + 1 \\ &= (T(n // 4) + 1) + 1 = T(n // 2^2) + \underbrace{1 + 1}_2 \\ &= \dots \\ &= T(n // 2^k) + \underbrace{1 + \dots + 1}_k \\ &= T(1) + k, \text{ for } k = \log n \end{aligned}$$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Alternative calculation

- $T(n)$  : the time to search a list of length  $n$

- If  $n = 0$ , we exit, so  $T(n) = 1$
- If  $n > 0$ ,  $T(n) = T(n // 2) + 1$

- Recurrence for  $T(n)$

- $T(0) = 1$
- $T(n) = T(n // 2) + 1, n > 0$

- Solve by “unwinding”

- $$\begin{aligned} T(n) &= T(n // 2) + 1 \\ &= (T(n // 4) + 1) + 1 = T(n // 2^2) + \underbrace{1 + 1}_2 \\ &= \dots \\ &= T(n // 2^k) + \underbrace{1 + \dots + 1}_k \\ &= T(1) + k, \text{ for } k = \log n \\ &= (T(0) + 1) + \log n = 2 + \log n \end{aligned}$$

```
def bsearch(v,l):  
    if l == []:  
        return(False)  
  
    m = len(l)//2  
  
    if v == l[m]:  
        return(True)  
  
    if v < l[m]:  
        return(bsearch(v,l[:m]))  
    else:  
        return(bsearch(v,l[m+1:]))
```

# Summary

- Search in an unsorted list takes time  $O(n)$ 
  - Need to scan the entire list
  - Worst case is when the value is not present in the list

# Summary

- Search in an unsorted list takes time  $O(n)$ 
  - Need to scan the entire list
  - Worst case is when the value is not present in the list
- For a sorted list, binary search takes time  $O(\log n)$ 
  - Halve the interval to search each time

# Summary

- Search in an unsorted list takes time  $O(n)$ 
  - Need to scan the entire list
  - Worst case is when the value is not present in the list
- For a sorted list, binary search takes time  $O(\log n)$ 
  - Halve the interval to search each time
- In a sorted list, we can determine that  $v$  is absent by examining just  $\log n$  values!

# Selection Sort

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?



# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?
- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?
- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

## Strategy 1

- Scan the entire pile and find the paper with minimum marks

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?
- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

## Strategy 1

- Scan the entire pile and find the paper with minimum marks
- Move this paper to a new pile

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?
- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

## Strategy 1

- Scan the entire pile and find the paper with minimum marks
- Move this paper to a new pile
- Repeat with the remaining papers
  - Add the paper with next minimum marks to the second pile each time

# Sorting a list

- Sorting a list makes many other computations easier
  - Binary search
  - Finding the median
  - Checking for duplicates
  - Building a frequency table of values
- How do we sort a list?
- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

## Strategy 1

- Scan the entire pile and find the paper with minimum marks
- Move this paper to a new pile
- Repeat with the remaining papers
  - Add the paper with next minimum marks to the second pile each time
- Eventually, the new pile is sorted in descending order

# Sorting a list

74      32      89      55      21      64

# Sorting a list

74      32      89      55      ~~21~~      64

21

# Sorting a list

74    ~~32~~    89    55    21    64

21    32



# Sorting a list

74      32      89      ~~55~~      21      64

21      32      55

# Sorting a list

74      32      89      55      21      64

21      32      55      64

# Sorting a list

~~74~~ 32 89 55 21 64

21 32 55 64 74

# Sorting a list

74      32      89      55      21      64

21      32      55      64      74      89

# Selection sort

- **Select** the next element in sorted order

# Selection sort

- **Select** the next element in sorted order
- Append it to the final sorted list

# Selection sort

- **Select** the next element in sorted order
- Append it to the final sorted list
- Avoid using a second list
  - Swap the minimum element into the first position
  - Swap the second minimum element into the second position
  - ...

# Selection sort

- **Select** the next element in sorted order
- Append it to the final sorted list
- Avoid using a second list
  - Swap the minimum element into the first position
  - Swap the second minimum element into the second position
  - ...
- Eventually the list is rearranged in place in ascending order



# Selection sort

- **Select** the next element in sorted order
- Append it to the final sorted list
- Avoid using a second list
  - Swap the minimum element into the first position
  - Swap the second minimum element into the second position
  - ...
- Eventually the list is rearranged in place in ascending order

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant

```
def SelectionSort(L):
    n = len(L)
    if n < 1:
        return(L)
    for i in range(n):
        # Assume L[:i] is sorted
        mpos = i
        # mpos: position of minimum in L[i:]
        for j in range(i+1,n):
            if L[j] < L[mpos]:
                mpos = j
        # L[mpos] : smallest value in L[i:]
        # Exchange L[mpos] and L[i]
        (L[i],L[mpos]) = (L[mpos],L[i])
        # Now L[:i+1] is sorted
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant
- Efficiency

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $n - i$  steps to find minimum in  $L[i:]$

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $n - i$  steps to find minimum in  $L[i:]$
  - $T(n) = n + (n - 1) + \dots + 1$

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant

- Efficiency

- Outer loop iterates  $n$  times
- Inner loop:  $n - i$  steps to find minimum in  $L[i:]$
- $T(n) = n + (n - 1) + \dots + 1$
- $T(n) = n(n + 1)/2$

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of selection sort

- Correctness follows from the invariant

- Efficiency

- Outer loop iterates  $n$  times
- Inner loop:  $n - i$  steps to find minimum in  $L[i:]$
- $T(n) = n + (n - 1) + \dots + 1$
- $T(n) = n(n + 1)/2$

- $T(n)$  is  $O(n^2)$

```
def SelectionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        mpos = i  
        # mpos: position of minimum in L[i:]  
        for j in range(i+1,n):  
            if L[j] < L[mpos]:  
                mpos = j  
        # L[mpos] : smallest value in L[i:]  
        # Exchange L[mpos] and L[i]  
        (L[i],L[mpos]) = (L[mpos],L[i])  
        # Now L[:i+1] is sorted  
    return(L)
```



# Summary

- Selection sort is an intuitive algorithm to sort a list

# Summary

- Selection sort is an intuitive algorithm to sort a list
- Repeatedly find the minimum (or maximum) and append to sorted list

# Summary

- Selection sort is an intuitive algorithm to sort a list
- Repeatedly find the minimum (or maximum) and append to sorted list
- Worst case complexity is  $O(n^2)$ 
  - Every input takes this much time
  - No advantage even if list is arranged carefully before sorting

# Insertion Sort

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Sorting a list

- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

# Sorting a list

- You are the TA for a course
  - Instructor has a pile of evaluated exam papers
  - Papers in random order of marks
  - Your task is to arrange the papers in descending order of marks

## Strategy 2

# Sorting a list

- You are the TA for a course

- Instructor has a pile of evaluated exam papers
- Papers in random order of marks
- Your task is to arrange the papers in descending order of marks

## Strategy 2

- Move the first paper to a new pile

# Sorting a list

- You are the TA for a course

- Instructor has a pile of evaluated exam papers
- Papers in random order of marks
- Your task is to arrange the papers in descending order of marks

## Strategy 2

- Move the first paper to a new pile
- Second paper
  - Lower marks than first paper? Place below first paper in new pile
  - Higher marks than first paper? Place above first paper in new pile



# Sorting a list

- You are the TA for a course

- Instructor has a pile of evaluated exam papers
- Papers in random order of marks
- Your task is to arrange the papers in descending order of marks

## Strategy 2

- Move the first paper to a new pile
- Second paper
  - Lower marks than first paper? Place below first paper in new pile
  - Higher marks than first paper? Place above first paper in new pile
- Third paper
  - **Insert** into correct position with respect to first two

# Sorting a list

- You are the TA for a course

- Instructor has a pile of evaluated exam papers
- Papers in random order of marks
- Your task is to arrange the papers in descending order of marks

## Strategy 2

- Move the first paper to a new pile
- Second paper
  - Lower marks than first paper? Place below first paper in new pile
  - Higher marks than first paper? Place above first paper in new pile
- Third paper
  - **Insert** into correct position with respect to first two
- Do this for the remaining papers
  - **Insert** each one into correct position in the second pile

# Sorting a list

74      32      89      55      21      64

# Sorting a list

~~74~~ 32 89 55 21 64

74

# Sorting a list

74    ~~32~~    89    55    21    64

32    74

# Sorting a list

74      32      ~~89~~      55      21      64

32      74      89

# Sorting a list

74      32      89      55      21      64

32      55      74      89

# Sorting a list

74      32      89      55      ~~21~~      64

21      32      55      74      89



# Sorting a list

74      32      89      55      21      64

21      32      55      64      74      89

# Insertion sort

- Start building a new sorted list

# Insertion sort

- Start building a new sorted list
- Pick next element and **insert** it into the sorted list

# Insertion sort

- Start building a new sorted list
- Pick next element and **insert** it into the sorted list
- An iterative formulation
  - Assume `L[:i]` is sorted
  - Insert `L[i]` in `L[:i]`

# Insertion sort

- Start building a new sorted list
- Pick next element and **insert** it into the sorted list
- An iterative formulation
  - Assume `L[:i]` is sorted
  - Insert `L[i]` in `L[:i]`

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(j > 0 and L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Insertion sort

- Start building a new sorted list
- Pick next element and **insert** it into the sorted list
- An iterative formulation
  - Assume `L[:i]` is sorted
  - Insert `L[i]` in `L[:i]`
- A recursive formulation
  - Inductively sort `L[:i]`
  - Insert `L[i]` in `L[:i]`

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(j > 0 and L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Insertion sort

- Start building a new sorted list
- Pick next element and **insert** it into the sorted list
- An iterative formulation
  - Assume `L[:i]` is sorted
  - Insert `L[i]` in `L[:i]`
- A recursive formulation
  - Inductively sort `L[:i]`
  - Insert `L[i]` in `L[:i]`

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else:  
        return(Insert(L[:-1],v)+L[-1:])
```

```
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```



# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $i$  steps to insert  $L[i]$  in  $L[:i]$

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $i$  steps to insert  $L[i]$  in  $L[:i]$
  - $T(n) = 0 + 1 + \dots + (n-1)$

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $i$  steps to insert  $L[i]$  in  $L[:i]$
  - $T(n) = 0 + 1 + \dots + (n-1)$
  - $T(n) = n(n-1)/2$

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of iterative insertion sort

- Correctness follows from the invariant
- Efficiency
  - Outer loop iterates  $n$  times
  - Inner loop:  $i$  steps to insert  $L[i]$  in  $L[:i]$
  - $T(n) = 0 + 1 + \dots + (n-1)$
  - $T(n) = n(n-1)/2$
- $T(n)$  is  $O(n^2)$

```
def InsertionSort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    for i in range(n):  
        # Assume L[:i] is sorted  
        # Move L[i] to correct position in L[:i]  
        j = i  
        while(L[j] < L[j-1]):  
            (L[j],L[j-1]) = (L[j-1],L[j])  
            j = j-1  
        # Now L[:i+1] is sorted  
    return(L)
```

# Analysis of recursive insertion sort

- For input of size  $n$ , let
  - $T_I(n)$  be the time taken by `Insert`
  - $T_S(n)$  be the time taken by `ISort`

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else  
        return(Insert(L[:-1],v)+L[-1:])
```

```
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```

# Analysis of recursive insertion sort

- For input of size  $n$ , let
  - $TI(n)$  be the time taken by `Insert`
  - $TS(n)$  be the time taken by `ISort`
- First calculate  $TI(n)$  for `Insert`
  - $TI(0) = 1$
  - $TI(n) = TI(n-1) + 1$

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else  
        return(Insert(L[:-1],v)+L[-1:])
```

```
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```



# Analysis of recursive insertion sort

- For input of size  $n$ , let
  - $TI(n)$  be the time taken by `Insert`
  - $TS(n)$  be the time taken by `ISort`
- First calculate  $TI(n)$  for `Insert`
  - $TI(0) = 1$
  - $TI(n) = TI(n-1) + 1$
  - Unwind to get  $TI(n) = n$

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else  
        return(Insert(L[:-1],v)+L[-1:])
```

```
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```

# Analysis of recursive insertion sort

- For input of size  $n$ , let
  - $TI(n)$  be the time taken by `Insert`
  - $TS(n)$  be the time taken by `ISort`
- First calculate  $TI(n)$  for `Insert`
  - $TI(0) = 1$
  - $TI(n) = TI(n-1) + 1$
  - Unwind to get  $TI(n) = n$
- Set up a recurrence for  $TS(n)$ 
  - $TS(0) = 1$
  - $TS(n) = TS(n-1) + TI(n-1)$

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else  
        return(Insert(L[:-1],v)+L[-1:])  
  
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```

# Analysis of recursive insertion sort

- For input of size  $n$ , let
  - $TI(n)$  be the time taken by `Insert`
  - $TS(n)$  be the time taken by `ISort`
- First calculate  $TI(n)$  for `Insert`
  - $TI(0) = 1$
  - $TI(n) = TI(n-1) + 1$
  - Unwind to get  $TI(n) = n$
- Set up a recurrence for  $TS(n)$ 
  - $TS(0) = 1$
  - $TS(n) = TS(n-1) + TI(n-1)$
- Unwind to get  $1 + 2 + \dots + n - 1$

```
def Insert(L,v):  
    n = len(L)  
    if n == 0:  
        return([v])  
    if v >= L[-1]:  
        return(L+[v])  
    else  
        return(Insert(L[:-1],v)+L[-1:])  
  
def ISort(L):  
    n = len(L)  
    if n < 1:  
        return(L)  
    L = Insert(ISort(L[:-1]),L[-1])  
    return(L)
```

# Summary

- Insertion sort is another intuitive algorithm to sort a list

# Summary

- Insertion sort is another intuitive algorithm to sort a list
- Create a new sorted list
- Repeatedly insert elements into the sorted list

# Summary

- Insertion sort is another intuitive algorithm to sort a list
- Create a new sorted list
- Repeatedly insert elements into the sorted list
- Worst case complexity is  $O(n^2)$ 
  - Unlike selection sort, not all cases take time  $n^2$
  - If list is already sorted, **Insert** stops in 1 step
  - Overall time can be close to  $O(n)$

# Merge Sort

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Beating the $O(n^2)$ barrier

- Both selection sort and insertion sort take time  $O(n^2)$
- This is infeasible for  $n > 10000$



# Beating the $O(n^2)$ barrier

- Both selection sort and insertion sort take time  $O(n^2)$
- This is infeasible for  $n > 10000$
- How can we bring the complexity below  $O(n^2)$ ?

# Beating the $O(n^2)$ barrier

- Both selection sort and insertion sort take time  $O(n^2)$
- This is infeasible for  $n > 10000$
- How can we bring the complexity below  $O(n^2)$ ?

## Strategy 3

- Divide the list into two halves

# Beating the $O(n^2)$ barrier

- Both selection sort and insertion sort take time  $O(n^2)$
- This is infeasible for  $n > 10000$
- How can we bring the complexity below  $O(n^2)$ ?

## Strategy 3

- Divide the list into two halves
- Separately sort the left and right half

# Beating the $O(n^2)$ barrier

- Both selection sort and insertion sort take time  $O(n^2)$
- This is infeasible for  $n > 10000$
- How can we bring the complexity below  $O(n^2)$ ?

## Strategy 3

- Divide the list into two halves
- Separately sort the left and right half
- Combine the two sorted halves to get a fully sorted list

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**
  - Compare first elements of **A** and **B**

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**
  - Compare first elements of **A** and **B**
  - Move the smaller of the two to **C**

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**
  - Compare first elements of **A** and **B**
  - Move the smaller of the two to **C**
  - Repeat till you exhaust **A** and **B**



# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

- Compare first elements of **A** and **B**
- Move the smaller of the two to **C**
- Repeat till you exhaust **A** and **B**

32   74   89

21   55   64

# Combining two sorted lists

- Combine two sorted lists A and B into a single sorted list C

- Compare first elements of A and B
- Move the smaller of the two to C
- Repeat till you exhaust A and B

32 74 89

~~21~~ 55 64

21

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

- Compare first elements of **A** and **B**
- Move the smaller of the two to **C**
- Repeat till you exhaust **A** and **B**

~~32~~ 74 89

~~21~~ 55 64

21 32

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

- Compare first elements of **A** and **B**
- Move the smaller of the two to **C**
- Repeat till you exhaust **A** and **B**

32 74 89

21 ~~55~~ 64

21 32 55

# Combining two sorted lists

- Combine two sorted lists A and B into a single sorted list C

- Compare first elements of A and B
- Move the smaller of the two to C
- Repeat till you exhaust A and B

32 74 89

21 55 ~~64~~

21 32 55 64

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

- Compare first elements of **A** and **B**
- Move the smaller of the two to **C**
- Repeat till you exhaust **A** and **B**

32   ~~74~~   89

21   55   64

21   32   55   64   74

# Combining two sorted lists

- Combine two sorted lists **A** and **B** into a single sorted list **C**

- Compare first elements of **A** and **B**
- Move the smaller of the two to **C**
- Repeat till you exhaust **A** and **B**

32   74   89

21   55   64

21   32   55   64   74   89

# Combining two sorted lists

- Combine two sorted lists A and B into a single sorted list C

- Compare first elements of A and B
- Move the smaller of the two to C
- Repeat till you exhaust A and B

32 74 89

21 55 64

21 32 55 64 74 89

- Merging A and B



# Merge sort

- Let  $n$  be the length of  $L$

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

43	32	22	78
----	----	----	----

63	57	91	13
----	----	----	----



# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43	22	78	57	63	91	13
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43	22	78	57	63	13	91
----	----	----	----	----	----	----	----

- Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

43	32	22	78
----	----	----	----

63	57	91	13
----	----	----	----

32	43
----	----

22	78
----	----

57	63
----	----

13	91
----	----



# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

22	32	43	78
----	----	----	----

63	57	91	13
----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43
----	----

22	78
----	----

57	63
----	----

13	91
----	----

- Recursively, same strategy!

# Merge sort

- Let  $n$  be the length of  $L$

- Sort  $A[:n//2]$

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

- Sort  $A[n//2:]$

- Merge the sorted halves into  $B$

22	32	43	78
----	----	----	----

13	57	63	91
----	----	----	----

- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?

32	43
----	----

22	78
----	----

57	63
----	----

13	91
----	----

- Recursively, same strategy!

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

43	32	22	78	63	57	91	13
----	----	----	----	----	----	----	----

22	32	43	78
----	----	----	----

13	57	63	91
----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

13	22	32	43	57	63	78	91
----	----	----	----	----	----	----	----

22	32	43	78
----	----	----	----

13	57	63	91
----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

13	22	32	43	57	63	78	91
----	----	----	----	----	----	----	----

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

# Merge sort

- Let  $n$  be the length of  $L$
- Sort  $A[:n//2]$
- Sort  $A[n//2:]$
- Merge the sorted halves into  $B$
- How do we sort  $A[:n//2]$  and  $A[n//2:]$ ?
  - Recursively, same strategy!

## Divide and Conquer

- Break up the problem into disjoint parts
- Solve each part separately
- Combine the solutions efficiently

# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**



# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**
  - If **A** is empty, copy **B** into **C**

# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**
  - If **A** is empty, copy **B** into **C**
  - If **B** is empty, copy **A** into **C**

# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**
  - If **A** is empty, copy **B** into **C**
  - If **B** is empty, copy **A** into **C**
  - Otherwise, compare first elements of **A** and **B**
    - Move the smaller of the two to **C**

# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**
  - If **A** is empty, copy **B** into **C**
  - If **B** is empty, copy **A** into **C**
  - Otherwise, compare first elements of **A** and **B**
    - Move the smaller of the two to **C**
  - Repeat till all elements of **A** and **B** have been moved

# Merging sorted lists

- Combine two sorted lists **A** and **B** into **C**
  - If **A** is empty, copy **B** into **C**
  - If **B** is empty, copy **A** into **C**
  - Otherwise, compare first elements of **A** and **B**
    - Move the smaller of the two to **C**
  - Repeat till all elements of **A** and **B** have been moved

```
def merge(A,B):  
    (m,n) = (len(A),len(B))  
    (C,i,j,k) = ([],0,0,0)  
    while k < m+n:  
        if i == m:  
            C.extend(B[j:])  
            k = k + (n-j)  
        elif j == n:  
            C.extend(A[i:])  
            k = k + (n-i)  
        elif A[i] < B[j]:  
            C.append(A[i])  
            (i,k) = (i+1,k+1)  
        else:  
            C.append(B[j])  
            (j,k) = (j+1,k+1)  
    return(C)
```

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise



# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise
  - Sort  $A[:n//2]$  into  $L$

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise
  - Sort  $A[:n//2]$  into  $L$
  - Sort  $A[n//2:]$  into  $R$

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise
  - Sort  $A[:n//2]$  into  $L$
  - Sort  $A[n//2:]$  into  $R$
  - Merge  $L$  and  $R$  into  $B$

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise
  - Sort  $A[:n//2]$  into  $L$
  - Sort  $A[n//2:]$  into  $R$
  - Merge  $L$  and  $R$  into  $B$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Summary

- Merge sort using divide and conquer to sort a list

# Summary

- Merge sort using divide and conquer to sort a list
- Divide the list into two halves

# Summary

- Merge sort using divide and conquer to sort a list
- Divide the list into two halves
- Sort each half

# Summary

- Merge sort using divide and conquer to sort a list
- Divide the list into two halves
- Sort each half
- Merge the sorted halves



# Summary

- Merge sort using divide and conquer to sort a list
- Divide the list into two halves
- Sort each half
- Merge the sorted halves
- Next, we have to check that the complexity is less than  $O(n^2)$

# Analysis of Merge Sort

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 2

# Merge sort

- To sort  $A$  into  $B$ , both of length  $n$
- If  $n \leq 1$ , nothing to be done
- Otherwise
  - Sort  $A[:n//2]$  into  $L$
  - Sort  $A[n//2:]$  into  $R$
  - Merge  $L$  and  $R$  into  $B$

## Merging two sorted lists $A$ and $B$ into $C$

- If  $A$  is empty, copy  $B$  into  $C$
- If  $B$  is empty, copy  $A$  into  $C$
- Otherwise, compare first elements of  $A$  and  $B$ 
  - Move the smaller of the two to  $C$
- Repeat till all elements of  $A$  and  $B$  have been moved

# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$

```
def merge(A,B):  
    (m,n) = (len(A),len(B))  
    (C,i,j,k) = ([],0,0,0)  
    while k < m+n:  
        if i == m:  
            C.extend(B[j:])  
            k = k + (n-j)  
        elif j == n:  
            C.extend(A[i:])  
            k = k + (n-i)  
        elif A[i] < B[j]:  
            C.append(A[i])  
            (i,k) = (i+1,k+1)  
        else:  
            C.append(B[j])  
            (j,k) = (j+1,k+1)  
    return(C)
```

# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$
- Output list  $C$  has length  $m + n$

```
def merge(A,B):
    (m,n) = (len(A),len(B))
    (C,i,j,k) = ([],0,0,0)
    while k < m+n:
        if i == m:
            C.extend(B[j:])
            k = k + (n-j)
        elif j == n:
            C.extend(A[i:])
            k = k + (n-i)
        elif A[i] < B[j]:
            C.append(A[i])
            (i,k) = (i+1,k+1)
        else:
            C.append(B[j])
            (j,k) = (j+1,k+1)
    return(C)
```

# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$
- Output list  $C$  has length  $m + n$
- In each iteration we add (at least) one element to  $C$

```
def merge(A,B):
    (m,n) = (len(A),len(B))
    (C,i,j,k) = ([],0,0,0)
    while k < m+n:
        if i == m:
            C.extend(B[j:])
            k = k + (n-j)
        elif j == n:
            C.extend(A[i:])
            k = k + (n-i)
        elif A[i] < B[j]:
            C.append(A[i])
            (i,k) = (i+1,k+1)
        else:
            C.append(B[j])
            (j,k) = (j+1,k+1)
    return(C)
```

# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$
- Output list  $C$  has length  $m + n$
- In each iteration we add (at least) one element to  $C$
- Hence `merge` takes time  $O(m + n)$

```
def merge(A,B):  
    (m,n) = (len(A),len(B))  
    (C,i,j,k) = ([],0,0,0)  
    while k < m+n:  
        if i == m:  
            C.extend(B[j:])  
            k = k + (n-j)  
        elif j == n:  
            C.extend(A[i:])  
            k = k + (n-i)  
        elif A[i] < B[j]:  
            C.append(A[i])  
            (i,k) = (i+1,k+1)  
        else:  
            C.append(B[j])  
            (j,k) = (j+1,k+1)  
    return(C)
```

# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$
- Output list  $C$  has length  $m + n$
- In each iteration we add (at least) one element to  $C$
- Hence `merge` takes time  $O(m + n)$
- Recall that  $m + n \leq 2(\max(m, n))$

```
def merge(A,B):
    (m,n) = (len(A),len(B))
    (C,i,j,k) = ([],0,0,0)
    while k < m+n:
        if i == m:
            C.extend(B[j:])
            k = k + (n-j)
        elif j == n:
            C.extend(A[i:])
            k = k + (n-i)
        elif A[i] < B[j]:
            C.append(A[i])
            (i,k) = (i+1,k+1)
        else:
            C.append(B[j])
            (j,k) = (j+1,k+1)
    return(C)
```



# Analysing merge

- Merge  $A$  of length  $m$ ,  $B$  of length  $n$
- Output list  $C$  has length  $m + n$
- In each iteration we add (at least) one element to  $C$
- Hence `merge` takes time  $O(m + n)$
- Recall that  $m + n \leq 2(\max(m, n))$
- If  $m \approx n$ , `merge` take time  $O(n)$

```
def merge(A,B):
    (m,n) = (len(A),len(B))
    (C,i,j,k) = ([],0,0,0)
    while k < m+n:
        if i == m:
            C.extend(B[j:])
            k = k + (n-j)
        elif j == n:
            C.extend(A[i:])
            k = k + (n-i)
        elif A[i] < B[j]:
            C.append(A[i])
            (i,k) = (i+1,k+1)
        else:
            C.append(B[j])
            (j,k) = (j+1,k+1)
    return(C)
```

# Analysing mergesort

- Let  $T(n)$  be the time taken for input of size  $n$ 
  - For simplicity, assume  $n = 2^k$  for some  $k$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

- Let  $T(n)$  be the time taken for input of size  $n$ 
  - For simplicity, assume  $n = 2^k$  for some  $k$
- Recurrence
  - $T(0) = T(1) = 1$
  - $T(n) = 2T(n/2) + n$ 
    - Solve two subproblems of size  $n/2$
    - Merge the solutions in time  $n/2 + n/2 = n$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

- Let  $T(n)$  be the time taken for input of size  $n$ 
  - For simplicity, assume  $n = 2^k$  for some  $k$
- Recurrence
  - $T(0) = T(1) = 1$
  - $T(n) = 2T(n/2) + n$ 
    - Solve two subproblems of size  $n/2$
    - Merge the solutions in time  $n/2 + n/2 = n$
- Unwind the recurrence to solve

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$
- $T(n) = 2T(n/2) + n$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$
- $T(n) = 2T(n/2) + n$   
 $= 2[2T(n/4) + n/2] + n$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

$$\begin{aligned}\text{■ } T(n) &= 2T(n/2) + n \\ &= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n\end{aligned}$$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```



# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

$$\begin{aligned}\text{■ } T(n) &= 2T(n/2) + n \\ &= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n \\ &= 2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n\end{aligned}$$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

$$\begin{aligned}\text{■ } T(n) &= 2T(n/2) + n \\ &= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n \\ &= 2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n \\ &\quad \vdots \\ &= 2^k T(n/2^k) + kn\end{aligned}$$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

$$\begin{aligned}\text{■ } T(n) &= 2T(n/2) + n \\ &= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n \\ &= 2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n \\ &\quad \vdots \\ &= 2^k T(n/2^k) + kn\end{aligned}$$

- When  $k = \log n$ ,  $T(n/2^k) = T(1) = 1$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$

- $T(n) = 2T(n/2) + n$

- $T(n) = 2T(n/2) + n$

$$= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n$$

$$= 2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n$$

$$\vdots$$

$$= 2^k T(n/2^k) + kn$$

- When  $k = \log n$ ,  $T(n/2^k) = T(1) = 1$

- $T(n) = 2^{\log n} T(1) + (\log n)n = n + n \log n$

```
def mergesort(A):
```

```
    n = len(A)
```

```
    if n <= 1:
```

```
        return(A)
```

```
    L = mergesort(A[:n//2])
```

```
    R = mergesort(A[n//2:])
```

```
    B = merge(L,R)
```

```
    return(B)
```

# Analysing mergesort

## ■ Recurrence

- $T(0) = T(1) = 1$
- $T(n) = 2T(n/2) + n$

$$\begin{aligned}\text{■ } T(n) &= 2T(n/2) + n \\ &= 2[2T(n/4) + n/2] + n = 2^2 T(n/2^2) + 2n \\ &= 2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n \\ &\vdots \\ &= 2^k T(n/2^k) + kn\end{aligned}$$

- When  $k = \log n$ ,  $T(n/2^k) = T(1) = 1$
- $T(n) = 2^{\log n} T(1) + (\log n)n = n + n \log n$
- Hence  $T(n)$  is  $O(n \log n)$

```
def mergesort(A):  
    n = len(A)  
  
    if n <= 1:  
        return(A)  
  
    L = mergesort(A[:n//2])  
    R = mergesort(A[n//2:])  
  
    B = merge(L,R)  
  
    return(B)
```

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible
  - Union of two sorted lists — discard duplicates, if  $A[i] == B[j]$  move just one copy to  $C$  and increment both  $i$  and  $j$



# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible
  - Union of two sorted lists — discard duplicates, if  $A[i] == B[j]$  move just one copy to  $C$  and increment both  $i$  and  $j$
  - Intersection of two sorted lists — when  $A[i] == B[j]$ , move one copy to  $C$ , otherwise discard the smaller of  $A[i]$ ,  $B[j]$

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible
  - Union of two sorted lists — discard duplicates, if  $A[i] == B[j]$  move just one copy to  $C$  and increment both  $i$  and  $j$
  - Intersection of two sorted lists — when  $A[i] == B[j]$ , move one copy to  $C$ , otherwise discard the smaller of  $A[i]$ ,  $B[j]$
  - List difference — elements in  $A$  but not in  $B$

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible
  - Union of two sorted lists — discard duplicates, if  $A[i] == B[j]$  move just one copy to  $C$  and increment both  $i$  and  $j$
  - Intersection of two sorted lists — when  $A[i] == B[j]$ , move one copy to  $C$ , otherwise discard the smaller of  $A[i]$ ,  $B[j]$
  - List difference — elements in  $A$  but not in  $B$
- Merge needs to create a new list to hold the merged elements
  - No obvious way to efficiently merge two lists in place
  - Extra storage can be costly

# Summary

- Merge sort takes time  $O(n \log n)$  so can be used effectively on large inputs
- Variations on merge are possible
  - Union of two sorted lists — discard duplicates, if  $A[i] == B[j]$  move just one copy to  $C$  and increment both  $i$  and  $j$
  - Intersection of two sorted lists — when  $A[i] == B[j]$ , move one copy to  $C$ , otherwise discard the smaller of  $A[i]$ ,  $B[j]$
  - List difference — elements in  $A$  but not in  $B$
- Merge needs to create a new list to hold the merged elements
  - No obvious way to efficiently merge two lists in place
  - Extra storage can be costly
- Inherently recursive
  - Recursive calls and returns are expensive