

Click for Update

VER. 24.5.16 by Flyingdeuk

Domestic

<u>Japan</u>

China

S.E Asia(GUM)

Supplement

FUEL Consumption

NO Engine Bleed

GND Air / Cross Bleed

Cold Temp Correction

Cold Wx Operation

ENG ON Deicing ENG OFFDeicing

Domestic

GMP CJU

GMP PUS

CJU KWJ

CJU CJJ

CJU TAE

CJU TAE

CJU PUS

ICN PUS

ICN TAE

Welcome PA

Next Page

Home

저는 기장 입니다. 저희 대한항공을 이용해 주셔서 대단히 감사합니다 (국제)공항까지 비행시간은 시간 분 으로 예상됩니다.

비행 중에는 항공기가 갑자기 흔들릴 수도 있으니. 자리에 않아 계실 때에는 항상 좌석벨트를

WELCOME PA

손님 여러분, 안녕하십니까?

매주시기 바랍니다.

저는 여러분을 안전하게 모시기 위해 최선을 다하겠습니다. 감사한니다.

Good morning (afternoon /evening), ladies and gentlemen.

This is captain last name speaking. Welcome aboard Korean Air.

This flight is bound for (international) airport and our flight time is ____ hours(s) and minutes. For your safety, keep your seatbelts fastened

while you are seated. Thank you for choosing Koreanair. Please enjoy the flight.

Domestic

서울/김포국제

서울/인천국제 제주국제 부산/김해국제

CII KWI TAF

GMP

ICN CJU

PUS

광주 대구국제

Home Domestic Next Page

청주국제

출발저 기준 2200-0800 Quiet Hour 손님 여러분, 저는 기장입니다. 우리 비행기는 앞으로 약 (40)분 후에

현재 공항의 날씨는 ◐___, 기온은 섭씨 모입니다.

◐ 눈이 오고 있으며

● 황사가 있으며

아개가 끼어 있으며

도착 방송 (5시간이상, 40분전)

국제공항에 착륙 예정입니다.

● (이슬)비가 내리며/소나기가 내리며

◐ 맑으며

❶ (다소)흐리며

(40) minutes.

D 바람이 불고 있으며

The current temperature at ___ is __ degrees Celsius, or __ degrees Fahrenheit $(\mathsf{OPT} \, ^ \text{삼고})$ and it is \mathbb{O} ___.

감사합니다.

Ladies and gentlemen, this is <u>the</u> captain speaking.

We expect to land at ___international airport in about

지금 이곳의 시각은 __월 __일 __요일, 오전(오후) __시 __분 입니다. 강사합니다.

(mostly) clear
 (partly) cloudy
 drizzling / raining
 windy
 snowing
 foggy
 hazy or smoggy

The current time is __ : __ a.m(p.m), on (day-of-the-

Thank you for flying with us today.

week), (month)(date).

omestic

Japan GMP

KIX

NRT

KIX

HND

NGO

ICN NRT

PUS

ICN

ICN

ICN

ICN FUK
ICN AOJ

<u>ome</u>

Welcome PA

Next Page

____ ..., __ 입니다. 저는 기장 ___입니다. 저희 대한항공을 이용해 주셔서 대단히 감사합니다 (국제)공항까지 비행시간은 시간 분

손님 여러분 안녕하십니까?

WELCOME PA

으로 예상됩니다.

비행 중에는 항공기가 갑자기 흔들릴 수도 있으니, 자리에 않아 계실 때에는 항상 좌석벨트를 매주시기 바랍니다.

저는 여러분을 안전하게 모시기 위해 최선을 다하겠습니다. 강사한니다.

Good morning (afternoon /evening), ladies and gentlemen.
This is captain <u>last name</u> speaking.
Welcome aboard Korean Air.

This is captain <u>last name</u> speaking.

Welcome aboard Korean Air.

This flight is bound for ___(international) airport and our flight time is ___ hours(s) and minutes.

minutes.
For your safety, keep your seatbelts fastened while you are seated.
Thank you for choosing Koreanair.

Thank you for choosing Koreanair. Please enjoy the flight.							
	Japan						
KIX	오사카/간사이						
HND	도쿄/하네다						
NRT	도쿄/나리타						

삿포로/신(NEW) 치토세

NGO 나고야/주부(Centera) FUK 후쿠오카 AOJ 아오모리

CTS

China							
<u>GMP</u>	<u>SHA</u>						
GMP	PEK						
<u>CJU</u>	<u>PEK</u>						
<u>PUS</u>	PVG						
<u>ICN</u>	<u>NKG</u>						
<u>ICN</u>	<u>TAO</u>						
<u>ICN</u>	<u>PEK</u>						
<u>ICN</u>	<u>SHE</u>						
<u>ICN</u>	<u>PVG</u>						
<u>ICN</u>	<u>YNJ</u>						
<u>ICN</u>	<u>HGH</u>						
<u>ICN</u>	<u>WHE</u>						
<u>ICN</u>	XIY						
<u>ICN</u>	CSX						
<u>ICN</u>	<u>HKG</u>						
<u>ICN</u>	<u>TSN</u>						
<u>ICN</u>	<u>CGO</u>						
<u>ICN</u>	DYG						
Home							

손님 여러분, 안녕하십니까? 저는 기장 ___입니다. 저희 대한항공을 이용해 주셔서 대단히 감사합니다 (국제)고하까지 비해시가요 시가 보으로

저희 대한항공을 이용해 주셔서 대단히 감사합니다 ___ (국제)공항까지 비행시간은 ___시간 __분 으로 예상됩니다.

예상됩니다. 비행 중에는 항공기가 갑자기 흔들릴 수도 있으니, 자리에 않아 계실 때에는 항상 좌석벨트를 매주시기 바랍니다.

저는 여러분을 안전하게 모시기 위해 최선을 다하겠습니다. 감사합니다. Good morning (afternoon (ovening) ladies and

Good morning (afternoon /evening), ladies and gentlemen.

This is captain <u>last name</u> speaking.

Welcome aboard Korean Air.
This flight is bound for ___(international) airport
and our flight time is ___ hours(s) and minutes.
For your safety, keep your seatbelts fastened

while you are seated. Thank you for choosing Koreanair. Please enjoy the flight

WELCOME PA

16	lease enjoy the night.								
		China							
	SHA	상하이/홍차오							
	NKG	난징/루커우							
	TAO	칭다오/자오동							
	PEK	베이징/소우뚜(캐피털)							
	SHE	선양/탸오쎈							
	PVG	상하이/푸동							
	YNJ	옌지/차오양촨							
	HGH	황저우/샤오산							
	WHE	웨이하이/따쉐이푸오							
	XIY	시안/시엔양							
	CSX	창사/후앙후아							
	HKG	홍콩							
	TSN	톈진/빈하이							
	CGO	정저우/신정							
	DYG	장자제/허화							

<u>China</u>

S.E Asia

CXR

SGN

PNH

MNL

TPE

TPE

BKK

ICN

ICN

ICN

ICN

ICN RMQ

ICN DUS

PUS ICN

PUS

Welcome PA

Next Page

ome

손님 여러분, 안녕하십니까? 저는 기장 입니다.

WELCOME PA

저희 대한화공을 이용해 주셔서 대단히 감사합니다 ___ (국제)공항까지 비행시간은 ___시간 ___분 으로 예상됩니다.

으로 예상됩니다. 비행 중에는 항공기가 갑자기 흔들릴 수도 있으니, 자리에 않아 계실 때에는 항상 좌석벨트를 매주시기 바랍니다. 저는 여러분을 안전하게 모시기 위해 최선을

다하겠습니다. 감사합니다. Good morning (afternoon /evening), ladies and gentlemen.

This is captain <u>last name</u> speaking.

Welcome aboard Korean Air.

This flight is bound for ____(international)

This flight is bound for ___(international) airport and our flight time is ___ hours(s) and minutes.

For your safety, keep your seatbelts fastened

while you are seated.
Thank you for choosing Koreanair.
Please enjoy the flight.

•	rease enjoy the manti							
		S.E Asia						
	CXR	베트남 나짱/깜라인						
	SGN	베트남 호찌민/탄소넛						
	PNH	캄보디아 프놈펜						
	MNL	필리핀 마닐라/니노이 아키노						
	TPE	타이완/타이페이 타오유엔						
	RMQ	타이완/타이중 칭찬강						
		괌						
	BKK	방콕/수완나폼						



현재 공항의 날씨는 ◐___, 기온은 섭씨 __도 입니다. ① 맑으며 ○ (다소)흐리며 ○ (이슬)비가 내리며/소나기가 내리며 ○ 바람이 불고 있으며 ○ 바람이 불고 있으며 지금 이곳의 시각은 __월 __일 __요일, 오전(오후) __시 __분 입니다. 감사합니다. Ladies and gentlemen, this is the captain speaking. We expect to land at __ international airport in about (40) minutes. The current temperature at is degrees Celsius,

or degrees Fahrenheit (OPT 참고)

and it is **①** .

도착 방송 (5시간이상, 40분전)

손님 여러분, 저는 기장입니다. 우리 비행기는 앞으로 약 (40)분 후에 국제공항에 착륙 예정입니다.

(mostly) clear
 (partly) cloudy
 drizzling / raining
 windy
 snowing
 foggy
 hazy or smoggy

The current time is __ : __ a.m(p.m), on (day-of-the-

Thank you for flying with us today.

week), (month)(date).

E Asia

RKSS(GMP) 59ft RKPC(CJU) 119ft KE GMP 131.15 DCL -15분 가능 TOBT 5분 차이 KF CIU 129.4 시 CTC Comm Rwv 32R Takeoff (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) GMP: SID (NADP 1) BUILTI xT 324 324 5000 324 32L/R 324 324 5000 (BULTI xO) 324 BULTI xU 144 144 6000 144 14L/R (BULTI xZ) 144 144 6000 144 KIP 32L 32R 141 14R

110.7

113.6 108.3 32L/R: EO32L/R. R225 YIU R271

32L(41')

32R(42')

109.9 14L/R: EO14L/R. R220 P73 /2

108.7

14R(34')

14L(38')

APRON(130.875) -> GND(121.9) -> TWR (All by ATC)

HUD

10499

11811'

Domestic CJU: STAR

AFT Merge PT(220kts) DCT IAF(210kts), FAF (160kts)

DOTOL xP YUMIN **DOTOL 160**

ILS Z 07

ILS Z 25 DOTOL xT DUKAL DOTOL/-10 160

25(76') HUD 07(87') 10433'

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO)

25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)

Entering Rapid TWY CTC GND 121.675 (STOP x) HST 40KTS

RKPC(CJU) 119ft RKSS(GMP) 59ft **PA** KE GMP 131.15 **KE CJU 129.4** DCI -10분 **Rwy 32L Landing** (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) CJU: SID (NADP 1)

07	KAMIT	06	6		
25	KAMIT x	w	246		
YDM	109.0		07 1	109.9	
		25			

10000 066 246

10000 246 25 111.3 25: YDM246/3, R290 25(76')

066

07(87') 10433' 07: Passing G4 CTC TWR 109.0 YDM RKPC

TC TWR	

CRS-290 D3 YDM **GMP: STAR** ILS 32L/R OLMEN xT BUMSI

Domestic

OLMEN 160

OLMEN 160

14R(34')

14L(38')

OLMEN xU

32L(41')

32R(42')

32L: D3(6532'), E2(9117'), 32R: E1(6614')

32L/R: 8 KIP L/G, 14R: LOC CAPT L/G

TWR -> GND -> APRON (All by ATC) Except RWY14R Landing (Until R)

DOKDO

10499'

11811'

KIP /8(RWY 32), YJU R271, P73 /2

ILS 14R

HUD

14R: C1(6578')

FAF: Final Flap

- 25: 31 Holding PSN on P, E1,2,3 C
- HUD

RKSS(GMP) 59ft RKPK(PUS) 13ft KE GMP 131.15 DCL -15분 가능 TOBT 5분 차이 **PA** KE Gimhae 129.2 KE GMP 131.15 시 CTC Comm Rwv 32R Takeoff (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) GMP: SID (NADP 1) **OSPOT xT** 324 324 5000 324 32L/R (OSPOT xQ) 324 324 5000 324 OSPOT xU 144 144 6000 144 14L/R (OSPOT xZ) 144 144 6000 144 **KIP** 32L 32R 14L 14R 109.9 113.6 108.3 110.7 108.7 14L/R: EO14L/R, R220 32L/R: EO32L/R, R225 YIU R271 P73 /2 32L(41') 10499' 14R(34') HUD 32R(42') 11811' 14L(38') APRON(130.875) -> GND(121.9) -> TWR (All by ATC) Domestic

PUS: STAR (Tail Wind 36R 136000lbs F40)

9DME LG. 8DME FLAP

18 Circling Click!!

18R(13') 8530'

18L(13') 8999'

18: KMH R284, R280

MASTA

MASTA

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

ILS 36

VOR 18

HUD

KFVOX x

GAYHA x

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9. /8

RKPK(PUS) 13ft | RKSS(GMP) 59ft KE Gimhae 129.2 KE GMP 131.15 DCL -5분 **Rwy 32L Landing** (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) PUS: SID (Mod NADP CLB2 1000, 14000 MAX) SOORO x 306 280 36 ATC 342 KALOD tx

182

KMH 113	PSN 114.0	
	6 : KMH R09	
HUD	:	36L(13') 104 36R(8') 899
RWY36	400°	ft Man L/H t
433, 6 8	5	3093,

GIMHAF x

18

1, R271, R185 99' 18R(13') 8530' q, 18L(13') 8999' urn. Max Taxi SPD 20KTS

182

36L 108.5

5000

182

36R 109.5

KMH R-091 113.8 KMH **GMP: STAR**

Domestic **GUKDO xT** ILS 32L/R BUMSI **GUKDO 160**

ILS 14R

GUKDO xU

DOKDO

10499'

32L(41') HUD 32R(42')

GUKDO 160

14R(34')

11811'

14L(38')

KIP /8(RWY 32), YJU R271, P73 /2

32L: D3(6532'), E2(9117'), 32R: E1(6614') 14R: C1(6578')

32L/R: 8 KIP L/G, 14R: LOC CAPT L/G FAF: Final Flap

TWR -> GND -> APRON (All by ATC) Except RWY14R Landing (Until R)



End of RWY Vacating 9301'

LOC 22L, VOR 22L/R -> LOC/VOR LNAV 지시고도 유지후

TAXI MAX 15 kts (Max 30kts by ATC)

Final Establish 이후 강하 (TERR!!) PAR 04L/R. 22R 가능 : 강하각 3도 (6NM. 3도) RKJJ(KWJ) 48ft | RKPC(CJU) 119ft PA KF KWI 129.4 **KF CILI 129 4** NO DCI KWJ: SID (NADP 1) DALSU - Y711 - DOTOL Comm RTE(ATC CLR) 확인! (Join Air Way - DCT DOTOL CRS 192- LNAV) KWA 5 ALL 8000 041 (GWJ 3) 038 በ3ጸ **ATC** กรร (GWJ 4) 22R 218 218 **ATC** 218 **KWA 114.4** 04R 111.1 22L 108.5 04: KWA /4.5, R225 22 · None 04L(46') 9301' 22R(48') HUD 04R(46') 9301' 22L(48') Taxi SPD MAX 15kts MAX 30kts by ATC A147 B 114.4 KWA Domestic CJU: STAR

AFT Merge PT(220kts) DCT IAF(210kts), FAF (160kts)

YUMIN

DUKAL

10433'

DOTOL 160

DOTOL/-10 160

25(76')

ILS Z 07

ILS Z 25

HUD

DOTOL xP

DOTOL xT

07(87')

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO)
25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)
Entering Rapid TWY CTC GND 121.675 (STOP x)
HST 40KTS

RKPC(CJU) 119ft RKTU(CJJ) 192ft KE CJJ 129.05 KE CJU 129.4 DCL -10분 NO DCL. ATIS CJU: SID (NADP 1) 07 KAMIT xF 066 066 10000 066 25 KAMIT xW 246 246 10000 246 07 109.9 25 111.3 YDM 109.0 07: NONE 25: YDM246/3, R290 HUD 07(87') 10433' 25(76') 07: Passing G4 CTC TWR 25: 31 Holding PSN on P. E1.2.3 CTC TWR D 109.0 YDM RKPC CRS-290 Domestic D3 YDM CJJ: NO STAR After OSPOT H/D060 - RDR Vector **TU761 / BAKJO NO STAR** OSPOT II S 7 061 (STAR 안줌) (MATIZ x) (JIKJI tx) NO STAR OSPOT HYFIN

ILS Z 24R

(MATIZ x) (HYEIN tx) (STAR 안줌)

GS fluc' - A/P Dis' - Back to Normal - A/P Reengage Reg full length Landing (Vacate End of RWY) 180 BACK LINE 지나 Taxi Line 있음

Entering TWY A3, B3, B4, C3, D3 change GND freq

9003'

9003'

24R(182')

24L(191')

06L(166')

06R(173')

06L: B3 (6443'), A3 (8786') 24R: C3 (6230'), D3 (8825')

HUD



DOTOL 160

DOTOL/-10 160

25(76')

Domestic

07(87')

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO) 25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)

DOTOL xP

DOTOL xT

ILS Z 07

ILS Z 25

HUD

AFT Merge PT(220kts) DCT IAF(210kts), FAF (160kts)

YUMIN

DUKAL

Entering Rapid TWY CTC GND 121.675 (STOP x) HST 40KTS

CJU: STAR

10433'

KF CIU 129.4 KF TAF 129 2 DCL -10분 CJU: SID (NADP 1) 07 AKPON xF 066 066 9000 066 25 **AKPON xW** 246 246 **ATC** 246 YDM 109.0 07 109.9 25 111.3 07: NONE 25: YDM246/3, R290 HUD 07(87') 10433' 25(77') 07: Passing G4 CTC TWR 25: 31 Holding PSN on P. E1.2.3 CTC TWR D 109.0 YDM

RKPC(CJU) 119ft RKTN(TAE) 120ft

Domestic

D3 YDM

TAE: NO STAR (TL 140 확인)

31L(118') 9039'

TGU/-10

TGU/-10

CRS-290

ILS 31L

ILS 13R

HUD 31R(120')

YAWAN

CF31L

CF31L222/7

RKPC

13R(111') 3.3

8999'

13L(112')

31L: D1(8848'), 13R: A1(8772')

13R ILS 3.3도 PAPI 3.3도 (산악지형 주의)

TAXI MAX 20kts (do not reg) 최소 2000ft 간격

RKTN(TAE) 120ft RKPC(CJU) 119ft KF TAF 129.2 KF CILI 129 4 NO DCL TAE: SID (NADP 1) 31L/R DAFGU xD 312 312 8000 192 13L/R DAEGU xD 132 132 192 2000 DOC 116.5 **TGU 112.2** 31L 108.7 13R 108.7 31: DOC 245/11 13: TGU076/17 DOC R245 **TGU R076** 31L(118') 13R(112') 3.3 9039' HUD 31R(120') 8999' 13L(112') TAXI MAX 20kts (do not reg) 최소 2000ft 간격 116.5 DOC Domestic

CJU: STAR

AFT Merge PT(220kts) DCT IAF(210kts), FAF (160kts)

ILS Z 07 UPGOS xP YUMIN **ILS Z 25 UPGOS xT** DUKAL

HUD 07(87') 10433' 25(76')

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO)

25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)

Entering Rapid TWY CTC GND 121.675, STOP X

HST 40KTS

PA KE Gimhae 129.2 DCL -10분 CJU: SID (NADP 1) 066 07 AKPON xF 066 066 9000 246 246 246 25 **AKPON xW ATC** 07 109.9 YDM 109.0 25 111.3 07: NONE 25: YDM246/3, R290

RKPC(CJU) 119ft RKPK(PUS) 13ft

HUD 07(87') 10433' 07: Passing G4 CTC TWR 25: 31 Holding PSN on P. E1.2.3 CTC TWR D 109.0 YDM RKPC

CRS-290

KF CIU 129.4

25(76')

Domestic

PUS: STAR (Tail Wind 36R 136000lbs F40)

D3 YDM

ILS 36 KEVOX x ANROD

9DME LG, 8DME FLAP

VOR 18 GAYHA x ANROD 18 Circling Click!!

36L(13') 10499' 18R(13') 8530'

HUD 36R(8') 8999' 18L(13') 8999'

36: IKMA/IKHE /9, /8 18: KMH R284, R280

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339')

18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792')

Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

PUS: SID (Mod NADP CLB2 1000, 14000 MAX) SOORO x 36 306 280 ATC 279 TOPAX tx BUILIM x 18 182 182 5000 182 **FNGOT tx** 36R 109.5 **KMH 113.8 PSN 114.0** 36L 108.5 36: KMH R091, R271, R185

RKPK(PUS) 13ft RKPC(CJU) 119ft PA

KF CILI 129 4

36L(13') 10499' 18R(13') 8530' HUD 36R(8') 8999' 18L(13') 8999' RWY36 400ft Man L/H turn, Max Taxi SPD 20KTS



KE Gimhae 129.2

DCL -5분

Domestic

25(76')

CJU: STAR

AFT Merge PT(220kts) DCT IAF(210kts), FAF (160kts)

10433'

ILS Z 07 UPGOS xP YUMIN **ILS Z 25 UPGOS xT** DUKAL

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO)

07(87')

HUD

25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)

Entering Rapid TWY CTC GND 121.675, STOP X HST 40KTS

RKSI(ICN) 23ft RKPK(PUS) 13ft										
KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm										
1	ICN : SID (33/34 NADP 1, 15/16 NADP 2)									
33L/R	OSP xE/		333		333		5500 ATO	•	333	
34L/R	OSPO	T xY	3	33	3	33	ATO	2	333	
15L/R	OSPO	ТхС	1	53	1	53	500	0	153	
16L/R	OSPO	T xH	1	53	1	53	500	0	153	
NC 113		33L 109.3		33R 108.9		15L 111.9		15R 109.1		
WN 112		34L 109.95		34R 108.1		16L 110.35		16R 108.55		
	: NC05L YJU R27		34L/R : EO34L/R, R24 YJU R271				242			
HUD	33L/R	34L(2	3′)	12303′ 15			5L/R 16R(23')			
пор	34R (23')			13123′ 16L (2			(23')	23')		
Р	arallel	TWY 1	LOKTS	이싱	(R1	7 MA	X 15k	ts)	1	
ICN 국제선 이후 TRANSIT GD 필요(팀장님) -> PUS PASSPORT Immigration 해야함. Domestic										
P	US : ST	AR (T	iil W	ind 36	6R 1	3600	Olbs F	40)	
ILS 36	KEVC	X X	MA	STA	9D	ME L	G, 8D	M	E FLAP	

MASTA

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only, Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

18 Circling Click!!

18R(13') 8530'

18L(13') 8999'

18: KMH R284, R280

VOR 18

HUD

GAYHA x

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9, /8

RKP	((PU	S) 13	ft	RK	SI(IC	<u>N</u>) 2:	3ft
KE G	Simhae DCL -5	e 129.2 분	PA	7	KE ICN	V 1	31.5	
PUS	: SID (Mod NA	DP CLE	2 10	000, 14	000	MAX	X)
36	36 SOORO x KALOD tx		306		280	ATO		342
18	GIMHAE x		182		182		000	182
KMH 1	KMH 113.8 PSN 1			36	5L 108.	5	36R	109.5
	3	6 : KMH	R091,	R27:	1, R185	,		
HUD		36L(13') 36R(8')) 10499' 18R(13') 8530) 8999' 18L(13') 8999					
RWY	36 400	ft Man I	L/H turr	n, M	ax Taxi	SP	D 20k	KTS
					D.		106	49 -

Domestic **ICN: STAR**

ENPIL

MUNAN

12303'

13123'

GUKDO 180

GUKDO 180 15L/R

16R(23')

16L(23')

GUKDO xE

GUKDO xH

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7463'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

ILS 33/34

ILS 15/16

HUD

RKSI(ICN) 23ft RKTN(TAE)120ft										
KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm										
ı	CN : SII) (33/	34 N	ADP 1	, 15	/16	NADP	2)		
33L/R	OSP xE/		3	33	3	33	5500 ATO	•	333	
34L/R	OSPO	T xY	3	33	3	33	ATO	2	333	
15L/R	OSPO	ТхС	1	53	1	53	500	0	153	
16L/R	OSPO	TxH	1	53	1	.53	500	0	153	
NC 113		33 109		33R 108.9		15L 111.9		15R 109.1		
WN 112		34 109	_	34R 108.1		16L 110.35		1	16R 108.55	
	: NC05L YJU R2		42 34L/R : EO34L/R, R242 YJU R271							
HUD	33L/R	33L/R 34L(23')			3'	15L,	/R 16I	₹(2	3′)	
НОО	34R (2	34R (23')			13123' 16L (2					
Р	arallel	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)		
<u>Domestic</u>										
	TA	AE : NO	O STA	AR (TL	. 140	9 확인	<u>Pl)</u>			
ILS 31L	T	GU/-1	0	CF	31L	222/	7	CF	31L	
ILS 13R		TGU		١	ſΑW	/AN				
HUE		31L(118')			9039	9'	13R(11:	1′) 3.3	

31R(120')

13R ILS 3.3도 PAPI 3.3도 (산악지형 주의) TAXI MAX 20kts (do not req) 최소 2000ft 간격

31L: D1(8848'), 13R: A1(8772')

8999'

13L(112')

RKTN	RKSI(ICN) 23ft								
KE	KE TAE 129.2 NO DCL					A KE ICN 131.5			
TAE : SID (NADP 1)									
31L/R	DAEC	GU xD	312	312	2	800	0	192	
13L/R	DAEC	GU xD	132	132	2	800	0	192	
DOC 1	16.5	TGU	112.2	311	. 108	3.7	13	R 108.7	
	: DOC : DOC R	245/11 245		1		GU0 GU R(•	L7	
- IIIID	3	31L(118	')	9039	,	13R	(112	2′) 3.3	
HUD	3	31R(120)')	8999	,	1	3L(1	12')	
TAXI MA	XX 20kt	ts (do n	ot req) 최소	2000	Oft 긴	·격		
50 (11.8 FOC	111 SOC (112 TOU) 112 TOU								
			ICN:	STAR					
ILS 33/3	34	GUKDO) xE	El	NPIL	•	GUK	DO 180	
ILS 15/1	16	GUKDO) xH	MU	JNA	N (GUK	DO 180	
HUD	33	3L/R 34	L(23')	12	303	,		5L/R R(23')	
		34R(2	3′)	13	123	,	16	L(23')	
FIX	RW	/Y /8, /!	5 , YJU	R271					
33R : C4(7529'), C5(8513'), 33L : B4(7463'), B5(8513')									

15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641')
34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507')
16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')
8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKPK(PUS) 13ft RJAA(NRT) 135ft											
KE Gimhae 129.2 PA KE Tokyo 131.7											
PUS : SID (Mod NADP CLB2 1000, 14000 MAX)											
36		ORO x SN tx	30	06	280	ATC	162				
18		JLIM x SN tx	18	32	182	5000	182				
KMH 1	13.8	PSN 1	L14.0		36L 108.	36R	109.5				
		36 : KMH	R09	1, R2	71, R185						
HUD		36L(13') 36R(8')				R(13') 85 .(13') 89					
RWY	36 40	00ft Man	L/H t	urn, l	Max Taxi	SPD 201	(TS				
DEP 12 FUK 13	DEP 125.5 – TGU 125.37 FUK 133.15 – TKO 133.8 – 133.02 – 132.45 – 124.1 TKO 128.2 – TKO APP 124.4										
NRT H		330,YAG Prepare H					150				
34L/		SWAM (SWAM	P E	E	LGAR YLER)	ILS 341	L/R(Z)				
16L/	R	SWAMI			EMIN ORMA)	ILS Z 1	L6L/R				
HUE	,	16L(13	5')	8	3202'	34R(141′)				
1102		16R(13	0')	1	3123′	34L(1	139')				
16L: ITM 4 / 34R: ITJ 14, 4 (DME) 16R: IKF 4 / 34L: IYQ 12, 4 (DME)											
16L : B6(6433'), B7(7017'), 34R : B4(5849'), B2(6778') 16R : A6(6076'), A7(7624'), 34L : A5(6167'), A4(7641')											
L/D DOWN before 14/12 DME, L/D FLAP 4 DME Arrival Taxi RTE in Jeppesen (No Numbering)											

RJAA(NRT) 135ft RKPK(PUS) 13ft PA KE Gimhae 129.2 KE Tokvo 131.70 DCL -15분 NRT: SID - ENPAR tx (NADP 1) 16L/R 157 157 **ATC** 157 TFTRA x ENPAR tx 337 34L/R 337 7000/ATC 337 NRF 16L 16R 34L **34R** 111.9 117.9 110.7 111.5 110.9 16L(135') 8202' 34R(141') HUD 16R (130') 13123 34L (139') 34R: CLB 220/10000, A4R21/22/23 220KTS 확인 Verity ENPAR tx TETRA 12000A APU Start, TAXI RTE 1, 2, 3, 4 RWY 별 DEP RTE **DEP 124.2** TKO 120.5 - 133.45 - 133.02 - 133.8 FUK 133.15 TGU 125.37 Japan APP 125.5 PUS: STAR (Tail Wind 36R 136000lbs F40) 9DME LG. 8DME FLAP **ILS 36** PEDLO x KALFK **VOR 18 GAYHA** x **PSN** 18 Circling Click!! 36L(13') 10499' 18R(13') 8530' HUD 36R(8') 8999' 18L(13') 8999'

36: IKMA/IKHE /9, /8

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

18: KMH R284, R280

RKSI(ICN) 23ft RKPK(PUS) 13ft							<u>13ft</u>		
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm									
ا	ICN : SII) (33/	34 N.	ADP 1	l, 15	/16	NADP	2)	
33L/R	OSPOT xE/A		333		333		5500/ ATC		333
34L/R	OSPO	ΤxΥ	3	33	3	33	ATC		333
15L/R	OSPO	T xC 1		53	153		5000		153
16L/R	OSPO	TxH 1		53	153		5000		153
	NCN 113.8		L).3	33R 108.9		_	5L 1.9		15R 109.1
WN 112		34 109	_	34 108		_	.6L 0.35		16R 108.55
33L/R	: NC05L YJU R27		42	34L/R : EO34L/R, R242 YJU R271					
HUD	33L/R	34L(2	3′)	1230	3' 15L		/R 16R(23')		
нор	34R (23')			1312	23'	16L	(23')		
Parallel TWY 10KTS 이상(R17 MAX 15kts)									
						D.			-4 : -
						Ν)M(US	<u>stic</u>

PUS: STAR (Tail Wind 36R 136000lbs F40)

MASTA

MASTA

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only, Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9, /8

ILS 36

VOR 18

HUD

KEVOX x

GAYHA x

9DME LG. 8DME FLAP

18 Circling Click!!

18R(13') 8530'

18L(13') 8999'

18: KMH R284, R280

RKP	((PU	S) 13	ft	RKSI(ICN) 23ft						
KE G	Simhae DCL -5	e 129.2 분	PA	7	KE ICN	V 1	31.5			
PUS	: SID (Mod NA	DP CLE	2 10	000, 14	000	MAX	X)		
36	SOORO x KALOD tx		306		280		ATC	342		
18	GIM	GIMHAE x			182	5000		182		
KMH 113.8 PSN 1			L14.0	36	5L 108.	5	36R	109.5		
	3	6 : KMH	R091,	R27:	1, R185	,				
HUD	HUD 36L(13')						18R(13') 8530' 18L(13') 8999'			
RWY	36 400	ft Man I	L/H turr	n, M	ax Taxi	SP	D 20k	KTS		
					D.		106	49 -		

Domestic **ICN: STAR**

ENPIL

MUNAN

12303'

13123'

GUKDO 180

GUKDO 180 15L/R

16R(23')

16L(23')

GUKDO xE

GUKDO xH

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7463'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

ILS 33/34

ILS 15/16

HUD

RKSI(ICN) 23ft RJBB(KIX) 17ft										
KE ICN 131.5 DCL-10분 TOBT 5분차이시 CTC Comm										
ICN : SID (33/34 NADP 1, 15/16 NADP 2)										
33L/R		OBA /A	333		333		5500/ ATC		333	
34L/R	EGOI	ЗА хҮ	3	33	3	33	ATC		333	
15L/R	EGO	ЗА хС	1	53	1	53	5000	0	153	
16L/R	EGO	BA xH	1	53	1	53	5000)	153	
NC 113		33l 109.			33R 108.9		15L 111.9		15R 109.1	
	VNG 34		_		34R 108.1		16L 110.35		16R 108.55	
33L/R : NC05L/R, R242 34L/R : EO34/R, R242 YJU R271 YJU R271									242	
	R 34L(23')		1230	12303' 15L		/R 16F	₹(2	23')		
HUD	34R (2	23')	13123′ 1			16L	16L (23')			
DEP 12	Parallel 5.15 –				•					
KIX RDF						Ş	Ja	D	<u>an</u>	
	KIX :	STAR	(SAE	KI 170), R/	ANDY	150)			
061		ALIS	A B		BERRY		II	ILS Y 06L		
06F	₹	ALIS	A A		ALL	AN	IL	S.	Y 06R	
24L/	'R	ALIS	A C	ı	MAY	/AH	ILS	δZ	24L/R	
ни			06L(1	L5')	131	23′	24R(2	23')	
поі		(06R(!	5′)	114	83'	24L(1	12 ′)	
	06L: B8(5160'), B6(6751'), 24R: B7(5318'), B9(6751') 06R: A7(5137'), A6(6938'), 24L: A8(5269'), A9(6976')									
RWY06 : After 2500ft L/G DN, After 1500ft L/D FLAP										

TAXI RTE 1(via J4), 2(via J3)

RJB	B(KI)	7 <u>ft</u>	RK	RKSI(ICN) 23ft							
KI	KE KIX 130.95 DCL -15분 KE ICN 131.5										
KIX : SID – SOUJA tx (NADP 1)											
06L/R	HELE	HELEN x - SOUJA tx		059		059	9 ATC (9000)		059		
24L/R	- SOU.			239		ATC (9000)					
KI 111	_	06L 108.7		06R 108.1			24R 108.5				
IIIID	06L(15')	13	123′	:	24R(23')					
HUD	06R	(5')	13	123′	24L (12')						
	APU St	tart, T	AXI RT	E 1(via J	4), 2(vi	ia J3)					
TKO 13 FUK 13 TGU 1	DEP 119.2 TKO 132.7 – 133.8 EUK 124.15 TGU 120.57 APP 119.75										
ICN : STAR											
ILS 33/3	34 (SUKDO) xE	EN	IPIL	GUR	(DO 180				
ILS 15/1	.6 0	UKDO) xH	MU	NAN	GUK	(DO 180				
HUD	331	L/R 34	L(23')	123	303′		.5L/R 6R(23')				

34R(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

13123'

16L(23')

RKS	I(ICI	N) 23	3 <u>ft</u>	RJ	A/	A(N	RT)	135f		
KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm										
ICN : SID (33/34 NADP 1, 15/16 NADP 2)										
33L/R	EGC xE,		333		3	333		333		
34L/R	EGOE	BA xY	3	33	3	33	ATC	333		
15L/R	EGOB	A xC	1	53	1	53	5000	153		
16L/R	EGOB	A xH	1	53	1	53	5000	153		
NC		33		331			5L	15R		
113 WN		109 34		108 34I			1.9 6L	109.1 16R		
112		109	_	108	-	_).35	108.55		
33L/R : NC05L/R, R242 34L/R : E034L/R, R242 YJU R271 YJU R271										
	33L/R 34L(23')			1230	12303' 15L/R			16R(23')		
HUD	34R (2	3')	13123′ 16L (2			(23')	23')			
F	arallel	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)		
DEP 125.	15 – TG	U 134.	17 – ⁻	TKO 12	24.1	5 – 13	2.02			
TKO 124.								pan		
NRT : F	IAKKA:	330,Y <i>A</i>	AGAN	l 240,	LIVI	T 21	o,sw	AMP 150		
34L/	R	SWAI IAWS)			ELG		ILS	34L/R(Z)		
		•			TYL	•				
16L/	R	SWAN (SWAN			GEMIN (NORMA)			ILS Z 16L/R		
HUD 16			35′)		8202'		34	34R(141')		
ПОВ		16R(1	L30')		13123′			4L(139')		
16L: ITM 4 / 34R: ITJ 14, 4 (DME) 16R: IKF 4 / 34L: IYQ 12, 4 (DME)										
16L: B6(6433'), B7(7017'), 34R: B4(5849'), B2(6778') 16R: A6(6076'), A7(7624'), 34L: A5(6167'), A4(7641')										
L/D DOWN before 14/12 DME, L/D FLAP 4 DME Arrival Taxi RTE in Jeppesen (No Numbering)										

RJAA(NRT) 135ft					RKSI(ICN) 23ft					
KE.	Tokyo DCL -1!		0	P	A	KE ICN	131	1.5		
NRT : SID – ENPAR tx (NADP 1)										
16L/R	TETR	TETRA x ENPAR tx		157		157 A1		157		
34L/R	ENPA			7	337	7000	7000/ATC			
NR 117	_	16 110			16R 111.5	34L 111.9		34R 110.9		
HUD	16L(1	.35′)		820	02'	3	4R(1	l 41 ′)		
пор	16R (1	L30')	:	131	.23′	3	4L (1	139')		
34R: CLB 220/10000, A4R21/22/23 220KTS 확인 Verity ENPAR tx TETRA 12000A APU Start, TAXI RTE 1, 2, 3, 4 RWY 별 DEP RTE DEP 124.2 TKO 120.5 - 133.45 - 133.02 - 133.8 TGU 120.57 APP 119.75										
			ICN	l : S	TAR					
ILS 33/3	34 (SUKDO) xE		EN	PIL	GU	KDO 180		
ILS 15/1	.6 0	GUKDO) xH		MU	NAN	GU	KDO 180		
HUD	33	L/R 34	L(23	3')	123	303'	15L/R 16R(23')			
		34R(23')			13123′		1	6L(23')		
FIX	RW	Y /8, /	5 , Y.	JU I	R271					
33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L : C2(7522'), C1(8536'), 15R : B3(7454'), B2(8641')										
241 - P7(E600') P9(6E79') 24P - N4(6976') NE(9E07')										

34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507')

16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKS	<u>R</u>	RJCC(CTS) 70ft								
KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm										
ICN : SID (33/34 NADP 1, 15/16 NADP 2)										
33L/R	EGO xE/	_,,	3	33	3 333		5500/ ATC		333	
34L/R	EGOB	A xY	3	33	3	33	ATC	2	333	
15L/R	EGOB	АхС	1	53	1	53	500	0	153	
16L/R	EGOB	A xH	1	53	1	53	500	0	153	
NC 113		33 109	_	33I 108			5L 1.9		15R 109.1	
WN 112			_	34I 108			6L).35	1	16R 108.55	
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 YJU R271 YJU R271						242				
HUD	33L/R	34L(2	3′)	12303' 15L/R			/R 16I	R 16R(23')		
НОР	34R (2	3')		13123′ 16L		(23')	(23')			
F	arallel [•]	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)		
DEP 125					24.	15 – 1	33.02			
TKO 132		3 133.	3 –11	9.3		9	la	D	<u>an</u>	
CTS:	STAR (0	1R : II	DEMI	FL15	0, 1	9L : N	IAVER	F	L170)	
01R		TEI SC JKII W			YOTEI not YOSEI			ILS Y/Z 01R 3000/2000		
19L 19R CAT III	YUI	AVER(: NEY SC (AOR)	OUTH	1	KAORY YUNEY (KAORY)		II	ILS Z 19L		
HUD		01R(5: 01L(62		9X43			.(77') R(82')			
01R : B4 01L : A5										
Do not Cross 01L/19R After L/D (No TWY)										

TAXI to Gate Via D(J) or G

RJCC(CTS) 70ft RKSI(ICN) 23ft						
Chitose Oper 132.05 PA KE ICN 131.5						
	CTS : SID (NADP 1)					
ALL	DALBI x SUVIT x SOSHU x		002	2 002	ATC	002
ALL			182	2 182	ATC	182
CH 116	_	01 110.		19L 109.35	01L 110.9	19R 111.5
HUD	01R(9843'	19L(19R(•
APU, Deicing at the Gate R/H turn DCT to HWE -> Confirm R/H Turn ND						
DEP 124.7						
<u>SPR 1</u>	19.3 – 1	KO 1	24.5	- 132.3		
FUK 13	33.02 –	124.1	15			

TGU 120.57 APP 119.75

Japa

ICN: STAR

FNPIL

GUKDO xE GUKDO 180 GUKDO xH MUNAN **GUKDO 180**

ILS 33/34 ILS 15/16

15L/R 33L/R 34L(23') 12303 HUD

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RWY /8, /5, YJU R271

RKSI(ICN) 23ft RJTT(HND) 21ft									
	KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm								
	CN : SIE	(33/	34 N.	ADP 1	l, 1 5	/16 [NADP	2)	
33L/R	EGO xE/		3	33	3	33	5500 ATO	•	333
34L/R	EGOB	A xY	3	33	3	33	ATC	:	333
15L/R	EGOB	АхС	1	53	1	.53	500	0	153
16L/R	EGOB	A xH	1	53	1	.53	500	0	153
NC 113		33 109	_	33I 108		_	5L 1.9		15R 109.1
WN 112		34 109	IL .95	34I 108		_	6L).35	1	16R 108.55
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 YJU R271 YJU R271									
36	33L/R	34L(2	3')	1230	3'	15L,	/R 16I	₹(2	23')
HUD	34R (2	3′)		1312	123' 16L (23')				
	arallel [•]				-				
DEP 125		3U 134	.17 –	FUK 1	33.	02 – T			_
TKO APE		- 119.6	<u>65</u>			9	la		<u>an</u>
HND:	STAR XA	AC Nig	ht– /	APP x	кх Ү	1400	z~ SP	ΕN	IS 220
34L /R	XAC xK	/H K /	OHIA	/CAC	O		ILS X	/ V	'IS
22	XAC x	В	ВА	CON		LDA	W(RI	٧V	W 22)
16R /L	XAC I	R N	ATTY	/SANI	DY	RNP(R16R	T /	R16LT)
23	-		DA	NON		LDA	W(RI	٧V	W 23)
	3	4L(18	') 984	43'		16R((77') 8	26	8' DIS
HUD	34R(2	21') 9	843'	DIS TH	4	16L(19') 9	74	4' DIS
	2	2(35') 820	2'		23	3(55')	82	202'
241 - 142(CE4E') 142(74CE') 22 - B4(C2O7') B2(CO2O')									

34L: L12(6515'), L13(7165'), 22: B4(6207'), B3(6830')

16R: L5(5147'), L3(6361'), 23: D5(5072'), D3(6391')

xxx Z: 180kts, 160kts limit APP Chart, xxx Y After 1400z

RJTT	RJTT(HND) 21ft RKSI(ICN) 23ft							
Delta Oper 132.075 PA KE ICN 131.5								
HND : SID (xx B/C 2200-0230z 0600-1000z) NADP 1								
ALL		LA x AR x	RWY H/D	RWY CRS	ATC	RWY H/D		
HME 112.2	34L 111.7	16R 111.55	34R 108.9	16L 111.95	22 108.1	23 110.5		
		34L	(18')	9843'	16R(77')		
HU	ID	34R	(21')	11024′	16L	(19')		
		04	(19')	8202'	05(4	6')		
34L : HI	ME 351/			HME RO	80, R09	95, 22 :		
F HAND	HME /2.2 R185 34R BEKLA : KAIJI 230kts, TORAM Flap5 SPD 16L : BEKLA : PLUTO 230kts RWY05 RTE5 TAXI Chart							
21.1 Hand	CRS 095	DEP AT		JK 133.0	າດ			
Дозания		TGU 12		JK 100.	12			
09 8 8 8 8 8 8 8 8		APP 11		d	lap	an		
				Ť				
		ICI	N : STAF	R				
ILS 33/3	4 G	UKDO xE		ENPIL	GUK	DO 180		
ILS 15/1	6 G	UKDO xI	1 N	/UNAN	GUK	DO 180		
HUD	33L	/R 34L(2	3')	12303'	_	5L/R R(23')		
	34R(23') 13123' 16L(23				L(23')			
FIX	FIX RWY /8, /5 , YJU R271							
33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L : C2(7522'), C1(8536'), 15R : B3(7454'), B2(8641')								
34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')								

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft RJGG(NGO) 12ft									
	KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm OPERATION 132.05								
١	CN : SI) (33/	34 N	ADP 1	, 15	/16 [NADP	2)	
33L/R	EGO xE/	_,,	3.	33	3	33	5500 ATO	•	333
34L/R	EGOB	A xY	3	33	3	33	ATO		333
15L/R	EGOB	АхС	1	53	1	53	500	0	153
16L/R	EGOB	A xH	1	53	1	53	500	0	153
NC 113		33 109	_	33R 108.9		15L 111.9		15R 109.1	
WN 112		34 109	_			6L).35			
	: NC05L YJU R27		.42	34	4L/F		34L/R R271		242
HUD	33L/R	34L(2	3′)	1230	12303' 15L/		/R 16I	R 16R(23')	
ПОБ	34R (2	3')		1312	13123' 16L ((23')		
F	Parallel	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)	
TGU	1 <u>25.15</u> 134.17 OF APF				133.	.02	Ja	P	<u>an</u>
NGO : STAR (SAMON 290, MARIA 130)									
36		SS(CA)	PRC	BE	ı	ILS	Z 36
18		SS(CA)	QUI	EST	ı	ILS	Z 18

36(15')

RWY36: After 1500ft L/D FLAP RWY 18: After 3000ft L/G DN & L/D FLAP Caution Stop line, Yellow Ramp line, VDGS!!!

36: A6(5213'), A7(6525'), A8(7837') 18: A5(5393'), A4(6528'), A3(7841')

11483'

18(15')

RJGG(NGO) 12ft RKSI(ICN) 23ft SWISSPORT OPERATION **KF ICN 131.5** 132.05 DCL -15분 NGO: SID - TANGO tx (NADP 1) **ATC** 36 356 356 356 (7000)**OUMI x** TANGO tx **ATC** 18 176 176 176 (7000)**CBF 117.8** 18 109.7 36 111.9 HUD 36(15') 11483' 18(15') APU Start 30min, Prepare Intersection T/O **DEP 120.0** TKO 133.55 - 133.8 - TGU 120.52 APP - 119.75 apan ICN: STAR ILS 33/34 **GUKDO xE ENPIL GUKDO 180** ILS 15/16 GUKDO xH MUNAN **GUKDO 180**

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

HUD

15L/R

16R(23')

12303'

13123'

16L(23')

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641')

RKSI(ICN) 23ft RJFF(FUK) 30ft									
DCL -10	KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm								
ļ	CN : SII) (33/	34 N	ADP 1	, 15	/16 [NADP	2)	
33L/R	OSP xE/		3	33	3	33	5500 ATO	•	333
34L/R	OSPO	T xY	3	33	3	33	ATO	2	333
15L/R	OSPO	T xC	1	53	1	.53	500	0	153
16L/R	OSPO	TxH	1	53	1	.53	500	0	153
NC		33	_	331			5L 1 0		15R 109 1
WN	113.8 109.3 108.9 111.9 109.: WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.5			16R					
•	: NC05L YJU R27		42	34	1L/F		34L/R R271	, R	242
HUD	33L/R	34L(2	3′)	1230	3'	15L/	/R 16I	₹(2	23')
1105	34R (2	3')		1312	3'	16L	(23')		
P	Parallel	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)	
TGU 12	5.37						_		
Kobe 11	8.9 – [FUK A	PP 1	19.65	2	اِ	a	2	<u>an</u>
FUK RD	R – 121	1.125							
	FUK : RNAV STAR, RDR Vectoring from IKE (PAVGA 13000ft) Hold W of IKE published								
16	16 SARUP ENTIX RNP, LOC 16								
34		V34 /KS WE		RWY3 HAWK	-	R	VIS 3 NP, LO	٠.	34
HUD									
16 : C6	16 : C6(5505'), C7(6407'), 34 : C4(5193'), C3(6354')								

DGC VOR out of 6NM A/P
VIS 34: After IKE – RDR Vector Downwind – 1800ft –
RWY Insight 1500ft – Before L/D CHK Complete
before base (Do not Extend Downwind due Terrain)

RKSI(ICN) 23ft RJFF(FUK) 30ft PA KF FUK 132.05 **KF ICN 131 5** DCL -15min. Voice -5min FUK: SID (Consider C2, C8 Intersection T/O) ATC (10000) 16 158 158 158 HAKATA XX 34 338 338 ATC (10000) 338 **DGC 114.5** 16 111.7 34 108.9 16: DGC 156/20 R240 (DGC VOR out of 6NM A/P) HUD 16(15') 9186' 34(32') Caution GP HOLD LINE Initial CTC TWR, "Ready for departure" RWSL(Runway Status Lights) in operation **DEP 127.9** Kobe 135.65 114.5 DGC TGU 125.37 54 Japan **ICN: STAR** ILS 33/34 **GUKDO xE ENPIL GUKDO 180** ILS 15/16 GUKDO xH MUNAN **GUKDO 180**

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7463'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts 이상, HIRO

HUD

15L/R

16R(23')

16L(23')

12303'

13123'

RKSI(ICN) 23ft RJSA(AOJ) 650ft									
K DCL -10	KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm								
ı	CN : SIE	(33/	34 N.	ADP 1	l, 1 5	/16	NADP	2)	
33L/R	EGO xE/		3	33	333		5500 ATO	1	333
34L/R	EGOB	A xY	3	33	3	33	ATC	2	333
15L/R	EGOB	АхС	1	53	1	53	500	0	153
16L/R	EGOB	A xH	1	53	1	53	500	0	153
NC 113		33 109	_	33I 108		_	5L .1.9		15R 109.1
WN 112		34 109	_	34I 108		_	6L 0.35	1	16R 108.55
•	33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 YJU R271 YJU R271								
HUD	33L/R	34L(2	3')	1230	3'	15L	/R 16I	R(2	23')
пор	34R (2	3′)		1312	3'	16L	(23')		
F	arallel [•]	TWY 1	OKTS	이상	(R1	7 M <i>A</i>	X 15k	ts)	
DEP 125					24.	15			
FUK 125 SPR 133					8.3	9	Ja	D	<u>an</u>
AOJ : (Obstack	e Arou	and A	\irpor	t (H				
	over IV								EFC
					MRE	_			Z 24
24		NON	Ė	Y	ACH	11	RNP	Z 2	4 (AR)
06	MELOS SOUTH YACHI RNP Z 06 (AR) MELOS VOR Z 06(5 \(\frac{1}{2} \)				٠,				
HUD	HUD 24(664') 9843' 06(647')								
24: T2(5043'),T1(7043'), 06: T3(5043'), T4(7043')									
ILS Y 24 ⁻ (<mark>선호</mark>	Turn SP 반경의 RWY, 1	2로 선	1회 :	늦어짐	주	의!,	SPD N	10	rn 시작 dify)

RISA(AOJ) 650ft RKSI(ICN) 23ft JPN AIR AOJ 130.17 **KF ICN 131 5** NO ATIS, TWR 118.3 Voice AOJ: SID (NADP 1) 24 241 241 ATC 241 **IWAKI** xx 061 061 061 06 **ATC** MRF 114.1 24 111.9 HUD 24(664') 9843' 06(647') 24: MRE 241/2. MRE R008 FO 06: MRE 061/1, R350, MRE R008 ATC 순서 특이함. Deicing at the Gate TWR 118.3 SPR 127.57 - 133.3 MRE 1.0DME 3022 TKO 132.3 - 132.45 - 133.02 TKO 133.8 TGU 120.57 APP 119,75 ICN: STAR ILS 33/34 GUKDO xF **FNPIL GUKDO 180** ILS 15/16 GUKDO xH MUNAN **GUKDO 180**

15L/R 33L/R 34L(23') 12303 16R(23')

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

13123'

16L(23')

34R(23')

RWY /8, /5, YJU R271

HUD

RKSS(GMP) 59ft | ZSSS(SHA) 10ft KE GMP 131.15 DCL -15분 가능 TOBT 5분 차이 PAChina Eastern 131.5 시 CTC Comm Rwv 32R Takeoff (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) GMP: SID (NADP 1) BULTI xT 324 324 5000 324 32L/R 324 324 5000 (BULTI xO) 324 144 144 6000 144

BULTI XU 14L/R (BULTI xZ) KIP 32L 113.6 108.3

32L/R: EO32L/R, R225 YIU R271

32L(41')

32R(42')

144 32R 110.7

11811'

144 10499'

6000 144 14R 14L 109.9 108.7 14L/R: EO14L/R, R220 P73 /2 14R(34') 14L(38')

APRON(130.875) -> GND(121.9) -> TWR (All by ATC) China

36R(9')

CJU 124.52 SHA 120.95

SHA APP - 125.625 - 125.4 - 126.65 SHA: STAR

HUD

SS204

above 2960ft PUD ORH Below 2960ft SHA QRH **PUD 71A** SS405

18L: A3(6555'), A4(7578') 36R: A2(5738'), A1(7089') Traffic PTN West of RWY, Landing East RWY Normally

ILS Z 18L **PUD 61A**

ILS Z 36R

HUD 18L(6') 10499'

Des 550m (1800ft) "five five zero meters" L08. L09 not available B737 Shall CTC Apron Before Entering

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ FL Conversion Westbound (180° 359°) (360° 13700 M 13100 M 43000 FT 12500 M 12200 M 40100

38100

36100 34100

11600 M

11000 M

10400 M

	34100 F1	10400 IVI				
	32100 FT	9800 M				
-	30100 FT	9200 M				
	27600 FT	8400 M				
	25600 FT	7800 M				
	23600 FT	7200 M				
-	21700 FT	6600 M				
	19700 FT	6000 M				
	17700 FT	5400 M				
	15700 FT	4800 M				
	13800 FT	4200 M				
TL	11800 FT	3600 M				
TΑ	9800 FT	3000 M				
	7900 FT	2400 M				
	5900 FT	1800 M				
	3900 FT	1200 M				
■ ALT / HEIGHT Conversion						

СТ			
FT		11900 M	39100 FT
FT		11300 M	37100 FT
FT		10700 M	35100 FT
FT		10100 M	33100 FT
FT		9500 M	31100 FT
FT		8900 M	29100 FT
FT		8100 M	26600 FT
FT		7500 M	24600 FT
FT		6900 M	22600 FT
FT	7	6300 M	20700 FT
FT		5700 M	18700 FT
FT		5100 M	16700 FT
FT		4500 M	14800 FT
FT		3900 M	12800 FT
FT	TL	3300 M	10800 FT
FT	ТА	2700 M	8900 FT
		2700 W	0900 F1
FT		2100 M	6900 FT

Eastbound

179°)

44900 FT

41100 FT

Feet

3300 FT

3000 FT

2600 FT

2300 FT

Meter

1000 M

900 M

800 M

700 M

1500 M

550M

Meter

500M

450M

400 M

350 M

00 M

China

		_
600 M	2000 FT	3

4900 FT

1800ft

Feet 1600FT

1500FT

1300 FT

1100 FT

1000 FT



OLMEN xT BUMSI

ILS 32L/R ILS 14R OLMEN xU DOKDO

HUD

OLMFN 160 OLMEN 160 32L(41') 10499 14R(34')

14L(38')

32R(42') 11811' KIP /8(RWY 32), YJU R271, P73 /2 32L: D3(6532'), E2(9117'), 32R: E1(6614')

32L/R: 8 KIP L/G, 14R: LOC CAPT L/G

14R: C1(6578') FAF: Final Flap

TWR -> GND -> APRON (All by ATC) Except RWY14R Landing (Until R)

RKSS(GMP) 59ft ZBAA(PEK) 116ft KE GMP 131.15 Air China Beijing DCL -15분 가능 TOBT 5분 차이 1315 시 CTC Comm Rwv 32R Takeoff (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) GMP: SID (NADP 1) NOPIK xT 324 324 5000 324 32L/R (NOPIK xQ) 324 324 324 5000 14L/R NOPIK xU 144 144 6000 144 **KIP** 32L 32R 14L 14R 113.6 108.3 110.7 109.9 108.7 32L/R: EO32L/R. R225 14L/R: EO14L/R. R220 YJU R271 P73 /2 32L(41') 14R(34') 10499 HUD 11811' 32R(42') 14L(38') APRON(130.875) -> GND(121.9) -> TWR (All by ATC) DEP 125.15 - TGU 132.8 - DLC 132.95 TAO 133.72 - 128.15 - PEK 125.6 PEK APP 120.6 - Final 119.0 PEK: STAR (RW01/19 main (RW36L/18R)) 01(36L) DUMAP xZA **AA421** ILS Z 01(Y 36L) DUMAP xZA AA521 19(18R)) ILS Z 19(Y 18R) 19(94') 3.2도 01(84') 12467' HUD 36L(107') 10499' 18R(115') FIX: RWxx /8(180kts), /6(160kts) TMA Max 280kts 01: Q5(5223'), Q6(7024'), 19: Q4(5298'), Q3(7103') 36L: P6(6276'), P7(7719'), 18R: P3(6223'), P2(7552') APU off Procedure (GND Air Cond' & GPU)

Standard TAXI RTE in Jeppesen Chart

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M		
M	32100 FT		1	9500 M		
М	30100 FT		1	8900 M		
М	27600 FT		1	8100 M		
М	25600 FT		1	7500 M		
М	23600 FT			6900 M		
М	21700 FT			6300 M		
М	19700 FT		-	5700 M		
М	17700 FT			5100 M		
М	15700 FT			5100 W		
				4500 M		
М	13800 FT			3900 M		
M	11800 FT	T	니	3300 M		
M	9800 FT	T,	Α	2700 M		
М	7900 FT		1	2100 M		
М	5900 FT		-	1500 M		
М	3900 FT			1000 111		
			١	550M		
T / HE	IGHT Conv	ersi	10	1		
r	Feet			Meter		
М	3300 FT			500M		
М	3000 FT			450M		
M	2600 FT			400 M		
М	2300 FT			350 M		

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



BAA(PEK) 116ft RKSS(GMP) 59ft Air China Beijing 131.5 DCL -30분, Voice -10분 KE GMP 131.15 (COBT/STD 15분 차이 CTC Comm) Rwv 32L Landing (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) PEK: SID (NADP 1) RW36R/18L Intersec T/O W2, W7 MUGLO 36R 359 359 ATIS/DCL 359 (01)xWD(xYD)18L MUGLO ATIS/DCL 179 179 179 (19) xZD(xYD) PFK 36R 18L 01 19 111.55 109.3 108.5 114.7 108.9 36R: PEK 325/11, 36L: PEK 326/13, 01: PEK 323/9 R124 36R(98') 18L(110') HUD 12467' 01(84') 19(94') COBT from ATIS "Enroute", Bad Wx DOTRA SID DEP 124.4 PEK APP 120.6 - PEK 125.6 DLC 123.2 - 132.95 ICN 132.8 - APP 119.75 **GMP: STAR** ILS 32L/R REBIT xT(xQ) BUMSI RFBIT 170 ILS 14R REBIT xU DOKDO 32L(41') 10499 14R(34') HUD 32R(42') 11811' 14L(38') KIP /8(RWY 32), YJU R271, P73 /2

32L: D3(6532'), E2(9117'), 32R: E1(6614')

32L/R: 8 KIP L/G. 14R: LOC CAPT L/G

TWR -> GND -> APRON (All by ATC) Except RWY14R Landing (Until R)

14R: C1(6578')

FAF: Final Flap

RKSS(GMP) 59ft | RJBB(KIX) 17ft KE GMP 131.15 DCL -15분 가능 TOBT 5분 차이 KE KIX 130.95 시 CTC Comm Rwv 32R Takeoff (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) GMP: SID (NADP 1) FGOBA xT 324 324 5000 324 32L/R (EGOBA xQ) 324 324 5000 324 14L/R EGOBA xU 144 144 6000 144 KIP 321 141 14R 32R 113.6 108.3 110.7 109.9 108.7 32L/R: EO32L/R. R225 14L/R: EO14L/R. R220 YJU R271 P73 /2 32L(41') 10499' 14R(34') HUD 32R(42') 11811' 14L(38') APRON(130.875) -> GND(121.9) -> TWR (All by ATC) DEP 125.15 - TGU 134.17 - TKO 133.8 KIX RDR 120.85 KIX APP 120.25 KIX: STAR (SAEKI 170, RANDY 150) 061 ALISA B RFRRY ILS Y 06L 06R ALISA A ALLAN ILS Y 06R 24L/R ILS Z 24L/R ALISA C MAYAH 06L(15') 13123' 24R(23') HUD 06R(5') 11483' 24L(12') 06L: B8(5160'), B6(6751'), 24R: B7(5318'), B9(6751')

06R: A7(5137'), A6(6938'), 24L: A8(5269'), A9(6976')

RWY06: After 2500ft L/G DN, After 1500ft L/D FLAP TAXI RTE 1. 2

RJBB(KIX) 17ft | RKSS(GMP) 59ft **PA** KE GMP 131.15 KF KIX 130 95 DCL -15분 **Rwy 32L Landing** (06:00L~0900L / 12:00L~15:00L /18:00L~21:00L) KIX: SID - SOUJA tx (NADP 1) **ATC** 06L/R 059 059 059 (9000)HFI FN x - SOUIA tx ATC 24L/R 239 239 239 (9000)KIF 061 06R 241 24R 111.6 108.7 108.1 110.7 108.5 06L(15') 24R(23') 13123' HUD 06R (5') 13123' 24L (12') APU Start, TAXI RTE 1, 2 **DEP 119.2** TKO 132.7 - 133.8 apan TGU 120.57

GMP: STAR

BUMSI

DOKDO

10499'

11811'

GUKDO xT

GUKDO xU

32L/R: 8 KIP L/G, 14R: LOC CAPT L/G

TWR -> GND -> APRON (All by ATC) Except RWY14R Landing (Until R)

32L(41')

32R(42')

APP 119.75

ILS 32L/R

ILS 14R

HUD

14R: C1(6578')

FAF: Final Flap

OLMFN 160 OLMEN 160 14R(34') 14L(38')

KIP /8(RWY 32), YJU R271, P73 /2 32L: D3(6532'), E2(9117'), 32R: E1(6614')

RKPC(CJU) 119ft ZBAA(PEK) 116ft Air China Beijing **KF CILI 129 4** DCL -10분 132 0 CJU: SID (NADP 1) 07 LIMDI xF 066 066 9000 066 KAMIT xW 25 246 246 **ATC** 246 07 109.9 YDM 109.0 25 111.3 07: NONE 25: YDM246/3, R290 HUD 07(87') 10433' 25(76') 07: Passing G4 CTC TWR 25: 31 Holding PSN on P. E1.2.3 CTC TWR D 109.0 YDM RKPC CRS-290 China D3 YDM DEP 121.2 - TGU 124.52 - 120.72 - 126.17 - 132.8 DLC 132.95 - TAO 133.72 - 128.15 - PEK 125.6 PEK APP 120.6 - Final 119.0 PEK: STAR (RW01/19 main (RW36L/18R)) 01(36L) DUMAP xZA **AA421** ILS Z 01(Y 36L) DUMAP xZA AA521 19(18R)) ILS Z 19(Y 18R) 01(84') 12467' 19(94') 3.2도 HUD

36L(107') 10499' 18R(115')

FIX: RWxx /8(180kts), /6(160kts) TMA Max 280kts

01: Q5(5223'), Q6(7024'), 19: Q4(5298'), Q3(7103') 36L: P6(6276'), P7(7719'), 18R: P3(6223'), P2(7552')

APU off Procedure (GND Air Cond' & GPU) Standard TAXI RTE in Jeppesen Chart

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M		
M	32100 FT		1	9500 M		
M	30100 FT		1	8900 M		
М	27600 FT		1	8100 M		
М	25600 FT		1	7500 M		
М	23600 FT			6900 M		
М	21700 FT			6300 M		
М	19700 FT		-	5700 M		
М	17700 FT			5100 M		
М	15700 FT			5100 W		
				4500 M		
М	13800 FT			3900 M		
M	11800 FT	T	니	3300 M		
M	9800 FT	T,	Α	2700 M		
М	7900 FT		1	2100 M		
М	5900 FT		-	1500 M		
М	3900 FT			1000 111		
			١	550M		
T / HE	IGHT Conv	ersi	10	1		
r	Feet			Meter		
М	3300 FT			500M		
М	3000 FT			450M		
M	2600 FT			400 M		
М	2300 FT			350 M		

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



ZBAA(PEK) 116ft RKPC(CJU) 119ft Air China Beijing 132.0 DCL 30분전, Voice 10분전 **KF CILI 129 4** (COBT/STD 15분 차이 CTC Comm) PEK: SID (NADP 1) RW36R/18L Intersec T/O W2, W7 36R MUGIO ATIS/DCL 359 359 359 xWD(xYD) (01)181 MUGLO 179 179 ATIS/DCL 179 (19)xZD(xYD) PFK 36R 18L 01 19 111.55 109.3 114.7 108.5 108.9 36R: PEK 325/11, 36L: PEK 326/13, 01: PEK 323/9 R124 18L(110') 36R(98') HUD 12467' 01(84') 19(94') COBT from ATIS "Enroute", Bad Wx DOTRA SID **DEP 124.4** PEK APP 120.6 - PEK 125.6 DLC 123.2 - 132.95 114.7 PEK ICN 132.8 - 126.17 - 120.72 5300 124.52 - APP 119.75 3800 China CJU: STAR LIMDI xP ILS Z 07 YUMIN **ILS Z 25** DUKAL LIMDI xT HUD 07(87') 10433' 25(76')

07: P6(5176'), P5(5882'), P4(6840'-ATC HIRO)

25: P7(5219'), P8(5882'), P10(7524'-ATC HIRO)

Entering Rapid TWY CTC GND 121.675 (STOP x)

HST 40KTS

<u>RKPI</u>	((PU	S) 13	ft ZS	SPD(P	VG) 1	L3ft	
KE (KE Gimhae 129.2 PA China Eastern 130.5						
PUS	: SID (Mod NA	DP CLB2	1000, 14	000 MA	X)	
36		RO x AX tx	306	280	ATC	279	
18		IM x OT tx	182	182	5000	182	
KMH 1	13.8	PSN 1	14.0	36L 108.	5 36R	109.5	
	3	6 : KMH	R091, R2	271, R185	i		
HUD	3	36L(13') 36R(8')			R(13') 85 L(13') 89		
RWY	36 400f	ft Man L	./H turn,	Max Taxi	SPD 20k	CTS	
KMH R-2	CASTAS!		кмн R- GIMH (1)113.8 17 — 124	AF -	<u>72)</u>		
SHA 120		20/440	075) 46		Chi	na	
			975) – 12	25.4		1141	
				B', R-276			
34R(L)/	` '		91A/92A	MP2		Z xx	
16L(R)/	17R(L)		31A/82A			Z xx	
				12467'			
HU	D		5R(10')	13123'	17L10	•	
35L(12') 11155' 17R(12') 34R: G4(5603'), G5(6896'), 16L: G3(5577'), G2(6909') 35L: D4(5636'), D5(6932'), 17R: D3(5626'), D2(6942')							
Normally DUMET 6000m Follow Me Car Insight – TAXI L/T off,APU off Procedure							

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359") (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
M	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT	Г	400 M	
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



ZSPD(PVG) 13ft							
China Eastern 130.5 PA KE Gimhae 129.2 DCL 20분전, No READ BACK!							
	PVG : SID (NADP 1) (ATC Hold Expected Fuel Add!!)						
34L/R 35R/L		AM 92D AM 91D)		48	348	ATC (900m)	348
16R/L 17L/R		AM 82D AM 81D)		.68	168	ATC (900m)	168
PUD 1	16.9	34R 108.9 16L 111.5			. 108.1 17R 11.1	34L 108.3 16R 108.7	35R 111.9 17L 110.7
HUD	HUD 34R/L(11'/12') 12467' 16L/R(12'/11') 35R(10') 13123' 17L(10') 35L(12') 11155' 17R(12')						
APU Start, TUG Connect After Beacon L/T ON Ready for Intersection T/O							
		5.4 (Witho 5.62(119.			tructio	nd Chi	ina

PUS: STAR (Tail Wind 36R 136000lbs F40)

ANROD

ANROD

C2 HOLD SHORT 가까움(Vacate TaxiSPD)

SHA 120.95

APP - 125.5

ILS 36

VOR 18

HUD

ICN 125.725(124.52) - 128.17

KEVOX x

GAYHA x

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9, /8

18R(13') 8530' 18L(13') 8999' 18: KMH R284, R280 36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS

9DME LG, 8DME FLAP

18 Circling Click!!

RKS	<u>Z</u> :	ZSNJ(NKG) 49ft							
	KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm								
ı	CN : SII) (33/	34 N.	ADP 1	l, 15	/16 [NADP	2)	
33L/R	ВОРТ	АхА	3	33	3	33	ATO	:	333
34L/R	BOPT	A xY	3	33	3	33	ATO	2	333
15L/R	BOPT	АхС	1	53	1	53	500	0	153
16L/R	ВОРТ	A xH	1	53	1	53	500	0	153
NC 113		33 109	_	33 108		_	5L 1.9		15R 109.1
WN 112		34 109	-	34 108		_	6L).35	1	16R 108.55
•	: NC05L YJU R27	• •	.42	34	4L/F		34L/R R271	, F	242
HUD	33L/R	34L(2	3′)	1230	3'	15L,	/R 16I	₹(2	23')
нор	34R (2	3')		1312	3'	16L	(23')		
F	Parallel	TWY 1	OKTS	이싱	(R1	7 MA	X 15k	ts)	
DEP 12	5.15 - ⁻	TGU 1	26.1	7 – 1	20.7	72 – 1	24.5	2(25.72)
SHA 12					<u> </u>	19.0			ma
NKG AP								₹	IIa
NKG	: STAR	•			18 4	2.1 –			
07 (06)	ESB 7 (ESB 6			S	NQ	-	_	Z 07 Z 06)
25 (24)	ESB 5	•		N	J210	-		Z 25 Z 24)
ни			07(4	1′)	118	11′	25(3	9')
- по	<i>)</i> -		06(4	3′)	118	11′	24(3	8')
07 : D5(06 : A5(•					•		

Follow Me Car on C 13, APU off Procedure

IAF, Missed App SPD APP: 210kts or 205kts

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359") (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
M	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT	Г	400 M	
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



ZSNJ(NKG) 49ft					RK	SI(IC	CN)	<u>23ft</u>
None DCL 가능, READ BACK! PA KE ICN 131.5								
	NKG : SID (NADP 1) (ATC Hold Expected Fuel Add!!)							
06 (07)		61X/11D 71X/21D)	06	54	064	300 (900	_	064
24 (25)		42X/12D 52X/22D)	24	14	244	244 300 (900		244
NJL 1	13.6	07 108.7		1	25 111.3	06 110		24 110.9
HUD		06(43') 07(41')			24(38') 25(39')			
	APU S	tart, TUG (Cor	ine	ct Afte	r Beacc	n L/T	ON
DEP 119.25								
NKG	NKG APP 126.55							
		<u>075 – 125.</u>						
ICN	125.7	<u> 25(124.52</u>) -	- 12	20.72 -	126.1	Z	

APP - 119.75 China

ICN: STAR

ILS 33/34 OLMEN xE **ENPIL OLMEN 180**

OLMEN xH MUNAN **OLMEN 180**

ILS 15/16

12303'

15L/R 33L/R 34L(23') 16R(23') HUD

13123'

34R(23') 16L(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513')

15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641')

34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507')

16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKS	RKSI(ICN) 23ft					D(1	ΊΑΟ)	<u>30ft</u>
	KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm								
ı	CN : SI) (33/	34 N.	ADP 1	, 15	/16 [NADP	2)	
33L/R	NOPI	КхА	3	33	3	33	ATO		333
34L/R	NOPI	K xY	3	33	3	33	ATO		333
15L/R	BINII	. xC	1	53	1	53	500	0	153
16L/R	BINIL	.xH	1	53	1	53	500	0	153
NC 113		33 109	_				5L 1.9	:	15R 109.1
WN 112		34 109	_	34 108		_	6L).35	1	16R .08.55
	: NC05L 8 R068,		42	34	•		34L/R 068, R	•	
HUD	33L/R	34L(2	3′)	1230	03' 15L/R 16R(2			R(2	3')
нор	34R (2	3')		1312	3′	16L	(23')		
F	Parallel	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)	
DEP 12	<u>5.15 – </u>	TGU 1	28.7	7 – DL	<u>.C 1</u>	32.9	<u>5</u>		
TAO 12	<u>8.55 – </u>	134.8	<u>5</u>				Ch	ı	na
TAO AF	TAO 128.55 – 134.85 TAO APP 119.77 – 119.4								
TAO	: STAR (AVBIK	(R01	4 - LA	ROF	R15	9 동즉	<u> </u>	글지)
35 (3	4)	LAT 9	1A/()1A	JE	0405	ILS	6 Z	35 (34)
17 (1	6)	LAT 81A/11A JD305 ILS Z 1					17 (16)		

35(27')

34(27')

FIX : AVBIK R014, LAROP R159, R183 (두점 연결)
35 : S2(5255'), S4(6624'), 17 : S1(5282'), S3(6604')
34 : R2(5278'), R4(6650'), 16 : R1(5318'), R3(6706')
위의 Point 불가시 TWR 보고, Apron CTC 주의
Follow Me Car on Lxx APU off Procedure

HUD

11811'

11811'

17(29')

16(27')

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359") (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
M	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT	Г	400 M	
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



ZSQD(TAO) 30ft				t Rk	SI(IC	CN)	<u>23ft</u>	
	None DCL 가능, No READ BACK! (Voice 10분전 부터)							
TAC	TAO : SID (NADP 1) Walk Around Ramp Pass & PW							
34 (35)	LAT	91D/01D	35	0 350	ATC 3		350	
16 (17)	LAT	LAT 81D/11D		0 170	ATC 3000 (900m)		170	
-	JDG 17 114.45 110.15			35 109.75			34 108.55	
HUD	HUD 34(27') 35(27')		118	11811' ¹				
FIX:	AVBIK	R014, LAF	ROP	R159, R1	83 (두	점 연	결)	
Н	eadin	g 190, Join	W	209 -> DO	CT LAT	JX CR	S 148	
TAO APP 119.4 TAO 119.73 TAO 134.85 - DLC 132.95 ICN 128.7 - APP 119.75 China								
ICN : STAR								
ILS 3	3/34	REBIT	хA	P.	AMBI	RE	BIT 170	

ILS 15/16 REBIT xH MUNAN REBIT 170

15L/R

33L/R 34L(23') 12303' HUD

16R(23') 34R(23') 13123' 16L(23')

RWY /8, /5, P518 R068, R278 33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft			ZE	ZBAA(PEK) 116ft					
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm 132.0									
١	CN : SII) (33/	34 N.	ADP 1	1, 15	/16	NADP	2)	
33L/R	NOPI	КхА	3	33	333		ATC		333
34L/R	NOPI	K xY	3	33	3	33	ATO		333
15L/R	BINII	L xC	1	53	1	53	500	0	153
16L/R	BINII	_xH	1	53	1	53	500	0	153
NC 113		33 109	_	33 108	••	_	5L 1.9		15R 109.1
WN 112		34 109	_	34 108	••	_	6L 0.35	1	16R 108.55
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 P518 R068, R278 P518 R068, R278									
	33L/R	34L(23') 1		1230	12303′ 151		L/R 16R(23')		
HUD	34R (2	3′)	13123′ 161		16L	L (23')			
Parallel TWY 10KTS 이상(R17 MAX 15kts)									
DEP 12	5.15 –	TGU 1	132.8	3 – DI	C 1	32.9	<u>5</u>		
TAO 13	3.72 -	128.1	5 – F	PEK 1	25.6	ì	Ch	ı	na
PEK AP	P 120.	6 – Fir	nal 1	19.0			<u>VI</u>		112
P	EK : ST	AR (RV	V01/	19 m	ain (RW	36L/18	BR))
01 (36	5L)	DUM	AP x	ZA	AA4	121	ILS Z	01	(Y 36L)
19 (18	R))	DUM	AP x	ZA	AA5	21	ILS Z	19	(Y 18R)
HUI		01(84')	12	46 7 ′	1	9(94')	3.	2도
— поі		36	L(10	7')	104	99'	18R	(11	.5′)
FIX : RW	/xx /8(1	.80kts), /6(160kt	s) TI	MA N	/lax 28	30k	cts

01: Q5(5223'), Q6(7024'), 19: Q4(5298'), Q3(7103')

36L: P6(6276'), P7(7719'), 18R: P3(6223'), P2(7552')

Standard TAXI RTE in Jeppesen Chart

APU off Procedure (GND Air Cond' & GPU)

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359") (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M	
M	32100 FT		1	9500 M	
M	30100 FT		1	8900 M	
М	27600 FT		1	8100 M	
М	25600 FT		1	7500 M	
М	23600 FT			6900 M	
М	21700 FT			6300 M	
М	19700 FT		-	5700 M	
М	17700 FT			5100 M	
М	15700 FT			5100 W	
				4500 M	
М	13800 FT			3900 M	
M	11800 FT	T	니	3300 M	
M	9800 FT	T,	Α	2700 M	
М	7900 FT		1	2100 M	
М	5900 FT		-	1500 M	
М	3900 FT			1000 111	
			١	550M	
T / HE	IGHT Conv	ersi	10	1	
r	Feet		Meter		
М	3300 FT			500M	
М	3000 FT		450M		
M	2600 FT		Г	400 M	
М	2300 FT			350 M	

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



RKSI(ICN) 23ft ZBAA(PEK) 116ft Air China Beijing 132.0 DCL 30분전, Voice 10분전 **KE ICN 131.5** (COBT/STD 15분 차이 CTC Comm) PEK: SID (NADP 1) RW36R/18L Intersec T/O W2, W7 36R MUGIO 359 359 ATIS/DCL 359 (01)xWD(xYD)18L MUGLO ATIS/DCL 179 179 179 (19)xZD(xYD) PFK 36R 18L 01 19 114.7 111.55 109.3 108.5 108.9 36R: PEK 325/11, 36L: PEK 326/13, 01: PEK 323/9 R124 36R(98') 18L(110') 12467' 01(84') 19(94') **COBT from ATIS "Enroute", Bad Wx DOTRA SID DEP 124.4** PEK APP 120.6 - PEK 125.6 DLC 123.2 - 132.95 ICN 132.8 - APP 119.75 114.7 PEK 5300 China 3800 3000 30 **ICN: STAR** ILS 33/34 REBIT xA PAMBI REBIT 170 ILS 15/16 RFBIT xH MUNAN RFBIT 170 15L/R 33L/R 34L(23') 12303' 16R(23') HUD 34R(23') 13123' 16L(23') RWY /8, /5, P518 R068, R278

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft ZYTX(SHE) 198ft										
	KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm 131.5									
ı	CN : SII) (33/	34 N.	ADP 1	l, 15	/16 [NADP	2)		
33L/R	NOPI	КхА	3	33	3	33	ATO	333		
34L/R	NOPI	K xY	3	33	3	33	ATO	333		
15L/R	BINII	L xC	1	53	1	53	500	153		
16L/R	BINIL	.xH	1	53	1	53	500	0 153		
			L).3				5L 1.9	15R 109.1		
WN 112		34 109			••	16L 110.35		16R 108.55		
33L/R : NC05L/R, R242 34L/R : EO34L/R, R24 P518 R068, R278 P518 R068, R278				•						
HUD	33L/R	34L(2	3′)	') 12303' 15			/R 16I	R(23')		
חטט	34R (2	34R (23')			13123' 16L			(23')		
F	arallel	TWY 1	OKTS	이싱	(R1	7 MA	X 15k	ts)		
DEP 12	<u>5.15 – </u>	TGU 1	32.8	3 – DL	C 1	32.9	<u>5 – 18</u>	35.65		
DLC 134.325(128.775)										
	SHE APP 125.55 – 119.825 THE APP 125.55 – 119.825 China									
TWR 118.1										
SHE: STAR (CLR Limit TOSID Late Handoff to SHE)										
06	TOS	SID 62.	A, 61	Α .	TX5	04	ILS	Z 06		
24	TOS	SID 72	A, 11	Α .	TX6	62	ILS	S Z 24		
HUD		06(17	'O')	10	0499	9'	24(1	98')		

Around TOSID - Present TRK or HDG - CTC SHE CTL 06 : D(6210'), C(7854'), 24 : J(6227'), K(7864') - ATC 06: HP06(03), 24: HP06(03) Follow Me Car **Normally Remain Parking Brake SET!!** APU off Procedure (GND Air Cond' & GPU)

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359") (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M	
M	32100 FT		1	9500 M	
M	30100 FT		1	8900 M	
М	27600 FT		1	8100 M	
М	25600 FT		1	7500 M	
М	23600 FT			6900 M	
М	21700 FT			6300 M	
М	19700 FT		-	5700 M	
М	17700 FT			5100 M	
М	15700 FT			5100 W	
				4500 M	
М	13800 FT			3900 M	
M	11800 FT	T	니	3300 M	
M	9800 FT	T,	Α	2700 M	
М	7900 FT		1	2100 M	
М	5900 FT		-	1500 M	
М	3900 FT			1000 111	
			١	550M	
T / HE	IGHT Conv	ersi	10	1	
r	Feet		Meter		
М	3300 FT			500M	
М	3000 FT		450M		
M	2600 FT		Г	400 M	
М	2300 FT			350 M	

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT



ZYTX(SHE) 198ft				RKSI(ICN) 23ft			
China Southern Dispatch PA 131.5 DCL 가능, 5분전 READ BACK! (Voice 10분전)							
SI	SHE: SID (NADP 1) A2, A8 Intersec T/O by ATC						
06	TOS	D 61,62D	056	056	ATC/DCL		056
24	TOS	D 71,72D	236	236	ATIS/	DCL	236
SEY 114.1 06 110.5				5		24 11	0.3
HUD	HUD 06(170')				10499' 24(198')		
Follow FollowMe Car Until HPxx Be Careful "Hold short CAT I Hold line"							

Maintain Present TRK/HDG Join A588(CRS 217) Offset R3 → Active Fix DCT and EXE again!!

CTC APP without TWR Instruction APP 119.825 - 125.55 DLC 134.325 - 135.65

DLC 132.95

HUD



16L(23')

ICN 132.8 - APP 119.75	<u>Chin</u>
ICN : STAR	

ICN 132.8 - APP 119.75	<u>China</u>
ICN : STAR	

1011 102.0	7.11 110.10		
	ICN :	STAR	

		-	
	ICN : S	TAR	
IS 33/34	RFRIT χΔ	PAMRI	RERIT 170

ILS 33/34	REBIT xA	PAMBI	REBIT 170
ILS 15/16	REBIT xH	MUNAN	REBIT 170

шпр	33L/R 34L(23')	12303'	15L/R 16R(23')
ILS 15/16	REBIT xH	MUNAN	REBIT 170

RWY /8, /5, P518 R068, R278 33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

13123'

34R(23')

RKSI(ICN) 23ft				<u>Z</u> :	ZSPD(PVG) 13ft					
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm				PA	China Eastern 130.5					
ı	CN : SIE	(33/	34 N.	ADP 1	, 15	/16	NADP	2)		
33L/R	ВОРТА хА		333		333		ATC		333	
34L/R	ворта хү		333		333		ATC		333	
15L/R	BOPTA xC		153		153		5000		153	
16L/R	ВОРТ	OPTA xH		153 1		53	5000	0	153	
	NCN 33 113.8 10		_			_	5L .1.9		15R 109.1	
	WNG 112.9		L .95	34F 108.		_	16L 10.35		16R 108.55	
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 YJU R271 YJU R271					242					
	33L/R	34L(23')		1230	2303' 15L/R 16R(23')			3')		
HUD	34R (23')			13123' 16L (23')						
Parallel TWY 10KTS 이상(R17 MAX 15kts)										
DEP 12	DEP 125.15 - TGU 126.17 - 120.72 - 124.52(125.72)								25.72)	
SHA 120.95 China										
SHA APP 125.62(119.975) – 125.4 PVG: STAR (North of 'PVGNB', R-276 Prohibited)										
34R (L)/35L(R)		DUM 91A/92A		\/92A		MP2		ILS Z xx		
16L(R)/ 17R(L)		DUM 81A/82		•		MP1		ILS Z xx		
HUD		34R/L(11'/12') 12467' 16L/R(12'/								
		35R(10')		•					(10')	
		35L(12')						17R(12')		
34R : G4(5603'), G5(6896'), 16L : G3(5577'), G2(6909') 35L : D4(5636'), D5(6932'), 17R : D3(5626'), D2(6942')										
Normally DUMET 6000m										

Normally DUMET 6000m
Follow Me Car Insight – TAXI L/T off,APU off Procedure

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ FL Conversion Westbound (180° 359°) (360° 13700 M 13100 M 43000 FT 12500 M 12200 M 40100

38100

36100 34100

11600 M

11000 M

10400 M

	34100 F1	10400 IVI				
	32100 FT	9800 M				
-	30100 FT	9200 M				
	27600 FT	8400 M				
	25600 FT	7800 M				
	23600 FT	7200 M				
-	21700 FT	6600 M				
	19700 FT	6000 M				
	17700 FT	5400 M				
	15700 FT	4800 M				
	13800 FT	4200 M				
TL	11800 FT	3600 M				
TΑ	9800 FT	3000 M				
	7900 FT	2400 M				
	5900 FT	1800 M				
	3900 FT	1200 M				
ALT / HEIGHT Conversion						

СТ			
FT		11900 M	39100 FT
FT		11300 M	37100 FT
FT		10700 M	35100 FT
FT		10100 M	33100 FT
FT		9500 M	31100 FT
FT		8900 M	29100 FT
FT		8100 M	26600 FT
FT		7500 M	24600 FT
FT		6900 M	22600 FT
FT	7	6300 M	20700 FT
FT		5700 M	18700 FT
FT		5100 M	16700 FT
FT		4500 M	14800 FT
FT		3900 M	12800 FT
FT	TL	3300 M	10800 FT
FT	ТА	2700 M	8900 FT
		2700 W	0900 F1
FT		2100 M	6900 FT

Eastbound

179°)

44900 FT

41100 FT

Feet

3300 FT

3000 FT

2600 FT

2300 FT

Meter

1000 M

900 M

800 M

700 M

1500 M

550M

Meter

500M

450M

400 M

350 M

00 M

China

		_
600 M	2000 FT	3

4900 FT

1800ft

Feet 1600FT

1500FT

1300 FT

1100 FT

1000 FT

ZSPD(PVG) 13ft RKSI(ICN) 23ft									
China Eastern 130.5 PA KE ICN 131.5									
PVG : SID (NADP 1) (ATC Hold Expected Fuel Add!!)									
34L/R 35R/L		LAM 92D (LAM 91D)				48	348	ATC (900m)	348
16R/L 17L/R		LAM 82D (LAM 81D)				68	168	ATC (900m)	168
PUD 1	PUD 116.9 34R 108.9 16L 111.5				. 108.1 17R 11.1	34L 108.3 16R 108.7	35R 111.9 17L 110.7		
HUD	34	34R/L(11'/12') 35R(10') 35L(12')		1	2467' 3123' 1155'	16L/R(12 17L(10 17R(1	0')		

APU Start, TUG Connect After Beacon L/T ON

Ready for Intersection T/O

SHA APP 125.4 (Without Instruction) China SHA APP 125.62(119.975)

<u>SHA 120.95</u> ICN 125.725(124.52) – 120.72 – 126.17 APP – 119.75					
ICN : STAR					
ILS 33/34	OLMEN xE	ENPIL	OLMEN 180		
ILS 15/16	OLMEN xH	MUNAN	OLMEN 180		

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

12303'

13123'

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

HUD

15L/R

16R(23')

16L(23')

RKSI(ICN) 23ft				<u>Z</u>	YY.	J(Y	NJ)	<u>624ft</u>
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm				PA	•		lone D-ATI	S
	ICN : SII) (33/	34 N.	ADP:	1, 15	/16	NADP	2)
33L/R	NOPI	КхА	3	33	3	33	ATO	333
34L/R	NOPI	K xY	3	33	3	33	ATO	333
15L/R	BINII	. xC	1	53	1	53	500	0 153
16L/R	BINIL	.xH	1	53	1	53	500	0 153
NO 113	***	33 109	_	33 108		_	5L 1.9	15R 109.1
WI 112		34 109	_	34 108		_	6L).35	16R 108.55
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 P518 R068, R278 P518 R068, R278								
5	33L/R	34L(2	3′)	1230	12303' 15L/R 16		R(23')	
HUD	34R (2	3')		1312	3123′ 16L (23′)			
	Parallel [°]	TWY 1	OKTS	이상	۱ R1(7 MA	X 15k	ts)
DEP 12	25.15 -	TGU 1	32.8	3 – DI	C 1	32.9	<u>5 – 18</u>	35.65
128.77	- SHE	119.3	<u>- 11</u>	8.9			OL	ino
YNJ TV	VR 118.	<u>75</u>					<u>UI</u>	ina
CHK NA	YNJ : F V DATA) Mil Train)
09	KAN/C	OMB C			YJ5 (D26	04 57T)		S Z 09 8 4도 off)
27	KAN/O				YJ6 (D34			S Z 27 8 4도 off)
HUD	0	9(621	')	8530	' :	27(59	7') 3.	3도
PIX DPRKK(N43 01.6/E129 52.0) R100, R200 RWY27 /12 (Do not overshoot 12DME ARC)								
09 : C(5330'),180 BACK(8530'), 27 : B(7400'),A (8350') Expect Hold Due to MIL Train(ADD FUEL 30min)								
	Windov		t clos	sed B	etwe	een A	PP an	,

□ China, Mongolia & North Korea ■ FL Conversion Westbound (180° 359°) 13700 M 13100 M 43000 FT 12500 M 12200 M 40100 FT 11600 M 38100 FT 11000 M 36100 FT 10400 M 34100 FT 9800 M 32100 FT 9200 M 30100 FT 8400 M 27600 FT 8100 M 7800 M 25600 FT 7500 M 7200 M 23600 FT 6900 M 6600 M 21700 FT 6300 M 6000 M 19700 FT 5700 M 5400 M 17700 FT 5100 M 4800 M 15700 FT 4500 M 4200 M 13800 FT 3900 M 3600 M 11800 FT TL 3300 M 3000 M 9800 FT TA 2700 M 2400 M 7900 FT 2100 M 1800 M 5900 FT 1500 M 1200 M 3900 FT 550M ALT / HEIGHT Conversion Meter Feet Meter 3300 FT 1000 M 500M 900 M 3000 FT 450M 800 M 2600 FT 400 M 700 M 2300 FT 350 M 600 M 2000 FT 300 M **QFE Next Page** China

11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT

Eastbound

179°)

44900 FT

41100 FT

(360°

Meter/Feet Conversion Table

10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT

26600 FT 24600 FT 22600 FT 20700 FT 18700 FT

16700 FT

14800 FT

12800 FT

10800 FT 8900 FT 6900 FT 4900 FT

Feet 1600FT 1500FT 1300 FT

1100 FT

1000 FT

1800ft

YNJ Altitude / Height Conversion Table					
xxxx meters on STD 이후 적용 xxxx meters on QFE xxxx -> REQ QNH -> QNH xxx SET후 Conversion Table 사용 YNJ A/P Elevation : 623ft = 22.5hPa					
Height based on QFE (instructed by ATC)					
xxx m on QFE	xxx m plus Elevation Set				
3000 m	10500 ft				
2700 m	9500 ft				
2400 m	8500 ft				
2100 m	7500 ft				
1800 m	6500 ft				
1500 m	5600 ft				
1200 m	4600 ft				
1100 m	4200 ft				
1000 m	3900 ft				
850 m	3400 ft				
800 m	3200 ft				
750 m	3100 ft				
550 m	2400 ft				
515 m	2300 ft				
500 m	2300 ft				
425 m	2000 ft				
355 m	1800 ft				
200 m	1300 ft				
100 m	1000 ft				
0 m	623 ft				

ZYYJ(YNJ) 624ft				RK	SI(IC	N) 23	3ft
None TWR 118.75 By Voice KE ICN 131.5							
	T fro	NJ : RNP SI om GND Sta Improve C _/	aff du	e to Mil	Train (ADD Fu	
27		NVU 19D (11D)	271	271		6500ft mQFE)	271
09		NVU 09D (01D)	091	091		6500ft 200kts	091
YNJ 1	13.1	09	108.7	,	2	27 109.3	
FIX	FIX 27 : YNJ 271/3.6, YNJ 073/10 (MAX 162kts) 09 : YNJ 091/4.5, YNJ 287/11 (MAX 162kts)						
HUD	27	7(597') 3.3 .	도	853	0'	09(62	21')
		Mu: RWY 27		•	ckwise)		
٦٨٠	DILEYNU	\$113.7 NU	The Mark Trust	A)	J 118.7 E 132.	7 <u>5</u> 35 – 119	9.3
Sale Lifer	TURN 16	X TURN 2 FAM DE SAN YOU	DAS WO			<u>77 – 13</u>	
		*532 (g) 1243 (No	4	13	2.95 –	Chi	1a
			ICN :	STAR			
ILS 33	/34	REBIT	хA	PA	MBI	REBIT	170
ILS 15	/16	REBIT	хН	MU	INAN	REBIT	170
HU	D	33L/R 34	L(23')	12	303′	15L, 16R(2	
		34R(2	(3')	13	123′	16L(2	23')
FI	(RWY /8, /	5, P51	18 R068,	, R278		

DITE YOU OUT D & 20 MAY TURN NO DE YOU DE YO	OLS WO	DLC 128.77 – 135.65 132.95 – ICN 132.8			
	### ##	<u>China</u>			
ICN - STAP					

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft					SH	C(F	IGH)	<u> 22ft</u>
	KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm 130.65								
	CN : SI) (33/	34 N.	ADP 1	., 15	/16	NADP	2)	
33L/R	ВОРТ	А хА	3	33	3	33	ATO	2	333
34L/R	BOPT	A xY	3	33	3	33	ATO	:	333
15L/R	ВОРТ	А хС	1	53	1	53	500	0	153
16L/R	ВОРТ	A xH	1	53	1	53	500	0	153
NC 113		33 109	_	33I 108		_	5L 1.9		15R 109.1
WN 112		34 109	_	34I 108	-	_	6L).35	1	16R .08.55
-	: NC05L YJU R27		.42	34	4L/F		34L/R R271		242
	33L/R	34L(2	3′)	1230	3' 15L/R 16F		₹(2	3')	
HUD	34R (2	3')		1312	13123' 16L (23')		(23')		
DEP 12:		rgu 1	26.1	7 – 1	20.7	72 – ·	124.5	2(1	25.72)
HGH AF							Ch		na
	STAR - n Milita								
07/06	5 (OKT, S	UP 9)1A	ŀ	IC41	0	ILS	Zxx
25/24	1 (OKT, S	SUP 8	31A	H	1C30	5	ILS	Zxx
HUD		06(2	22')	1	115	5'	24(22′)
1100		07(22') 11811' 25(22'))				
FIX		Α	PP S	PD RE	ST i	n AP	P Cha	rt	
06 : C5(5613'), C6(6899'), 24 : C4(5613'), C3(6981') 07 : A5(6266'), A6(7565'), 25 : A4(6250'), A3(7555')									

TWR Permisson Report RWY Vacated

TAXI RTE In Jeppesen Chart, Follow Me Car, APU off

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ FL Conversion Westbound (180° 359°) (360° 13700 M 13100 M 43000 FT 12500 M 12200 M 40100

38100

36100 34100

11600 M

11000 M

10400 M

	34100 F1	10400 IVI				
	32100 FT	9800 M				
-	30100 FT	9200 M				
	27600 FT	8400 M				
	25600 FT	7800 M				
	23600 FT	7200 M				
-	21700 FT	6600 M				
	19700 FT	6000 M				
	17700 FT	5400 M				
	15700 FT	4800 M				
	13800 FT	4200 M				
TL	11800 FT	3600 M				
TΑ	9800 FT	3000 M				
	7900 FT	2400 M				
	5900 FT	1800 M				
	3900 FT	1200 M				
ALT / HEIGHT Conversion						

СТ			
FT		11900 M	39100 FT
FT		11300 M	37100 FT
FT		10700 M	35100 FT
FT		10100 M	33100 FT
FT		9500 M	31100 FT
FT		8900 M	29100 FT
FT		8100 M	26600 FT
FT		7500 M	24600 FT
FT		6900 M	22600 FT
FT	7	6300 M	20700 FT
FT		5700 M	18700 FT
FT		5100 M	16700 FT
FT		4500 M	14800 FT
FT		3900 M	12800 FT
FT	TL	3300 M	10800 FT
FT	ТА	2700 M	8900 FT
		2700 W	0900 F1
FT		2100 M	6900 FT

Eastbound

179°)

44900 FT

41100 FT

Feet

3300 FT

3000 FT

2600 FT

2300 FT

Meter

1000 M

900 M

800 M

700 M

1500 M

550M

Meter

500M

450M

400 M

350 M

00 M

China

		_
600 M	2000 FT	3

4900 FT

1800ft

Feet 1600FT

1500FT

1300 FT

1100 FT

1000 FT

ZSHC(HGH) 22ft RKSI(ICN) 23ft Hangzhou Reporting Office 130.65 **KF ICN 131.5** DCL(NO Readback) Voice 10min전 HGH: SID (NADP 1) 3000 OKT, SUP 91D 069 069 069 07/06 (900m) 3000 SLIP 81D 249 249 249 25/24 (900m)06 07 24 25 **HGH 113.0** 110.5 110.35 111.5 108.5 24/25: HGH 249/5.5. R020 06(22') 111551 24(22') HUD 07(22') 11811' 25(22') APU Start, TUG Connect After Beacon L/T ON Red/Blue PushBack, Verify RWY & Direction After T/O, Report T/O RWY 113.0 HGH HGH APP 120.4 - 119.82 SHA APP 119.975 SHA 120.55 - 120.95 ICN 125.725(124.52) - 120.72 - 126.17 ICN: STAR ILS 33/34 OLMEN xF **ENPIL OLMEN 180** ILS 15/16 OLMFN xH MUNAN **OLMFN 180** 15L/R 33L/R 34L(23') 12303' 16R(23') HUD 34R(23') 13123' 16L(23') RWY /8, /5, YJU R271 33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft ZSWH(WEH)146ft **KF ICN 131.5** None DCI -10분 TORT 5분 차이시 No D-ATIS CTC Comm ICN: SID (33/34 NADP 1, 15/16 NADP 2) 33L/R NOPIK XA 333 333 ATC 333 34L/R NOPIK xY 222 222 **ATC** 222 15L/R BINIL xC 153 153 5000 153 16L/R BINIL xH 153 153 5000 153 33L NCN 33R 15L 15R 113.8 109.3 108.9 111.9 109.1 WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.55 33L/R: NC05L/R, R242 34L/R: EO34L/R, R242 P518 R068, R278 P518 R068, R278 33L/R 34L(23') 15L/R 16R(23') 12303 HUD 13123' 16L (23') 34R (23') Parallel TWY 10KTS 이상(R17 MAX 15kts) DEP 125.15 - TGU 132.8 - DLC 132.95 TAO 133,725 China WHE TWR 118.65 (130.0) WEH (TL 69): RNAV STAR Around AGAVO ATIS 126.25 get RWY, APP info **RNP II S 7 03** 03 IKF xx F WH106 21 IKE xx F WH206 RNP ILS Z 21 HUD 03(113') 8530° 21(146') 03: B(6500'), C(5300'), 21: D(7300') 90 Turn Vacate 180 Back No Terminal Side Turn

RWY 21 Short Track Miles -> Reg one Orbit WH113

Watch MLDW Due to RWY 21 ShortCut

Descend Published Report Published = CLR APP PAX Window must closed Between APP and DEP

□ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360° 13700 M 13100 M 43000 FT 12500 M 12200 M 40100 FT 11900 M 11600 M 38100 FT 11300 M 11000 M 36100 FT 10700 M 10400 M 34100 FT 10100 M 9800 M 32100 FT 9500 M 9200 M 30100 FT 8900 M 8400 M 27600 FT 7800 M 25600 FT 7200 M 23600 FT 6600 M 21700 FT 6300 M 6000 M 19700 FT 5700 M 5400 M 17700 FT 5100 M 4800 M 15700 FT 4500 M 4200 M 13800 FT 3600 M 11800 FT 3000 M 9800 FT 2400 M 7900 FT TL 2100 M 1800 M 5900 FT TA 1500 M 1200 M 3900 FT 550M ALT / HEIGHT Conversion Meter Feet Meter 3300 FT 1000 M 500M 900 M 3000 FT 450M 800 M 2600 FT 700 M 2300 FT 600 M 2000 FT 300 M **QFE Next Page** China

Meter/Feet Conversion Table

8100 M 26600 FT **7500 M 24600 FT** 6900 M 22600 FT

Eastbound

179°)

44900 FT

41100 FT

39100 FT

37100 FT

35100 FT

33100 FT

31100 FT

29100 FT

20700 FT

18700 FT

16700 FT

14800 FT

3900 M 12800 FT 3300 M 10800 FT **2700 M 8900 FT** 2100 M 6900 FT

4900 FT

1800ft

Feet

1600FT

1500FT

1000 FT

400 M 1300 FT 350 M 1100 FT

WEH Altitude / Height Conversion Table xxxx meters on STD 이후 적용 xxxx meters on QFE xxxx -> REQ QNH -> QNH xxx SET후 Conversion Table 사용 03 Elev: 113ft = 4.0hPa, 21 Elev: 146ft = 5.2hPa Height based on QFE Altitude base on QNH (instructed by ATC) (Set Altitude : QFE + Elev SET) xxx m on OFF xxx m plus Elevation Set 8000 ft 2400 m 2100 m 7000 ft 1800 m 6000 ft 1500 m 5100 ft 1200 m 4100 ft 1100 m 3700 ft 3400 ft 1000 m 900 m 3100 ft 800 m 2700 ft 700 m 2400 ft 600 m 2100 ft 550 m 1900 ft 500 m 1800 ft 400 m 1400 ft 350 m 1300 ft 1100 ft 300 m 1000 ft 280 m 800 ft 200 m 400 ft 100 m 0 m03:113 ft 21:146 ft

ZSWH(WEH)146ft RKSI(ICN) 23ft None **KF ICN 131 5** -5 Min. TWR 118.65 By Voice WEH (TA 4930'): RNP SID (NADP 1) ATC 03 IKF xx X 026 026 026 4500m(14800') ATC 21 IKF xx X 206 206 206 4500m(14800') WHF 03 110.1 21 110.7 115.8 03(113') 8530' 21(146') RWY03/21 Expect C - Taxi down on RWY - 180 Back Taxi to RWY21 via B -> Confirm 180 Back!!! 180 Back No Terminal Side Turn PAX Window must closed Between APP and DEP TWR 118.65 TAO 133.725 DLC 132.95 TGU 132.8

China

ICN: STAR

ILS 33/34 REBIT xA PAMBI

REBIT 170 ILS 15/16 RFBIT xH MUNAN RFBIT 170

15L/R

RWY /8. /5 . P518 R068. R278 33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

12303'

13123'

16R(23')

16L(23')

33L/R 34L(23')

34R(23')

HUD

RKSI(ICN) 23ft | ZLXY(XIY) 1572ft **KF ICN 131.5** PA Airport Operation DCL -10분 TOBT 5분 차이시 Center 132.0 CTC Comm ICN: SID (33/34 NADP 1, 15/16 NADP 2) 33L/R NOPIK xA ATC 333 333 333 34L/R NOPIK xY 333 222 ATC 333 15L/R BINIL xC 153 153 5000 153 16L/R BINIL xH 153 153 5000 153 NCN 33L 33R 15L 15R 113.8 109.3 108.9 111.9 109.1 WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.55 33L/R: NC05L/R, R242 34L/R: EO34L/R, R242 P518 R068, R278 P518 R068, R278 33L/R 34L(23') 15L/R 16R(23') 12303' HUD 13123' 16L (23') 34R (23') Parallel TWY 10KTS 이상(R17 MAX 15kts) DEP 125.15 - TGU 132.8 - DLC 132.95 TAO 133.725 - 128.15 PEK 125.6 - 120.35 - 133.65 - 134.15 - 126.7 XIY 125.3 - 120.95 China XIY APP 119.05 - 120.2 - 125.1 XIY (TL 118): RNAV STAR (Spd Restriction at REF Page) RNAV ILS Z 05L/R **05L/R** LOVRA xx W XY906 23R/L XY801 RNAV ILS Z 23R/L LOVRA xx Y 05L(1562') 9843' 23R(1569') 05R(1556') 12467' 23L(1538') 05L: A3(6778'), A2(9032'), 23R: A6(5544'), A7(6512') 05R: D4(5613'), D3(7322'), 23L: D5(5646'), D6(7408') Follow Me Car, CTC Apron before Gate in "Closing to xx TWY, apply to change to xx Freq"

Taxi RTE in Jeppesen Chart.

Meter/Feet Conversion Table ☐ China, Mongolia & North Korea ■ FL Conversion Westbound (180° ~ 359°) (360° 13700 M

43000 FT

13100 M

12200 M	40100 FT	
11600 M	38100 FT	
11000 M	36100 FT	
10400 M	34100 FT	
9800 M	32100 FT	
9200 M	30100 FT	
8400 M	27600 FT	
7800 M	25600 FT	
7200 M	23600 FT	
6600 M	21700 FT	
6000 M	19700 FT	
5400 M	17700 FT	
4800 M	15700 FT	
4200 M	13800 FT	
3600 M	11800 FT	TL
3000 M	9800 FT	TA
2400 M	7900 FT	
1800 M	5900 FT	
1200 M	3900 FT	
		_
■ ALT / HE	IGHT Conve	ersion
Meter	Feet	
1000 M	3300 FT	
900 M	3000 FT	

ior	550M	1800ft
1	1500 M	4900 FT
	2100 M	6900 FT
A	2700 M	8900 FT
4	3300 M	10800 FT
. 1	3900 M	12800 FT
	4500 M	14800 FT
	5100 M	16700 FT
	5700 M	18700 FT
	6300 M	20700 FT
	6900 M	22600 FT
	7500 M	24600 FT
	8100 M	26600 FT
	8900 M	29100 FT
	9500 M	31100 FT
1	10100 M	33100 FT
	10700 M	35100 FT
1	11300 M	37100 FT
	11900 M	39100 FT
- 1		

Meter

500M

450M

400 M

350 M

Eastbound 179°)

12500 M

44900 FT

41100 FT

600 M	2000 FT	300 M
)

2600 FT

2300 FT

China

800 M

700 M

1800ft

Feet


1600FT

1500FT

1300 FT

1100 FT

1000 FT



DÉP 119.9- XIY 120.95 - 124.1

DLC 123.2 - 132.95

PEK 126.7 - 134.15 - 128.3 - 120.35

TAE 132.8

China

ICN: STAR

ILS 33/34 REBIT xA PAMBI REBIT 170

RFBIT xH MUNAN

ILS 15/16 RFBIT 170

15L/R 33L/R 34L(23') 12303' 16R(23')

RWY /8. /5 . P518 R068. R278 33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

13123'

16L(23')

34R(23')

HUD

RKS	<u>z</u> (3H	A(0	CSX)	2	20ft			
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm					Changsha Reporting Office 131.15				
-	CN : SIE) (33/	34 N	ADP 1	, 15	/16 [NADP	2)	
33L/R	NOPII	КхА	3	33	3	33	ATO	:	333
34L/R	NOPI	K xY	3	33	3	33	ATC		333
15L/R	BINIL	. xC	1	53	1	53	500	0	153
16L/R	BINIL	.xH	1	53	1	53	500)	153
NC 113		33 109	_	33I 108		_	5L 1.9		15R 109.1
WN 112		34 109	_	34I 108		_	6L).35	1	16R 108.55
33L/R: NC05L/R, R242 34L/R: EO34L/R, R242 P518 R068, R278 P518 R068, R278									
HUD	33L/R	34L(2	3′)	12303' 15L/R 16			R(2	23')	
нор	34R (2	3')		13123' 16L (23')					
P	arallel [•]	TWY 1	OKTS	이상	(R1	7 MA	X 15k	ts)	
DEP 1	25.15 -	TGU	132.	8 – D	LC	132.9	<u>95</u>		
	33.725							_	
	32.2 - 9 32.55 -					19.7			
	WR 118				•		<u>Ch</u>		na
CSX (TL 118) : RNAV STAR									
After C	DLMIB 6			AR or	RDR				
18L /R	PE	X xx V	V	НА3	66	RN	AV IL	SZ	18L/R
36R/ L		X xx X							36R/L
HUD	HUD 18L(212') 12467' 36R(188') 18R(219') 10499' 36L(198')								
18L: C9(5629'),C7(6948'),36R: C11(5675'),C13(6961') 18R: B4(5167'), B3(6427'), 36L: B5(5206'), B6(6443')									
TOK : B	Pos	ition F	Repoi	rt to G	ND	first	CTC	0(0443)
TWY T9 less 29.2m , Follow Me Car									

APU Procedure but APU available cabin 26도 이하시

Meter/Feet Conversion Table ☐ China, Mongolia & North Korea ■ FL Conversion Westbound (360° 13700 M

(180° ~	359°)	
13100 M	43000 FT	l
12200 M	40100 FT	l
11600 M	38100 FT	1
11000 M	36100 FT	l
10400 M	34100 FT	1
9800 M	32100 FT	l
9200 M	30100 FT	1
8400 M	27600 FT	
7800 M	25600 FT	1
7200 M	23600 FT	1
6600 M	21700 FT	1
6000 M	19700 FT	
5400 M	17700 FT	1
4800 M	15700 FT	
4200 M	13800 FT	L
3600 M	11800 FT	TL
3000 M	9800 FT	TA
2400 M	7900 FT	[

GHT Conversion		550M	1800ft
3900 FT			
5900 FT		1500 M	4900 FT
7900 FT		2100 M	6900 FT
9800 FT	TA	2700 M	8900 FT
11800 FT	TL	3300 M	10800 FT
13800 FT		3900 M	12800 FT
15700 FT		4500 M	14800 FT
17700 FT		5100 M	16700 FT
19700 FT		5700 M	18700 FT
21700 FT		6300 M	20700 FT
23600 FT		6900 M	22600 FT
25600 FT		7500 M	24600 FT
27600 FT		8100 M	26600 FT
30100 FT		8900 M	29100 FT
32100 FT		9500 M	31100 FT
34100 FT		10100 M	33100 FT
36100 FT		10700 M	35100 FT
38100 FT		11300 M	37100 FT
40100 FT		11900 M	39100 FT

Meter

500M

450M

Feet

1600FT

1500FT 1300 FT 1100 FT 1000 FT

Eastbound 179°)

12500 M

44900 FT

41100 FT

1200 M ■ ALT / HEIGHT Conversion

1800 M

Meter

1000 M

900 M

800 M	2600 FT	400 M
700 M	2300 FT	350 M
600 M	2000 FT	300 M

Feet

3300 FT

3000 FT



ZGHA(CSX)220ft					RKS	I(IC	N) 23	<u>ft</u>
J		132	orting Of 2.0 Read Back		A KE	E ICN :	131.15	
	XIY (TA 9850') : RNAV SID (NADP 1)							
18R,	/L	OP	O xx W	181	181	ATC(900m)	181
36L/	'R	OP	О хх Х	001	001	ATC(900m)	001
18R	110.	110.3 36L 10		9.9	18L 10	9.3	36R 1	11.1
FIX	FIX 36L/R: LYH217/8.5, R190 (LYH 113.55 for EO)							
HUD		1	8R(219')	:	10499'	36	L(198')	
	18L(212')			1	2467'	36	R(188')	
	СТС	DE	P 119.65	with	out TWR	Instr	uction	
D8.5	<u> </u>	° 113.5	DEP	119.6	55- CSX	132.	<u>55</u>	
	1	-	> WUH	134.	<u> 35 – 120</u>	0.975	<u> – 135.6 </u>	<u>5</u>
R-217		S	125.	775				
CRS 190 SHA 132.4 - 125.325 - 120.55								
120.95								
<u>China</u>								
ICN : STAR								

ILS 33/34

ILS 15/16

HUD

REBIT xA

REBIT xH

33L/R 34L(23')

34R(23')

FIX RWY /8, /5 , P518 R068, R278

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513')
15L : C2(7522'), C1(8536'), 15R : B3(7454'), B2(8641')
34L : P7(5600'), P8(6578'), 34R : N4(6876'), N5(8507')
16R : P6(5597'), P5(6574'), 16L : N3(7043'), N2(8444')
8NM 180kts, 5NM 160kts, Parr TAXI 10kts 이상, HIRO

PAMBI

MUNAN

12303'

13123'

REBIT 170

REBIT 170 15L/R

16R(23')

16L(23')

RKSI(ICN) 23ft					ΉΗ	H(I	HKG	i)	28ft
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm					НА		T Dis _l 31.6	oa ⁻	tch
-	CN : SIE	(33/	34 N	ADP	1, 15	/16	NADP	2)	
33L/R	ВОРТ	АхА	3	33	3	33	ATC		333
34L/R	ВОРТ	A xY	3	33	3	33	ATO	2	333
15L/R	ВОРТ	A xC	1	53	1	.53	500	0	153
16L/R	ВОРТ	4 хН	1	53	1	.53	500	0	153
NC 113		33 109			3R 8.9	_	5L 1.9		15R 109.1
WN 112		34 109	_		4R 8.1	_	6L 0.35	1	16R 108.55
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 YJU R271 YJU R271					242				
HUD	33L/R	34L(2	3′)	12303′ 151		15L	./R 16R(23')		
пор	34R (2	3′)		13123' 16L (23')					
F	arallel [•]	TWY 1	OKTS	이성	낭(R1	7 MA	X 15k	ts)	ĺ
ICN 124						- TP	E 125	.5	<u> – 126.7</u>
129.1 - DEP 12							Cl	1	ina
	(G : Ter								
	ET FL26								
07L (R)		BBEY :			LIMI	ES	ILS 07L(R)		/L (R)
25R (L)		ABBEY xxB SIERA xxB/D		тр		RNAV tx ILS 25R ILS 25L			
HUD	07	07L(23') 118			96' D	IS TH	2	5R	(23')
07R(27') 11942' DIS TH 12467' 25L(27')									
07L: C7(5882'), C8(7194'), 25R: C6(5882'), C5(7211') 07R: J7(6916'), J8(7998'), 25L: J5(6916'), J4(8192')									
Tx RTE - STAR - APP Chart Many SPD Restrictions xxR Dash Line for B737, APU BAN off Procedure									

VHHH(HKG) 28ft RKSI(ICN) 23ft							
HAS FLT Disp 131.6 DCL 20분전 5분 차이시 CTC Comm							
HKG: SID + Terminal Tx RTE Chart TA 9000 NADP2: 1000 SPD INTV (Vzf+10~20kts), 1500 CLB TH (NADP 1/2 for 07L/R)							
07L (R)		OCEAN xxE(A) (RASSE xxZ/X)		74	074	5000	074
25 R(L)	OCE	AN xxB/F	25	54	254	5000	254
SMT 1	14.8	07L 111.5			25R 08.75	07R 110.9	25L 110.9
HUD	07	R/L(27'/2	3′)	1	2467'	25L/R(27	'/23')
E. O	E. O 07L(R): LKC R105(SMT /3), LKC105/9.5 R185 25R(L): ITFR(ITFL)254/10, R156						
SID – Tx RTE Chart Many SPD Restriction							
HKG DEP 123.8 – RDR 118.925							
014 0140 Atturnment	Ber Dag 33 Ag	TPE	12	9.1	- 126.	<u>7 – 123.6 -</u>	<u>- 125.5</u>
Q Strong		_ / EUK	12	7.5	- ICN	125.725(1	<u> 24.52)</u>

ICN - 120.72 - 126.17

<u>APP - 119.75</u>	China
ICN : STAR	

APP - 119	.75	Chir
ICN : S	TAR	
 A		

OLMEN 180 ILS 33/34 OLMEN xE **ENPIL**

ILS 15/16 OLMEN xH MUNAN **OLMEN 180**

15L/R

33L/R 34L(23') 12303' 16R(23')

HUD

34R(23') 13123' 16L(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513')

15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641')

34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507')

16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft					ZB	TJ(TSN)	<u>6ft</u>
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm				PA	Air China Tianjin 132.0				
	ICN : SID (33/34 NADP 1, 15/16 NADP 2)								
33L/R	NOPI	КхА	3	33	3	33	ATC		333
34L/R	NOPI	K xY	3	33	3	33	ATC	2	333
15L/R	BINI	L xC	1	53	1	53	500	0	153
16L/R	BINI	_xH	1	53	1	53	500	0	153
NC 113		33 109	_	33 108			5L 1.9		15R 109.1
WN 112		34 109	_	34 108		_	6L 0.35	1	16R 108.55
33L/R : NC05L/R, R242 34L/R : EO34L/R, R242 P518 R068, R278 P518 R068, R278									
HUD	33L/R	34L(2	3′)	1230	303' 15L/R 16R(23			3')	
пор	34R (2	3')		1312	.3123' 16L (23')				
F	Parallel	TWY 1	OKTS	이싱	(R1	7 MA	X 15k	ts)	
DEP 12	<u>5.15 –</u>	TGU 1	32.8	3 – DI	<u>C 1</u>	32.9			
TAO 13	3.72 -	128.1	<u>5 – F</u>	PEK 1	25.6	ì	<u>Ch</u>	Ţ	<u>na</u>
TSN AP									
	TSN : S	TAR (I	Vlisse	ed Ap			nitiall	y)	
16L /16	R D L	JMAP	xYA/	ZA	TJ9		ILS :	161	_/16R
34R /34	IL I	DUMA	P xZ	A	TJ8 TJ8		ILS :	34F	R /34L
HUD		16 l	.(4')	1	049	9'	34R	(5'	')
1100		IS TH	16R(!	5′) 1	049	9'/11	.811′	3	4L(6')
FIX: RWxx /8									
16L : W3(6269'),W2(9809'), 34R : W7(6443'),W8(7591') 16R:B4(5177'),B3(7191'), 34L:B5(5183'),B6(7201')									
	Follow	me ca	r on l	D, TA	XI SF	D M	ax 27k	cts	

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
М	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT			400 M
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT

300 M



<u>ZB</u>	TJ(<u>TSN) 6f</u>	<u>t</u>	RKS	(ICN)	<u>23ft</u>	
Air China Tianjin 132.0 PA KE ICN 131.5 (Read Back!)							
TSN: SID (NADP 1) Caution 600m Level Off – SPD Inc							
16R /16L	M	UGLO xZD	161	161	600m ATC	161	
34L /34R	M	uglo xzd xYD	341	341	600m ATC	341	
TAJ 11	2.1	16L 109.7	34R 111.5		16R 110.9	34L 110.5	

11811'

10499

16R: Do not pass A11
Confirm Parking Brake Release before Push back

ICN: STAR

PAMBI

MUNAN

12303'

13123'

REBIT xA

RFBIT xH

33L/R 34L(23')

34R(23')

FIX RWY /8, /5 , P518 R068, R278

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513')
15L : C2(7522'), C1(8536'), 15R : B3(7454'), B2(8641')
34L : P7(5600'), P8(6578'), 34R : N4(6876'), N5(8507')
16R : P6(5597'), P5(6574'), 16L : N3(7043'), N2(8444')
8NM 180kts, 5NM 160kts, Parr TAXI 10kts 이상, HIRO

34L(6')

34R(5')

China

REBIT 170

REBIT 170 15L/R

16R(23')

16L(23')

TAJ 112.1 16L 109.7 HUD 16R(5') 16L(4')

DEP 119.27 PEK 125.6

ILS 33/34

ILS 15/16

HUD

DLC 123.2 - 132.95 ICN 132.8 - APP 119.75

RKS	RKSI(ICN) 23ft				ICO	C(C	GO)	4	1 <u>96ft</u>
	E ICN 1 0분 TOBT CTC Cor	5분 차0	기시 -	PA	Zhengzhou AOC 132.0				
	CN : SI) (33/	34 N	ADP 1	, 15	/16	NADP	2)	
33L/R	NOPI	КхА	3	33	3	33	ATO		333
34L/R	NOPI	K xY	3	33	3	33	ATC		333
15L/R	BINII	L xC	1	53	1	.53	500	0	153
16L/R	BINIL	.xH	1	.53	1	.53	500)	153
NC 113		33 109	-	33 108		_	5L 1.9	:	15R 109.1
WN 112		34 109		34 108	••	_	6L 0.35	1	16R .08.55
	: NC05L 8 R068,			34	•		34L/R 068, R	•	
HUD	33L/R	34L(2	3′)	1230	12303' 15L/R 16R(23'			3')	
НОО	34R (2	3′)		1312	3123' 16L (23')				
P	Parallel	TWY 1	LOKTS	이상	(R1	7 MA	X 15k	ts)	
DEP 12	<u>5.15 –</u>	TGU 1	128.7	7 – DL	C 1	32.9	5- TA	0	133.05
128.55	<u> </u>	<u> 15 – P</u>	EK 1	27.3	5 – 1	TAO	_	-	
CGO 11	9.35 –	120.7	<u>'2 –</u>	APP 1	26.	<u>35</u>	<u>Ch</u>	Ī	na
	GO : STA								
12L /12	R NC	OP xxU	J RN/	٩V	DZ	Υ	ILS Z	12	L /12R
30R/ 30	L NC	OP xxV	/ RN/	٩V	CC5	27	ILS Z	30	R /30L
HUD		12L(4	96')	1	181	1′	30R	(48	34')
1100		12R(4	94').	1	115	5′	301	.(48	84')
FIX: ILS	Ident /	8 (180	kts)	/6 (16	0kts	s) API	SPD	in .	JEPP
12L : D7 12R :F	'(5853') H7(5702	•	•			•	••	•	•

Follow me car, APU Off But 26도 이하 사용가능

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
М	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT			400 M
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT

300 M



RKSI(ICN) 23ft HCC(CGO) 496ft Zhengzhou AOC 132.0 **KF ICN 131 5** DCL (Read Back!) CGO: SID (NADP 1) Lower ALT - Consider Add Fuel 12R 1200m OKT xX RNAV 116 116 116 /12L ATC 30L 1200m OKT xV RNAV 296 296 296 /30R **ATC** CGO 121 12**R** 30L 30R 110.7 114.5 108.5 110.3 109.3 12R(494') 11155' 30L(484') HUD 12L(496') 11811' 30R(484') 30L: CGO 296/4, R180 30R: CGO 296/4, R070 Req Pushback to Apron 121.7 2700 3700 DEP 126.35(AUTO or NOT) CGO 124.2 - 119.35 TAO 128.35 - PEK 127.35 - 128.15

HUD

16R(23')

16L(23')

12303'

13123'

	DLC 132.95 -	- ICN 128.7							
360	4		<u>China</u>						
ICN : STAR									
\$ 22/2/	RERIT VA	DAMRI	DEBIT 170						

ILS 33/34

ILS 15/16 RFBIT xH MUNAN REBIT 170 15L/R 33L/R 34L(23')

RWY /8, /5, P518 R068, R278 33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

34R(23')

RKS	RKSI(ICN) 23ft					Y(D	YG)	713ft
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm									
	ICN : SIE) (33/	34 N	ADP 1	l, 15	/16 [NADP	2)	
33L/R	ВОРТ	A xA	3	33	3	33	ATC		333
34L/R	ВОРТ	A xY	3	33	3	33	ATC	:	333
15L/R	BOPT	АхС	1	53	1	53	500	0	153
16L/R	ВОРТ	A xH	1	.53	1	53	500	0	153
NC 113		33 109		33I 108	••	_	5L 1.9		15R 109.1
WN 112		34 109	-	34 108		_	6L).35	1	16R 108.55
•	: NC05L YJU R27		.42	34	4L/R		34L/R R271	, R	242
HUD	33L/R	34L(2	3′)	1230	12303' 15L/R 16R(23')				23')
ПОБ	34R (2	3')		1312	3'	16L	(23')		
F	Parallel [*]	TWY 1	LOKTS	3 이상	(R1	7 MA	X 15k	ts)	ı
DEP 12									
SHA 12							2 – 1	32	.32
120.1 - CHS 12		<u>33.25</u>	<u> – 13</u>	<u> 33.5 –</u>	124	4.9	Cł	ı	ina
DYG TV		45							
D	YG : ST	AR Hi	gh Te	err, Al	ΓIS v	vithir	1001	١N	
08		LIN x	xA R	NP	JX	(001	ı	LS	X 08
26		LIN xxA RNF		NP	DO	3944	ı	LS	X 26
HU		08(713	3') 3.2	2도	853	30'	26(66	55') 3.2도
08	: J(6530)'), Do	wnSl	lope 0	0.659	% 26	: B(6	53(O')

Do not Intercept RWY08 inside DYG 11NM RWY Grooved (AIP), Follow Me Car on C 13

Meter/Feet Conversion Table □ China, Mongolia & North Korea ■ Fl Conversion Westbound (180° 359°) (360 13700 M 13100 M 43000 FT

40100 FT

38100 FT

36100 FT

34100 FT

12200 M

11600 M

11000 M

10400 M

9800

9200

8400

7800

7200

6600

6000

5400

4800

4200

3600

3000

2400

1800

1200

Mete

700 I

600 M

4111	0410011			10100 M
M	32100 FT		1	9500 M
M	30100 FT		1	8900 M
М	27600 FT		1	8100 M
М	25600 FT		1	7500 M
М	23600 FT			6900 M
М	21700 FT			6300 M
М	19700 FT		-	5700 M
М	17700 FT			5100 M
М	15700 FT			5100 W
				4500 M
М	13800 FT			3900 M
M	11800 FT	T	니	3300 M
М	9800 FT	T,	Α	2700 M
М	7900 FT		1	2100 M
М	5900 FT		-	1500 M
М	3900 FT			1000 111
			١	550M
T / HE	IGHT Conv	ersi	10	1
r	Feet			Meter
М	3300 FT			500M
М	3000 FT			450M
M	2600 FT			400 M
М	2300 FT			350 M

2000 FT

12500 M 41100 FT 11900 M 39100 FT 11300 M 37100 FT 10700 M 35100 FT 10100 M 33100 FT 9500 M 31100 FT 8900 M 29100 FT 8100 M 26600 FT 7500 M 24600 FT 6900 M 22600 FT 6300 M 20700 FT 5700 M 18700 FT 5100 M 16700 FT 4500 M 14800 FT 3900 M 12800 FT

Eastbound

179°)

44900 FT

■ ALT

4900 FT

1800ft

Feet

1100 FT

1000 FT

10800 FT

8900 FT

6900 FT

	3300 FT	500M	1600FT
	3000 FT	450M	1500FT
A	2600 FT	400 M	1300 FT

300 M



GDY(DYG) 713ft RKSI(ICN) 23ft None **KF ICN 131 5** Voice TWR DYG: SID (NADP 1) **ATC** 08 LIN xxD 079 079 079 (2400m) ATC 26 LIN xxD 259 259 259 (2400m) **DYG 114.4** 08 109.7 26 108.9 HUD 08(713') 8530' 24(665') 08: DYG 079/8, R055 26: DYG, R250 *319

114.4 DYG TWR 118.45 CHS 123.9

GZU 124.9 - 133.5 - 133.25 - SHA 120.1 - 132.32

128.12 - 125.32 - 126.17 - 120.55 - 120.95 ICN 125.725(124.52) - 120.72 - 126.17

China APP - 119.75

ICN: STAR

ILS 33/34 OLMEN xE **ENPIL OLMEN 180**

ILS 15/16 OLMFN xH MUNAN

OLMFN 180

15L/R 33L/R 34L(23') 12303' 16R(23')

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

13123'

16L(23')

34R(23')

RWY /8, /5, YJU R271

HUD

RKSI(ICN) 23ft				V	VVCR(CXR) 46ft					
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm				PA						
ı	CN : SI) (33/	34 N	ADP 1	l, 15	/16	NADP	2)		
33L/R	ВОРТ	АхА	333		333		ATC		333	
34L/R	BOPT	A xY	333		333		ATC		333	
15L/R	ВОРТА хС		153		1	153		0	153	
16L/R	ВОРТ	ворта хн		53	153		5000		153	
NC 113		33 109	_	33R 108.9			5L 1.9		15R 109.1	
WN 112		34 109	-			16L 110.35		16R 108.55		
33L/R: NC05L/R, R242 34L/R: EO34L/R, R242 YJU R271 YJU R271										
HUD	33L/R 34L(23')			1230	12303' 15L/R 16R(23')			23')		
עטח	34R (2	3')		13123' 16L (23')						
F	Parallel TWY 10KTS 이상(R17 MAX 15kts)									
	FUK 127.5 - TPE 125.5 - 127.9 - 129.1 - MNL 119.3									
MNL RD						-6	F	Δ	sia	
CXR: STAR (Wx, Using RWY from HoChiMinh CTL) RWY20 Max Tail Wind 15kts, chk condition										
		V STA								
20L /R	COTUN, BANKE, HUNTA, NHATA X				CR:			ILS Y 20L RNP 20R		
02R/ L				\ XX			ILS X	(/Z	02L/R	
HUD	021	02R(15') 3.5도			1	10000'		20L(34')		
-1100	02L(20') 3.5도			Ξ.	1	.0010' 20R(46')			R(46')	
20L : G3(20L : G3(6735'), G1(9603'), 02R : G5(6528'), G7(9662')									

20R : W4(5971'), W3(7680'),02L : W5(5606'), W6(7345')

FollowMe Car Service, Sensitie VDGS Caution!!

VVCR(CXR) 46ft				RK	RKSI(ICN) 23ft			
None TWR 118.2 By Voice				PA	KE ICN	l 131.5		
F	CNX : RNP SID (NADP 1) Follow Restrictions due to Military Traffic							
02L /R	O2L/R NIHOA xxA		020	020	ATC/	'FL100	020	
20 R/L	NIHOA xxB		200	200	ATC/	'FL100	200	
CRA 11	6.5	02R 111	.9	02L 1	10.7	20L 1	10.3	
02 : CRA 020/2, R090 20 : CRA 200/6, R150								
HUD	02L(20') 3.5도			100	10010′		20R(46')	
пор	02R(15') 3.55		도	1000	10000′		20L(34')	
TWY Y5 only below wingspan 36m/118ft								
33012	CAM RANH	MAG 090*	EP 1	27.9 – 1	HCM 1	34.05		
5	DEP 127.9 – HCM 134.05 DAD 123.3 – SNY 122.6(–5min)							
HKG 132.15 – 127.1 – TPE 129.1								
125.5 – FUK 127.5(SENKA /20)								
		90.0			SI	E A s	Ria	
ICN : STAR								
ILS 33/	3/34 OLMEN xE			EI	NPIL	OLME	N 180	

ILS 15/16

HUD

OLMEN xH

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

38R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

MUNAN

12303'

13123'

OLMEN 180 15L/R

16R(23')

16L(23')

RKSI(ICN) 23ft VVTS(SGN) 33ft DCL -10분 TOBT 5분 차이시 None No D-ATIS ICN: SID (33/34 NADP 1, 15/16 NADP 2) 33L/R **BOPTA XA** 333 333 ATC 333 34L/R ROPTA xY 333 333 ATC 333 15L/R **BOPTA xC** 153 153 5000 153 16L/R **BOPTA xH** 153 153 5000 153 33L 33R 15L 15R **NCN** 113.8 109.3 108.9 111.9 109.1 WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.55 33L/R: NC05L/R. R242 34L/R: EO34L/R. R242 YJU R271 YJU R271 33L/R 34L(23') 12303' 15L/R 16R(23') HUD 16L (23') 34R (23') 13123' Parallel TWY 10KTS 이상(R17 MAX 15kts) FUK 127.5(SENKA /20) - TPE 125.5 - 127.9 - 129.1 MNL 119.3 - MNL RDO 8942(5655) - HCM 120.7 SE Asia 132.35 - SGN APP 125.5 SGN: STAR (CPDLC: VVHM) TL 190 ILS W 25R/L 25R(L) DALAP xxH SOKAN **ILS W 07R, VOR 07L** 07R(L) DALAP xxG SAMDU 25R(33') 10007' 07L(20') HUD 12559' 10036' (DISP TH) 07R(24') 25L(32')

25R:P4(6158'), P5(6991'), 07R:S6(4412'), S5(6574', 110도) B737 P4, P5, S6, S5 Unable Tell ATC 25L: S7(6824'), S8(9671'), 07L: P3(6266'), P2(8907') FollowMe Car Service in Ramp (Caution STOPBAR L/T) Sensitie VDGS!!! (0.5m이내, 2m STOP시 바로 정지)

VVI	<u> 5(5</u>	<u> GN) 331</u>	<u>rt</u> .	RKSI(ICN) 23ft					
-15mir		None L 121.8 By Voic	P/	PA KE ICN 131.5					
	SGN : RNP SID (NADP 1) TA 18000' Request RWY due to Performance								
25L (R)	KADUM xxD		250	250	11000		250		
07L (R)	KADUM xxE/A		070	070	ATC		070		
TSH 116.8 25R 110.5		07R 111.7			25L 108.3				
HUD		25R(33')		10007′		07L(20')			
טטוו	25L(32')		12559'		0	07R(24')			

25L(32') 12559' Caution TSAT +- 5min

ATC CLR. RWY CHG After TAXI

Caution STOPBAR L/T, Follow Car Service APP 125.5 - HCM 120.1 - 134.05

HNI 123.3 - SNY 122.6(-5min) HKG 132.15 - 127.1 - TPE 129.1 - 127.9

126.7 - 123.6 - FUK 127.5(SENKA /20)

SE Asia

ICN: STAR

ILS 33/34 OLMEN xE **ENPIL OLMEN 180**

MUNAN

12303'

OLMEN 180 15L/R

16R(23')

OLMEN xH

33L/R 34L(23')

ILS 15/16

HUD

34R(23') 13123' 16L(23')

RWY /8, /5, YJU R271

33R : C4(7529'), C5(8513'), 33L : B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641')

34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507')

16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKSI(ICN) 23ft VDPP(PNH) 40ft DCL -10분 TOBT 5분 차이시 **PNH DIS 129.0** ICN: SID (33/34 NADP 1, 15/16 NADP 2) 33L/R **BOPTA xA** 333 333 ATC 333 34L/R ROPTA xY 333 333 ATC 333 15L/R **BOPTA xC** 153 153 5000 153 153 153 16L/R **BOPTA xH** 5000 153 **NCN** 33L 33R 15L 15R 113.8 109.3 108.9 111.9 109.1 WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.55 33L/R: NC05L/R, R242 34L/R: EO34L/R. R242 YJU R271 YJU R271 33L/R 34L(23') 12303' 15L/R 16R(23') HUD 16L (23') 34R (23') 13123' Parallel TWY 10KTS 이상(R17 MAX 15kts) FUK 127.5(SENKA /20) - TPE 125.5 - 127.9 - 129.1 MNL 119.3 - MNL RDO 8942(5655) HCM 120.7(MIGUG) - PNH 127.5 SE Asia APP 123.8 PNH: RNAV STAR (TL ATC. ATIS) 05 NANXY xxB **BOSET RNP 05** DFTMA KOSDA 23 **ILS 23** xxΑ **Del Holding Data** 05(40') 9350' (DISP TH) 23(37') HUD 9843' 05 : E(6240'), H(7148'), 23 : C(7004'), 180 Back No Centerline L/T, No Vacate Lead L/T(Only Edge L/T)

APU Off after 5min after parking Stand xx Yellow Lead-in Marking(xx A,B Blue Line!!)

VDPP(PNH) 40ft RKSI(ICN) 23ft							
PNH DIS 129.0 PA READY! TWR 118.0 By Voice KE ICN 131.5							
	PNH: RNAV SIE RWY 23 SEYH						
05	NANXY xx	046	046	ATC (5000)	046		
23	(SEYHA xx)	226	226	ATC	226		
I	PNH 114.3		23	3 109.7			
HUD	05(40')	9	9843' 23(37')				
E.O	E.O PNH 226/2.5, R160						
L	APU Start 10min Before DEP Line up 180 Back follow Yellow Guide Line						
APP 123.8 – PNH 127.5 APP 123.8 – PNH 127.5 HCM 134.05 – 120.7 MNL RDO 8942/5655(ARESI) MNL 119.3(AKOTA) TPE 127.9 – 125.5 FUK 127.5(SENKA /20)							
ICN : STAR							
ILS 33/	34 OLMEN x	E	ENPIL	OLN	1EN 180		

33L/R 34L(23')

34R(23')

RWY /8, /5, YJU R271

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

MUNAN

12303'

13123'

OLMEN 180 15L/R

16R(23')

16L(23')

ILS 15/16 OLMEN xH

HUD

RKSI(ICN) 23ft | RPLL(MNL) 75ft KE ICN 131.5 DCL-10분 TOBT 5분 차이시 CTC Comm ICN: SID (33/34 NADP 1, 15/16 NADP 2) 33L/R **BOPTA xA** 333 333 ATC 333 34L/R ROPTA xY 333 333 ATC 333 15L/R **BOPTA xC** 153 153 5000 153 153 153 16L/R **BOPTA xH** 5000 153 NCN 33L 33R 15L 15R 113.8 109.3 108.9 111.9 109.1 WNG 34L 34R 16L 16R 112.9 109.95 108.1 110.35 108.55 33L/R: NC05L/R. R242 34L/R: EO34L/R. R242 YJU R271 YJU R271 33L/R 34L(23') 12303' 15L/R 16R(23') HUD 16L (23') 34R (23') 13123' Parallel TWY 10KTS 이상(R17 MAX 15kts) FUK 133.6 - 127.5 - 132.3 - 123.9(BISIG ETA) MNL RDO 8903(13300) **SE Asia** MNL 128.7(BEDIP) - APP 121.1 MNL: RNP STAR with RNP APP (CPDLC: RPHI) TL 130 DAGAT **RNP 06** POLIO, NABAL 06 (GONDO) **ILS 06** xxR/P **DCT MIA RDR Vec** MEDAM **RNP 24** 24 (TMA 250, 20NM 210) (MUTAN) **ILS 24** HUD 06 (16') 11188' 24 (75') 06: R2(6223'), R1(8221'), 24: R4(6095'), R5(7746') Unable advise ATC, Do not confuse R2, E2, RWY31 CTC Ramp before Entering apron, Report Chockin Time

Caution HotSpot RWY31

RPLI	RPLL(MNL) 75ft RKSI(ICN) 23ft							
PAGSS Oper 131.0 -5min, CLR 125.1 By Voice KE ICN 131.5 Aircraft Type, Proposing ALT								
MNL: RDR Vector to CAB (NADP 1) TA 11000' Main RWY H/D Climb 7000ft, CLR for T/O								
06		CAB xx R Cabanatu	•	061	061	1200 ATC	061	
24		CAB xx P Cabanatu	•	241	241	9000 ATC	241	
MIA	4 1 1	14.4		06 10	9.1	2	4 109.9	
E.O			0	6 : MI	A /2, R2	50		
HUD		06(16') 11188' 24(75')						
Req E	Req ENG Startup to GND -> Req Pushback to Ramp							
DEP 121.1(124.4)								
MNL 120.5 – 119.3(LEBIX ETA)								
	£	D2.0 MITA	2					
R-250	-	D2.0 MRA CRS 270° CRS	2700	UK 1	23.9 – 1			
R-250	-	DZ O WHITA	2700	UK 1				
8.240		D2 Q MMIS CRS 2706	2700	UK 1	23.9 - 1 24.52	<u> 27.5 -</u>		
R.730		D22 WIND A	270°	EUK 1	23.9 – 1 24.52	<u> 27.5 -</u>	<u>- 133.6</u>	
	34	7,14	270°	EUK 1 CN 12 IN:ST	23.9 – 1 24.52	27.5 - SE	<u>- 133.6</u>	
ILS 33/		OLM	1C	EUK 1 CN 12 IN : ST	23.9 – 1 24.52 AR	27.5 - SE	- 133.6 Asia	
	16	OLM	IC IEN x	EUK 1 CN 12 CN : ST E	23.9 – 1 24.52 AR ENPIL	27.5 - SE 	Asia LIMEN 180	
ILS 33/ ILS 15/	16	OLM OLM 33L/R	IC IEN x	FUK 1 CN 12 IN : ST E H	23.9 – 1 24.52 AR ENPIL MUNA	27.5 -	ASIA PLMEN 180 PLMEN 180 PLMEN 180 15L/R	
ILS 33/ ILS 15/	16	OLM OLM 33L/R	IC IEN xi IEN xi 34L(2 R(23')	EN: ST E H	23.9 – 1 24.52 TAR ENPII MUNA 12303 13123	27.5 -	ASIA PLMEN 180 PLMEN 180 15L/R 16R(23')	
ILS 33/ ILS 15/ HUD FIX 33R: C	16 4(7	OLM OLM 33L/R 34R RWY/8, 529'), C5	ICO IEN xi IEN xi IEN xi 34L(2 (23') , /5, ' 6(851:3)	EUK 1 12	23.9 – 1 24.52 TAR ENPIL MUNA 12303 13123 271 BL: B4(75)	27.5 - BE . C N C ,	ASIA PLMEN 180 PLMEN 180 15L/R 16R(23')	
ILS 33/ ILS 15/ HUD FIX 33R : C 15L : C 34L : P	16 4(7 2(7!	OLM OLM 33L/R 34F RWY /8 529'), C5 522'), C1 600'), P8	IC IEN xi IEN xi 34L(23') , /5 , '5 (8513:68536)	EUK 1 12 CN	23.9 – 1 24.52 FAR ENPIL MUNA 12303 13123 271 BL: B4(75 R: B3(74 R: N4(66	27.5 CON	ASIA PLMEN 180 PLMEN 180 15L/R 16R(23') 16L(23')	

RKS	I(ICN	1) 23	3ft	RC	M	Q(R	RMC	RKSI(ICN) 23ft RCMQ(RMQ)665ft					
KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm 131.85/95													
ICN : SID (33/34 NADP 1, 15/16 NADP 2)													
33L/R	ВОРТ	АхА	3	33	3	33	ATO	2	333				
34L/R	ВОРТ	A xY	3	33	3	33	ATC	:	333				
15L/R	BOPT	АхС	1	53	1	53	500	0	153				
16L/R	ВОРТ	A xH	1	53	1	53	500	0	153				
NC 113		33 109	_			15L 111.9		:	15R 109.1				
WN 112		34 109	_	34R 108.1		_	16L 110.35		16R 108.55				
•	: NC05L YJU R27		42	34	4L/R		34L/R R271	, R	242				
HUD	33L/R	34L(2	3′)	1230	3'	15L,	/R 16I	R(2	3')				
пор	34R (2	3')		1312	3'	16L	(23')						
F	Parallel	TWY 1	OKTS	이싱	(R1	7 MA	X 15k	ts)					
FUK 12	7.5(SE	NKA /	20)										
TPE 129						<u>S</u>	<u>E /</u>	1	<u>sia</u>				
	PMO	. No C	TAD	TI 120		DDA :	FI 220						

RMQ: No STAR TL130 COPRA FL220

18 HLG **ILS 18 RDR Vector**

18: EOR(12005'), 36: W5(8500') E1~4, W1 for Military Follow Me Car on W, Report W3 Intersection

18(653')

RWxx/8

ARROZ


12005'

ILS Y/Z 36

36(663')

36

HUD



34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444')

8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RKS	I(ICN	1) 23	3ft	R	СТ	P(T	PE)	1	08ft
CCL -10	E ICN 1 0분 TOBT CTC Con	5분 차0	기시	PA	Dyn		Ope 31.3	rat	tion
ı	ICN : SID (33/34 NADP 1, 15/16 NADP 2)								
33L/R	ВОРТ	A xA	3	33	3	33	ATO	2	333
34L/R	ВОРТ	A xY	3	33	3	33	ATC		333
15L/R	ВОРТ	A xC	1	53	1	53	500	0	153
16L/R	ВОРТ	A xH	1	53	1	53	500	0	153
NC 113		33 109	_	33I 108		_	5L 1.9		15R 109.1
WN 112		34 109	_	34I 108		_	6L).35	1	16R 108.55
•	: NC05L YJU R27		42	34	4L/R		34L/R R271	R, R	242
HUD	33L/R	34L(2	3')	1230	3′	15L,	/R 16I	R 16R(23')	
НОВ	34R (2	3')		1312	3'	16L	(23')		
F	Parallel [*]	TWY 1	LOKTS	이상	(R1	7 MA	X 15k	ts)	
FUK 12	<u>7.5(SEI</u>	NKA /	20)						
TPE 125.5 APP 128.5 125.6 APP 128.5									
	TAR TL 130-100								•

05L/R

23R/L

HUD

BAKER xx A

BAKER xx B

05L(74')

05R(107') DIS 12139'

05L: N7(5787'), N6(6738'), 23R: N6(4468'), N4(6656') 05R: S6(5419'), S7(7244'), 23L: S5(5442'), S4(7470') No VOR at TPE, A-VDGS see above

ILS 05L/R

ILS 23R/L

23L(96') DIS 11319'

23R(63')

JAMMY

AUGUR

12008'

1,01	٠,٠	1 1/10010		701/10		<u> </u>
Dynasty Operation 131.3 PA KE ICN 131.5						
TPE: RNAV SID (NADP 1) TA 11000 Be Ready Intersection T/O, A030 -> 3000ft						
05 R/L	PIANO xxA/C		054	054	ATC	054
23L /R	P	IANO xxD/B	234	234	ATC	234
05L 11	1.1	23R 109.3	05R	110.7	23L 111.9	
HUD	05L(74')		12008′		23R(63')	
ПОО	05R(107')		12467' 23L(96'			96')
	"	T DIANO II				

DEP 128.5 TPE 125.5

FUK 127.5 (SENKA /20)

			SE	As	ia
	ICN : ST	ΓAR			

ICN:	STAR	
 	=1.5	0111511400

ILS 33/34 OLMEN xE **ENPIL OLMEN 180**

OLMEN xH MUNAN **OLMEN 180**

ILS 15/16

15L/R

12303'

33L/R 34L(23')

16R(23') HUD

13123'

34R(23') 16L(23')

33R: C4(7529'), C5(8513'), 33L: B4(7563'), B5(8513') 15L: C2(7522'), C1(8536'), 15R: B3(7454'), B2(8641') 34L: P7(5600'), P8(6578'), 34R: N4(6876'), N5(8507') 16R: P6(5597'), P5(6574'), 16L: N3(7043'), N2(8444') 8NM 180kts, 5NM 160kts, Parr TAXI 10kts이상, HIRO

RWY /8, /5, YJU R271

RKSI(ICN) 23ft PGUM(GUM) 305ft										
DCL ·	KE ICN 131.5 DCL -10분 TOBT 5분 차이시 CTC Comm									
	ICN : SID (33/34 NADP 1, 15/16 NADP 2)									
33L/R	ł	OSP(• .	3	33	3	33	5500 ATO	•	333
34L/R	t	OSPO	ΤxΥ	3	33	3	33	ATC	:	333
15L/R	t	OSPO	T xC	1	53	1	53	500	0	153
16L/R	t	OSPO	TxH	1	53	1	53	500	0	153
	ICI 13.		33 109	_	331		_	5L 1.9		15R 109.1
V	/N 12.	G	34 109.	L	34	34R 1		6L :		16R 108.55
33L/I		NC05L YJU R27		.42	34	4L/R		34L/R R271	•	242
HUD		33L/R	34L(2	3′)	1230	03' 15L/R 16R			R(2	3')
		34R (2	3')		1312	.23' 16L (23')				
		arallel ⁻				(R1	7 MA	X 15k	ts)	
		3.15 – 1								
		O (BIX/					_	_	_	_
		<mark>o (Pak</mark> Atss)			<u>/8903</u>		S	<u>E /</u>	4	<u>sia</u>
GUIVI	JAC.				LUTC	1	O TI	180)		
СТ	GUM : no STAR (UTC + 10, TL 180) CPDLC BIXAK to NATSS : RJJJ to KZAK CTC GUM CERAP 118.7 (SQ2100) Before 250NM									
06L/R	U	NZ/-15,0	OBALE	(MEN	1KE)	IL	S 6L/	R (Up	slo	pe)
24L/R	U	NZ/-15,	CIBOL(WAB	OX) F	RNA	VY2	4L/R (Dov	wnslope)

6L(256') 11014' DIS TH 24R(305') 12014'

06L : E(6473'), F(6975'), 24R : D(6282'), C(8264') 06R : E(6502'), G(7808'), 24L : B(8254')

Prepare GS OUT, Vacate RWY CTC Ramp CTL

UNZ /250 (UNZ VOR out of 3.3NM A/P)

6R(258') 10014'

24L(293') 8710' DIS TH

PREFLIGHT Apply Alternate Airport IFR Wx Minima for Planning

EDTO Procedure APU Remain ON

(Ons Pecs C055) RVSM CHK: CAPT/FO 50ft, PILOT/FE 75ft

FUEL CROSS FEED V/V CHK: On -> Off. V/V I /T CHK NAV DATA Input: EEP, ETP1, ETP2, EXP HF SELCAL CHK: Jeppesen - ENT DATA Pacific SEOUL RADIO: 8903(3004.6532.13300.13303.17904)

AFTER START APU Remain ON Until Passing EXP

AFTER LEVEL OFF (CRZ CHK) RVSM CHK: CAPT/FO 200ft

BEFORE EEP (Entry Point)

60min 기준: B737-900 398NM. Others 408NM APU Fail Before EEP: Reroute, Turnback, Divert

FIX 1 : **EEP**. FIX 2 : **ETP1** FMS ALT A/P SET : ALTN Page EDTO C/L: Fuel, A/C, MSA, ALT Wx & NOTAM

Review Contingency Procedure

EDTO Segment APU Fail After EEP: Continue **Apply Actual Wx for Actual Divert**

ETP (Equal Time Point) FIX, ALTN Page SET EDTO C/L: Fuel, A/C, MSA, ALT Wx & NOTAM

EXP (Exit Point)

APU - OFF

1 HR Before TOD

FUEL CROSS FEED V/V CHK: On -> Off, V/V L/T CHK





05L(74') 12008' 23R(63') HUD 05R(107') DIS 12139' 23L(96') DIS 11319'

05L: N7(5787'), N6(6738'), 23R: N6(4468'), N4(6656') 05R: S6(5419'), S7(7244'), 23L: S5(5442'), S4(7470')

No VOR at TPE, A-VDGS see above

DCL. Voice -5min 129 2 TPE: RNAV SID (NADP 1) TA 11000 05R/L PIANO xxA/C 054 054 ATC 054 23L/R PIANO xxD/B 234 234 ATC 234 05L 111.1 23R 109.3 05R 110.7 23L 111.9 05L(74') 12008' 23R(63') HUD 05R(107') 12467 23L(96') "DCT PIANO then L3 RNAV Transition"

RKPK(PUS) 13ft

KF Gimhae

RCTP(TPE)108ft

DEP 128.5 TPE 125.5

ILS 36

VOR 18

HUD

KEVOX x

GAYHA x

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9, /8

Dynasty Operation 131.3

FUK 127.5 (SENKA /20) ICN 125.725(124.52) - 128.17 APP - 125.5

	SE	Asia

ANROD

ANROD

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

PUS: STAR (Tail Wind 36R 136000lbs F40)

9DME LG, 8DME FLAP

18 Circling Click!!

18R(13') 8530'

18L(13') 8999'

18: KMH R283, R280

RKP	K(PUS) 13	ft V	TBS(E	BKK)	4ft			
KE (Gimhae 129.2 DCL -5분	PA		ngkok 1.25				
PU:	S : SID (Mod NA	DP CLB2	1000, 14	000 MA	X)			
36	SOORO x TOPAX tx	306	280	ATC	279			
18	BULIM x ENGOT tx	182	182	5000	182			
KMH:	113.8 PSN 1	14.0	36L 108.	36R	109.5			
	36 : KMH	R091, R2	71, R185					
HUD	36L(13') 36R(8')			R(13') 85 .(13') 89				
RW	/36 400ft Man L	/H turn, N	∕lax Taxi	SPD 20k	CTS			
DEP 12	DEP 125.5 – TGU 128.17 – 124.52(125.72) FUK 127.5(SENKA /20)							
	5.5 – 129.1 – H 2.6 – HNI 123.3		28.3		• -			
<u>BKK 13</u>	<u> 2.1 – 133.1 – A</u>	NPP 119.1	5	E As	<u>sia</u>			
	BKK : ST	AR TL130	UTC+7					
19L /R	EASTE xxC RUKSA tx	No tx	Vector	ILS Z 1	1 9L /R			
01L /R	EASTE xxD RUKSA tx	No tx	Vector	ILS Z ()1L /R			
HUD	19L(4')	13123	No Gro	ov 01	R(4')			
пор	19R(4')	1	2139′	01	L(4')			
	8 <mark>(5567'), B10(69</mark> 9(5052'), E13(71	**	•	,, ,	,			

19R : E9(5052'), E13(7139'), **01L : E12(4872'), E7**HIRO, Standard Taxi Route, APU Off

VTI	VTBS(BKK) 4ft				<u> </u>	<u>U</u>	<u>S)</u>	<u>13ft</u>
KE Bangkok 131.25 DCL -20min, Voice 133.8 KE Gimhae 129.2								
BKK: RNAV SID (NADP 1) TA 11000 A-CDM REQ Pushback +-5min of TSAT TSAT/CTOT Inform to GND CTL								
19R/ L	ι	JPKUP xxG	/J	195	195	60	000	195
01 R/L	U	JPKUP xxK/	Ή	015	015	60	000	015
SVB 111.4	Ļ	19L 110.5	01	L 109.1	19R 109.		011	R 110.1
HUD		19R(4')		12:	139'		011	.(4')
пор		19L (4')	1	3123' N	o Groov	,	01R	(4')
Al	PU:	Start withir 19R I		min, Sta		AXI	Rou	ite
DEP 1	19.	25 (AUTO)	<u> – E</u>	3KK 133	3.1			
HNI 12	23.3	3 - SNY 12	2.6	– HKG	127.1 -	12	5.35	i
TPE 12	29.	1(126.7. 1	27.9	9) – 125	<u>i.5</u>			
		5 (SENKA			8	E	A	eia
	ICN 125.725(124.52) – 128.17 SE Asia							
APP 1	APP 125.5							
	PUS: STAR (Tail Wind 36R 136000lbs F40)							

ANROD

ANROD

36L: C4 (6299'), C2(7795') / 36R: E3(5866'), E2(7339') 18R: C6(5770'), C7 (6824') / 18L: E4(5882'), E5(8792') Vacate C3,C4 by ATC only. Max Taxi SPD 20KTS C2 HOLD SHORT 가까움(Vacate TaxiSPD)

ILS 36

VOR 18

HUD

KEVOX x

GAYHA x

36L(13') 10499'

36R(8') 8999'

36: IKMA/IKHE /9, /8

9DME LG, 8DME FLAP

18 Circling Click!!

18R(13') 8530'

18L(13') 8999'

18: KMH R283, R280

CRZ FUEL Penalty (Approximation) ISA+10°C: 1% increase trip fuel 2000ft above/below OPT ALT: 1~2% increase trip fuel NG 4000ft below OPT ALT: 3~5% increase trip fuel 8000ft below OPT ALT: 8~14% increase trip fuel -8 4000ft below OPT ALT: 2% increase in trip fuel

8000ft below OPT ALT: 7% increase in trip fuel 0.01M above LRC: 1~2% increase in trip fuel

FUEL Consumption ΔΡΙΙ GND: 270LBS/hr

IN FLT: 180LBS/hr TAXI

2 ENG. no APU: 1500LBS/hr (400LBS 16분 연료)

CRZ 1시간당 750ft 상승가능

Holding

분당 100LBS (4000LBS는 40분 Holding가능)

Missed App & Landing

1200LBS (과거 EDTO자료) 1500LBS이상 적용

FUEL Loading

Center Tank 1000LBS 이상시 Main Tank FULL FUEL Overfill: 1000LBS 기준

- 8: CTR fuel 1000~2000LBS T/O人 Low Press L/T ON -> CTR Fuel 필요시 2000LBS이상으로

Dispatch Home

Engine No. 1 BLEED air switch OFF
APU BLEED air switch ON
Engine No. 2 BLEED air switch OFF
Trim Air Switch ON
WING ANTI-ICE switch OFF
(ENG BLEED ON & ISOL V/V AUTO까지 OFF)

NO ENGINE BLEED TAKEOFF AFTER START (APU ON)

Consideration

CLOSE

Bleed Air DUCT PRESS indicator . Check Ensure that eng bleed air supplies the packs. APU Remain – ON (OFF 주의)

RECALL CHK

Home Continue

Next Page

... AUTO

NO ENGINE BLEED AFTERTAKEOFF ENG Fail시 FE+1500ft or Obstacle CLR후 수행하라. N1. Climb Thrust (APU Bleed MAX 17000ft) Engine No. 2 BLEED air switch ON APU BLEED air switch..... OFF CABIN rate of CLIMB indicator 안정되면 Engine No. 1 BLEED air switch ON ISOLATION VALVE switch AUTO APU switch OFF (or ON for EDTO) For EDTO flights. APU EXP까지 ON 유지하라 Bleed Air DUCT PRESS indicator . . Check Ensure that eng bleed air supplies the packs. NO ENGINE BLEED LANDING GA Thrust 추가 필요시 10000ft 이하에서 수행 FL200 or TOD 이하 APU switch START When below 10,000 ft: WING ANTI-ICE switch OFF Right PACK switch AUTO **ISOLATION VALVE switch CLOSE** Left PACK switch AUTO Engine No. 1 BLEED air switch OFF APU BLEED air switch ON

Engine No. 2 BLEED air switch OFF Bleed Air DUCT PRESS indicator . . Check Ensure that APU bleed air supplies the packs.

Home

GND CONDITIONED AIR USE 공항 요구로 APU OFF후 기내 온도 조절을 위한 방법 Air Cart와는 다르며 단순 에어컨 기능만 함. GPU Connect - GPU ONBUS - APU OFF APU Bleed OFF (no POM) (APU 시동후 2분뒤 APU Bleed ON을 위해서 OFF) Ground conditioned air 연결 전 PACK switches OFF Packs의 damage를 방지하기 위함.

PACK switches As needed After 2min, APU Bleed ON (no POM)

Set for desired temperature.

20 psi이하고 APU 사용가능시

APU Start - APU ONBUS - GPU, GND Air 제거

GND AIR CART USE

APU 부작동시 AIR CART로 PACK과 시동을 위해 사용

AIR CART는 외부 BLEED AIR의 역할을 함.

Duct pressure 20 psi minimum

APU BLEED air switch OFF ISOLATION VALVE switch OPEN

RECIRC FAN switches AUTO

Trim Air Switch ON

PACK switches AUTO or HIGH Cabin temperature selectors AUTO

ISOLATION VALVE switch AUTO APU BLEED air switch..... ON APU - left pack, external air - right pack.

Next Page

STARTING with GND AIR SOURCE #1 ENG 먼저 (우측에 AIR CART, GPU 연결됨) 'Reg Engine Start up Present Positon Engine No. 1 must be started first. When cleared to start: -> Before Start CHKLIST APU BLEED air switch OFF Engine No. 1 start Accomplish Use normal start procedures. -> PACKS - OFF... Generator No. 1 switch ON Disconnect Air Cart & GPU "Request Pushback" (if needed) #2 시동전 Air Cart 제거 반드시 확인!! **ENG CROSSBLEED START**

#1 FNGRI FFD 로 #2 FNG START

PushBack 위료, #2 ENG Area CLR

Parking brake SET Engine BLEED air switches ON

APU BLEED air switch OFF

PACK switches OFF ISOLATION VALVE switch AUTO ENG Bleed air 들어오는지 확인하라.

#1 thrust lever Advance thrust lever

Duct Press 30PSI까지 TH 증가(-8: IDLE) Starting ENG #2 Stabilized - #1 ENG IDLE - After START Flow

AFTER START CHKLIST

Home

Min 은 반드시 수정 (중간 고도 CORRECTION은 PIC 결정) Missed App 고도는 ATC 협조 필요 반드시 고도 - FE 후의 고도를 보정해야함.

Height Above FE (Feet) 200-800ft

GMP, CJU, CJJ next page

Fx) FF 200ft 공항 : 5000ft는 4800ft만 보정해야함.

Height Above FE (Feet) 900-5000ft

മററ

COLD TEMP CORRECTION General 5도 간격은 보수적으로 보간법 적용됨

TEMP

Domestic

-5

-10

-15

-20

TEMP

n

-5

-10

-15

-20

COLD TEMP CORRECTION 1/2 Min 은 반드시 수정 (중간 고도 CORRECTION은 PIC 결정) Missed App 고도는 ATC 협조 필요 GMP 32L (261') / 32R (262') / 14R (254') 32L/R മറററ O -5

CJJ 06L (387') / 24R (296')

CJU 07 (307') / 25 (296')

Home

-10

R14

n

-5

-10

n

-5

-10

06L

-5

-10

24R

n

-5

-10

ICN, KWJ, PUS next page

COL) TEM	IP CO	RREC	TION	2/2	COLD TEMP CORRECTION 2/2							
		ICN	ALL RV	WY (243	3')								
33/34	7000	6000	5000	3600	2600	1600							
0	7400	6340	5290	3810	2760	1700							
-5	7520	6460	5390	3880	2810	1730							
-10	7680	6580	5490	3950	2860	1760							
15/16	3000	2600	1600		4000		3000						
0	3170	2760	1700		4230		3170						
-5	3230	2810	1730		4310		3230						
-10	3290	2860	1760		4390		3290						
	KWJ	04R(26	6'),04L	(610')	/ 22 L(6	10')							
04L/R	4000	3000	2000				7000						
0	4230	3170	2120				7500						
-5	4310	3230	2160		lon	10	7590						
-10	4390	3290	2200	-			7680						
22L	5000	4100	3500	2900	2200		4000						
0	4230	3170	2120	3070	2340		4230						
-5	4310	3230	2160	3130	2430		4310						
-10	4390	3290	2200	3190	2420		4390						
PU	JS 36L(2	233'),3	6R(228	') / 18L	./R (see	below	()						
36L/R	6000	5000	3300	2100		6000							
0	6340	5290	3490	2210		6340							
-5	6460	5390	3560	2250		6460							
-10	6580	5490	3620	2290		6580							
18L/R	6000	5000	4000	2600	1700		6000						
0	6340	5290	4230	2760	1800		6340						
-5	6460	5390	4310	2810	1830		6460						
-10	6580	5490	4390	2860	1870		6580						

OAT (GND) / TAT (TAT) is 10°C (50°F) or below: visible moisture (clouds, fog with VIS 1SM (1600 m) or rain, snow, sleet, ice crystals...) ice, snow, slush and standing water is present

COLD Wx Operation 1/2

on the ramps, taxiways, or runways, PREFLIGHT PROBE HEAT switches -- ON

ENGINE START

NG: OAT -35°C TH변경전 2분간 IDLE. Min Oil Press 까지 IDLE 수분간 유지, Oil Temp Nor 후 Oil Press High시 ShutDown

ENGINE ANTI-ICE

ENGINE START switches ----- CONT ENGINE ANTI-ICE switches ----- ON

COWL V/V OPEN 지속 Bright: APU Bleed OFF -ISO V/V AUTO - TH 서서히 증가 (Max 30%)

WING ANTI-ICE

WING ANTI-ICE switch ----Type II or IV로 Deicing 안할 거면 사용하라

AFTER START GENERATOR 1 and 2 switches ----- ON IDG 1분이내 안정. 늦어도 5분이내 안정된다. FLIGHT controls ----

Deicing 할거면 Deicing 하고 한다. Full Travel UP - 40 - UP (Deicing시 하고 실시) FLAP UP Taxi 고려

TAXI OUT OAT 3°C 이하 RUN UP, Ice Shedding - RUNUP: Behind CLR, Min 70% 30초, 30분간격

- Ice Shedding (FZRA, FZDZ, FZFG, +SN): Min 70%, 1초, 10분간격 (-8: 없음)

Home

(-8:50%-IDLE, 60분 간격)

---- ON

TWY 상태 고려 허용되는 만큼 N1 사용

COWL V/V OPEN 지속 Bright: APU Bleed OFF, ISO V/V AUTO, TH 서서히 증가 (Max 30%)

FAN ICE REMOVAL one ENG at a time

FAN ICE REMOVAL one ENG at a time
Moderate Severe Icing 가능하면 회피하라. FAN
ICE로 Vibration 발생 또는 예방을 위한 절차
ENGINE START switches (both) -------FLT

Autothrottle (if engaged) ----- Disengage

THRUST ----- Increase(min 80%, 1초) & Adjust 15초이내 Vib 4.0이하 안정화(15분 간격 반복가능) Autothrottle (if needed) ------ Engage 4.0보다 크면 Engine High Vibration Check List

WING ANTI-ICE Icing 보이면 Deicer로 사용(Anti-icer도 사용가능)

SAT -41°C 부터 OFF 가능

FL350이상 사용금지 -> Emer Descend Icing 지역 Holding - Flap 사용금지 WING ANTI-ICE switch ------ON

APPROACH L/D

FLAP 15 사용 조건일 경우만 VREF ICE 사용

AFTER L/D, SHUTDOWN

TAXI RUNUP. ICE SHEDDING 절차적용



ENG ON Deicing in ICN
TOBT- 40min CTC KE ICN (사전신청, 결과확인)
ICN Deicing "Deicing Required ENG On Deicing"
ICN Apron "Reg Pushback Deicing Zone xxx" SQ2000

PARKING BRAKE ----- SET

Report Parking Brake SET - > Ice Man
B737-8 BROADBAND s/w ------ OFF
FI APS ------ IIP

Pad Control Arrange Deicing Pad No.

Ice Man Manage Deicing Process

THRUST LEVERS ------ IDLE STABILIZER TRIM ------ CHECK ENGINE BLEED AIR SWITCHES ---- OFF APU BLEED air switch ----- OFF

Report Ready for Deicing - > Ice Man

START DE/ANTI-ICING REQ DCL(CTC DEL)

항공기이동 및 Configuration 변경 금지

항공기이동 및 Configuration 변경 금지

AFTER DE/ANTI-ICING IS COMPLETED

(TIME CHECK 1분) 용액과 마지막 용액 뿌린 시간 받고 적는다. Holdover Time 결정!!!

B737-8 BROADBAND s/w ------ ON
TIME CHECK 1분후
APU BLEED air switch ----- As needed

Engine BLEED air switches ------ ON FLAP LEVER ------ Set for takeoff or UP ice, snow, slush or standing water, 강수 지속시 – FLAP UP고려 (FLAP full travel check 고려)

Flight controls ----- Check, as needed
After Start Cheklist

TAXI, BEFORE T/O, T/O Procedure

Cold Wx

DECISION TREE next page







ENG OFF Deicing in TOBT- 20min CTC KE GMP (PAD, New TOBT) **REQ DCL** Deicing "Deicing Required PADxxx" +5min TOBT Apron "Reg Pushback Deicing PADxxx" PARKING BRAKE ----- SET Establish communications with GND personnel. B737-8 BROADBAND s/w ----- OFF FI APS ----- UP THRUST LEVERS -----IDLE STABILIZER TRIM ------ CHECK **ENGINE BLEED AIR SWITCHES ----- OFF** APU BLEED air switch ----- OFF APU ----- START(시동후 ON 유지) APU GENERATOR bus switches ----- ON ENGINE ANTI-ICE switches----- OFF Engine Start levers ----- CUTOFF SHUTDOWN CHECKLIST START DE/ANTI-ICING 항공기이동 및 Configuration 변경 금지 AFTER DE/ANTI-ICING IS COMPLETED (TIME CHECK 1분) 용액과 마지막 용액 뿌린 시간 받고 적는다. Holdover Time 결정!!! B737-8 BROADBAND s/w ----- ON TIME CHECK 1분후 APU BLEED air switch ----- ON Engine BLEED air switches ----- ON PREFLT CHKlist -> Reg STARTUP -> CHKlist AFTER BOTH ENGINES ARE STARTED **ENGINE ANTI-ICE switches----As needed** APU----- As needed FLAP LEVER ----- Set for takeoff or UP ice, snow, slush or standing water, 강수 지속시 -FLAP UP고려 (FLAP Full travel check고려) Flight controls ----- Check, as needed AFTER START CHKlist (ATC CLR Confirm) TAXI, BEFORE T/O, T/O Procedure **DECISION TREE next page**





RKPK ARRIVALS STARS RUNWAYS VOR10R-SEL> SEL>108 GAYHASEL> RNY EXT FRANS GAYHASEL> RHY EXT FRANS GAYHA (Modify Required)

FIX: KMH 280(Base Turn), 284(Missed App)

PUS VOR 18L/R



Missed App

Base Turn 이전 : L/H Turn **KMH 284** OUTBD (SEL HDG SEL – INT H/D - VOR/LOC Engage)

Base Turn 이후 : Continue R/H Turn KMH 284 OUTBD (SEL HDG SEL – INT H/D - VOR/LOC Engage)

Domestic LOC 36 Circling Next Page

PUS LOC 36L/R Circling 18L/R RKPK ARRIVALS STARS RUNWAYS STARS RIE 36L18R<SEL> 36L18L/R 18L/R TRANS GEOJE<SEL> TRANS, KMH22 Vref+wind RWY EXT

GEOJE (Modify Required) CI36L(CF36R) 3500 FI36L(FF36R) 2100



Missed App

Base Turn 이전: L/H Turn KMH 310 OUTBD (SEL HDG SEL - INT H/D - VOR/LOC Engage)

Base Turn 이후: Continue R/H Turn KMH 310

OUTBD (SEL HDG SEL - INT H/D - VOR/LOC Engage)

Domestic

GS KTS	KM	MILES
300	560	350
310	570	360
320	590	370
330	610	380
340	630	390
350	650	400
360	670	410
370	690	430
380	710	440
390	720	450
400	740	460
410	760	470
420	780	480
430	800	500
440	820	510
450	830	520
460	850	530
470	870	540
480	890	550
490	910	560
500	930	580
510	950	590
520	960	600
530	980	610
540	1000	620
550 560	1020 1040	630 650
570	1040	660
580	1070	670
590	1070	680
600	1110	690
610	1130	700
620	1150	710
630	1170	730
640	1190	740
650	1200	750
660	1220	760
670	1240	770
680	1260	780
690	1280	800
700	1300	810

