Component	Variations	Use when	Avoid when
box()	plain, titled via headerBox(), surface path via boxSurface()	grouping related content, creating section rhythm, framing dense text or controls	signaling urgency, transient messaging, or deep application layout
badge()	semantic/status variants	short inline state, counts, labels inside other content	multi-line explanation, required action, or standalone messaging
alert()	semantic alert variants, surface path via alertSurface()	persistent in-flow status that should remain visible while the user reads or edits nearby content	transient events, stacked interruptions, or app-level runtime events
separator()	labeled/unlabeled, surface path via separatorSurface()	dividing content regions or labeling subsections within a page	primary hierarchy, alerts, or content grouping that needs its own container
skeleton()	line/block loading placeholders	communicating expected shape during loading	exact progress, actionable status, or long-lived empty state
kbd()	keycap styling only	showing shortcuts near commands or instructions	representing arbitrary code or primary labels
spinnerFrame() / createSpinner()	spinner styles and live controller	unknown-duration ongoing work in a narrow space	progress with known completion, historical logs, or large layout regions
progressBar() / live progress controllers	static, live, animated	known-progress work, install flows, downloads, percentages	binary yes/no states or tiny inline labels
timer() / createTimer() / createStopwatch()	static timer, live countdown, live stopwatch	elapsed or remaining time is a first-class fact	generic status or event history
log()	levels debug through fatal	audit streams, diagnostics, sequential event feeds	replacing notifications, alerts, or structured page UI