Component	Variations	Use when	Avoid when
table()	aligned columns, width-constrained cells, surface path via tableSurface()	comparing multiple rows across fixed columns	active row-by-row inspection, hierarchical data, or graph structure
tree()	hierarchical nodes	showing expandable hierarchy or filesystem-like structure in static content	dependency graphs, tabular comparison, or heavily interactive browsing
accordion()	collapsed/expanded sections	progressive disclosure inside one page or form	peer navigation across views, dense row comparison, or app shell navigation
timeline()	status/dated events	chronological history, release/event streams, process storytelling	exact comparison tables or dependency graphs
tabs()	tab items with badges/active state	peer sections where only one pane should be considered active	process progress, deep hierarchy, or command/action lists
breadcrumb()	path segments	showing location/path hierarchy	step-by-step progress, app-global command navigation, or large menus
paginator()	dots/text display	communicating page position or finite carousel/page count	workflow steps or arbitrary tabs
stepper()	step states	sequential progress through a process	peer page navigation or location hierarchy
dag() / dagSlice() / dagStats()	full graph, fragment, metrics	dependency reasoning, build pipelines, workflow graphs	simple trees, tables, or ordinary lists
enumeratedList()	ordered/unordered bullet styles	prose-adjacent ordered or unordered lists	row/column comparison, hierarchy, or active selection