Gate	Rule	Current enforcement
REL-TOOL-NODE	Node.js is available for metadata and validation commands.	release:readiness
REL-TOOL-NPM	npm is available for workspace, pack, audit, and registry checks.	release:readiness, workflows
REL-TOOL-GIT	Git is available for tag, ancestry, and clean-tree checks.	operator, workflows
REL-TOOL-GH	GitHub CLI can read the repository before live issue gates run.	operator
REL-TAG-FORMAT	Release tags use leading-v SemVer with optional alpha, beta, or rc prerelease suffix.	tag-guard.yml, release:preflight
REL-GH-ACCESS	gh can read flyingrobots/bijou before final issue gates run.	operator
REL-GH-PRIORITY-HIGH-ZERO	There are zero open release-blocking issues labeled priority:high, unless the evidence packet names the accepted risk and owner.	operator
REL-GH-TARGET-MILESTONE-ZERO	The target GitHub milestone exists and has zero open issues or PRs.	operator
REL-GH-PRIOR-RELEASE-ZERO	Lower v* milestones have zero open issues or PRs.	operator
REL-META-VERSION-LOCKSTEP	Every workspace package version and internal Bijou dependency version matches X.Y.Z.	release:preflight
REL-GIT-CLEAN	The worktree is clean before release prep starts, before the release PR is opened, and before final tagging.	operator
REL-GIT-ORIGIN-MAIN	The final tag commit is exactly origin/main.	operator
REL-DOC-CHANGELOG-DATED	docs/CHANGELOG.md has a dated [X.Y.Z] - YYYY-MM-DD entry.	operator
REL-DOC-EVIDENCE	docs/releases/X.Y.Z/README.md records release evidence, review disposition, replay commands, and residual risk.	operator