

Génie Logiciel

UML to model the dynamic

Sylvain Lobry

21/10/2022

UML to model the dynamic

Types of diagrams

- UML defines 13 diagrams in 3 categories which can define a system according to different points of view
- Structure diagrams
 - Class Diagram, Object Diagram, Component Diagram, Composite Structure Diagram, Package Diagram and Deployment Diagram
- Behavior diagrams
 - Use Case Diagram, Activity Diagram and State Machine Diagram
- Interaction diagrams
 - Sequence Diagram, Communication Diagram, Timing Diagram and Interaction Overview Diagram

UML to model the dynamic

Types of diagrams

- UML defines 13 diagrams in 3 categories which can define a system according to different points of view
- Structure diagrams
 - Class Diagram, Object Diagram, Component Diagram, Composite Structure Diagram, Package Diagram and Deployment Diagram
- Behavior diagrams
 - Use Case Diagram, Activity Diagram and State Machine Diagram
- Interaction diagrams
 - **Sequence Diagram, Communication Diagram**, Timing Diagram and Interaction Overview Diagram

UML to model the dynamic

The dynamic

- We have seen a diagram allowing to model the interaction between internal (system) and external (actor) entities
- How do they interact?
- Sequence diagram: model the **temporal** aspects
- Communication diagram: model the **spatial** aspects

Sequence diagram


Sequence diagram

- A **sequence diagram** describes the interactions between different objects by showing which messages transmitted between them.
- Shows:
 - How do objects interact with each other
 - What information do they exchange (optional)
 - In what order do they communicate
- Use it to show how small methods are sequenced.
- One use case should come with one sequence diagram

Sequence diagram

Lifeline of an object


- Each instance of an object is named with the notation “role: Class”. If there is no ambiguity, “:Class” can be sufficient.
- Each instance of an object has a **lifeline**, shown with a dashed lined.
- The diagram is read top to bottom: time increases when we go down.
- **Activation period** represents the time during which the instance is active (i.e. runs a method)



Sequence diagram

Sending messages


- Horizontal arrow from the sender's lifeline to the receiver.
- One message = 1 number (in sequential order) + a name.



Sequence diagram

Sending messages


- Horizontal arrow from the sender's lifeline to the receiver.
- One message = 1 number (in sequential order) + a name.
- When a message is sent while the previous one is not finished: sub-numbering.



Sequence diagram

Sending messages

- Horizontal arrow from the sender's lifeline to the receiver.
- One message = 1 number (in sequential order) + a name.
- When a message is sent while the previous one is not finished: sub-numbering.



Sequence diagram

Sending messages

- The message can be
 - Synchronous: the sender stops its activity while the recipient is working on the message



- Asynchronous: the sender does not stop its activity



- Reply




- Possible to send message to itself



Sequence diagram

Sending messages


- The message does not have to have a name. In this case:



- The message can embed data through parameters




- Parameters can be omitted through '-'



Sequence diagram

Taking time into account


- If necessary, you can give time indication in your sequence diagram.
- Between brackets



Sequence diagram

Creating and destructing object

- Possible to create and destroy objects
- To create: start the lifeline at the message.
- To destroy: put a cross



Sequence diagram

Simple example

