

Fișierele de configurare pentru P3

| <i>/etc/sysconfig/network-scripts/ifcfg-enp0s3</i> | <i>/etc/sysconfig/network-script-ifcfg-enp0s8</i> | <i>/etc/sysconfig/network-script-ifcfg-enp0s9</i> |
|---|--|--|
| TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s3 DEVICE=enp0s3 ONBOOT=yes IPADDR=172.16.61.66 NETMASK=255.255.255.192 GATEWAY=172.16.61.65 | TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s8 DEVICE=enp0s8 ONBOOT=yes IPADDR=172.16.61.129 NETMASK=255.255.255.192 | TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s9 DEVICE=enp0s9 ONBOOT=yes IPADDR=172.16.61.193 NETMASK=255.255.255.224 |

| <i>/etc/hostname</i> | <i>/etc/sysctl.conf</i> | <i>/etc/sysconfig/network-scripts/route-enp0s8</i> |
|----------------------|-------------------------|--|
| P3 | net.ipv4.ip_forward = 1 | 172.16.3.224/27 via 172.16.3.130 dev enp0s8 |

| <i>/etc/sysconfig/network</i> | <i>/etc/resolv.conf</i> |
|-------------------------------|--------------------------|
| NETWORKING=yes HOSTNAME=P3 | nameserver 192.168.100.1 |

| <i>/etc/sysconfig/iptables</i> |
|--|
| <pre>#Generated by iptables-save v1.4.21 on Fri Dec 4 07:41:07 2020 *nat :PREROUTING ACCEPT [0:0] :INPUT ACCEPT [0:0] :OUTPUT ACCEPT [0:0] :POSTROUTING ACCEPT [0:0] COMMIT # Completed on on Fri Dec 4 07:41:07 2020 # Generated by iptables-save v1.4.21 on Fri Dec 4 07:41:07 2020 *filter :INPUT ACCEPT [0:0] :FORWARD ACCEPT [0:0] :OUTPUT ACCEPT [0:0] -A INPUT -m state --state RELATED,ESTABLISHED -j ACCEPT -A INPUT -p icmp -j ACCEPT -A INPUT -i lo -j ACCEPT</pre> |

```
-A INPUT -p tcp -m tcp --dport 80 -j ACCEPT
-A INPUT -p tcp -m tcp --dport 443 -j ACCEPT
-A INPUT -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT
-A INPUT -j REJECT --reject-with icmp-host-prohibited
-A FORWARD -i enp0s3 -j ACCEPT
-A FORWARD -i enp0s8 -j ACCEPT
-A FORWARD -i enp0s9 -j ACCEPT
-A FORWARD -j REJECT --reject-with icmp-host-prohibited
COMMIT
```