

Fișierele de configurare pentru P4

<i>/etc/sysconfig/network-scripts/ifcfg-enp0s3</i>	<i>/etc/sysconfig/network-script-ifcfg-enp0s8</i>
TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s3 DEVICE=enp0s3 ONBOOT=yes IPADDR=172.16.61.130 NETMASK=255.255.255.192 GATEWAY=172.16.61.129	TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s8 DEVICE=enp0s8 ONBOOT=yes IPADDR=172.16.61.225 NETMASK=255.255.255.224

<i>/etc/ hostname</i>	<i>/etc/sysctl.conf</i>	<i>/etc/sysconfig/network-scripts/route-enp0s3</i>
P4	net.ipv4.ip_forward = 1	172.16.3.0/26 via 172.16.3.129 dev enp0s3 172.16.3.64/26 via 172.16.3.129 dev enp0s3

<i>/etc/sysconfig/network</i>	<i>/etc/resolv.conf</i>
NETWORKING=yes HOSTNAME=P4	nameserver 192.168.100.1