

Fișierele de configurare pentru P2

<i>/etc/sysconfig/network-scripts/ifcfg-enp0s3</i>	<i>/etc/sysconfig/network-script-ifcfg-enp0s8</i>
TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s3 DEVICE=enp0s3 ONBOOT=yes IPADDR=172.16.61.3 NETMASK=255.255.255.192 GATEWAY=172.16.61.2	TYPE=Ethernet PROXY_METHOD=none BROWSER_ONLY=no BOOTPROTO=none DEFROUTE=yes NAME=enp0s8 DEVICE=enp0s8 ONBOOT=yes IPADDR=172.16.61.65 NETMASK=255.255.255.192

<i>/etc/ hostname</i>	<i>/etc/sysctl.conf</i>	<i>/etc/sysconfig/network-scripts/route-enp0s8</i>
P2	net.ipv4.ip_forward = 1	172.16.3.128/26 via 172.16.3.66 dev enp0s8 172.16.3.192/27 via 172.16.3.66 dev enp0s8 172.16.3.224/27 via 172.16.3.66 dev enp0s8

<i>/etc/sysconfig/network</i>	<i>/etc/resolv.conf</i>
NETWORKING=yes HOSTNAME=P2	nameserver 192.168.100.1

<i>/etc/sysconfig/iptables</i>
<pre>#Generated by iptables-save v1.4.21 on Thu Dec 3 18:09:28 2020 *nat :PREROUTING ACCEPT [0:0] :INPUT ACCEPT [0:0] :OUTPUT ACCEPT [0:0] :POSTROUTING ACCEPT [0:0] COMMIT # Completed on on Thu Dec 3 18:09:28 2020 # Generated by iptables-save v1.4.21 on Thu Dec 3 18:09:28 2020 *filter :INPUT ACCEPT [0:0] :FORWARD ACCEPT [0:0] :OUTPUT ACCEPT [0:0] -A INPUT -m state --state RELATED,ESTABLISHED -j ACCEPT</pre>

```
-A INPUT -p icmp -j ACCEPT
-A INPUT -i lo -j ACCEPT
-A INPUT -p tcp -m state --state NEW -m tcp --dport 22 -j ACCEPT
-A INPUT -j REJECT --reject-with icmp-host-prohibited
-A FORWARD -i enp0s8 -j ACCEPT
-A FORWARD -i enp0s3 -j ACCEPT
-A FORWARD -j REJECT --reject-with icmp-host-prohibited
COMMIT
```