

The Reachability Problem for Petri Nets is Not Elementary

Wojciech Czerwiński¹, Sławomir Lasota¹, Ranko Lazić²,
Jérôme Leroux³ and Filip Mazowiecki³

¹University of Warsaw

²University of Warwick

³LaBRI

Rennes 2018

The Reachability Problem for Petri Nets is Not Elementary

Wojciech Czerwiński¹, Sławomir Lasota¹, Ranko Lazić²,
Jérôme Leroux³ and Filip Mazowiecki³

¹University of Warsaw

²University of Warwick

³LaBRI

Rennes 2018

Introduction

Petri Nets, VASS, programs with no zero tests


Vector addition systems with states (VASS)

(d, Q, T) , where $T \subseteq Q \times \mathbb{Z}^d \times Q$

Vector addition systems with states (VASS)

(d, Q, T) , where $T \subseteq Q \times \mathbb{Z}^d \times Q$


Example: $d = 3$, $Q = \{p, q\}$



Vector addition systems with states (VASS)

(d, Q, T) , where $T \subseteq Q \times \mathbb{Z}^d \times Q$

Example: $d = 3$, $Q = \{p, q\}$




Configurations $p(\mathbf{v}) = (p, \mathbf{v}) \in Q \times \mathbb{N}^d$

Vector addition systems with states (VASS)

(d, Q, T) , where $T \subseteq Q \times \mathbb{Z}^d \times Q$

Example: $d = 3$, $Q = \{p, q\}$



Configurations $p(\mathbf{v}) = (p, \mathbf{v}) \in Q \times \mathbb{N}^d$


Example run:

$$p(0, 0, 1) \rightarrow p(0, 1, 0) \rightarrow q(0, 1, 0) \rightarrow q(0, 0, 2) \rightarrow p(1, 0, 2)$$

Vector addition systems with states (VASS)

(d, Q, T) , where $T \subseteq Q \times \mathbb{Z}^d \times Q$

Example: $d = 3$, $Q = \{p, q\}$



Configurations $p(\mathbf{v}) = (p, \mathbf{v}) \in Q \times \mathbb{N}^d$

Example run:

$p(0, 0, 1) \rightarrow p(0, 1, 0) \rightarrow q(0, 1, 0) \rightarrow q(0, 0, 2) \rightarrow p(1, 0, 2)$

Notation: $p(0, 0, 1) \rightarrow^* p(1, 0, 2)$

Decision problems

Decision problems

Reachability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether $p(\mathbf{u}) \rightarrow^* q(\mathbf{v})$?

Decision problems

Reachability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether $p(\mathbf{u}) \rightarrow^* q(\mathbf{v})$?

Coverability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether exists \mathbf{v}' s.t. $p(\mathbf{u}) \rightarrow^* q(\mathbf{v}')$ and $\mathbf{v}' \geq \mathbf{v}$?

Decision problems

Reachability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether $p(\mathbf{u}) \rightarrow^* q(\mathbf{v})$?

Coverability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether exists \mathbf{v}' s.t. $p(\mathbf{u}) \rightarrow^* q(\mathbf{v}')$ and $\mathbf{v}' \geq \mathbf{v}$?

- Coverability can be reduced to reachability

Decision problems

Reachability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether $p(\mathbf{u}) \rightarrow^* q(\mathbf{v})$?

Coverability problem:

GIVEN: VASS (d, Q, T) and configurations $p(\mathbf{u}), q(\mathbf{v})$

DECIDE: whether exists \mathbf{v}' s.t. $p(\mathbf{u}) \rightarrow^* q(\mathbf{v}')$ and $\mathbf{v}' \geq \mathbf{v}$?

- Coverability can be reduced to reachability
- We can assume $\mathbf{u} = \mathbf{v} = \mathbf{0}$

Counter programs (with or without zero tests)

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

All variables are initialized to 0, and are never negative

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

All variables are initialized to 0, and are never negative

Example

- 1: $x' \ += B$
- 2: **goto** 6 **or** 3
- 3: $x \ += 1$ $x' \ -= 1$
- 4: $y \ += 2$
- 5: **goto** 2
- 6: **halt if** $x' = 0$.

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

All variables are initialized to 0, and are never negative

Example

1: $x' \ += B$

2: **goto** 6 **or** 3

3: $x \ += 1$ $x' \ -= 1$

4: $y \ += 2$

5: **goto** 2

6: **halt if** $x' = 0$.

$x' \ += B$

loop

$x \ += 1$ $x' \ -= 1$

$y \ += 2$

halt if $x' = 0$.

Counter programs (with or without zero tests)

$x \ += m$	(add m to variable x)
$x \ -= m$	(subtract m from variable x)
goto L or L'	(jump to either line L or line L')
test $x = 0$	(continue if variable x is zero)
halt if $x_1, \dots, x_l = 0$	(terminate if listed variables are zero).

All variables are initialized to 0, and are never negative

Example

1: $x' \ += B$	$x' \ += B$
2: goto 6 or 3	loop
3: $x \ += 1$ $x' \ -= 1$	$x \ += 1$ $x' \ -= 1$
4: $y \ += 2$	$y \ += 2$
5: goto 2	halt if $x' = 0$.
6: halt if $x' = 0$.	

A complete run ends with $x = B$, $y = 2B$

Programs with no zero test = VASS

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.


DECIDE: Does it have a complete run (executing **halt**)?

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?




Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?




$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?



$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$


```
z += 1
loop
  loop
    y += 1    z -= 1
  loop
    y -= 1    z += 2
  x += 1
x -= 1    z -= 2
halt if x, y, z = 0.
```

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?



$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$

z += 1

loop

loop

y += 1 z -= 1

loop

y -= 1 z += 2

x += 1

x -= 1 z -= 2

halt if x, y, z = 0.

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?



$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$

```
z += 1
loop
  loop
    y += 1    z -= 1
  loop
    y -= 1    z += 2
  x += 1
x -= 1    z -= 2
halt if x, y, z = 0.
```

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?



$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$

$z \ += \ 1$

loop

loop

$y \ += \ 1 \quad z \ -= \ 1$

loop

$y \ -= \ 1 \quad z \ += \ 2$

$x \ += \ 1$

$x \ -= \ 1 \quad z \ -= \ 2$

halt if $x, y, z = 0$.

Programs with no zero test = VASS

Reachability problem (for programs):

GIVEN: A counter program with no zero tests.

DECIDE: Does it have a complete run (executing **halt**)?



$p(0, 0, 1) \rightarrow^* p(1, 0, 2)?$

Coverability if **halt** is empty

$z += 1$
loop

```
loop
  y += 1    z -= 1
loop
  y -= 1    z += 2
```

$x += 1$
 $x -= 1$ $z -= 2$
halt if $x, y, z = 0$.

Reachability state of art



Reachability state of art

1976 — EXPSPACE-hard (Lipton)

Reachability state of art

1976 — EXPSPACE-hard (Lipton)

1981 — Decidable (Mayr)

Reachability state of art

A vertical timeline diagram with a central vertical line and three horizontal tick marks. To the left of the line are the years 1976, 1981, and 1982. To the right of the line are the corresponding milestones: EXPSPACE-hard (Lipton), Decidable (Mayr), and Decidable (Kosaraju).


1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)

Reachability state of art

A vertical timeline diagram with a central vertical line. Four horizontal tick marks cross the line at different points, corresponding to the years 1976, 1981, 1982, and 1992. To the left of the line are the years, and to the right are the corresponding reachability results.

1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)
1992	Decidable (Lambert)


Reachability state of art



A vertical timeline illustrating the state of the art in reachability for Petri nets. A central vertical line has horizontal tick marks on either side. To the left of the line are the years, and to the right are the corresponding results and authors.

1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)
1992	Decidable (Lambert)
2009	Decidable (Leroux)
2011	Decidable (Leroux)
2012	Decidable (Leroux)


Reachability state of art



A vertical timeline with a central line and horizontal tick marks. To the left of the line are years, and to the right are descriptions of the reachability state of art.

1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)
1992	Decidable (Lambert)
2009	Decidable (Leroux)
2011	Decidable (Leroux)
2012	Decidable (Leroux)
2015	In \mathbf{F}_{ω^3} (Leroux and Schmitz)


Reachability state of art



A vertical timeline with a central line and horizontal tick marks. To the left of the line are years, and to the right are descriptions of the reachability state of art.

1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)
1992	Decidable (Lambert)
2009	Decidable (Leroux)
2011	Decidable (Leroux)
2012	Decidable (Leroux)
2015	In \mathbf{F}_{ω^3} (Leroux and Schmitz)
2019?	Nonelementary (this talk)


Reachability state of art




A vertical timeline with a central line and horizontal tick marks. To the left of the line are years, and to the right are descriptions of the reachability state of art.

1976	EXPSPACE-hard (Lipton)
1981	Decidable (Mayr)
1982	Decidable (Kosaraju)
1992	Decidable (Lambert)
2009	Decidable (Leroux)
2011	Decidable (Leroux)
2012	Decidable (Leroux)
2015	In \mathbf{F}_{ω^3} (Leroux and Schmitz)
2019?	Nonelementary (this talk)
2019?	In \mathbf{F}_{ω} (Leroux and Schmitz)

Reachability state of art



Reachability state of art



Outline

- High level idea of the proof
- Key construction

Programs with zero tests

Additional command: **test** $x = 0$

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Let k – size of input

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Let k – size of input

Suppose counters are bounded by $B = f(k)$

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Let k – size of input

Suppose counters are bounded by $B = f(k)$

If f is n -EXP, i.e., $f(k) = 2^{\overbrace{\dots 2^k}^{n \text{ times}}}$

Then reachability is $(n - 1)$ -EXPSPACE-complete

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Let k – size of input

Suppose counters are bounded by $B = f(k)$

If f is n -EXP, i.e., $f(k) = 2^{\underbrace{\dots 2^k}_{n \text{ times}}}$

Then reachability is $(n - 1)$ -EXPSPACE-complete

Lipton encoded programs for $f = 2$ -EXP

Programs with zero tests

Additional command: **test** $x = 0$

Reachability becomes undecidable

Let k – size of input

Suppose counters are bounded by $B = f(k)$

If f is n -EXP, i.e., $f(k) = 2^{\underbrace{\dots 2^k}_{n \text{ times}}}$

Then reachability is $(n - 1)$ -EXPSPACE-complete

Lipton encoded programs for $f = 2$ -EXP

We can do it for any $f = n$ -EXP

Encoding programs with zero tests and bounded counters

B – bound on the counters

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding: for every x_i add x'_i

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding: for every x_i add x'_i

Intuitively $x_i + x'_i = B$, so start with:

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding: for every x_i add x'_i

Intuitively $x_i + x'_i = B$, so start with:

loop

$$\begin{array}{l} x'_1 += 1 \quad \cdots \quad x'_l += 1 \\ b -= 1 \end{array}$$

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding: for every x_i add x'_i

Intuitively $x_i + x'_i = B$, so start with:

loop

$x'_1 += 1 \quad \dots \quad x'_l += 1$
 $b -= 1$

Replace $x_i += m$ with $x_i += m \quad x'_i -= m$

Encoding programs with zero tests and bounded counters

B – bound on the counters

We encode this into programs with no zero tests

Suppose we get (magically) three counters b, c, d
initialized to $b = B, c \geq 0, d = c \cdot b$

Encoding: for every x_i add x'_i

Intuitively $x_i + x'_i = B$, so start with:

loop

$x'_1 += 1 \quad \dots \quad x'_l += 1$
 $b -= 1$

Replace $x_i += m$ with $x_i += m \quad x'_i -= m$

Replace $x_i -= m$ with $x_i -= m \quad x'_i += m$

Encoding (continued)

B – bound on the counters

$$b = B, \ c \geq 0, \ d = c \cdot b$$

$$x'_i = B - x_i$$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” · 2

$$x'_i = B - x_i$$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” · 2

$$x'_i = B - x_i$$

Replace **test** $x_i = 0$ with

loop

$$x_i += 1 \quad x'_i -= 1$$

$$d -= 1$$

$$c -= 1$$

loop

$$x_i -= 1 \quad x'_i += 1$$

$$d -= 1$$

$$c -= 1$$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” · 2

$$x'_i = B - x_i$$

Replace **test** $x_i = 0$ with

loop

$$x_i += 1 \quad x'_i -= 1$$

$$d -= 1$$

$$c -= 1$$

loop

$$x_i -= 1 \quad x'_i += 1$$

$$d -= 1$$

$$c -= 1$$

Extend **halt** with $b, d = 0$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” · 2

$x'_i = B - x_i$ ← holds because $b = 0$

Replace **test** $x_i = 0$ with

loop

$x_i += 1 \quad x'_i -= 1$

$d -= 1$

$c -= 1$

loop

$x_i -= 1 \quad x'_i += 1$

$d -= 1$

$c -= 1$

Extend **halt** with $b, d = 0$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” $\cdot 2$

$x'_i = B - x_i$ ← holds because $b = 0$

Replace **test** $x_i = 0$ with

loop	}	c decreased by 2 and d by at most $2B$
$x_i += 1$		
$x'_i -= 1$		
$d -= 1$		
$c -= 1$		
loop		
$x_i -= 1$		
$x'_i += 1$		
$d -= 1$		
$c -= 1$		

Extend **halt** with $b, d = 0$

Encoding (continued)

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$ ← c is “number of zero tests” $\cdot 2$

$x'_i = B - x_i$ ← holds because $b = 0$

Replace **test** $x_i = 0$ with

loop

$x_i += 1 \quad x'_i -= 1$

$d -= 1$

$c -= 1$

loop

$x_i -= 1 \quad x'_i += 1$

$d -= 1$

$c -= 1$

} c decreased by 2 and d by at most $2B$

so a false zero test implies $d \neq 0$

Extend **halt** with $b, d = 0$

Encoding (continued)

B – bound on the counters

$$b = B, c \geq 0, d = c \cdot b$$

c is “number of zero tests” $\cdot 2$

$$x'_i = B - x_i$$

holds because $b = 0$

Replace **test** $x_i = 0$ with

loop

$$x_i += 1 \quad x'_i -= 1$$

$$d -= 1$$

$$c -= 1$$

loop

$$x_i -= 1 \quad x'_i += 1$$

$$d -= 1$$

$$c -= 1$$

c decreased by 2 and d by at most $2B$

so a false zero test implies $d \neq 0$

Extend **halt** with $b, d = 0$

This is the challenge

The main construction

to obtain b , c and d

Recall what we wanted

B – bound on the counters

$$b = B, \ c \geq 0, \ d = c \cdot b$$

Recall what we wanted

B – bound on the counters

$$b = B, \ c \geq 0, \ d = c \cdot b$$

If B is fixed, just start the program with:

$b \ += \ B$

loop

$\quad c \ += \ 1 \quad d \ += \ B$

Recall what we wanted

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$

If B is fixed, just start the program with:

$b \mathrel{+=} B$ ← “gadget for ratio B ”
loop
 $c \mathrel{+=} 1 \quad d \mathrel{+=} B$

Recall what we wanted

B – bound on the counters

$$b = B, c \geq 0, d = c \cdot b$$

If B is fixed, just start the program with:

$b \ += \ B$ ← “gadget for ratio B ”

loop

$c \ += \ 1 \quad d \ += \ B$

But in general we want $B = 2^{\dots^{2^k}}$ } n times.

Recall what we wanted

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$

If B is fixed, just start the program with:

$b \ += \ B$ ← “gadget for ratio B ”

loop

$c \ += \ 1 \quad d \ += \ B$

But in general we want $B = 2^{\dots^{2^k}}$ } n times.

For this we need an iterative construction

Recall what we wanted

B – bound on the counters

$b = B, c \geq 0, d = c \cdot b$

If B is fixed, just start the program with:

$b \ += \ B$ ← “gadget for ratio B ”

loop

$c \ += \ 1 \quad d \ += \ B$

But in general we want $B = 2^{\dots^{2^k}}$ } n times.

For this we need an iterative construction

Some variables will be bounded and allowed to be 0-tested

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

A program with B -bounded 0-tests that ends with

$b \approx 2^B$, $c \geq 0$, $d = c \cdot b$

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

A program with B -bounded 0-tests that ends with

$b \approx 2^B$, $c \geq 0$, $d = c \cdot b$

How to use the lemma:

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

A program with B -bounded 0-tests that ends with

$b \approx 2^B$, $c \geq 0$, $d = c \cdot b$

How to use the lemma:

- By the previous slide we can start with B linear in the input

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

A program with B -bounded 0-tests that ends with

$b \approx 2^B$, $c \geq 0$, $d = c \cdot b$

How to use the lemma:

- By the previous slide we can start with B linear in the input
- Afterwards lift the gadget n times

Gadget for ratio $B = n\text{-EXP}$

$b = B$, $c \geq 0$, $d = c \cdot b$ allows for 0-tests on variables bounded by B

Lemma (lifting the gadget)

Using a gadget for ratio B we can get a gadget for ratio $\approx 2^B$

A program with B -bounded 0-tests that ends with

$b \approx 2^B$, $c \geq 0$, $d = c \cdot b$

How to use the lemma:

- By the previous slide we can start with B linear in the input
- Afterwards lift the gadget n times

A program proving the lemma is what's left

How to use B -bounded 0-tests?

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += i$

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += i$

1: **loop**

2: $x += 1$ $i -= 1$ $i' += 1$

3: **test** $i = 0$

4: **loop**

5: $i += 1$ $i' -= 1$

6: **test** $i' = 0$

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += \boxed{i}$

1: **loop**

2: $x += 1$ $i -= 1$ $i' += 1$

3: **test** $i = 0$

4: **loop**

5: $i += 1$ $i' -= 1$

6: **test** $i' = 0$

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += \boxed{i}$ or $x -= \boxed{i}$

1: **loop**

2: $x += 1$ $i -= 1$ $i' += 1$

3: **test** $i = 0$

4: **loop**

5: $i += 1$ $i' -= 1$

6: **test** $i' = 0$

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += \boxed{i}$ or $x -= \boxed{i}$

1: **loop**

2: $x += 1$ $i -= 1$ $i' += 1$

3: **test** $i = 0$

4: **loop**

5: $i += 1$ $i' -= 1$

6: **test** $i' = 0$

- Or **loop at most b times** $\langle body \rangle$

(b has no bound)

How to use B -bounded 0-tests?

Let $i \leq B$ stored in i , and i' auxiliary (guaranteed to be 0)

- We want e.g.: $x += \boxed{i}$ or $x -= \boxed{i}$

1: **loop**

2: $x += 1$ $i -= 1$ $i' += 1$

3: **test** $i = 0$

4: **loop**

5: $i += 1$ $i' -= 1$

6: **test** $i' = 0$

- Or **loop at most b times** $\langle body \rangle$

(b has no bound)

loop

$b -= 1$ $b' += 1$

loop

$b' -= 1$ $b += 1$

$\langle body \rangle$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

$b += 1, \quad k += B$

loop

$c += 1 \quad d += 1 \quad x += 1 \quad y += 1$

$i += 1 \quad k -= 1$

<main loop>

loop

$x -= i \quad y -= 1$

halt if $y, k = 0$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

$b += 1, \quad k += B$

loop

$c += 1 \quad d += 1 \quad x += 1 \quad y += 1 \quad \leftarrow c, d, x, y := c \cdot B!$

$i += 1 \quad k -= 1$

<main loop>

loop

$x -= i \quad y -= 1$

halt if $y, k = 0$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

$b += 1, \quad k += B$

loop

$c += 1 \quad d += 1 \quad x += 1 \quad y += 1 \quad \leftarrow c, d, x, y := c \cdot B!$

$i += 1 \quad k -= 1$

$\langle \text{main loop} \rangle \leftarrow c := c / (B - 1)!, \quad d, x := d \cdot B, \quad b := b \cdot B!, \quad k = 0, \quad i = B$

loop

$x -= i \quad y -= 1$

halt if $y, k = 0$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

$b += 1, \quad k += B$

loop

$c += 1 \quad d += 1 \quad x += 1 \quad y += 1 \quad \leftarrow c, d, x, y := c \cdot B!$

$i += 1 \quad k -= 1$

<main loop> $\leftarrow c := c/(B-1)!, \quad d, x := d \cdot B, \quad b := b \cdot B!, \quad k = 0, \quad i = B$

loop

$x -= i \quad y -= 1$

halt if $y, k = 0$

Invariants

$i + k = B, \quad b \cdot c = d$

High level description of the program

B – previous bound

Output: $b = B!$, $c \geq 0$, $d = c \cdot b$

Auxiliary variables x, y, k, i (to check correctness)

$b += 1, \quad k += B$

loop

$c += 1 \quad d += 1 \quad x += 1 \quad y += 1 \quad \leftarrow c, d, x, y := c \cdot B!$

$i += 1 \quad k -= 1$

<main loop> $\leftarrow c := c/(B-1)!, \quad d, x := d \cdot B, \quad b := b \cdot B!, \quad k = 0, \quad i = B$

loop

$x -= i \quad y -= 1$

halt if $y, k = 0$

Invariants

$$i + k = B, \quad b \cdot c = d$$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

The main loop

Invariants

$$i + k = B, \quad b \cdot c = d$$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

The main loop

Invariants
 $i + k = B, \quad b \cdot c = d$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

```
1: loop
2:   loop
3:     c -= i    c' += 1
4:     loop at most b times
5:       d -= i    d' += i + 1    x -= i    x' += i + 1
6:   loop
7:     b -= 1    b' += i + 1
8:   loop
9:     b' -= 1    b += 1
10:  loop
11:    c' -= 1    c += 1
12:    loop at most b times
13:      d' -= 1    d += 1    x' -= 1    x += 1
14:  k -= 1    i += 1
```

The main loop

Invariants
 $i + k = B, \quad b \cdot c = d$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

```
1: loop
2:   loop
3:      $c \text{ -- } [i] \quad c' \text{ += } 1$ 
4:     loop at most b times
5:        $d \text{ -- } [i] \quad d' \text{ += } [i+1] \quad x \text{ -- } [i] \quad x' \text{ += } [i+1]$ 
6:   loop
7:      $b \text{ -- } 1 \quad b' \text{ += } [i+1]$ 
8:   loop
9:      $b' \text{ -- } 1 \quad b \text{ += } 1$ 
10:  loop
11:     $c' \text{ -- } 1 \quad c \text{ += } 1$ 
12:    loop at most b times
13:       $d' \text{ -- } 1 \quad d \text{ += } 1 \quad x' \text{ -- } 1 \quad x \text{ += } 1$ 
14:   $k \text{ -- } 1 \quad i \text{ += } 1$ 
```

$$c' := c \cdot \frac{1}{i}, \quad d' := d \cdot \frac{i+1}{i}$$

The main loop

Invariants
 $i + k = B, \quad b \cdot c = d$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

```
1: loop
2:   loop
3:      $c \text{ -- } [i] \quad c' \text{ += } 1$ 
4:     loop at most b times
5:        $d \text{ -- } [i] \quad d' \text{ += } [i+1] \quad x \text{ -- } [i] \quad x' \text{ += } [i+1]$ 
6:   loop
7:      $b \text{ -- } 1 \quad b' \text{ += } [i+1]$ 
8:   loop
9:      $b' \text{ -- } 1 \quad b \text{ += } 1$ 
10:  loop
11:     $c' \text{ -- } 1 \quad c \text{ += } 1$ 
12:    loop at most b times
13:       $d' \text{ -- } 1 \quad d \text{ += } 1 \quad x' \text{ -- } 1 \quad x \text{ += } 1$ 
14:   $k \text{ -- } 1 \quad i \text{ += } 1$ 
```

$$c' := c \cdot \frac{1}{i}, \quad d' := d \cdot \frac{i+1}{i}$$

$$b' := b \cdot (i+1)$$

The main loop

$$\text{Invariants} \\ i + k = B, \quad b \cdot c = d$$

$$\prod_{i=1}^{k-1} \frac{i+1}{i} = k$$

```
1: loop
2:   loop
3:     c -= [i]    c' += 1
4:     loop at most b times
5:       d -= [i]  d' += [i+1]  x -= [i]  x' += [i+1]
6:   loop
7:     b -= 1    b' += [i+1]
8:   loop
9:     b' -= 1    b += 1
10:  loop
11:    c' -= 1    c += 1
12:    loop at most b times
13:      d' -= 1    d += 1    x' -= 1    x += 1
14:  k -= 1    i += 1
```

$$c' := c \cdot \frac{1}{i}, \quad d' := d \cdot \frac{i+1}{i}$$

$$b' := b \cdot (i+1)$$

if any **loop** not maximal
then $x < y \cdot B$

Conclusion

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words
- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words
- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)
Can we do Tower in fixed dimension?

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words
- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)
Can we do Tower in fixed dimension?
- The complexity is almost tight
Unless you believe in things between Tower (\mathbf{F}_3) and Ackermann (\mathbf{F}_ω)

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words
- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)
Can we do Tower in fixed dimension?
- The complexity is almost tight
Unless you believe in things between Tower (\mathbf{F}_3) and Ackermann (\mathbf{F}_ω)
- Can we improve lower bounds of Pushdown-VASS, BVASS...?

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words
- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)
Can we do Tower in fixed dimension?
- The complexity is almost tight
Unless you believe in things between Tower (\mathbf{F}_3) and Ackermann (\mathbf{F}_ω)
- Can we improve lower bounds of Pushdown-VASS, BVASS...?
- This originated from studying 1-Pushdown-VASS

Conclusion

- Several applications and corollaries
e.g. satisfiability of FO2 on data words

- We can do k -EXPSPACE-hardness in dimension $\mathcal{O}(k)$ (so fixed)
Can we do Tower in fixed dimension?

- The complexity is almost tight
Unless you believe in things between Tower (\mathbf{F}_3) and Ackermann (\mathbf{F}_ω)

- Can we improve lower bounds of Pushdown-VASS, BVASS...?

- This originated from studying 1-Pushdown-VASS

So maybe it's good to study restrictions of generalizations of etc. . .