

1. Motivation

- MVL is key for model the complex and heterogeneous EO data sources.
- Some EO sources may not be available: remote sensors have a finite lifetime, satellite missions can fail.
- Re-training the model is not an option.

Our focus: **evaluate** how the predictions of different MVL models are affected.

2. Methodology

We consider a **view** as an entire data source, while MVL a multi-source scenario.

Fusion strategies [1]:

- **Input, Feature, Ensemble.**

Missing views techniques:

- **Impute:** Fill in the missing view with the average from the training data.
 - Using **concatenation** in the fusion
- **Exemplar:** Search for the missing view in the training data using the available views in a shared space (obtained with **CCA embeddings**).
- **Ignore:** Omit the missing views in the aggregation step of the fusion.
 - Using **average** in the fusion

3. Dataset


- **CH-M** [2]: crop-type classification growing in a location (10 classes).
- **LFMC** [3]: predict the vegetation water per dry biomass in a location.

4. Experimental Setting

- 10-fold cross-validation with missing views in the validation fold.

Predictive quality:

- Classification: Average accuracy (AA)
- Regression: Coef. of Determination (R2)



	Samples	Years	Where	Pixel	Temporal views	Static Views
CH-M	29642	2016 - 2022	Global	10 m	Optical, Radar	Topographic
LFMC	2578	2015 - 2019	USA	250 m	Optical Radar	Topographic, land-cover class, canopy height, soil

5. Results

T1. AA for missing views scenarios on the CH-M.		No Missing	Radar	Optical	Weather + static	Radar + weather+static	Optical + weather+static
Impute	Input-concat	0.738	0.641	0.296	0.534	0.534	0.142
	Feature-concat	0.727	0.624	0.290	0.558	0.390	0.159
Exemplar	Feature-cca	0.727	0.285	0.384	0.094	0.107	0.100
Ignore	Feature-avg	0.726	0.674	0.542	0.582	0.529	0.306
	Ensemble-avg	0.715	0.708	0.613	0.711	0.715	0.523

T2. R2 for missing views scenarios on the LFMC.		No Missing	Radar	Optical	Static	Radar + Static	Optical + Static
Impute	Input-concat	0.717	0.650	0.060	0.060	0.165	-0.047
	Feature-concat	0.667	0.599	0.274	0.352	0.290	0.081
Exemplar	Feature-cca	0.667	†	-0.260	†	†	†
Ignore	Feature-avg	0.683	0.618	0.142	†	†	†
	Ensemble-avg	0.312	0.292	0.243	0.407	0.392	0.239


6. Findings

1. Ignoring techniques are the least affected by missing view:
 - **Ensemble-avg** with the highest robustness.
2. The impact of missing views is more severe in **regression** than classification task.
3. Missing **optical view** significantly affects predictions, as well as with static view.

On-going study

- F1. Performance Robustness Score (PRS, [4]) allow relative analysis.
- T3. **Sensor dropout** (randomly drop some EO sources) to the MVL training.

F1. PRS for missing views scenarios on the CH-M.



T3. for CH-M	No Missing	Optical	Weather + static	Radar + weather+static	Optical + weather+static
Input-concat	0.687	0.508	0.683	0.655	0.277
Feature-concat	0.659	0.510	0.591	0.515	0.292
Feature-avg	0.731	0.610	0.720	0.698	0.455

[1] Garnot et al. 2022. Multi-modal temporal attention models for crop mapping from satellite time.

[2] Tseng et al. 2021. CropHarvest: A global dataset for crop-type classification.

[3] Rao et al. 2020. SAR-enhanced mapping of live fuel moisture content.

[4] Heinrich et al. 2023. Targeted adversarial attacks on wind power forecasts.

