

BACKWARD FILTERING FORWARD GUIDING

Frank van der Meulen (Vrije Universiteit Amsterdam)

Moritz Schauer (Chalmers University of Technology & University of Gothenburg)

Algorithms and Computationally Intensive Inference Seminar (ACIIS)

Warwick, December 2 (2022)

General problem setting

Conditioning, Doob's h -transform and the Backward Information Filter

Guided process

- Discrete case

- Numerical illustration

- Continuous time transitions


- Numerical illustration

Wrap-up / conclusions

General problem setting

Problem setting


Consider a directed *Markovian* tree:



- latent vertices, \circ leaf/observation-vertices.

Problem setting

Consider a directed *Markovian* tree:



- latent vertices, \circ leaf/observation-vertices.

To each edge corresponds a Markov kernel $\kappa_{\rightarrow t}(x_{\text{pa}(t)}, dx_t)$.

Problem setting

Think of either a discrete- or continuous-time Markov process evolving over edges.


Problem setting

Think of either a discrete- or continuous-time Markov process evolving over edges.

We aim for

1. sampling values at \bullet , conditional on values at \circ ;
2. estimating parameters in kernels;
3. not just on a tree, but on a general Directed Acyclic Graph (DAG).

Example of a DAG



Example 1: interacting particle process

Setup:

- population of n individuals;
- each individual is either **S**usceptible, **I**nfectious or **R**ecovered;
- each individual has a known (possibly time varying) set of neighbours .

Example 1: interacting particle process

Setup:

- population of n individuals;
- each individual is either **S**usceptible, **I**nfectious or **R**ecovered;
- each individual has a known (possibly time varying) set of neighbours .

Dynamics:

- If $x_i = \mathbf{S}$, then it transitions to **I** with intensity $\lambda N_i(t, x)$, with $N_i(t, x)$ number of infected neighbours of individual i at time t .

Example 1: interacting particle process

Setup:

- population of n individuals;
- each individual is either **S**usceptible, **I**nfected or **R**ecovered;
- each individual has a known (possibly time varying) set of neighbours .

Dynamics:

- If $x_i = \mathbf{S}$, then it transitions to **I** with intensity $\lambda N_i(t, x)$, with $N_i(t, x)$ number of infected neighbours of individual i at time t .
- If $x_i = \mathbf{I}$, then it transitions to **R** with intensity μ .

Example 1: interacting particle process

Setup:

- population of n individuals;
- each individual is either **S**usceptible, **I**nfectious or **R**ecovered;
- each individual has a known (possibly time varying) set of neighbours .

Dynamics:

- If $x_i = \mathbf{S}$, then it transitions to **I** with intensity $\lambda N_i(t, x)$, with $N_i(t, x)$ number of infected neighbours of individual i at time t .
- If $x_i = \mathbf{I}$, then it transitions to **R** with intensity μ .
- If $x_i = \mathbf{R}$, it transitions to **S** with intensity ν .

Example 1: Dynamics of each particle

- Time-discretised version of the problem, where time steps are multiples of $\tau > 0$.

Example 1: Dynamics of each particle

- Time-discretised version of the problem, where time steps are multiples of $\tau > 0$.
- In each time interval of length τ , conditional on the the present state of *all* individuals, each individual independently transitions.

Example 1: Dynamics of each particle


- Time-discretised version of the problem, where time steps are multiples of $\tau > 0$.
- In each time interval of length τ , conditional on the the present state of *all* individuals, each individual independently transitions.

The transition matrix for individual i at time t , given “full state” x :


$$\kappa_i(t, x) = \begin{bmatrix} \psi(\lambda N_i(t, x)) & 1 - \psi(\lambda N_i(t, x)) & 0 \\ 0 & \psi(\mu) & 1 - \psi(\mu) \\ 1 - \psi(\nu) & 0 & \psi(\nu) \end{bmatrix},$$

where $\psi(u) = \exp(-\tau u)$

Example 1: data and challenges



Example 1: data and challenges



Observe state of each individual at times $t_0 < t_1 < \dots t_n$.

Goals:

- identify most probable latent states (partial observations...);
- estimate rate parameters λ , μ and ν .

Example 1: data and challenges



Dimension of state-space is 3^n .

Example 1: data and challenges

⚠ Dimension of state-space is 3^n .

Variation: observe

$$V_{t_i} \sim \text{Bin}(I(X_{t_i}), \rho),$$

with $I(X_{t_i})$ the number of infected individuals at time t_i .

Example 1: data and challenges

⚠ Dimension of state-space is 3^n .

Variation: observe

$$V_{t_i} \sim \text{Bin}(I(X_{t_i}), \rho),$$

with $I(X_{t_i})$ the number of infected individuals at time t_i .

JU, HENG, JACOB – Sequential Monte Carlo algorithms for agent-based models of disease transmission

Example 2: Wright-Fisher diffusion on a tree

Diffusion approximation to Wright-Fisher model (with mutation) for N diploid individuals.

Consider a directed tree where along each branch

$$dX_t = (\beta_1(1 - X_t) + \beta_2 X_t) dt + \sqrt{X_t(1 - X_t)} dW_t.$$

At a leaf vertex observe $V \sim \text{Bin}(2n, x)$, where x is the state at the parent vertex.

Example 2: Wright-Fisher diffusion on a tree

Diffusion approximation to Wright-Fisher model (with mutation) for N diploid individuals.

Consider a directed tree where along each branch

$$dX_t = (\beta_1(1 - X_t) + \beta_2 X_t) dt + \sqrt{X_t(1 - X_t)} dW_t.$$


At a leaf vertex observe $V \sim \text{Bin}(2n, x)$, where x is the state at the parent vertex.

Wish to

- reconstruct X_t along edges;
- estimate parameters (β_1, β_2) .


STOLTZ ET AL. – Bayesian inference of species trees using diffusion models

State-space models / hidden Markov models



Well-known filtering, smoothing algorithms dating back to 1960-1970.


State-space models / hidden Markov models



Well-known filtering, smoothing algorithms dating back to 1960-1970.

- **Finite state space:** Baum-Welch, Viterbi, forward-backward algorithm.
- **Linear Gaussian models:** Kalman filter, Rauch-Tung-Striebel smoother.
- **Linear stochastic differential equations:** Kalman-Bucy filter & smoother.

State-space models / hidden Markov models



Well-known filtering, smoothing algorithms dating back to 1960-1970.

- **Finite state space:** Baum-Welch, Viterbi, forward-backward algorithm.
- **Linear Gaussian models:** Kalman filter, Rauch-Tung-Striebel smoother.
- **Linear stochastic differential equations:** Kalman-Bucy filter & smoother.


More recently much work on **SMC**
(twisted particle samplers, controlled SMC).

Conditioning, Doob's h -transform and the Backward Information Filter

Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.




Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.

Key identity (Bayesian notation):


$$p(x_t \mid x_{\text{pa}(t)}, x_{\mathcal{V}_t})$$



Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.




Key identity (Bayesian notation):

$$p(x_t \mid x_{\text{pa}(t)}, x_{\mathcal{V}_t}) \propto p(x_t, x_{\mathcal{V}_t} \mid x_{\text{pa}(t)})$$
$$=$$

Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.




Key identity (Bayesian notation):

$$\begin{aligned} p(x_t \mid x_{\text{pa}(t)}, x_{\mathcal{V}_t}) &\propto p(x_t, x_{\mathcal{V}_t} \mid x_{\text{pa}(t)}) \\ &= p(x_t \mid x_{\text{pa}(t)}) \underbrace{p(x_{\mathcal{V}_t} \mid x_t, x_{\text{pa}(t)})}_{h_t(x_t)} \end{aligned}$$

Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.



Key identity (Bayesian notation):

$$\begin{aligned} p(x_t \mid x_{\text{pa}(t)}, x_{\mathcal{V}_t}) &\propto p(x_t, x_{\mathcal{V}_t} \mid x_{\text{pa}(t)}) \\ &= p(x_t \mid x_{\text{pa}(t)}) \underbrace{p(x_{\mathcal{V}_t} \mid x_t, x_{\text{pa}(t)})}_{h_t(x_t)} \end{aligned}$$


Rewrite to

$$\boxed{\kappa_{\rightarrow t}^*(x; \text{d}y) \propto \kappa_{\rightarrow t}(x; \text{d}y) h_t(y)}.$$

Conditioning on a tree

Define

- \mathcal{V}_t : all leaf descendants of vertex t .
- $\mathcal{V}_t = \{v_1, v_2\}$.



Key identity (Bayesian notation):

$$\begin{aligned} p(x_t \mid x_{\text{pa}(t)}, x_{\mathcal{V}_t}) &\propto p(x_t, x_{\mathcal{V}_t} \mid x_{\text{pa}(t)}) \\ &= p(x_t \mid x_{\text{pa}(t)}) \underbrace{p(x_{\mathcal{V}_t} \mid x_t, x_{\text{pa}(t)})}_{h_t(x_t)} \end{aligned}$$

Rewrite to

$$\boxed{\kappa_{\rightarrow t}^*(x; \text{d}y) \propto \kappa_{\rightarrow t}(x; \text{d}y) h_t(y)}.$$

⚠ Within the subtree, $h_t(x_t)$ is the likelihood of x_t .

Doob's h -transform

- *Doob's h -transform*: Transformation of each κ_s with h_s to κ_s^* :

$$\kappa_{\rightarrow s}^*(x, dy) = \frac{\kappa_{\rightarrow s}(x, dy)h_s(y)}{\int \kappa_{\rightarrow s}(x, dy)h_s(y)}, \quad s \in \mathcal{S}.$$

A forward pass: Needs $\kappa_{\rightarrow s}$ and h_s .

Doob's h -transform

- *Doob's h -transform*: Transformation of each κ_s with h_s to κ_s^* :

$$\kappa_{\rightarrow s}^*(x, dy) = \frac{\kappa_{\rightarrow s}(x, dy)h_s(y)}{\int \kappa_{\rightarrow s}(x, dy)h_s(y)}, \quad s \in \mathcal{S}.$$

A forward pass: Needs $\kappa_{\rightarrow s}$ and h_s .

- Recursive computation of h_s in a backward pass: (Backward Information Filter):
 - Compute h_s from the leaves back to the roots.
 - Acyclic belief propagation, sum-product algorithm, Felsenstein algorithm...

Doob's h -transform

- *Doob's h -transform*: Transformation of each κ_s with h_s to κ_s^* :

$$\kappa_{\rightarrow s}^*(x, dy) = \frac{\kappa_{\rightarrow s}(x, dy)h_s(y)}{\int \kappa_{\rightarrow s}(x, dy)h_s(y)}, \quad s \in \mathcal{S}.$$

A forward pass: Needs $\kappa_{\rightarrow s}$ and h_s .

- Recursive computation of h_s in a backward pass: (Backward Information Filter):
 - Compute h_s from the leaves back to the roots.
 - Acyclic belief propagation, sum-product algorithm, Felsenstein algorithm...
 - ⚠ Only in very specific models tractable.

Doob's h -transform


- *Doob's h -transform*: Transformation of each κ_s with h_s to κ_s^* :

$$\kappa_{\rightarrow s}^*(x, dy) = \frac{\kappa_{\rightarrow s}(x, dy)h_s(y)}{\int \kappa_{\rightarrow s}(x, dy)h_s(y)}, \quad s \in \mathcal{S}.$$


A forward pass: Needs $\kappa_{\rightarrow s}$ and h_s .

- Recursive computation of h_s in a backward pass: (Backward Information Filter):
 - Compute h_s from the leaves back to the roots.
 - Acyclic belief propagation, sum-product algorithm, Felsenstein algorithm...
 - ⚠ Only in very specific models tractable.
- ⚠ On a DAG conditioning changes the dependency structure.
There are **no** conditional kernels $\kappa_{\rightarrow s}^*$ from $\text{pa}(s)$ to s .

Backward Information Filter



Make kernels explicit



Example: finite state space

- Suppose $x_t \in \{\textcircled{1}, \textcircled{2}, \textcircled{3}\}$ and $v_t \in \{\textcircled{1,2}, \textcircled{3}\}$.

Idea: in observations we cannot distinguish $\textcircled{1}$ and $\textcircled{2}$

Example: finite state space

- Suppose $x_t \in \{\textcircled{1}, \textcircled{2}, \textcircled{3}\}$ and $v_t \in \{\textcircled{1,2}, \textcircled{3}\}$.

Idea: in observations we cannot distinguish $\textcircled{1}$ and $\textcircled{2}$

- Finite state space \implies Markov kernels can be identified with matrices

$$\lambda_i = \begin{bmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \kappa_{s,t} = \begin{bmatrix} 1 - \theta & \theta & 0 \\ 0.25 & 0.5 & 0.25 \\ 0.4 & 0.3 & 0.3 \end{bmatrix},$$

for $i \in \{1, 2, 3\}$, $s \in \{0, 1, 3\}$ and $t \in \text{ch}(s)$.

Example: finite state space

- Suppose $x_t \in \{\textcircled{1}, \textcircled{2}, \textcircled{3}\}$ and $v_t \in \{\textcircled{1,2}, \textcircled{3}\}$.

Idea: in observations we cannot distinguish $\textcircled{1}$ and $\textcircled{2}$

- Finite state space \implies Markov kernels can be identified with matrices

$$\lambda_i = \begin{bmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \kappa_{s,t} = \begin{bmatrix} 1-\theta & \theta & 0 \\ 0.25 & 0.5 & 0.25 \\ 0.4 & 0.3 & 0.3 \end{bmatrix},$$

for $i \in \{1, 2, 3\}$, $s \in \{0, 1, 3\}$ and $t \in \text{ch}(s)$.


- Prior on initial state:** set $x_{-1} = \textcircled{0}$ and

$$\kappa_{-1,0} = [\pi_1, \pi_2, \pi_3] =: \boldsymbol{\pi}.$$


Backward Information Filter (BIF)

- **BIF**: efficient way to compute $x \mapsto h_t(x)$.

Backward Information Filter (BIF)


- **BIF**: efficient way to compute $x \mapsto h_t(x)$.
-  For finite state space this map can be identified with a vector h_t .

Backward Information Filter (BIF)

- **BIF**: efficient way to compute $x \mapsto h_t(x)$.
-  For finite state space this map can be identified with a vector h_t .
- **Initialise from observations**: for $t = 1, 2, 3$

$$h_t^{\text{obs}} := \begin{bmatrix} 1 \\ 0 \end{bmatrix} \mathbf{1}\{v_t = \textcircled{1,2}\} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} \mathbf{1}\{v_t = \textcircled{3}\}.$$


Pullback along edges



$$h_2 = \lambda_3 h_3^{\text{obs}}$$

$$h_1 = \kappa_{1,2} h_2.$$

Pullback along edges




$$h_2 = \lambda_3 h_3^{\text{obs}}$$

$$h_1 = \kappa_{1,2} h_2.$$

$$h_1(x_1) = p(v_3 \mid x_1) =$$


Pullback along edges



$$h_2 = \lambda_3 h_3^{\text{obs}} \quad h_1 = \kappa_{1,2} h_2.$$

$$h_1(x_1) = p(v_3 \mid x_1) = \sum_{x_2} p(v_3, x_2 \mid x_1)$$

Pullback along edges




$$h_2 = \lambda_3 h_3^{\text{obs}}$$

$$h_1 = \kappa_{1,2} h_2.$$

$$\begin{aligned} h_1(x_1) = p(v_3 \mid x_1) &= \sum_{x_2} p(v_3, x_2 \mid x_1) \\ &= \sum_{x_2} \underbrace{p(v_3 \mid x_1, x_2)}_{h_2(x_2)} p(x_2 \mid x_1). \end{aligned}$$


Backward Information Filter (BIF)



Get

$$h_{0 \rightarrow 3} = \kappa_{0,3} h_3 \quad \text{and} \quad h_{0 \rightarrow 1} = \kappa_{0,1} h_1$$

Backward Information Filter (BIF)




Get

$$h_{0 \rightarrow 3} = \kappa_{0,3} h_3 \quad \text{and} \quad h_{0 \rightarrow 1} = \kappa_{0,1} h_1$$

Fusion: by conditional independence of children we have

$$h_0(x) = h_{0 \rightarrow 1}(x) h_{0 \rightarrow 3}(x).$$

Backward Information Filter (BIF)



Get

$$h_{0 \rightarrow 3} = \kappa_{0,3} h_3 \quad \text{and} \quad h_{0 \rightarrow 1} = \kappa_{0,1} h_1$$

Fusion: by conditional independence of children we have

$$h_0(x) = h_{0 \rightarrow 1}(x) h_{0 \rightarrow 3}(x).$$

By identifying with vectors

$$h_0 = h_{0 \rightarrow 1} \odot h_{0 \rightarrow 3}.$$

Backward Information Filter (BIF)

- Likelihood: $L(\theta) := h_{-1} = \kappa_{-1,0} h_0$.

Backward Information Filter (BIF)

- Likelihood: $L(\theta) := h_{-1} = \kappa_{-1,0} h_0$.
- Forward simulate:

$$x_t^* \mid x_s^* = i \sim \text{Cat}(\kappa_{s,t}[i,] \odot h_t), \quad t \in \text{ch}(s).$$

Backward Information Filter (BIF)

- Likelihood: $L(\theta) := h_{-1} = \kappa_{-1,0} h_0$.
- Forward simulate:

$$x_t^* \mid x_s^* = i \sim \text{Cat}(\kappa_{s,t}[i,] \odot h_t), \quad t \in \text{ch}(s).$$

⚠ This is all tractable because

1. the DAG is a directed tree;
2. the state space is finite.

There is essentially just one operation...

- Along an edge compute

$$h(x) = \int \kappa(x, \mathrm{d}y) h(y).$$

There is essentially just one operation...

- Along an edge compute

$$h(x) = \int \kappa(x, dy) h(y).$$

- At splits, make k -fold copy using kernel

$$\triangleleft_k(x, dy) = \delta_x(dy_1) \dots, \delta_x(dy_k).$$

There is essentially just one operation...

- Along an edge compute

$$h(x) = \int \kappa(x, dy) h(y).$$

- At splits, make k -fold copy using kernel

$$\triangleleft_k(x, dy) = \delta_x(dy_1) \dots, \delta_x(dy_k).$$

Then in BIF, with $h_{1,3}(y) = h_{0 \rightarrow 1}(y_1)h_{0 \rightarrow 3}(y_2)$, we get

$$h_0(x) = \int \triangleleft_2(x, dy) h_{1,3}(y) =$$

There is essentially just one operation...

- Along an edge compute

$$h(x) = \int \kappa(x, dy) h(y).$$

- At splits, make k -fold copy using kernel

$$\triangleleft_k(x, dy) = \delta_x(dy_1) \dots, \delta_x(dy_k).$$

Then in BIF, with $h_{1,3}(y) = h_{0 \rightarrow 1}(y_1)h_{0 \rightarrow 3}(y_2)$, we get

$$h_0(x) = \int \triangleleft_2(x, dy) h_{1,3}(y) = h_{0 \rightarrow 1}(x) h_{0 \rightarrow 3}(x).$$

Natural to convert DAG to string diagram...


Guided process

Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.


Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.




Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.



Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.




Get

$$h_{0 \rightarrow 3} = \kappa_{0,3} h_3 \quad \text{and} \quad h_{0 \rightarrow 1} = \kappa_{0,1} h_1$$

Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.




Get

$$h_{0 \rightarrow 3} = \tilde{\kappa}_{0,3} h_3 \quad \text{and} \quad h_{0 \rightarrow 1} = \tilde{\kappa}_{0,1} h_1$$

Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.




Get

$$g_{0 \rightarrow 3} = \tilde{\kappa}_{0,3} g_3 \quad \text{and} \quad g_{0 \rightarrow 1} = \tilde{\kappa}_{0,1} g_1$$

Backward Information Filter (BIF)

Key idea: replace $h_{s \rightarrow t}$ by $g_{s \rightarrow t}$ that makes BIF tractable.



Get

$$g_{0 \rightarrow 3} = \tilde{\kappa}_{0,3} g_3 \quad \text{and} \quad g_{0 \rightarrow 1} = \tilde{\kappa}_{0,1} g_1$$

Fusion: by conditional independence of children we have

$$g_0(x) = g_{0 \rightarrow 1}(x) g_{0 \rightarrow 3}(x).$$

By identifying with vectors

$$g_0 = g_{0 \rightarrow 1} \odot g_{0 \rightarrow 3}.$$

Let the maps $x \mapsto g_{s \rightarrow t}(x)$ be specified for each edge (s, t) and define

$$g_s(x) = \prod_{t \in \text{ch}(s)} g_{s \rightarrow t}(x), \quad s \in \mathcal{S}_0. \quad (1)$$

Let the maps $x \mapsto g_{s \rightarrow t}(x)$ be specified for each edge (s, t) and define

$$g_s(x) = \prod_{t \in \text{ch}(s)} g_{s \rightarrow t}(x), \quad s \in \mathcal{S}_0. \quad (1)$$

Practical way to choose $g_{s \rightarrow t}$: replace kernel $\kappa_{s \rightarrow t}$ by approximation $\tilde{\kappa}_{s \rightarrow t}$.

Let the maps $x \mapsto g_{s \rightarrow t}(x)$ be specified for each edge (s, t) and define

$$g_s(x) = \prod_{t \in \text{ch}(s)} g_{s \rightarrow t}(x), \quad s \in \mathcal{S}_0. \quad (1)$$

Practical way to choose $g_{s \rightarrow t}$: replace kernel $\kappa_{s \rightarrow t}$ by approximation $\tilde{\kappa}_{s \rightarrow t}$.

Define the **guided process** X° as the process starting in $X_0^\circ = x_0$ and from the roots onwards evolving *on* the DAG \mathcal{G} according to transition kernel

$$\kappa_{\text{pa}(s) \rightarrow s}^\circ(x_{\text{pa}(s)}; dy) = \frac{g_s(y) \kappa_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}; dy)}{\int g_s(y) \kappa_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}; dy)}, \quad s \in \mathcal{S}.$$

Use of guided process

Let \mathcal{S} denote the set of non-leaf vertices.

Theorem. Assume kernels towards leaf-nodes admit densities $h_{\text{pa}(v) \rightarrow v}$.
Then

$$h_0(x_0) = g_0(x_0) \mathbb{E} \left[\prod_{s \in \mathcal{S}} w_{\text{pa}(s) \rightarrow s}(X_{\text{pa}(s)}^\circ) \prod_{v \in \mathcal{V}} \frac{h_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)}{g_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)} \right]$$

with weights defined by

Use of guided process

Let \mathcal{S} denote the set of non-leaf vertices.

Theorem. Assume kernels towards leaf-nodes admit densities $h_{\text{pa}(v) \rightarrow v}$.
Then

$$h_0(x_0) = g_0(x_0) \mathbb{E} \left[\prod_{s \in \mathcal{S}} w_{\text{pa}(s) \rightarrow s}(X_{\text{pa}(s)}^\circ) \prod_{v \in \mathcal{V}} \frac{h_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)}{g_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)} \right]$$

with weights defined by

$$w_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}) = \frac{\int g_s(y) \kappa_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}; dy)}{\prod_{u \in \text{pa}(s)} g_{u \rightarrow s}(x_u)} \quad s \in \mathcal{S}.$$

Use of guided process

Let \mathcal{S} denote the set of non-leaf vertices.

Theorem. Assume kernels towards leaf-nodes admit densities $h_{\text{pa}(v) \rightarrow v}$.
Then


$$h_0(x_0) = g_0(x_0) \mathbb{E} \left[\prod_{s \in \mathcal{S}} w_{\text{pa}(s) \rightarrow s}(X_{\text{pa}(s)}^\circ) \prod_{v \in \mathcal{V}} \frac{h_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)}{g_{\text{pa}(v) \rightarrow v}(X_{\text{pa}(v)}^\circ)} \right]$$


with weights defined by

$$w_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}) = \frac{\int g_s(y) \kappa_{\text{pa}(s) \rightarrow s}(x_{\text{pa}(s)}; dy)}{\prod_{u \in \text{pa}(s)} g_{u \rightarrow s}(x_u)} \quad s \in \mathcal{S}.$$

Computationally, this implies a **bidirectional scheme**:

1. **Backward** pass for **Filtering**;
2. **Forward** pass for **Guiding**.

- If the state space is finite, BIF provides the likelihood.
- Key to tractability is that h can always be represented as a vector.
-  In general BIF is intractable.

- If the state space is finite, BIF provides the likelihood.
- Key to tractability is that h can always be represented as a vector.
-  In general BIF is intractable.
- Resolve by **backward filtering with simpler kernels** and forward simulating the corresponding **guided process**.
- This results in **weighted samples from the conditioned process**.

Application: interacting particle process

Forward transitions:

$$\kappa_i(t, x) = \begin{bmatrix} \psi(\lambda N_i(t, x)) & 1 - \psi(\lambda N_i(t, x)) & 0 \\ 0 & \psi(\mu) & 1 - \psi(\mu) \\ 1 - \psi(\nu) & 0 & \psi(\nu) \end{bmatrix},$$

where

$N_i(x) = \{\text{number of infected neighbours of individual } i \text{ in state } x\}$


and $\psi(u) = \exp(-\tau u)$.

Auxiliary kernel for backward filtering:


$$\tilde{\kappa}_i = \begin{bmatrix} \psi(\tilde{\lambda}_i(t)) & 1 - \psi(\tilde{\lambda}_i(t)) & 0 \\ 0 & \psi(\mu) & 1 - \psi(\mu) \\ 1 - \psi(\nu) & 0 & \psi(\nu) \end{bmatrix}.$$

Application: interacting particle process


initial iterate




middle iterate




final iterate



true forward simulated



Application: interacting particle process



Continuous time transitions

Rethinking the discrete-time case:

- Edge



Suppose $x \mapsto h(T, x)$ is given; wish to find $x \mapsto h(S, x)$.

Continuous time transitions

Rethinking the discrete-time case:

- Edge



Suppose $x \mapsto h(T, x)$ is given; wish to find $x \mapsto h(S, x)$.

- “Discrete-time” generator

$$(\mathcal{A}h)(S, x) : = \mathbb{E}[h(T, X_T) - h(S, X_S) \mid X_S = x]$$

Continuous time transitions

Rethinking the discrete-time case:


- Edge



Suppose $x \mapsto h(T, x)$ is given; wish to find $x \mapsto h(S, x)$.

- “Discrete-time” generator

$$\begin{aligned}(\mathcal{A}h)(S, x) : &= \mathbb{E}[h(T, X_T) - h(S, X_S) \mid X_S = x] \\ &= \int h(T, y) \kappa_{S \rightarrow T}(x, dy) - h(S, x).\end{aligned}$$

-  Obtain $x \mapsto h(S, x)$ by solving $(\mathcal{A}h)(S, x) = 0$.

Continuous time transitions

Define the **infinitesimal generator** of the space-time process (t, X_t) : for $S \leq s < s + h \leq T$

$$\begin{aligned}(\mathcal{A}h)(s, x) &= \lim_{h \downarrow 0} h^{-1} \mathbb{E}[h(s + h, X_{s+h}) - h(s, X_s) \mid X_s = x] \\ &= \end{aligned}$$

Continuous time transitions

Define the **infinitesimal generator** of the space-time process (t, X_t) : for $S \leq s < s + h \leq T$

$$\begin{aligned}(\mathcal{A}h)(s, x) &= \lim_{h \downarrow 0} h^{-1} \mathbb{E}[h(s + h, X_{s+h}) - h(s, X_s) \mid X_s = x] \\ &= (\mathcal{L}h)(s, x) + \frac{\partial}{\partial s} h(s, x).\end{aligned}$$

Continuous time transitions

Define the **infinitesimal generator** of the space-time process (t, X_t) : for $S \leq s < s + h \leq T$

$$\begin{aligned}(\mathcal{A}h)(s, x) &= \lim_{h \downarrow 0} h^{-1} \mathbb{E}[h(s + h, X_{s+h}) - h(s, X_s) \mid X_s = x] \\ &= (\mathcal{L}h)(s, x) + \frac{\partial}{\partial s} h(s, x).\end{aligned}$$

- Obtain $x \mapsto h(S, x)$ from solving

$$(\mathcal{A}h)(s, x) = 0 \quad \text{subject to} \quad h(T, \cdot).$$

Continuous time transitions

Define the **infinitesimal generator** of the space-time process (t, X_t) : for $S \leq s < s + h \leq T$

$$\begin{aligned}(\mathcal{A}h)(s, x) &= \lim_{h \downarrow 0} h^{-1} \mathbb{E}[h(s + h, X_{s+h}) - h(s, X_s) \mid X_s = x] \\ &= (\mathcal{L}h)(s, x) + \frac{\partial}{\partial s} h(s, x).\end{aligned}$$

- Obtain $x \mapsto h(S, x)$ from solving

$$(\mathcal{A}h)(s, x) = 0 \quad \text{subject to} \quad h(T, \cdot).$$

- h induces a change of measure from X to the process X^* with inf. generator

$$h\mathcal{L}^*f = \mathcal{L}(fh) - f\mathcal{L}h.$$

Continuous time transitions

Define the **infinitesimal generator** of the space-time process (t, X_t) : for $S \leq s < s + h \leq T$

$$\begin{aligned}(\mathcal{A}h)(s, x) &= \lim_{h \downarrow 0} h^{-1} \mathbb{E}[h(s + h, X_{s+h}) - h(s, X_s) \mid X_s = x] \\ &= (\mathcal{L}h)(s, x) + \frac{\partial}{\partial s} h(s, x).\end{aligned}$$

- Obtain $x \mapsto h(S, x)$ from solving

$$(\mathcal{A}h)(s, x) = 0 \quad \text{subject to} \quad h(T, \cdot).$$

- h induces a change of measure from X to the process X^* with inf. generator

$$h\mathcal{L}^*f = \mathcal{L}(fh) - f\mathcal{L}h.$$

 Solving Kolmogorov backward equation is usually intractable.

Defining the guided process via its inf.generator

- Backward filter with $\tilde{\mathcal{L}}$ instead of \mathcal{L} , such that solving $(\tilde{\mathcal{L}}g)(s, x) + \frac{\partial}{\partial s}g(s, x) = 0$ becomes tractable.

Defining the guided process via its inf.generator

- Backward filter with $\tilde{\mathcal{L}}$ instead of \mathcal{L} , such that solving $(\tilde{\mathcal{L}}g)(s, x) + \frac{\partial}{\partial s}g(s, x) = 0$ becomes tractable.
- g induces a change of measure from X to X° with inf. generator

$$g\mathcal{L}^\circ f = \mathcal{L}(fg) - f\mathcal{L}g$$

Identify **guided process** from \mathcal{L}° .

Defining the guided process via its inf.generator

- Backward filter with $\tilde{\mathcal{L}}$ instead of \mathcal{L} , such that solving $(\tilde{\mathcal{L}}g)(s, x) + \frac{\partial}{\partial s}g(s, x) = 0$ becomes tractable.
- g induces a change of measure from X to X° with inf. generator

$$g\mathcal{L}^\circ f = \mathcal{L}(fg) - f\mathcal{L}g$$

Identify **guided process** from \mathcal{L}° .

- Correct for “wrong” h by weight

$$\exp \left(\int_{t_i}^{t_{i+1}} \frac{(\mathcal{L} - \tilde{\mathcal{L}})g}{g}(u, X_u^\circ) du \right).$$

- Care is needed in choice of $\tilde{\mathcal{L}}$: **matching conditions**.

How to solve the Kolmogorov Backward Equation?


For $s \in (S, T]$,

$$(\tilde{\mathcal{L}}g)(s, x) + \frac{\partial}{\partial s}g(s, x) = 0, \quad g(T, \cdot) = g_T(\cdot).$$

Examples/strategies:

1. If $\tilde{\mathcal{L}}$ is the infinitesimal generator of a linear diffusion process, then $\log g(t, x) = c(t) + F(t)'x + x'H(t)x$ with ODE-system for $(H(t), F(t), c(t))$.
2. Ansatz $g(t, x) = \sum_j c(t)\psi_j(t)$. Derive ODE for $c(t)$.


Example: branching diffusion




SDE on a tree where on each branch

$$dX_t = \tanh \cdot \left(\begin{bmatrix} -\theta_1 & \theta_1 \\ \theta_2 & -\theta_2 \end{bmatrix} X_t \right) dt + \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} dW_t.$$

Numerical illustration: SDE on a tree



Numerical illustration: SDE on a tree



Numerical illustration: SDE on a tree

On each branch

$$dX_t = \tanh. \left(\begin{bmatrix} -\theta_1 & \theta_1 \\ \theta_2 & -\theta_2 \end{bmatrix} X_t \right) dt + \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} dW_t.$$

Numerical illustration: SDE on a tree

On each branch

$$dX_t = \tanh. \left(\begin{bmatrix} -\theta_1 & \theta_1 \\ \theta_2 & -\theta_2 \end{bmatrix} X_t \right) dt + \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} dW_t.$$

- Backward filter a linear process (essentially $\tilde{\kappa}$)

Numerical illustration: SDE on a tree

On each branch

$$dX_t = \tanh. \left(\begin{bmatrix} -\theta_1 & \theta_1 \\ \theta_2 & -\theta_2 \end{bmatrix} X_t \right) dt + \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} dW_t.$$

- Backward filter a linear process (essentially $\tilde{\kappa}$)
- Write X° as pushforward of (x_0, ξ, Z) , with $\xi = (\theta_1, \theta_2, \sigma_1, \sigma_2)$
- MCMC on (ξ, Z)

Numerical illustration: SDE on a tree


On each branch

$$dX_t = \tanh. \left(\begin{bmatrix} -\theta_1 & \theta_1 \\ \theta_2 & -\theta_2 \end{bmatrix} X_t \right) dt + \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} dW_t.$$


- Backward filter a linear process (essentially $\tilde{\kappa}$)
- Write X° as pushforward of (x_0, ξ, Z) , with $\xi = (\theta_1, \theta_2, \sigma_1, \sigma_2)$
- MCMC on (ξ, Z)

Implementation in `MitosisStochasticDiffEq.jl` by [Frank Schäfer](#) (MIT).

Numerical illustration: SDE on a tree



Numerical illustration: SDE on a tree



Wrap-up / conclusions

Backward Filtering Forward Guiding: framework for doing likelihood based inference in directed acyclic graphs, where transitions over edges may correspond to the evolution of a stochastic process for a certain time span.

Backward Filtering Forward Guiding: framework for doing likelihood based inference in directed acyclic graphs, where transitions over edges may correspond to the evolution of a stochastic process for a certain time span.

- Defining guided processes on graphical models (for “non-tree”-case: see preprint).
- Both discrete-time and continuous-time transitions incorporated.

Backward Filtering Forward Guiding: framework for doing likelihood based inference in directed acyclic graphs, where transitions over edges may correspond to the evolution of a stochastic process for a certain time span.

- Defining guided processes on graphical models (for “non-tree”-case: see preprint).
- Both discrete-time and continuous-time transitions incorporated.
- Illustrations for interacting particle process and branching diffusion.
- Not covered: **compositionality results** (some category theory, see earlier versions on arXiv).

Backward Filtering Forward Guiding: framework for doing likelihood based inference in directed acyclic graphs, where transitions over edges may correspond to the evolution of a stochastic process for a certain time span.

- Defining guided processes on graphical models (for “non-tree”-case: see preprint).
- Both discrete-time and continuous-time transitions incorporated.
- Illustrations for interacting particle process and branching diffusion.
- Not covered: **compositionality results** (some category theory, see earlier versions on arXiv).

Ongoing: SPDEs, SDEs on manifolds, chemical reaction networks.

Open postdoc position at VU Amsterdam.

References

- [Continuous-discrete smoothing of diffusions](#)
MIDER, SCHAUER, VDM, Electronic Journal of Statistics
Bayesian inference for partially observed diffusions.

References

- [Continuous-discrete smoothing of diffusions](#)
MIDER, SCHAUER, VDM, Electronic Journal of Statistics
Bayesian inference for partially observed diffusions.
- [Automatic Backward Filtering Forward Guiding for Markov processes and graphical models](#), VDM AND SCHAUER, preprint on arXiv.
A generalisation to Markov processes on graphical models including ideas on compositionality from category theory.

References

- [Continuous-discrete smoothing of diffusions](#)
MIDER, SCHAUER, VDM, Electronic Journal of Statistics
Bayesian inference for partially observed diffusions.
- [Automatic Backward Filtering Forward Guiding for Markov processes and graphical models](#), VDM AND SCHAUER, preprint on arXiv.
A generalisation to Markov processes on graphical models including ideas on compositionality from category theory.
- [Introduction to Automatic Backward Filtering Forward Guiding](#), VDM, arXiv, submitted.
Gentle introduction to the more advanced paper.

References

- [Continuous-discrete smoothing of diffusions](#)
MIDER, SCHAUER, VDM, Electronic Journal of Statistics

Bayesian inference for partially observed diffusions.
- [Automatic Backward Filtering Forward Guiding for Markov processes and graphical models](#), VDM AND SCHAUER, preprint on arXiv.

A generalisation to Markov processes on graphical models including ideas on compositionality from category theory.
- [Introduction to Automatic Backward Filtering Forward Guiding](#), VDM, arXiv, submitted.

Gentle introduction to the more advanced paper.
- [Inference in Hidden Markov Models](#), CAPPÉ, MOULINES AND RYDÉN

Good source on filtering, smoothing, parameter estimation in HMM.