


InterAxis


[Kim et al. 2015]

- Treat the **axes** in a 2D scatterplot as the main objects of interest, objects of modification
- Attribute-level *and* item-level direct manipulation to form axes

InterAxis: Visualization Design




Interactively Constructing Axes




Axis Representation

- Simply a vector (in the original data space)

$$T_x = \frac{1}{n_{x,u}} \sum_{i=1}^{n_{x,u}} a_i^{x,u} - \frac{1}{n_{x,l}} \sum_{i=1}^{n_{x,l}} a_i^{x,l}$$



upper



lower

(vector is subsequently normalized)


Data Projection

- The x and y vectors, corresponding to the axes, subsequently form a 2D linear subspace: **projection**


$$\left((T_x)^T a_i, (T_y)^T a_i \right)$$

- Questions:
 - What is the interpretation of this projection?
 - Suppose the selected data points for each axis had identical values in all dimensions, except for one (unique) dimension - what does that give us?


InterAxis: Interface




InterAxis: Example




InterAxis: Example



InterAxis: Example



InterAxis: Example



InterAxis: Demo


<http://va.gatech.edu/live-projects/interaxis/>

InterAxis: Limitation

- Restricted to *linear projections*. This might not be an appropriate representation for certain datasets.
- How can we provide support for *nonlinear projections*?
- Problems to address:
 - How does a user express a nonlinear axis?
 - How do we project data onto the axis?


AxiSketcher

[Kwon et al. 2016]




Axes

- Each axis is backed by a **curve** defined in the original high-dimensional space.
- A curve is specified by a user directly sketching in the 2D domain.




Curve: Point Selection




- User selects a sequence of points: the sequence implicitly orders the points, giving us a poly-line in 2D, and the high-dimensional curve is taken via replacing 2D points with corresponding high-dimensional points.

Curve: Polyline Selection



- Free-form polyline sketch in 2D.
- Challenge: what should an arbitrary point in 2D correspond with in the high-dimensional space?

Scattered Data Interpolation




$$w_{ij} = \frac{1/\|u_i^l - d_{ij}^l\|^2}{\sum_{m=1}^k 1/\|u_i^l - d_{im}^l\|^2}$$

$$u_i^h = \sum_{j=1}^k w_{ij} d_{ij}^h$$

- Principal curve [Hastie & Stuetzle 1989] fit to produce a smoother curve (though not completely necessary).


Curve: Freeform Sketch



- Continuous curve sampled at uniform intervals.
- Process used for polylines applied to this sampled curve.

Finding Projections


- Consider linear projection:



$$\hat{\mathbf{x}} = \mathbf{v}\mathbf{v}^T\mathbf{x} \quad , \quad \|\mathbf{v}\| = 1$$


- What is the analog when we have a curve?

Nonlinear Projection




- Ok, so how do we compute this from our polyline?

Piecewise Projection




- Some issues:
- What if the point is far from the curve?
- Keep this information around, visually encode it later.
- Larger issue (not addressed): uniqueness?

Visualization Design: Axis




- Visual Encoding:
 - ordinal: points on curve are ordered
 - category: attributes mapped to color *and* y-stacking
 - quantitative: attribute values mapped to length

Visualization Design: Glyph




- Known as an aster plot
- Category: attribute mapped to angle *and* color
- Quantitative: value mapped to radius

Full Interface



Example: Quality-of-Life Indicators (grain of salt!)



Limitations with Interaxis, Axisketcher

- The quality of the axes is highly dependent on the usefulness of the given 2D projection
 - Interaxis: necessary to find points of interest
 - Axisketcher: if the 2D projection is not useful to the user, neither will their sketched curve
- How do these methods scale with large amounts of dimensions (e.g. > 100)?