

Facility Onboarding Guide

System: Aegiscare

Model: One deployment per facility (Model A)

Overview

Aegiscare is designed so each facility gets its own isolated deployment:

- Own GitHub repository (forked from master)
- Own Supabase project (own database, own auth, own storage)
- Own Vercel deployment (own URL)

No facility can see another facility's patient data.

Steps to onboard a new facility

Step 1 — Fork the repository

1. Go to <https://github.com/fmurage6331-dev/confit-core>
2. Click **Fork** → create under the facility's GitHub account
3. Clone the fork locally

Step 2 — Create a new Supabase project

1. Go to supabase.com → New project
2. Name it after the facility (e.g. [aegiscare-facility-name](#))
3. Note the **Project URL** and **anon key** and **service role key**

Step 3 — Run migrations

In the new Supabase project's SQL Editor, run all files in [supabase/migrations/](#) in filename order (oldest first).

Step 4 — Deploy to Vercel

1. Go to <https://vercel.com> → New Project → Import from GitHub
2. Select the forked repository
3. Set environment variables in Vercel dashboard:
 - [VITE_SUPABASE_URL](#) — your Supabase project URL
 - [VITE_SUPABASE_ANON_KEY](#) — your Supabase anon key
4. Click **Deploy** → Vercel builds and publishes automatically
5. Note your deployment URL (e.g. [https://aegiscare-facilityname.vercel.app](#))

Step 5 — Configure facility details

1. Log in to the deployed app as admin

2. Go to **Admin** → **Settings** → **Facility tab**
3. Fill in:

◦ Facility name

◦ KMHFL code (find at hiskenya.org)

◦ County, address, phone, email

◦ SHA facility ID and provider number (when available)
4. Click **Save facility details**

Step 6 — Configure Edge Function secrets

In Supabase → Edge Functions → Secrets, set:

- `ICD_CLIENT_ID` — WHO ICD-11 API client ID (Task F)
- `ICD_CLIENT_SECRET` — WHO ICD-11 API client secret (Task F)

Step 7 — Create admin user

In Supabase → Authentication → Users → Invite user Set their role to `admin` in the `user_roles` table.

Kenya Data Residency & Cloud Migration

Current Hosting (Development Phase)

- Supabase Cloud: servers in `us-east-1` (USA) — acceptable for development
- Vercel: global CDN — acceptable for frontend

Required for ODPC + DHA Compliance (Production)

Kenya law (ODPC Data Protection Act 2019) requires health data to remain in Kenya.

Recommended Kenya-compliant hosting options:

Provider	Type	Notes
Safaricom Cloud	Kenya-based VPS	Preferred — local support
Azure East Africa	Johannesburg region	Closest Azure region
AWS af-south-1	Cape Town	Closest AWS region
Angani	Kenya-based	Local Kenyan cloud provider

Migration Steps (When Ready)

Step 1 — Self-host Supabase on Kenya server:

```
# On your Kenya cloud server
git clone https://github.com/supabase/supabase
cd supabase/docker
cp .env.example .env
# Edit .env with your settings
```

```
docker compose up -d
```

Step 2 – Export existing Supabase data:

Bash

```
# Export from current Supabase project
```

```
supabase db dump -p your-password > aegiscare-backup.sql
```

```
# Import to new Kenya-hosted Supabase
```

```
psql -h your-kenya-server -U postgres -d postgres < aegiscare-backup.sql
```

Step 3 – Update environment variables:

text

```
VITE_SUPABASE_URL=https://your-kenya-server.com
```

```
VITE_SUPABASE_ANON_KEY=your-new-anon-key
```

```
## Pushing updates to a deployed facility
```

When the master repo gets updates:

```
```bash
```

```
In the facility's forked repo
```

```
git remote add upstream https://github.com/fmurage6331-dev/confit-core
```

```
git fetch upstream
```

```
git merge upstream/main
```

```
git push origin main
```