

Climate Data Online: Web Services Documentation

Getting Started	Datasets	Data Categories	Data Types	Location Categories	Locations	Stations	Data
---------------------------------	--------------------------	---------------------------------	----------------------------	-------------------------------------	-----------	--------------------------	----------------------

Locations

Locations can be a specific latitude/longitude point such as a station, or a label representing a bounding area such as a city.

Endpoints

PATH	DESCRIPTION
<code>https://www.ncei.noaa.gov/cdo-web/api/v2/locations/{id}</code>	Used to find information about the location with id of {id}.
<code>https://www.ncei.noaa.gov/cdo-web/api/v2/locations</code>	When used without optional parameters, fetches list of available locations. Use with optional parameters below to filter results.

Additional Parameters

PARAMETER	EXAMPLE	DESCRIPTION
datasetid	GSOM	Optional. Accepts a valid dataset id or a chain of dataset ids separated by ampersands. Locations returned will be supported by dataset(s) specified.
locationcategoryid	CITY	Optional. Accepts a valid location id or a chain of location category ids separated by ampersands. Locations returned will be in the location category(ies) specified.
datacategoryid	TEMP	Optional. Accepts a valid data category id or an array of data category IDs. Locations returned will be associated with the data category(ies) specified.
startdate	1970-10-03	Optional. Accepts valid ISO formatted date (yyyy-mm-dd). Locations returned will have data after the specified date. Paramater can be use independently of enddate.
enddate	2012-09-10	Optional. Accepts valid ISO formatted date (yyyy-mm-dd). Locations returned will have data before the specified date. Paramater can be use independently of startdate.
sortfield	name	Optional. The field to sort results by. Supports id, name, mindate, maxdate, and datacoverage fields.
sortorder	desc	Optional. Which order to sort by, asc or desc. Defaults to asc.
limit	42	Optional. Defaults to 25, limits the number of results in the response. Maximum is 1000.
offset	24	Optional. Defaults to 0, used to offset the resultlist. The example would begin with record 24.

Examples

Click on the links below and a preview will display example results from each REST query. Copy the URL listed below to use as a reference.
*Note: Assigned token is required to use these queries and *must* be in the header

[Fetch available locations](#)
`https://www.ncei.noaa.gov/cdo-web/api/v2/locations`

[Fetch more information about location id FIPS:37](#)

<https://www.ncei.noaa.gov/cdo-web/api/v2/locations/FIPS:37>

[Fetch available locations for the GHCND \(Daily Summaries\) dataset](#)

<https://www.ncei.noaa.gov/cdo-web/api/v2/locations?datasetid=GHCND>

[Fetch all U.S. States](#)

<https://www.ncei.noaa.gov/cdo-web/api/v2/locations?locationcategoryid=ST&limit=52>
