Universitat de Girona Fundació UdG: Innovació i Formació





Data Visualization Programming Anton Bardera Data Visualization Programming Anton Bardera Data Visualization
Programming Anton Bardera

Data Visualization Programming Anton Bardera Data Visualization
Bardera Data Visualization
Programming Anton Bardera
Data Visualization Programming Anton Bardera Data Visualization
Programming Anton Bardera Data Visualization Programming Anton Bardera Data Visualization

## Visual Encoding

- The way in which data is mapped into visual structures, upon which we build the images on a screen
- Items or links are represented using marks or geometrical primitives
- The changes on the mark's appearance based on a data attribute are called **channels**

Channel = Visual Variable

### Marks

- Marks for Items: basic geometric elements
  - Points
  - Lines
  - Areas
  - Volume: rarely usea













- Marks for Links
  - Containment
  - Connection
  - Proximity




## Graphs and Trees

- A graph G consists of a collection of vertices or nodes
   V and a set of edges E
- Each edge e connects two vertices x and y
- For example: V={1,2,3,4,5,6},E={(1,4),(2,4),(3,4),(4,5),(4,6)}



# Graphs and Trees


- Trees: graphs with no cycles
- Connected graph with N-1 edges
- Represent hierarchical structure
- Nodes are related as parent, children, sibiling (family tree)
- Root node: highest hierarchy



# Graphs representations

Three types:

Node-Link Diagrams Connection Marks







Adjacency Matrix
 Derived Table







Enclosure Containment Marks








#### Tree visualization

#### Node-link approach

- Nodes are distributed in space
- Edges represented by straight or curved lines
- Typical approach in tree visualization is to use X for breadth and Y for depth (or viceversa)
- Often space is used to communicate hierarchical orientation
- Recursion makes it elegant and fast to draw trees

### Tree visualization

- Naïve approach: repeatedly divide space for subtrees by leaf count
- Problems:
  - Exponential growth of breadth
  - No efficient use of the whole canvas



# Tree visualization: Reingold-Tilford

#### Goal


- make smarter use of space
- maximize density and symmetry

#### Design concerns

- clearly encode depth level
- no edge crossings
- isomorphic subtrees drawn identically
- compact


#### Approach

- bottom-up recursive approach
- for each parent make sure every subtree is drawn
- pack subtrees as closely as possible
- center parent over subtrees



## Tree visualization: Reingold-Tilford


- Algorithm: <u>original paper</u>
  - Do a post-order traversal of the tree
  - if the node is a leaf, give it an x coordinate of O
  - otherwise, for each of its children, place the child as close to its left sibling as possible
  - place the parent node halfway between its leftmost and rightmost children



## Tree visualization: Radial layout

- Node-link diagram in polar coordinates
- Radius encodes depth with root in center
- Angular sectors assigned to subtrees

Reingold-Tilford can be applied



# Tree visualization: Node-link problems

#### Scale

- tree breadth often grows exponentially
- quickly run out of space!

#### Solutions

- hyperbolic layout
- filtering
- scrolling or panning
- zooming

## Tree visualization: Enclosure diagrams

#### Encode structure using spatial enclosure

often referred to as treemaps

#### Benefits


- provides single view of entire tree
- easier to spot small / large nodes


#### Problems

difficult to accurately read depth

## Tree visualization: Treemaps


- recursively fill space based on a size metric for nodes
- enclosure indicates hierarchy
- additional measures can control aspect ratio of cells






# Tree visualization: Treemaps


 Most often use rectangles, but other shapes are possible: circles, Voronoi tessellation,...






#### Tree visualization: Icicle

- Higher-level nodes get a larger layer area, whether that is horizontal extent.
- Child levels are layered, constrained to parent's extent



### Tree visualization: Sunburst Trees

- Similar than icicle using circular layout and angular extent
- Child levels are lavered. constrained to parent's extent



# Tree visualization survey

http://treevis.net/

