

Ticket Booth

Table of Contents

Welcome to the Ticket Booth!	2
Development Environment Setup	3
Streamlined Setup	3
Optional VIM and PostgreSQL Local Configuration	3
Running App Dependencies Installer	3
Running Tests and Linters	3
Additional Information	4
Optional Manual Setup	4
Manual 1: Services	4
Manual 2: Direnv Setup	4
Manual 3: NodeJS & Votal Setup	4
Manual 3: Ruby Setup	5
Manual 4: Starting the Server	5
Tooling	6
Adding Site Admin	6
Generating Music Submissions List	7
Adding Submissions to WordPress	7
API Documentation	9
Acknowledgements	10

 TicketBooth CI: RSpec passing

 TicketBooth CI: Lint passing

 DeployToGKE no status

 Create and publish a Docker image no status



Please see the [README.pdf](#) for the PDF version of this README.



Please see the [Acknowledgements](#) at the end of this page.

Welcome to the Ticket Booth!

The goal of the app is to make ticket and volunteer management for community events easier and automated.

Development Environment Setup

The following walks through a local setup on OS-X M1.

Streamlined Setup

If you installed [Homebrew](#) on your laptop, you should be able to boot the app.

Optional VIM and PostgreSQL Local Configuration

We provided a pretty comprehensive VIM configuration with auto-complete, as well as the `psql` configuration with a prompt and additional useful macros.

To install this, run

```
bin/install-dev-tooling
```

After that, your `vim` sessions will have auto-complete enabled, and your `psql -U postgres` sessions will have rich prompt.

Running App Dependencies Installer

You can run the following setup script to attempt a complete set up of the development environment, as well as the installation of the Rubies, Gems and Database:

```
bin/boot-up
```

This should automatically open the browser at the <http://localhost:3000> URL, if all the steps succeed.

The `bin/boot-up` script will start the Rails server, or show an error that needs to be fixed.

After you stop it with `Ctrl-C`, you can restart the server using the following shortcut:

```
make dev
```

This actually starts Foreman via `bundle exec foreman -f Procfile.dev` — this is required to start CSS and JS just-in-time compilation in addition to the Rails server.



Running `rails s` is no longer sufficient to start the application.

Running Tests and Linters

To verify that your local environment is working, run the following:

```
make ci
```

This will run DB Migrations, followed by RSpec, Rubocop, and ShellCheck.

Additional Information

We dedicated a separate document to the [developer setup](#), which helps you get the application running locally.

Alternatively, keep reading for step-by-step manual instructions.

Optional Manual Setup

If you prefer to run all the steps manually, then follow the guide below.

Manual 1: Services

Please make sure you have PostgreSQL and running locally, or install it via Homebrew:

```
brew install direnv  
  
brew install postgresql@16  
brew services postgresql@16 start  
  
brew install memcached  
brew services memcached start
```

Manual 2: Direnv Setup

Before you can start the Ruby Server, you need to configure `direnv` so that the environment in the file `.envrc` is loaded on OS-X.

To do that follow the instructions for setting direnv on [bash](#) or [zsh](#) depending on what you are running. To find out, run `echo $SHELL`.

After you setup the shell initialization file, restart your terminal or reload the shell configuration.

Once you are back in the project's folder, run:

```
direnv allow .
```

This will load the environment variables from the `.envrc` file.

Manual 3: NodeJS & Votal Setup

Run the following to get Volta Node Manager working:

```
curl https://get.volta.sh | bash
volta install node@lts
volta install yarn
volta pin node yarn
```

Now your Node & Yarn should be installed.

Manual 3: Ruby Setup

```
# install brew from https://brew.sh
brew bundle 2>/dev/null

# ensure the following packages exist
brew install rbenv ruby-build direnv volta

eval "$(rbenv init -)"
eval "$(direnv hook ${SHELL%/})"

direnv allow .

rbenv install -s $(cat .ruby-version)
rbenv local $(cat .ruby-version)

bundle install -j 12
rails db:prepare
rails db:test:prepare

# Run Specs at the end:
bundle exec rspec --parallel
```

Manual 4: Starting the Server

To start the server post-setup, run the following (NOTE: you must start the server via Foreman, since it also starts **yarn** tasks that monitor and dynamically recompile CSS and JS assets)

```
bundle exec foreman -f Procfile.dev
```

You can also use the **Makefile**:

```
make dev
```

Here is an example:

```

Finished app/assets/builds/application.css in 157 ms
14:46:03 web.1 | started with pid 54273
14:46:03 js.1 | started with pid 54274
14:46:03 css.1 | started with pid 54275
14:46:03 browser.1 | started with pid 54276
14:46:03 css.1 | [nodemon] 3.1.0
14:46:03 css.1 | [nodemon] to restart at any time, enter `rs`
14:46:03 css.1 | [nodemon] watching path(s): app/assets/stylesheets/**/*
14:46:03 css.1 | [nodemon] watching extensions: scss
14:46:03 css.1 | [nodemon] starting `yarn build:css`
14:46:03 js.1 | [nodemon] 3.1.0
14:46:03 js.1 | [nodemon] to restart at any time, enter `rs`
14:46:03 js.1 | [nodemon] watching path(s): app/javascript/**/*
14:46:03 js.1 | [nodemon] watching extensions: js
14:46:03 js.1 | [nodemon] starting `yarn build:js`
14:46:03 js.1 |
14:46:03 js.1 | app/assets/builds/application.js 846.4kb
14:46:03 js.1 | app/assets/builds/popovers.js 241.0kb
14:46:03 js.1 | app/assets/builds/add_jquery.js 240.5kb
14:46:03 js.1 | app/assets/builds/ticket_requests.js 3.0kb
14:46:03 js.1 | app/assets/builds/datepicker.js 47b
14:46:03 js.1 | app/assets/builds/payments.js 45b
14:46:03 js.1 | app/assets/builds/application.js.map 1.6mb
14:46:03 js.1 | app/assets/builds/popovers.js.map 461.4kb
14:46:03 js.1 | app/assets/builds/add_jquery.js.map 460.6kb
14:46:03 js.1 | app/assets/builds/ticket_requests.js.map 6.0kb
14:46:03 js.1 | app/assets/builds/datepicker.js.map 93b
14:46:03 js.1 | app/assets/builds/payments.js.map 93b
14:46:03 js.1 |
14:46:03 js.1 | ⚡ Done in 36ms
14:46:03 js.1 | [nodemon] clean exit - waiting for changes before restart
14:46:04 web.1 | DEBUGGER: Debugger can attach via UNIX domain socket (/var/folders/jq/853fg3814rs6xx_zxk9sgsv40000gn/T/rdbg-501/rdbg-54273)
14:46:05 css.1 | Processing app/assets/builds/application.css...
14:46:05 css.1 | Finished app/assets/builds/application.css in 173 ms
14:46:05 css.1 | [nodemon] clean exit - waiting for changes before restart
14:46:05 web.1 | => Booting Puma
14:46:05 web.1 | => Rails 7.1.3.2 application starting in development
14:46:05 web.1 | => Run `bin/rails server --help` for more startup options
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| Puma starting in cluster mode...
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Puma version: 6.4.2 (ruby 3.2.3-p157) ("The Eagle of Durango")
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Min threads: 1
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Max threads: 1
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Environment: development
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Master PID: 54273
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Workers: 1
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Restarts: (✓) hot (♥) phased
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Preloading application
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Listening on http://127.0.0.1:3000
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Listening on http://[::]:3000
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| Use Ctrl-C to stop
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| * Starting control server on http://127.0.0.1:32123
14:46:06 web.1 | DEBUGGER[bIn/rails#54354]: Debugger can attach via UNIX domain socket (/var/folders/jq/853fg3814rs6xx_zxk9sgsv40000gn/T/rdbg-501/rdbg-54273)
14:46:06 web.1 | 54273 | 2024-04-20 14:46:06 -0700 : |puma| - Worker 0 (PID: 54354) booted in 0.0s, phase: 0
14:46:06 web.1 | Started GET "/" for ::1 at 2024-04-20 14:46:13 -0700
14:46:13 web.1 | ActiveRecord::SchemaMigration Load (1.3ms) SELECT "schema_migrations"."version" FROM "schema_migrations" ORDER BY "schema_migrations"."version"
14:46:13 web.1 | Processing by HomeController#index as HTML
14:46:13 web.1 | User Load (2.0ms) SELECT "users".* FROM "users" WHERE "users"."id" = $1 ORDER BY "users"."id" ASC LIMIT $2 [["id", 1], ["LIMIT", 1]]
14:46:13 web.1 | ↳ app/controllers/home_controller.rb:5:in `index'
14:46:13 web.1 | Event Load (0.8ms) SELECT "events".* FROM "events" ORDER BY "events"."id" DESC LIMIT $1 [["LIMIT", 1]]
14:46:13 web.1 | ↳ app/controllers/home_controller.rb:6:in `index'
14:46:13 web.1 | SiteAdmin Load (1.5ms) SELECT "site_admins".* FROM "site_admins" WHERE "site_admins"."user_id" = $1 LIMIT $2 [["user_id", 1], ["LIMIT", 1]]
14:46:13 web.1 | ↳ app/models/user.rb:96:in `site_admin?'

```

Tooling

Adding Site Admin

When the database is completely blank, the first step is to create the initial account. Lets say you registered as 'kig@fnf.org':

The second step is to make that person a site admin:

```

RAILS_ENV=production
bin/site-admin add kig@fnf.org

# Or, to remove site admin from a given user:
bin/site-admin remove kig@fnf.org

```


Generating Music Submissions List

The repo contains a convenient script for generating HTML to embed into the Wordpress site, using a CSV generated out of Google Spreadsheet collected using Google Forms.

The CSV must contain three columns and a header row:

- DJ Name
- Full Name
- Set URL

To generate the HTML (we'll use the CSV file checked into the fixtures):

```
# eg, using the fixture file:
$ bin/music-submission-links spec/fixtures/chill_sets.csv > chill_set.html

# or, to include the simple CSS into the header:
$ bin/music-submission-links spec/fixtures/chill_sets.csv --simple-css >
chill_set.html
open chill_set.html
```



If you add `--simple-css` to the arguments, the generated HTML will include `<head>` element with the [Simple CSS Stylesheet](#). Do not use this flag if you plan to paste the output into the WordPress text box. Use this flag if you simply want to verify the resulting HTML in a browser by running `open chill_set.html`.

To verify that the script is working and generating correct HTML, you might want to install a handy tool called `bat`, eg using Homebrew on Mac OS-X:

```
$ brew install bat
$ bin/music-submission-links spec/fixtures/chill_sets.csv | bat
```

Adding Submissions to WordPress

Now you can open WordPress, create a two-column layout on the submissions page and paste the contents into one of the two columns, typically:

1. Night time / Peak Hour
2. Chill / Daytime

First, let's copy the resulting HTML into clipboard:

```
$ bin/music-submission-links chill_sets.csv | pbcopy
```

Now we can paste it into WordPress directly.

API Documentation

Yard-generated documentation is available via running:

```
$ bundle exec rake doc  
# this will automatically open the index.html
```

Acknowledgements

This app is formerly known as **Helping Culture**, which in turn was originally conceived and inspired by Tracy Page.

This project was originally written by [Shane de Silva](#).

It is currently maintained by the [FnF](#) org, and within it specifically

- [Konstantin Gredeskoul](#) for any application issues,
- [Mike Matera](#) for any issues related to deployment to the Google Public Cloud.
- [Matt Levy](#) for development, coordination and project management.

Please use labels to tag any reported issues.