

# Power Shelves 12V, 27kW (N+1)



- Supplies power up to 27kW
- 3U shelf accepts up to 10 hot-swappable 3kW Power Supply Units for maximum 10 slot operation
  21-inch shelf with a height of 3 OU, 5.17 inches
- Communication with Li-ion Battery Backup Shelf
- Confinuitication with Li-Ion Battery Backup Sher
   Deal time DCL and DDC menitoring and control
- Real-time PSU and BBS monitoring and control
  Remote control PSU On/Off through the required Shelf Controller
- Supports 3 sets of bus bars to deliver DC power to load

# 12V, 27kW, 2RU (N+1)



- 2RU, 21", 10 PSU slots5 single phase AC input
- 3kW Power Supply Unit
- Serviceable Power Shelf Controller at front of shelf

# 50V, 18kW (N+N) ORV3



- Dual AC inputs: single phase or three phase input cable option
  - 12 PSUs in N+N configuration
- DC output is ground-isolated for flexible grounding at rack level
- High efficiency 3kW PSU2 OU, 21-inch width power shelf
- Floating output DC power clip for quick connection to rack bus bar
- Shelf Management Controller provides system communication capability for shelf remote control along with power monitoring (not required for basic Power Shelf operation)



# Power Shelves 12V, 25kW



- Supplies power up to 25kW
- 3U shelf accepts up to 10 hot-swappable 2.5kW Power Supply Units for maximum 10 slot operation
- 21-inch shelf with a height of 3 OU, 5.17 inches
- Communication with Li-ion Battery Backup Shelf
- Real-time PSU and BBS monitoring and control
- Remote control PSU On/Off through the required Shelf Controller
  Supports 3 sets of bus bars to deliver DC power to load

### 12V, 22.5kW (N+1)



- Supplies power up to 22.5kW N+1
- 3U shelf accepts up to 10 hot-swappable 2.5kW PSUs for 9+1 redundant operation
- 21-inch shelf with a height of 3 OU, 5.17 inches
- Communication with Li-ion Battery Backup Shelf
- Real-time PSU and BBS monitoring and control
- Remote control PSU On/Off through the optional Shelf Controller
- Supports 3 sets of bus bars to deliver DC power to load
  Supports 6x C13 outlets for external AC load

### CTS outlets for external he load

# 12V, 15kW (N+1) HDHE



- OpenRack V2 compatible
- 1 OU, 21" 6 PSU slots
- 2 AC input3kW Power Supply Units
- Serviceable Power Shelf Controller at front of shelf

# LITEON

# **Power Shelves** 12V, 12.5kW (N+1) ATS-PSU



- OCP V2 rack compatible Fits 19-inch or 21-inch racks
- 2.5 OU, 6 PSU slots
- 2 AC input
- 2.5kW ATS-PSU
- Serviceable Power Shelf Controller at front of shelf

# 12V, 12.5kW (5+5)

- 3-phase, 5-wire 380Vac/400Vac, or 3-phase, 4-wire 208Vac, 12.5kW power output • Up to 5+5 redundant operation
- Hot-swappable 2.5kW Power Supply Unit • Communication with Li-ion Battery Backup Shelf
- 21-inch, 12.5kW Power Shelf with a height of 3 OU (5.17 inches)
- Supports 6x C13 outlets for external AC load
- Supports up to 3 sets of bus bars to deliver DC output loading Real-time PSU and BBS monitoring and control

# 12V, 10kW Scorpio



- China Scorpio rack compatible • 2 input, AC/HVDC
- 2.5kW Power Supply Unit
- Serviceable Power Shelf Controller at front of shelf



### **Power Shelves**

## 50V, 15kW (N+1) ORV3



- Flexible AC input options:
- 1. Single phase or three-phase input (208/240/277Vac nominal)
- 2. Single input source or dual input sources
- 6 PSUs to be configured in N+1 or N+N depending on input options
- DC output is ground-isolated for flexible grounding at rack level
- High efficiency 3kW PSU
- 10U, 21-inch width power shelf
- Floating output DC power clip for quick connection to rack bus bar
- Shelf Management Controller provides system communication capability for shelf remote control along with power monitoring. (Not required)

### 12V, 9kW (N+1)



- OpenRack V2 rack compatible
- 1 OU, 21-inch
- 2 AC input
- 3kW Power Supply Unit
- 4 PSU slots
- Power Shelf Controller embedded at back of shelf