



## Annex A1 (Normative)

### Expectation-Driven Handshake Synchronization, Attested Execution Environments, and Purpose-Bound Data Activation in BEAP™

#### A1.1 Status and Scope

This annex is normative.

It defines mandatory handshake semantics, storage rules, access boundaries, and synchronization constraints for BEAP™-compliant implementations that support expectation-driven handshakes and handshake-scoped data.

This annex does not modify or extend:

- wire formats,
- capsule serialization formats,
- cryptographic primitives,
- transport mechanisms, or
- PoAE™ execution semantics

defined in the BEAP™, qBEAP™, and PoAE™ specifications.

This annex defines behavioral, architectural, and security requirements that **MUST** be honored by conforming implementations.

---

## A1.2 Applicability and Environment Constraints

The handshake model defined in this annex SHALL impose hardware-attestation requirements only on environments that request, activate, process, or receive sensitive effects under a handshake-scoped cooperation state.

An implementation MUST NOT enable processing, activation, or access to handshake-scoped sensitive data unless:

- the requesting or processing environment is hardware-attested, and
- the attestation is bound to a verifiable identity recognized by the BEAP™ trust model.

Hardware attestation:

- SHALL be mandatory for environments that request, activate, or process:
  - PII,
  - sensitive data,
  - financial or other irreversible effects.
- SHALL NOT be mandatory for environments that:
  - initiate first contact,
  - negotiate expectations,
  - express consent,
  - participate in handshake establishment without processing sensitive data.

Non-attested environments MAY participate in BEAP™ interactions and MAY be parties to a handshake but SHALL NOT request, activate, process, or receive handshake-scoped sensitive data.

---

## A1.3 Handshake as an Operational Boundary

In BEAP™, a handshake SHALL represent a bounded, identity-anchored cooperation state shared between two parties.

A handshake state SHALL be:

- identity-bound,
- explicitly consented,
- cryptographically verifiable,
- revocable,
- and confined to attestation-enforced execution boundaries for sensitive operations.

The handshake SHALL function as a temporary operational contract governing:

- which data classes MAY exist within exchanged capsules,
- which expectations apply,

- which encrypted data regions MAY be accessed,
- and under which declared purposes activation MAY occur.

All shared context SHALL be strictly scoped to the lifetime and declared scope of the handshake.

---

## **A1.4 Local Handshake Persistence**

Each participating party SHALL store the handshake state locally.

Local handshake persistence:

- SHALL be encrypted at rest,
- SHALL be cryptographically bound to the handshake identifier,
- SHALL be bound to the local execution environment and identity,
- SHALL NOT constitute a global session state,
- SHALL NOT require continuous online availability of the counterparty.

For handshake-scoped sensitive data, local persistence and any subsequent activation SHALL require a hardware-attested execution environment.

Local persistence SHALL NOT relax capsule-local determinism or PoAE™ policy enforcement.

---

## **A1.5 Expectation-Driven Synchronization**

### **A1.5.1 Expectations as Declarative Signals**

An expectation SHALL be a declarative statement describing information that MAY be required for a handshake to transition into an active operational state.

An expectation:

- SHALL NOT mandate immediate disclosure,
- SHALL NOT imply processing,
- SHALL define requirements, not actions.

An expectation MAY specify:

- attribute identifiers,
- data class (e.g. PII, business-critical, informational),
- purpose identifiers,
- requirement level,
- additional constraints (e.g. jurisdiction, format, validation state).

### **A1.5.2 Iterative Capsule Synchronization**

Handshake completion SHALL occur through iterative capsule exchange.

Capsules exchanged during synchronization MAY contain:

- capsule-local deterministic execution context,
- shared informational references,
- encrypted handshake-scoped data regions.

Sensitive data SHALL NOT be required to be processed solely to satisfy expectation negotiation.

---

## **A1.6 qBEAP™ Capsule Structure and Encrypted Regions**

A qBEAP™ capsule used under an active handshake MAY contain multiple encrypted regions, each with distinct access semantics.

### **A1.6.1 Capsule Regions**

A capsule MAY conceptually contain:

#### **Region 1 — Tier-1 Context**

Capsule-local deterministic execution context and policy references.

This region SHALL be the sole authority for execution and automation decisions.

#### **Region 2 — Tier-2 Context**

Shared informational and non-sensitive material, including augmented overlay annotations and support context.

#### **Region 3 — Handshake-Scoped Encrypted Sub-Capsules**

One or more encrypted sub-capsules containing handshake-scoped data such as PII, sensitive data, or augmented overlay support for sensitive operations.

### **A1.6.2 Handshake-Scoped Encrypted Sub-Capsules**

Handshake-scoped data SHALL be stored exclusively within encrypted qBEAP™ sub-capsules.

Each such sub-capsule:

- SHALL be encrypted at rest and in transit,
- SHALL be cryptographically bound to the handshake identifier,
- SHALL be isolated from execution context,
- SHALL NOT influence execution logic,
- SHALL be inaccessible without explicit activation.

Multiple encrypted sub-capsules MAY coexist within a single qBEAP™ capsule.

---

## **A1.7 Access Semantics and Purpose-Bound Activation**

Processing or access to handshake-scoped sensitive data SHALL be permitted only when all of the following conditions are met:

- a matching expectation exists,
- a declared purpose identifier applies,
- policy conditions are satisfied,

- valid consent is present,
- the requesting or processing environment is hardware-attested.

Requesting or activating access to PII, sensitive data, or irreversible effects without hardware attestation SHALL NOT be permitted, regardless of consent or handshake existence.

Each party:

- SHALL be able to decrypt and access its own contributed handshake-scoped data at any time,
- SHALL NOT gain unrestricted access to counterparty-contributed data.

Access to counterparty-provided handshake data:

- SHALL be scope-bound,
- SHALL be purpose-bound,
- SHALL be denied by default.

Transport or storage of encrypted handshake-scoped data SHALL NOT constitute processing.

---

## **A1.8 Sub-Orchestrator Synchronization**

Handshake-scoped data MAY be synchronized between sub-orchestrators operating under the same identity, provided that:

- each sub-orchestrator that may activate or process sensitive data executes in a hardware-attested environment,
- attestation confirms equivalence of trust level,
- the identity binding is verifiable and unchanged.

Synchronization MAY include:

- an empty qBEAP™ capsule,
- the handshake identifier,
- encrypted handshake-scoped sub-capsules.

Sub-orchestrators that are not hardware-attested MAY receive handshake metadata but SHALL NOT receive, activate, or process handshake-scoped sensitive data.

Synchronization SHALL NOT relax access controls or activation rules defined in this annex.

---

## **A1.9 Permitted Data Introduction Paths**

BEAP™ SHALL permit two normative mechanisms for introducing sensitive data into a handshake-scoped cooperation state:

1. Expectation fulfillment via explicit data request
2. Handshake-anchored encrypted data presence

In both cases, data SHALL remain inactive until purpose-bound activation occurs.

---

## **A1.10 Security, Privacy, and Determinism Properties**

The model defined in this annex:

- restricts processing to explicitly declared purposes,
- prevents implicit or ambient data access,
- preserves auditability and traceability,
- enforces role- and operation-bound attestation requirements,
- maintains strict determinism.

Handshake revocation SHALL immediately affect future access and synchronization without altering historical integrity.

---

## **A1.12 First Contact and Handshake Eligibility**

A BEAP™ interaction MAY begin without an existing handshake.

First contact MAY occur via:

- public WR Codes,
- websites or applications,
- BEAP™ Packages containing pBEAP™ capsules,
- other BEAP™-compatible interaction mechanisms.

The absence of a handshake SHALL NOT prevent:

- expectation declaration,
- message exchange,
- automation execution,
- data requests,
- consent negotiation,
- or handshake establishment.

qBEAP™ capsules SHALL NOT be used for first contact. qBEAP™ capsules SHALL be permitted only for enterprise handshakes in which both parties execute in hardware-attested environments.

---

## **A1.13 Handshake Creation and Promotion**

A handshake MAY be created as a result of an interaction that includes:

- a declared expectation,
- an explicit data request,

- and valid user consent.

When these conditions are met, an implementation MAY promote the interaction into a handshake-scoped cooperation state.

Handshake creation:

- SHALL require explicit, informed consent,
- SHALL be identity-bound,
- SHALL be cryptographically verifiable,
- SHALL be locally persisted,
- SHALL be revocable at any time.

No prior authentication or handshake SHALL be required for handshake creation itself.

Handshake promotion SHALL NOT:

- imply immediate processing of sensitive data,
- bypass purpose or policy constraints,
- activate sensitive data without satisfying the requirements defined in this annex.

---

## **A1.14 Handshake Scope Anchoring and Reuse**

Each handshake SHALL be anchored to a declared cooperation scope.

A handshake scope SHALL define:

- the cooperating counterparty identity,
- the permitted interaction domain or service context,
- the allowed purpose identifiers,
- the permitted data classes.

A handshake SHALL NOT be implicitly bound to a specific WR Code.

Multiple interaction entry points, including multiple public WR Codes and BEAP™ Packages, MAY reference the same handshake, provided their declared scope requirements are compatible with the handshake scope.

Scope compatibility SHALL be evaluated deterministically at execution time.

---

## **A1.15 Capsule Formats, Automation, and Attestation Requirements**

BEAP™ defines multiple capsule formats with distinct security and deployment properties.

A pBEAP™ capsule:

- SHALL be unencrypted,
- MAY carry messages, expectations, and automation instructions,

- SHALL be used for first contact, public WR Code interactions, and general messaging,
- SHALL NOT require hardware attestation on both parties.

For public publishers of WR Codes, the publishing environment:

- SHALL be hardware-attested,
- SHALL be identity-bound within the BEAP™ trust model,
- SHALL NOT require the scanning or consuming party to be hardware-attested at first contact; however, additional use cases MAY require hardware attestation of the scanning or consuming party after handshake establishment.

A qBEAP™ capsule:

- SHALL be encrypted,
- MAY carry messages and automation instructions,
- SHALL be used exclusively for enterprise handshakes,
- SHALL require both parties to execute in hardware-attested environments.

Automation capability is not limited to qBEAP™ and MAY be executed within pBEAP™ capsules, subject to policy and trust constraints.

---

## **A1.16 Encrypted Handshake-Scoped Sensitive Data Containers**

In addition to capsule formats, an encrypted handshake-scoped sensitive data container MAY be used as an edge case for sensitive data handling.

Such encrypted handshake context:

- SHALL contain sensitive data only,
- SHALL NOT contain automation templates or execution logic,
- SHALL NOT constitute a qBEAP™ capsule,
- MAY be embedded within a BEAP™ Package containing a pBEAP™ capsule,
- SHALL require hardware attestation only for the requesting or processing environment,
- SHALL be encrypted using the same cryptographic construction, key management model, and post-quantum-ready primitives as defined for qBEAP™ capsules.

The existence of such encrypted containers SHALL NOT alter the classification of the enclosing capsule format.

---

## **A1.17 Sensitive Data Introduction During Handshake Establishment**

Sensitive data MAY be introduced during or after handshake establishment only when:

- a matching expectation exists,
- a declared purpose identifier applies,

- explicit consent is granted,
- the requesting or processing environment satisfies the hardware-attestation requirements defined in this annex.

Sensitive data introduced under a handshake:

- SHALL be stored exclusively within encrypted handshake-scoped containers,
- SHALL remain inactive until purpose-bound activation occurs,
- SHALL NOT influence execution logic.

Requesting or activating access to PII or sensitive data without hardware attestation SHALL NOT be permitted, regardless of consent or handshake existence.

---

## **A1.18 Public WR Codes and Handshake Interaction**

Public WR Codes:

- SHALL remain static and unencrypted,
- SHALL resolve to BEAP™ Packages containing pBEAP™ capsules,
- SHALL NOT contain sensitive data,
- SHALL NOT embed handshake identifiers or user-specific state.

Personalized behavior resulting from scanning a public WR Code:

- SHALL derive exclusively from an existing handshake,
- SHALL be enforced through scope and purpose evaluation,
- SHALL NOT alter the semantic meaning of the WR Code.

---

## **A1.19 Handshake Revocation Effects**

A handshake MAY be revoked at any time by either party.

Upon revocation:

- future access to encrypted handshake-scoped containers SHALL be denied,
- synchronization of handshake-scoped sensitive data SHALL cease,
- activation of encrypted handshake-scoped data SHALL be prevented.

Revocation SHALL NOT alter historical BEAP™ Package or capsule integrity or auditability.

## **A1.20 Handshake Establishment via Public WR Code®**

Public WR Code® instances SHALL function as static, unencrypted, replay-safe entry points into BEAP™ interactions.

They SHALL NOT embed handshake state, encrypted material, user-specific information, dynamic identifiers, or mutable execution logic.

Public WR Code® interactions SHALL require network access for:

- WR Code® resolution,
- retrieval of referenced templates and BEAP™ Packages,
- integrity verification of retrieved artefacts,
- verification of externally anchored integrity commitments as defined by the WR Code® protocol.

Resolution of a public WR Code® SHALL always result in a pBEAP™-based interaction, independent of whether a handshake exists.

---

### **A1.20.1 Resolution and Initial Execution Context**

Upon resolution of a public WR Code®, the orchestrator SHALL:

- resolve the publisher identity associated with the WR Code®,
- retrieve the referenced BEAP™ Package containing a pBEAP™ capsule,
- perform integrity verification of retrieved artefacts against externally anchored commitments,
- establish a deterministic execution context.

At this stage:

- no handshake SHALL be assumed to exist,
- no encrypted handshake-scoped context SHALL be active,
- no authentication or hardware attestation SHALL be implied for the consuming party.

The publishing environment of public WR Code® instances SHALL be hardware-attested and identity-bound within the BEAP™ trust model.

---

### **A1.20.2 Handshake Evaluation and Verifiable Continuity**

Once the required artefacts and verification material are available, the orchestrator SHALL evaluate whether a locally stored handshake exists that:

- is identity-bound to the resolved publisher,
- declares a cooperation scope compatible with the current interaction.

This evaluation:

- SHALL be performed within the orchestrator,
- SHALL be deterministic with respect to the retrieved artefacts and local handshake state,

- MAY involve verification of externally anchored commitments to ensure that the handshake state and scope have not been altered retroactively.

Handshake evaluation and establishment MAY rely on external verification mechanisms but SHALL NOT delegate execution authority, policy decisions, or access control to external systems.

If no compatible handshake exists, execution SHALL proceed in generic, non-personalized mode.

---

### **A1.20.3 Expectation Declaration and Handshake Eligibility**

A pBEAP™ capsule resolved from a public WR Code® MAY declare expectations indicating:

- intended cooperation scope,
- data classes that MAY be requested,
- purposes that would apply if cooperation were elevated.

Such expectations:

- SHALL remain declarative,
- SHALL NOT imply processing,
- SHALL NOT activate sensitive data,
- SHALL NOT require hardware attestation.

Expectations MAY designate the interaction as handshake-eligible but SHALL NOT, by themselves, establish a handshake.

---

### **A1.20.4 Handshake Establishment as a Verifiable State Transition**

A handshake SHALL be established only when:

- explicit user consent is provided,
- the cooperating publisher identity is known,
- the declared scope and purposes are accepted.

Handshake establishment:

- SHALL be implemented as a local, deterministic state transition within the orchestrator,
- SHALL create an identity-bound and scope-bound handshake record,
- SHALL NOT require modification of the WR Code®,
- SHALL NOT require modification of the capsule format,
- SHALL NOT require mutual hardware attestation.

To prevent repudiation, silent alteration, or post-hoc denial, the establishment of a handshake and its declared scope SHALL be cryptographically committed and externally anchored in a privacy-preserving manner.

Such anchoring:

- SHALL record only cryptographic commitments (e.g. salted hashes or aggregated roots),
- SHALL NOT expose identities, scopes, purposes, or user-specific metadata,
- SHALL serve as non-authoritative proof of existence and integrity.

The handshake SHALL become the continuity anchor for subsequent interactions with the same publisher and compatible scope.

---

### **A1.20.5 Post-Handshake Capability Escalation**

After handshake establishment, additional capabilities MAY become available, including:

- personalization of subsequent pBEAP™ interactions,
- storage and retrieval of encrypted handshake-scoped sensitive data containers,
- escalation of hardware attestation requirements for specific purposes or operations.

Such escalation:

- SHALL be strictly scope- and purpose-bound,
- SHALL require hardware attestation only for environments requesting or processing sensitive or irreversible actions,
- SHALL be verifiably attributable to the established handshake,
- SHALL NOT retroactively affect prior interactions.

---

### **A1.20.6 Integrity Anchoring and Non-Repudiation Guarantees**

Externally anchored integrity commitments SHALL be used to ensure that:

- publishers cannot deny or retroactively alter offered templates, scopes, or handshake terms,
- consumers can prove the origin, scope, and integrity of interactions they accepted,
- service providers and integrators can demonstrate non-manipulation of execution logic.

Such anchoring mechanisms:

- SHALL be used solely for verification and auditability,
- SHALL NOT become authoritative for execution, authorization, or policy enforcement,
- SHALL preserve unlinkability between independent interactions,
- SHALL prevent both unilateral repudiation and fabricated claims.

This anchoring model is intended to eliminate ambiguity, abuse, and post-hoc denial across all parties, thereby preventing unbounded or adversarial behavior in public WR Code®-based interactions.

### **A1.20.7 Purpose Binding, Consent Continuity, and Responsibility Allocation (Normative)**

Any access to handshake-scoped data **SHALL** be bound to an explicitly declared purpose provided by the data-processing party.

Consent for such purposes:

- **SHALL** be obtained explicitly at handshake establishment or handshake scope extension,
- **MAY** authorize repeated access to the declared data classes for the declared purpose,
- **SHALL** remain valid until explicitly revoked,
- **SHALL NOT** require repeated user interaction for each subsequent use within the same scope and purpose.

Each party that processes data under a handshake **SHALL** attach verifiable references to its applicable **privacy policy** and, where applicable, **terms of service**, as part of the handshake state.

Such policy and terms references:

- **SHALL** be provided and maintained by the data-processing party,
- **SHALL** be bound to the handshake identity, scope, and purpose,
- **SHALL** be immutable for the lifetime of the handshake,
- **SHALL** define responsibility, conditions, and limitations for lawful data processing and service execution.

**WR Desk™:**

- **SHALL** act solely as a technical enabler and orchestration platform,
- **SHALL NOT** act as a data controller, joint controller, or data processor,
- **SHALL NOT** define, validate, or interpret declared purposes, privacy policies, or terms of service,
- **SHALL** enforce only the existence, binding, and immutability of declared purposes and policy references within the handshake.

Responsibility for purpose limitation, data minimization, lawful processing, contractual obligations, and compliance with applicable data protection and consumer protection regulations remains exclusively with the operating entities participating in the handshake.

## **A1.11 Conclusion (Final, Corrected)**

This annex defines a deliberate architectural shift for **BEAP™ communications and automation** away from implicit trust, transient sessions, and unverifiable exchanges toward a **handshake-anchored cooperation model** that is explicit, auditable, and resistant to repudiation by any party.

The principles defined herein apply uniformly across **all BEAP™ interaction mechanisms**, including but not limited to public **WR Code®**–initiated interactions, application-based exchanges, service-to-service communication, and automated workflows.

WR Code® is treated as a prominent and security-critical entry mechanism, but not as a limitation of the handshake or context model itself.

The mechanisms specified in this annex intentionally separate:

- **interaction initiation** (which may occur through multiple BEAP™-compatible channels),
- **cooperation continuity** (established through identity- and scope-bound handshakes),
- **capability escalation** (controlled by purpose-, role-, and attestation-bound activation),
- and **accountability** (provided through cryptographic integrity anchoring).

By anchoring context, expectations, and sensitive cooperation state to explicit handshakes rather than to transport artefacts, session constructs, or user interface entry points, the model enables persistent, verifiable cooperation without embedding mutable or user-specific state into messages, capsules, or automation logic.

Beyond its security properties, this model is designed to **reduce friction in everyday operational routines**.

Data required to satisfy handshake expectations is maintained locally within the **WRVault™** and does not need to be re-entered or reconfigured for each handshake.

Handshake establishment can therefore draw from an existing, locally controlled data base, while access to that data remains strictly scope- and purpose-bound.

Knowledge bases, references, and previously consented data can be queried efficiently once a handshake exists, without repeated disclosure or negotiation.

Authentication and authorization can occur quickly and deterministically, as all required information is already locally available, yet remains inaccessible outside the declared scope and purpose.

A central design goal of this annex is to eliminate ambiguity and post-hoc denial in distributed and cross-organizational environments.

Both parties to a BEAP™ interaction are protected against false claims, silent modification, and retroactive reinterpretation of scope, consent, or permitted actions, while integrators and platform operators retain a defensible, non-authoritative audit trail.

The use of externally anchored cryptographic commitments is intentional and normative.

Such anchoring provides **proof of existence and integrity**, not authorization or control, and serves as a neutral witness for handshake-scoped cooperation states that would otherwise be unverifiable in adversarial, regulated, or high-risk contexts.

This annex defines the **target architecture** of the WR Desk™ and BEAP™ ecosystem.

It is expected that early implementations of WR Desk™ may not yet implement all primitives, enforcement points, or anchoring mechanisms described herein.

Such partial implementations do not weaken or reinterpret this specification; rather, they reflect a staged evolution toward the fully verifiable, non-repudiable cooperation model defined by this annex.

Conforming implementations are expected to evolve toward full compliance over time, without diluting the guarantees, boundaries, or intent established herein.

# Annex B — Trust Domains, Provenance Context, and Sandbox-Scoped Execution

## B.1 Canonical (Normative)

### B.1.1 Trust Domains

The system SHALL support multiple **trust domains** defining execution boundaries for BEAP capsules.

Trust domains SHALL differ in permitted interaction surfaces and policy strictness, but SHALL NOT alter BEAP integrity, confidentiality, or correctness guarantees.

At minimum, the system SHALL distinguish:

- a primary (host) trust domain, and
- one or more lower-trust sandbox domains.

The primary trust domain SHALL be authoritative.

---

### B.1.2 BEAP Security Invariance

All BEAP capsules, regardless of origin, provenance, or trust domain placement:

- SHALL remain valid BEAP capsules,
- SHALL retain full BEAP security guarantees,
- SHALL NOT be downgraded in security due to origin or transformation history.

BEAP security properties are invariant across trust domains.

---

### B.1.3 Provenance Context

Every BEAP capsule MUST include provenance metadata describing the **context of its creation**.

Provenance metadata SHALL:

- identify the origin mechanism by which the capsule was produced,
- identify the origin channel from which the payload was derived,
- identify the **handshake trust class** under which the capsule was created.

The handshake trust class SHALL be one of at least the following:

- enterprise handshake,
- professional (pro) handshake,

- standard handshake,
- none / depackaged.

Provenance metadata:

- is informational but **normative for trust classification**,
  - provides recipient context,
  - SHALL NOT modify BEAP validity or cryptographic security guarantees,
  - SHALL be used to determine trust-domain policies and execution constraints.
- 

#### B.1.4 Depackaged BEAP Capsules

A **Depackaged BEAP Capsule** is a BEAP capsule created by transforming an external payload into BEAP format through a depackaging process.

A depackaged BEAP capsule:

- SHALL remain a fully valid BEAP capsule,
- SHALL be subject to all BEAP guarantees,
- SHALL differ from other BEAP capsules only by provenance metadata.

Depackaging SHALL be understood as a format and context transformation, not a trust reduction.

---

#### B.1.5 Execution Scope and Sandbox Domains

Execution scope SHALL be explicitly defined and SHALL be independent of provenance and handshake-derived trust levels.

A BEAP capsule MAY be assigned a **sandbox execution scope**.

The sandbox execution scope:

- is an **optional flag**,
- MAY be applied at BEAP capsule creation time or during inbox handling,
- SHALL NOT be implied by provenance, handshake class, or trust level.

The sandbox execution scope is a **routing flag** indicating that a **logical clone of the BEAP capsule** SHALL be synchronized to a sandbox trust domain.

The sandbox execution scope:

- SHALL NOT alter execution semantics in the primary trust domain,
- SHALL NOT imply mandatory sandbox execution of the BEAP capsule itself, except where explicitly restricted or overridden by policy,
- SHALL solely control clone-based synchronization behavior.

Interaction with **original external artefacts or external links**, even when referenced by a BEAP capsule, SHALL always occur in a sandbox trust domain, independent of whether the BEAP capsule carries a sandbox execution scope.

---

### B.1.6 Clone-Based Sandbox Synchronization

Sandbox synchronization SHALL operate exclusively on BEAP capsules explicitly marked for sandbox execution.

Synchronization MUST occur only when:

1. the BEAP capsule carries a sandbox execution scope, and
2. the capsule exists in both the primary and sandbox trust domains.

Synchronization SHALL result in a **logical clone** within the sandbox domain.

The primary-domain capsule:

- SHALL remain authoritative,
  - SHALL NOT be modified by sandbox execution,
  - SHALL NOT receive implicit state or artifact propagation.
- 

### B.1.7 Authority and Promotion Rules

Artifacts, state, or outputs produced in sandbox trust domains:

- SHALL NOT be authoritative,
- SHALL NOT implicitly propagate to higher-trust domains.

There SHALL be no backchannel from the sandbox domain to higher-trust domains. The original BEAP capsule SHALL always remain on the primary (host) trust domain. Any explicit reuse of sandbox-derived results MUST occur via creation of a new BEAP capsule.

---

### B.1.8 Trust Levels

The system SHALL enforce **handshake-derived trust levels** based on provenance metadata.

At minimum, the following trust levels SHALL be supported:

- enterprise handshake (highest trust),
- professional (pro) handshake,
- standard handshake,
- depackaged / no-handshake (lowest trust).

Trust levels SHALL:

- be derived deterministically from handshake provenance,
- influence execution policy, sandbox requirements, and promotion rules,

- be immutable for a given BEAP capsule.

Enterprise trust levels SHALL enforce the strictest execution and promotion policies and MAY prohibit sandbox interaction entirely.

---

## B.2 Non-Canonical (Informative)

### B.2.1 Immediate Trust Differentiation

Implementations typically expose handshake-derived trust levels in a manner that allows recipients to **immediately distinguish** between:

- enterprise handshake capsules,
- professional handshake capsules,
- standard handshake capsules,
- depackaged capsules.

The concrete representation (e.g. visual indicators) is implementation-specific but SHALL preserve unambiguous differentiation.

---

### B.2.2 Purpose of Sandbox Domains

Sandbox trust domains enable controlled interaction with external systems and artefacts while preserving the primary domain as the system of record.

They also enable exploratory or experimental automation without authority escalation.

---

### B.2.3 Physical Separation Requirement

Sandbox orchestrators SHALL be **physically separated** from the host system.

Physical separation means that the sandbox orchestrator operates on distinct hardware and does not share a common execution environment with the host.

Virtualization or containerization alone SHALL NOT be considered sufficient isolation for a sandbox orchestrator.

Implementation choices MAY vary, but physical separation is a mandatory property and does not affect the canonical semantics defined above.

---

### B.2.4 Rationale

By separating:

- BEAP security guarantees,
- handshake-derived trust classification,
- provenance context,

- execution scope,

The architecture enables strict enterprise controls while retaining flexibility for lower-trust interaction and automation.

### B.2.5 Sandbox-Prepared Archival Media (Informative)

Sandbox environments MAY support the use of **sandbox-prepared removable storage** for archiving original artefacts outside of BEAP.

Such removable storage:

- SHALL be prepared and initialized exclusively by a sandbox orchestrator,
- SHALL be cryptographically or structurally bound to that sandbox orchestrator,
- SHALL NOT be usable by the primary (host) trust domain or other systems.

Sandbox-prepared archival media enables:

- long-term archiving of original artefacts outside BEAP,
- operation of RAM-only or ephemeral sandbox environments,
- optional persistence of session state and artefacts when explicitly configured.

Use of sandbox-prepared archival media is optional and SHALL require explicit setup and user intent.

### B.2.6 Ingestor and Validator Separation (Normative)

The system SHALL implement a mandatory, non-bypassable ingestion pipeline consisting of at least two distinct stages:

1. **Ingestor** (acquisition and depackaging), and
2. **Validator** (BEAP protocol conformance and integrity validation).

The ingestor and validator SHALL be logically separated components with an explicit interface.

#### B.2.6.1 Ingestor

The **Ingestor** SHALL act as the exclusive entry point for all external inputs and SHALL operate under the **identity of the host**.

All external inputs, regardless of channel or source, SHALL be processed exclusively by the ingestor prior to becoming BEAP capsules.

The ingestor SHALL:

- ingest messages and data from heterogeneous channels,
- depackage external inputs into **candidate BEAP capsules**,
- attach or preserve provenance metadata.

The ingestor SHALL NOT:

- validate BEAP protocol conformance beyond minimal framing required to produce a candidate capsule,
- render content,
- execute payloads,
- interact with original artefacts beyond depackaging,
- expose user-facing interfaces,
- distribute capsules to any trust domain.

#### **B.2.6.2 Validator**

The **Validator** SHALL be the sole authority for accepting candidate capsules as BEAP-conformant.

The validator SHALL:

- perform strict BEAP protocol conformance validation,
- validate structural integrity and required metadata presence,
- fail closed on any validation error,
- mark capsules as **validated** only upon successful verification.

A capsule that has not been marked validated SHALL NOT be treated as BEAP by any other component and SHALL NOT be distributed.

#### **B.2.6.3 Distribution Gate**

Distribution to any trust domain SHALL occur only for capsules marked validated by the validator.

The interface between ingestor and validator SHALL be non-bypassable. No component other than the validator SHALL be able to mark a capsule as validated.

#### **B.2.6.4 Isolation Requirements**

The ingestor and validator SHALL run in **strict isolation**.

Isolation SHALL be enforced by executing the ingestion pipeline:

- either on the host in a strictly isolated, non-interactive environment, or
- on a physically detached container or virtual machine with root control.

The ingestion environment MUST be configured for RAM-only operation, and all volatile memory used during depackaging or validation SHALL be securely cleared immediately after each depackaging process completes.

Isolation of the ingestion pipeline is mandatory and SHALL be treated as a non-bypassable security boundary. The specific isolation mechanism is implementation-dependent but MUST provide strong separation from both the primary (host) and sandbox orchestrators.

## **Annex X – Deterministic Client Execution, Extension Governance, and Off-Band Routing (Informative)**

In **High-Assurance Mode**, WRDesk operates the primary orchestrator under strictly deterministic conditions. All executable components, including browser extensions and client-side execution units, **MUST** be **cryptographically WRStamped, version-pinned, and identity-bound**. Dynamic runtime code, uncontrolled auto-updates, and non-verifiable execution paths are excluded from the authoritative execution domain.

To support this model, WRDesk plans a **WRStamped extension distribution framework**, enabling deterministic deployment, controlled updates, revocation, and lifecycle management of verified execution units in high-assurance environments.

The orchestrator enforces a **single authoritative browser context** configured exclusively with WRStamped extensions and a static execution profile. This context represents the **trusted execution cage**. Any content, action, or workflow that cannot be conclusively verified, is classified as risk-bearing, or does not meet deterministic assurance requirements is **automatically routed off-band**.

**Original artefacts extracted from emails (including attachments, embedded content, or referenced payloads) are automatically redirected to the off-band execution path.** If configured, the orchestrator **MAY** automatically trigger a **sandbox computation wake-up** to process or inspect these artefacts in an isolated environment. If no automatic off-band switch to the sandbox environment is provisioned, an **explicit manual context switch via hotkey** is the recommended and enforced interaction pattern.

Off-band execution targets **MAY** include isolated RAM-only systems, mini-PCs, tablets, or equivalent sandboxed devices. **Explicit separation between observation and effect is enforced via dedicated hotkeys or programmable KVM switches. Special-purpose KVM devices with RS232 interfaces MAY be used for deterministic, scriptable routing and are supported for direct control and integration within the orchestrator.**

Extensions and tools executed off-band **MAY** persist depending on the operating system and deployment profile. RAM-only configurations are **RECOMMENDED**. Regardless of persistence, the system guarantees a **return to a known-good baseline**, either manually or through automatically triggered reset intervals, preventing long-term state drift and accumulation of untrusted changes.

This architecture preserves unrestricted exploration while ensuring that all authoritative execution remains deterministic, auditable, revocable, and provably governed.

### **WRVault™ (Terminology Clarification — Single Sentence, Normative)**

**WRVault™** denotes a locally controlled, encrypted, multi-layered secure vault bound to the executing environment and identity, combining password management, PII storage, and sensitive data protection, in which all data **SHALL** be compartmentalized, scope- and purpose-restricted, cryptographically isolated by class, never directly accessible, and only exposed through controlled, augmented overlay contexts to prevent unauthorized extraction, misuse, or cross-domain leakage.

## License Notice

This annex (Annex A1), including all definitions, sections, and provisions contained herein, is an integral part of the **WR Desk™** specification.

It is licensed under the same license terms as **WR Desk™**, **BEAP™**, and **PoAE™**, as defined in the main repository README and the accompanying license files.