

Lecture 8: More DCGs

- Theory
 - Examine two important capabilities offered by DCG notation:
 - Extra arguments
 - Extra tests
 - Discuss the status and limitations of DCGs
- Exercises
 - Exercises of LPN: 8.1, 8.2
 - Practical session

Extra arguments

- In the previous lecture we introduced basic DCG notation
- But DCGs offer more than we have seen so far
 - DCGs allow us to specify extra arguments
 - These extra arguments can be used for many purposes

Extending the grammar

- This is the simple grammar from the previous lecture
- Suppose we also want to deal with sentences containing pronouns such as

she shoots him

and

he shoots her

- What do we need to do?

s --> np, vp.
np --> det, n.
vp --> v, np.
vp --> v.
det --> [the].

det --> [a].
n --> [woman].

n --> [man].

v --> [shoots].

Extending the grammar

- Add rules for pronouns
- Add a rule saying that noun phrases can be pronouns
- Is this new DCG any good?
- What is the problem?

```
s --> np, vp.  
np --> det, n.  
np --> pro.  
vp --> v, np.  
vp --> v.  
det --> [the].  
det --> [a].  
n --> [woman].  
n --> [man].  
v --> [shoots].  
pro --> [he].  
pro --> [she].  
pro --> [him].  
pro --> [her].
```

Some examples of grammatical strings accepted by this DCG

```
?- s([she,shoots,him],[ ]).
```

```
yes
```

```
?- s([a,woman,shoots,him],[ ]).
```

```
yes
```

```
s --> np, vp.
```

```
np --> det, n.
```

```
np --> pro.
```

```
vp --> v, np.
```

```
vp --> v.
```

```
det --> [the].
```

```
det --> [a].
```

```
n --> [woman].
```

```
n --> [man].
```

```
v --> [shoots].
```

```
pro --> [he].
```

```
pro --> [she].
```

```
pro --> [him].
```

```
pro --> [her].
```

Some examples of ungrammatical strings accepted by this DCG

?- s([a,woman,shoots,he],[]).

yes

?- s([her,shoots,a,man],[]).

yes

s([her,shoots,she],[]).

yes

s --> np, vp.

np --> det, n.

np --> pro.

vp --> v, np.

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

v --> [shoots].

pro --> [he].

pro --> [she].

pro --> [him].

pro --> [her].

What is going wrong?

- The DCG ignores some basic facts about English
 - *she* and *he* are subject pronouns and cannot be used in object position
 - *her* and *him* are object pronouns and cannot be used in subject position
- It is obvious what we need to do: extend the DCG with information about subject and object
- How do we do this?

A naïve way...

s --> np_subject, vp.

np_subject --> det, n.

np_subject --> pro_subject.

vp --> v, np_object.

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

v --> [shoots].

pro_subject --> [he].

pro_subject --> [she].

pro_object --> [him].

pro_object --> [her].

np_object --> det, n.

np_object --> pro_object.

Nice way using extra arguments

```
s --> np(subject), vp.  
np(_) --> det, n.  
np(X) --> pro(X).  
vp --> v, np(object).  
vp --> v.  
det --> [the].  
det --> [a].  
n --> [woman].  
n --> [man].  
v --> [shoots].  
pro(subject) --> [he].  
pro(subject) --> [she].  
pro(object) --> [him].  
pro(object) --> [her].
```

This works...

s --> np(subject), vp.
np(_) --> det, n.
np(X) --> pro(X).
vp --> v, np(object).
vp --> v.
det --> [the].
det --> [a].
n --> [woman].
n --> [man].
v --> [shoots].
pro(subject) --> [he].
pro(subject) --> [she].
pro(object) --> [him].
pro(object) --> [her].

?- s([she,shoots,him],[]).
yes
?- s([she,shoots,he],[]).
no
?-

What is really going on?

- Recall that the rule:
 $s \rightarrow np, vp.$
is really syntactic sugar for:
 $s(A,B):- np(A,C), vp(C,B).$

What is really going on?

- Recall that the rule:
 $s \rightarrow np, vp.$
is really syntactic sugar for:
 $s(A,B):- np(A,C), vp(C,B).$
- The rule
 $s \rightarrow np(\text{subject}), vp.$
translates into:
 $s(A,B):- np(\text{subject},A,C), vp(C,B).$

Listing noun phrases


```
s --> np(subject), vp.  
np(_) --> det, n.  
np(X) --> pro(X).  
vp --> v, np(object).  
vp --> v.  
det --> [the].  
det --> [a].  
n --> [woman].  
n --> [man].  
v --> [shoots].  
pro(subject) --> [he].  
pro(subject) --> [she].  
pro(object) --> [him].  
pro(object) --> [her].
```

```
?- np(Type, NP, [ ]).  
Type =_  
NP = [the,woman];  
  
Type =_  
NP = [the,man];  
  
Type =_  
NP = [a,woman];  
  
Type =_  
NP = [a,man];  
  
Type =subject  
NP = [he]
```


Building parse trees

- The programs we have discussed so far have been able to recognise grammatical structure of sentences
- But we would also like to have a program that gives us an analysis of their structure
- In particular we would like to see the trees the grammar assigns to sentences

Parse tree example



Parse tree in Prolog



DCG that builds parse tree

s --> np(subject), vp.

np(_) --> det, n.

np(X) --> pro(X).

vp --> v, np(object).

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

v --> [shoots].

pro(subject) --> [he].

pro(subject) --> [she].

pro(object) --> [him].

pro(object) --> [her].

DCG that builds parse tree

s --> np(subject), vp.
np(_) --> det, n.

np(X) --> pro(X).

vp --> v, np(object).

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

v --> [shoots].

pro(subject) --> [he].

pro(subject) --> [she].

pro(object) --> [him].

pro(object) --> [her].

s(s(NP,VP)) --> np(subject,NP), vp(VP).
np(_,np(Det,N)) --> det(Det), n(N).

np(X,np(Pro)) --> pro(X,Pro).

vp(vp(V,NP)) --> v(V), np(object,NP).

vp(vp(V)) --> v(V).

det(det(the)) --> [the].

det(det(a)) --> [a].

n(n(woman)) --> [woman].

n(n(man)) --> [man].

v(v(shoots)) --> [shoots].

pro(subject,pro(he)) --> [he].

pro(subject,pro(she)) --> [she].

pro(object,pro(him)) --> [him].

pro(object,pro(her)) --> [her].

Generating parse trees

$s(s(NP, VP)) \rightarrow np(\text{subject}, NP), vp(VP).$
 $np(_, np(\text{Det}, N)) \rightarrow \text{det}(\text{Det}), n(N).$

$np(X, np(\text{Pro})) \rightarrow \text{pro}(X, \text{Pro}).$
 $vp(vp(V, NP)) \rightarrow v(V), np(\text{object}, NP).$
 $vp(vp(V)) \rightarrow v(V).$

$np(_, np(\text{the})) \rightarrow [\text{the}].$

$\rightarrow [a].$

$\rightarrow [\text{woman}].$

$\rightarrow [\text{man}].$

$\rightarrow [\text{shoots}].$

$\text{pro}(\text{subject}, \text{pro}(\text{he})) \rightarrow [\text{he}].$

$\text{pro}(\text{subject}, \text{pro}(\text{she})) \rightarrow [\text{she}].$

$\text{pro}(\text{object}, \text{pro}(\text{him})) \rightarrow [\text{him}].$

$\text{pro}(\text{object}, \text{pro}(\text{her})) \rightarrow [\text{her}].$

?- $s(T, [\text{he}, \text{shoots}], []).$

$T = s(np(\text{pro}(\text{he})), vp(v(\text{shoots})))$

yes

Generating parse trees

?- s(Tree,S,[]).

s(s(NP,VP)) --> np(subject,NP), vp(VP).

np(Det,N)) --> det(Det), n(N).

np(Pro)) --> pro(X,Pro).

v(V,NP)) --> v(V), np(object,NP).

v(V)) --> v(V)).

det(the)) --> [the].

det(a)) --> [a].

det(woman)) --> [woman].

det(man)) --> [man].

v(v(shoots)) --> [shoots].

pro(subject,pro(he)) --> [he].

pro(subject,pro(she)) --> [she].

pro(object,pro(him)) --> [him].

pro(object,pro(her)) --> [her].

Beyond context free languages

- In the previous lecture we presented DCGs as a useful tool for working with context free grammars
- However, DCGs can deal with a lot more than just context free grammars
- The extra arguments gives us the tools for coping with any computable language
- We will illustrate this by looking at the formal language $a^n b^n c^n \setminus \{\epsilon\}$

An example

- The language $a^n b^n c^n \setminus \{\epsilon\}$ consists of strings such as abc, aabbcc, aaabbbccc, aaaabbbbcccc, and so on
- This language is not context free – it is impossible to write a context free grammar that produces exactly these strings
- But it is very easy to write a DCG that does this

DCG for $a^n b^n c^n \setminus \{\epsilon\}$

$s(\text{Count}) \text{-->} as(\text{Count}), bc(\text{Count}), cs(\text{Count}).$

$as(0) \text{-->} [].$

$as(\text{succ}(\text{Count})) \text{-->} [a], as(\text{Count}).$

$bs(0) \text{-->} [].$

$bs(\text{succ}(\text{Count})) \text{-->} [b], bs(\text{Count}).$

$cs(0) \text{-->} [].$

$cs(\text{succ}(\text{Count})) \text{-->} [c], cs(\text{Count}).$

Exercises

- LPN 8.1

Extra goals

- Any DCG rule is really syntactic structure for ordinary Prolog rule
- So it is not really surprising we can also call any Prolog predicate from the right-hand side of a DCG rule
- This is done by using curly brackets { }

Example: DCG for $a^n b^n c^n \setminus \{\epsilon\}$

$s(\text{Count}) \rightarrow as(\text{Count}), bc(\text{Count}), cs(\text{Count}).$

$as(0) \rightarrow [].$

$as(\text{NewCnt}) \rightarrow [a], as(\text{Cnt}), \{\text{NewCnt is Cnt} + 1\}.$

$bs(0) \rightarrow [].$

$bs(\text{NewCnt}) \rightarrow [b], bs(\text{Cnt}), \{\text{NewCnt is Cnt} + 1\}.$

$cs(0) \rightarrow [].$

$cs(\text{NewCnt}) \rightarrow [c], cs(\text{Cnt}), \{\text{NewCnt is Cnt} + 1\}.$

Separating rules and lexicon

- One classic application of the extra goals of DCGs in computational linguistics is separating the grammar rules from the lexicon
- What does this mean?
 - Eliminate all mention of individual words in the DCG
 - Record all information about individual words in a separate lexicon

The basic grammar

s --> np, vp.

np --> det, n.

vp --> v, np.

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

v --> [shoots].

The modular grammar

s --> np, vp.

np --> det, n.

vp --> v, np.

vp --> v.

det --> [the].

det --> [a].

n --> [woman].

n --> [man].

s --> np, vp.

np --> det, n.

vp --> v, np.

vp --> v.

det --> [Word], {lex(Word,det)}.

n --> [Word], {lex(Word,n)}.

v --> [Word], {lex(Word,v)}.

lex(the, det).

lex(a, det).

lex(woman, n).

lex(man, n).

lex(shoots, v).

v --> [shoots].

Concluding Remarks

- DCGs are a simple tool for encoding context free grammars
- But in fact DCGs are a full-fledged programming language and can be used for many different purposes
- For linguistic purposes, DCG have drawbacks
 - Left-recursive rules
 - DCGs are interpreted top-down
- DCGs are no longer state-of-the-art, but they remain a useful tool

Next lecture

- A closer look at terms
 - Introduce the identity predicate
 - Take a closer look at term structure
 - Introduce pre-defined Prolog predicates that test whether a given term is of a certain type
 - Show how to define new operators in Prolog