

Constraint Satisfaction Problem [Var, Dom, Con]

- ▶ a list $\text{Var} = [X_1, \dots, X_n]$ of *variables* X_i
- ▶ a list $\text{Dom} = [D_1, \dots, D_n]$ of finite sets D_i of size s_i
- ▶ a finite set Con of *constraints* that may or may not be satisfied by (a node) instantiating X_i with a value in D_i (search space size $\prod_{i=1}^n s_i$)

Constraint Satisfaction Problem [Var, Dom, Con]

- ▶ a list $\text{Var} = [X_1, \dots, X_n]$ of *variables* X_i
- ▶ a list $\text{Dom} = [D_1, \dots, D_n]$ of finite sets D_i of size s_i
- ▶ a finite set Con of *constraints* that may or may not be satisfied by (a node) instantiating X_i with a value in D_i (search space size $\prod_{i=1}^n s_i$)

E.g. SAT: $D_i = \{0, 1\}$, $s_i = 2$ for search space of size 2^n

Constraint Satisfaction Problem [Var, Dom, Con]

- ▶ a list $\text{Var} = [X_1, \dots, X_n]$ of *variables* X_i
- ▶ a list $\text{Dom} = [D_1, \dots, D_n]$ of finite sets D_i of size s_i
- ▶ a finite set Con of *constraints* that may or may not be satisfied by (a node) instantiating X_i with a value in D_i (search space size $\prod_{i=1}^n s_i$)

E.g. SAT: $D_i = \{0, 1\}$, $s_i = 2$ for search space of size 2^n

Problem: satisfy all constraints in Con , instantiating variables if necessary/convenient

Constraint Satisfaction Problem [Var, Dom, Con]

- ▶ a list $\text{Var} = [X_1, \dots, X_n]$ of *variables* X_i
- ▶ a list $\text{Dom} = [D_1, \dots, D_n]$ of finite sets D_i of size s_i
- ▶ a finite set Con of *constraints* that may or may not be satisfied by (a node) instantiating X_i with a value in D_i (search space size $\prod_{i=1}^n s_i$)

E.g. SAT: $D_i = \{0, 1\}$, $s_i = 2$ for search space of size 2^n

Problem: satisfy all constraints in Con , instantiating variables if necessary/convenient

| ?- $X \setminus=Y, X=a, Y=b.$

no

Constraint Satisfaction Problem [Var, Dom, Con]

- ▶ a list $\text{Var} = [X_1, \dots, X_n]$ of *variables* X_i
- ▶ a list $\text{Dom} = [D_1, \dots, D_n]$ of finite sets D_i of size s_i
- ▶ a finite set Con of *constraints* that may or may not be satisfied by (a node) instantiating X_i with a value in D_i (search space size $\prod_{i=1}^n s_i$)

E.g. SAT: $D_i = \{0, 1\}$, $s_i = 2$ for search space of size 2^n

Problem: satisfy all constraints in Con , instantiating variables if necessary/convenient

| ?- $X \neq Y$, $X=a$, $Y=b$.

no

| ?- $X=a$, $Y=b$, $X \neq Y$.

$X = a$, $Y = b$

Order-independent unification (Martelli-Montanari)

Input: set \mathcal{E} of pairs $[t, t']$

Output: substitution $[[X_1, t_1], \dots, [X_k, t_k]]$ unifying pairs in \mathcal{E}

Order-independent unification (Martelli-Montanari)

Input: set \mathcal{E} of pairs $[t, t']$

Output: substitution $[[X_1, t_1], \dots, [X_k, t_k]]$ unifying pairs in \mathcal{E}

Simplify \mathcal{E} non-deterministically until no longer possible

1. $[f(s_1, \dots, s_k), f(t_1, \dots, t_k)]$ (allowing $k = 0$)
 \implies replace by pairs $[s_1, t_1], \dots, [s_k, t_k]$
2. $[f(s_1, \dots, s_k), g(t_1, \dots, t_m)]$ where $f \neq g$ or $k \neq m$
 \implies halt with failure
3. $[X, X] \implies$ delete
4. $[t, X]$ where t is not a var \implies replace by $[X, t]$
5. $[X, t]$ where $X \notin \text{Var}(t)$ and X occurs elsewhere
 \implies apply $[X, t]$ to all other pairs
6. $[X, t]$ where $X \in \text{Var}(t)$ and $X \neq t \implies$ halt with failure

Order-independent unification (Martelli-Montanari)

Input: set \mathcal{E} of pairs $[t, t']$

Output: substitution $[[X_1, t_1], \dots, [X_k, t_k]]$ unifying pairs in \mathcal{E}

Simplify \mathcal{E} non-deterministically until no longer possible

1. $[f(s_1, \dots, s_k), f(t_1, \dots, t_k)]$ (allowing $k = 0$)
 \implies replace by pairs $[s_1, t_1], \dots, [s_k, t_k]$
2. $[f(s_1, \dots, s_k), g(t_1, \dots, t_m)]$ where $f \neq g$ or $k \neq m$
 \implies halt with failure
3. $[X, X] \implies$ delete
4. $[t, X]$ where t is not a var \implies replace by $[X, t]$
5. $[X, t]$ where $X \notin \text{Var}(t)$ and X occurs elsewhere
 \implies apply $[X, t]$ to all other pairs
6. $[X, t]$ where $X \in \text{Var}(t)$ and $X \neq t \implies$ halt with failure

N.B. Prolog omits *occurs check* $X \in \text{Var}(t)$ in 5, 6 for speed-up

Instantiate before negating (as failure)

```
% \+p :- (p,!,fail); true.
```

```
p(X) :- \+q(X), r(X).
```

```
q(a).  q(b).
```

```
r(a).  r(c).
```

```
-----
```

```
| ?- p(X).
```

```
% contra ?- p(c).
```

Instantiate before negating (as failure)

```
% \+p :- (p,!,fail); true.
```

```
p(X) :- \+q(X), r(X).
```

```
q(a). q(b).
```

```
r(a). r(c).
```

```
-----
```

```
| ?- p(X).
```

```
% contra ?- p(c).
```

```
p(X) :- \+q(X).
```

```
q(X) :- \+r(X).
```

```
r(c).
```

```
-----
```

```
| ?- p(X).
```

```
% contra ?- p(a).
```

Generate-and-test

brute force: instantiate all variables before testing constraints

```
genTest(D1...Dn) :- node(X1...Xn,D1...Dn),  
                    constraint(X1...Xn).  
node(X1...Xn,D1...Dn) :- member(X1,D1),...,  
                          member(Xn,Dn).
```

Generate-and-test

brute force: instantiate all variables before testing constraints

```
genTest(D1...Dn) :- node(X1...Xn,D1...Dn),  
                    constraint(X1...Xn).  
node(X1...Xn,D1...Dn) :- member(X1,D1),...,  
                          member(Xn,Dn).
```

For each of the $\prod_{i=1}^n s_i$ -choices of $X1 \dots Xn$ such that

```
node(X1...Xn,D1...Dn)
```

(with D_i of size s_i), assume

```
constraint(X1...Xn)
```

can be checked within a polynomial of $X1 \dots Xn$.

Generate-and-test

brute force: instantiate all variables before testing constraints

```
genTest(D1...Dn) :- node(X1...Xn,D1...Dn),  
                    constraint(X1...Xn).  
node(X1...Xn,D1...Dn) :- member(X1,D1),...,  
                          member(Xn,Dn).
```

For each of the $\prod_{i=1}^n s_i$ -choices of $X1 \dots Xn$ such that

`node(X1...Xn,D1...Dn)`

(with D_i of size s_i), assume

`constraint(X1...Xn)`

can be checked within a polynomial of $X1 \dots Xn$.

Nodes are generated in lexicographic order *without* regard to constraints.

Inferring changes

Horn-SAT by minimal changes to $00 \cdots 0$ (all variables 0/false)

CSAT	definite clause	list encoding
$\bar{u} \vee x \vee \bar{z}$	$x \text{ :- } u, z.$	$[x, u, z]$
$\bar{u} \vee \bar{v}$	$\text{false} \text{ :- } u, v.$	$[\text{false}, u, v]$

Inferring changes

Horn-SAT by minimal changes to $00 \cdots 0$ (all variables 0/false)

CSAT	definite clause	list encoding
$\bar{u} \vee x \vee \bar{z}$	$x :- u, z.$	$[x, u, z]$
$\bar{u} \vee \bar{v}$	$false :- u, v.$	$[false, u, v]$

For each stage i , collect the variables set at stage i to 1/true in A_i

$$A_0 := \emptyset \quad (\text{all variables false})$$

$$A_{i+1} := \{x \mid \underbrace{\text{member}([x|T], KB)}_{x :- t_1 \dots t_k \text{ in } KB} \text{ and } \underbrace{\text{all}(T, A_i)}_{\{t_1 \dots t_k\} \subseteq A_i}\}$$

check: $false \notin A_n$

Inferring changes

Horn-SAT by minimal changes to $00 \cdots 0$ (all variables 0/false)

CSAT	definite clause	list encoding
$\bar{u} \vee x \vee \bar{z}$	$x \text{ :- } u, z.$	$[x, u, z]$
$\bar{u} \vee \bar{v}$	$\text{false} \text{ :- } u, v.$	$[\text{false}, u, v]$

For each stage i , collect the variables set at stage i to 1/true in A_i

$$A_0 := \emptyset \quad (\text{all variables false})$$

$$A_{i+1} := \{x \mid \underbrace{\text{member}([x|T], KB)}_{x \text{ :- } t_1 \dots t_k \text{ in } KB} \text{ and } \underbrace{\text{all}(T, A_i)}_{\{t_1 \dots t_k\} \subseteq A_i}\}$$

check: $\text{false} \notin A_n$

No minimal set for non-Horn $x \vee y$ (or xor).

Instantiate one variable at a time

allow node to map X_i to ?, raising search space size from

$$\prod_{i=1}^n s_i \text{ to } \prod_{i=1}^n (s_i + 1) \text{ from adding ? to } D_i$$

PAY-OFF: search tree of depth n and branching factor $\max_i s_i$
with start node instantiating no variable, and
an arc instantiating least uninstantiated variable


Instantiate one variable at a time

allow node to map X_i to ?, raising search space size from

$$\prod_{i=1}^n s_i \text{ to } \prod_{i=1}^n (s_i + 1) \text{ from adding ? to } D_i$$

PAY-OFF: search tree of depth n and branching factor $\max_i s_i$
with start node instantiating no variable, and
an arc instantiating least uninstantiated variable

E.g. $n = 2$, $D_1 = D_2 = \{a, b\}$



Interleave generation with testing + backtracking

whenever $\text{arc}(N0, N1)$,

$N1$ instantiates one more variable than $N0$, and

$N1$ satisfies every constraint on instantiated variables

Interleave generation with testing + backtracking

whenever $\text{arc}(N0, N1)$,

$N1$ instantiates one more variable than $N0$, and

$N1$ satisfies every constraint on instantiated variables

Reduce domains of un-instantiated variables via constraints

Constraint Graph: node = variable (e.g. 3-Color)

$$\text{arc}(X_i, X_j) \iff \text{Con}[X_i, X_j] \neq \emptyset$$

Arc Consistency: for $\text{arc}(X_i, X_j)$ and $i < j$,

$$(\forall d \in D(X_i))(\exists d' \in D(X_j)) \text{ } d, d' \text{ satisfy } \text{Con}[X_i, X_j]$$

removing d from $D(X_i)$ when no such d' exists

Interleave generation with testing + backtracking

whenever $arc(N0, N1)$,

$N1$ instantiates one more variable than $N0$, and

$N1$ satisfies every constraint on instantiated variables

Reduce domains of un-instantiated variables via constraints

Constraint Graph: node = variable (e.g. 3-Color)

$$arc(X_i, X_j) \iff \text{Con}[X_i, X_j] \neq \emptyset$$

Arc Consistency: for $arc(X_i, X_j)$ and $i < j$,

$$(\forall d \in D(X_i))(\exists d' \in D(X_j)) \text{ } d, d' \text{ satisfy } \text{Con}[X_i, X_j]$$

removing d from $D(X_i)$ when no such d' exists

Optimizing the backtracking search

- ▶ MRV: instantiate variable with minimum remaining values (to minimize branching/cases)
- ▶ LCV: assign value that is least constraining (for greatest chance of success)