# Real-Time IoT Sensor Data Pipeline

## Digital Egypt Pioneers Initiative

## Track: Microsoft Data Engineer

**ONL5_AIS5_G1 – Team_1**

**2026**

# Literature Review

## 1. Purpose and Scope

This review explains the concepts behind a real-time IoT pipeline, compares the main tool options for each layer, and gives the reason for each choice.

## 2. Background

### 2.1 IoT data and why streaming

IoT devices produce continuous, time-stamped readings. Value is highest when readings are acted on quickly (equipment faults, environment alarms), so batch loads that run hourly or daily are often too slow. Sensor data is also messy as devices send duplicates, readings arrive late or out of order, and values can be missing or physically impossible. A pipeline has to handle these cases by design.

### 2.2 Architecture styles

- **Lambda architecture** runs a batch layer and a speed layer side by side. It gives accurate and fast results but means two code bases to maintain.
- **Kappa architecture** treats everything as a stream over a replayable log. It has one code base, and reprocessing means replaying the log (Kreps, 2014).
- **Medallion layering** (raw, clean, aggregated) organizes stored data by quality level. It fits the project's layered storage and makes replay and audit easy.

The project uses an event-driven, Kappa-style design with layered storage. Kafka is the replayable log, and a single streaming job produces the clean and aggregated layers.

### 2.3 Core streaming concepts

| Concept | Meaning | Why it matters here |
|---|---|---|
| Event time vs processing time | When a reading happened vs when the system saw it | Windows must use event time or late data lands in the wrong window (Akidau et al., 2015) |
| Watermark | The system's estimate of how late data can still arrive | Decides when a window is final and when old state can be dropped |
| Windowing | Grouping events into time buckets (tumbling, sliding) | Produces per-minute and per-site aggregates for the dashboard |

| Concept | Meaning | Why it matters here |
|---|---|---|
| Delivery semantics | At-most-once, at-least-once, exactly-once | At-least-once delivery plus idempotent writes can give an exactly-once effect, depending on the full persistence and recovery design |
| Deduplication | Removing repeated events using a unique event ID | Sensors and retries create duplicates |
| Dead-letter queue | A separate store for records that fail validation | Keeps bad data out of analytics without losing it |
| Backpressure and consumer lag | A consumer falling behind the producer | An early sign of an overloaded pipeline; a KPI in this project |

## 2.4 Data quality and observability

Streaming data needs checks at ingestion: schema validation, range checks, completeness and freshness. Observability adds metrics on latency, throughput, lag and error rates so that problems are seen before users notice. The project builds both into the pipeline instead of adding them later. Data quality rules are written and reported with Great Expectations.

## 3. Related Work: Tool Comparison

Each table compares the chosen tool with common alternatives. Statements are general characteristics, and the last column gives the reason for the decision.

## 3.1 Message broker

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| **Apache Kafka** | Durable partitioned log, replay within the retention period, high throughput, large ecosystem, works with Spark | Heavier to run than a simple broker | **Chosen:** replay supports reprocessing and the Kappa design; widely used in industry |
| RabbitMQ | Flexible routing, mature queueing | Classic queues remove messages once acknowledged, so replay is | Not chosen |

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| | | limited (RabbitMQ Streams add a log model) | |
| MQTT broker (for example Mosquitto) | Very light, the standard protocol for constrained devices | Not built for long retention or stream processing at scale | Not chosen; could sit in front of Kafka in a real deployment |
| Azure Event Hubs / IoT Hub | Managed, scalable, Kafka-compatible endpoint (Event Hubs) | Paid cloud service, outside the free-tools rule | Not chosen; design maps to it directly |

## 3.2 Stream processing

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| **PySpark Structured Streaming** | Python API, SQL-like operations, event-time windows and watermarks, same engine as the course (Armbrust et al., 2018) | Micro-batch model gives latency of seconds, not milliseconds | **Chosen:** fits the track, the team's skills, and the latency target |
| Apache Flink | Event-at-a-time processing, low latency, strong state handling (Carbone et al., 2015) | Steeper operations and learning curve, not covered in the course | Not chosen |
| Kafka Streams | Library inside the application, no separate cluster | JVM languages only, so no Python | Not chosen |
| Azure Stream Analytics | Managed, SQL-like queries | Paid, cloud only | Not chosen |

## 3.3 Storage and serving

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| **Apache Parquet** | Columnar, compressed, open file format, good for | No transactions or table features by itself; many | **Chosen (confirmed)** for the raw and clean layers; the |

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| | raw and clean history and replay | small files need periodic compaction | lake_compaction DAG handles small files |
| **SQL Server Developer** | Relational model with keys and constraints, T-SQL, SSMS tooling, in the course scope, free for development and testing | Developer edition is not licensed for production; heavier than lightweight databases | **Chosen (confirmed)** for the serving layer; supports the ER diagram and logical and physical schema in the guidelines |
| Delta Lake | Adds ACID transactions, schema enforcement and time travel on top of Parquet | Extra dependency and complexity | Not chosen; the lake format is plain Apache Parquet |
| PostgreSQL | Free open-source relational database | Outside the confirmed stack | Not chosen |
| TimescaleDB or InfluxDB | Purpose-built for time series | Extra component and different design work | Not chosen |
| Azure Data Lake or Synapse | Industry-grade cloud analytics | Paid, cloud only | Not chosen |

## 3.4 Dashboard

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| **Grafana** | Free, strong time-series panels, auto-refresh, built-in Microsoft SQL Server data source, runs in Docker | Another service to configure | **Chosen (confirmed)** |
| **Streamlit** | Pure Python, quick to build | Less polished for time-series monitoring | Not chosen |

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| Power BI | Familiar in the Microsoft ecosystem | Desktop is free, but live streaming and sharing need paid features | Not chosen |

Decision: Grafana, approved on 17 Oct 2026. Streamlit was considered and dropped.

## 3.5 Data quality

| Option | Strengths | Limitations for this project | Decision |
|---|---|---|---|
| **Great Expectations** | Open-source Python framework with reusable expectation suites, stored validation results and generated data docs; works with Spark and SQL data sources | Built around batch validation, so it validates the stored clean Parquet and SQL Server tables while Spark keeps the per-event checks; setup effort | **Chosen (confirmed)** |
| Deequ | Library for data unit tests on Spark | Scala-first, Python access through PyDeequ | Not chosen |
| Soda Core | Open-source checks written in a YAML-style language | Another tool outside the course | Not chosen |
| Custom rules and a Python runner | Full control and small footprint | Reporting, documentation and upkeep are built by hand | Not chosen |

## 3.6 Orchestration and deployment

| Option | Role | Decision |
|---|---|---|
| Apache Airflow | Schedules the five required DAGs: stream_health_check, dq_daily_report, lake_compaction, gold_backfill and warehouse_maintenance; in the course scope | Chosen (confirmed) |
| Docker Compose | Runs the whole stack locally with one command | Chosen (confirmed) |

| Option | Role | Decision |
|---|---|---|
| GitHub Actions | Lint and tests on each push | Optional CI |

## 4. Related Architectures and Patterns

- **Cloud reference design:** sensors, IoT Hub or Event Hubs, a stream processor, a data lake and a warehouse, then a BI tool. The project mirrors this with free equivalents, so the design can be moved to the cloud by swapping components.
- **Open-source reference design:** devices, Kafka, Spark or Flink, a lake and a database, then Grafana. This is the design chosen here.
- **Industrial monitoring:** predictive maintenance systems often add machine learning on top of the same pipeline. The project covers the data foundation and leaves models out of scope.

## 5. Gaps and How the Project Addresses Them

| Gap seen in typical tutorials | How the project addresses it |
|---|---|
| Happy-path data only | Simulator injects late, duplicate and malformed events |
| No measured results | KPIs for latency, throughput, freshness, errors and uptime, measured and reported |
| Hard to run elsewhere | One-command Docker Compose setup |
| Quality checked after the fact | Validation and dead-letter handling inside the stream, plus Great Expectations suites and a daily quality report |
| Little documentation | Full guideline set: design diagrams, tests, manual, README |

## 6. Summary of Decisions

The confirmed baseline is a Python simulator, Kafka, PySpark Structured Streaming, Apache Parquet for the lake, SQL Server Developer for serving, Great Expectations for data quality, Airflow for orchestration and Docker Compose for local deployment. The dashboard is Grafana. All tools are free to use, fit the course content, and match designs used in industry. Most choices have a cloud equivalent, so the work transfers to Azure.

## 7. References

Author names, years, venues and page ranges were checked against publisher and index records on 17 Oct 2026. Links were added on 18 Oct 2026 from the publishers' and official project sites.

1. Akidau, T. et al. (2015). The Dataflow Model: A Practical Approach to Balancing Correctness, Latency, and Cost in Massive-Scale, Unbounded, Out-of-Order Data Processing. Proceedings of the VLDB Endowment, 8(12), pp. 1792-1803. DOI: 10.14778/2824032.2824076. Page: Google Research.
2. Armbrust, M. et al. (2018). Structured Streaming: A Declarative API for Real-Time Applications in Apache Spark. Proceedings of the ACM SIGMOD International Conference on Management of Data, Houston, pp. 601-613. DOI: 10.1145/3183713.3190664.
3. Carbone, P. et al. (2015). Apache Flink: Stream and Batch Processing in a Single Engine. Bulletin of the IEEE Computer Society Technical Committee on Data Engineering, 36(4), pp. 28-38. Record: TU Delft repository. PDF copy: cs.uic.edu.
4. Kleppmann, M. (2017). Designing Data-Intensive Applications. O'Reilly Media, first edition, ISBN 978-1-449-37332-0. O'Reilly page.
5. Kreps, J. (2014). Questioning the Lambda Architecture. O'Reilly Radar, 2 July 2014. Article.
6. Kreps, J., Narkhede, N. and Rao, J. (2011). Kafka: a Distributed Messaging System for Log Processing. NetDB Workshop, Athens, 12 June 2011. PDF copy.
7. Official documentation: Apache Kafka, Apache Spark Structured Streaming Programming Guide, Apache Parquet, Microsoft SQL Server, Great Expectations (GX Core overview), Apache Airflow, Grafana (Microsoft SQL Server data source), Docker Compose.

# Project Planning and Management

## 1. Project Proposal

### 1.1 Overview

The project builds an end-to-end real-time data pipeline for IoT sensor data. A device simulator publishes readings (temperature, humidity, CO2, power draw) from a fleet of devices spread over several sites. The readings travel through a message broker, are validated and enriched by a streaming job, are stored in layered storage, and are served to a live dashboard. Bad records are quarantined instead of being lost or crashing the pipeline.

The whole system runs from one Docker Compose command, uses free tools only, and is tested with late, duplicate and malformed events.

### 1.2 Problem statement

Organizations that monitor equipment and buildings receive thousands of sensor readings per second. Batch processing shows problems hours late, raw data contains duplicates, gaps and corrupt values, and dashboards built on unvalidated data cannot be trusted. The project shows how to deliver validated, fresh sensor data to analysts within seconds, with measurable quality and reliability.

### 1.3 Objectives

- O1. Ingest simulated sensor events from at least 500 devices at a sustained rate of 500 events per second or more.
- O2. Process events in a streaming job that parses, validates, deduplicates, handles late data with watermarks, and computes windowed aggregates.
- O3. Route invalid events to a dead-letter store with the failure reason, so nothing is silently dropped, and check data quality with Great Expectations suites.
- O4. Store data in layers (raw, clean, aggregated) with Apache Parquet files for the lake, and expose a relational serving layer in SQL Server Developer for analytics.
- O5. Show live device and site metrics on a dashboard with data no more than 15 seconds old.
- O6. Meet the KPI targets in section 5 and prove it with a measured test report.
- O7. Deliver everything the guidelines require: documentation, GitHub repository, automated tests, one-command setup, presentation and infographic.
- O8. Orchestrate maintenance and reporting with Airflow DAGs: stream_health_check, dq_daily_report, lake_compaction, gold_backfill and warehouse_maintenance.

## 1.4 Scope Management

**In scope**

- A Python device simulator with configurable rate, device count and fault injection (late, duplicate, malformed, out-of-range events).
- Kafka topics for raw events, with a dead-letter topic.
- PySpark Structured Streaming jobs for validation, deduplication, enrichment and windowed aggregation.
- Layered storage: raw and clean Apache Parquet files, plus a SQL Server Developer serving database.
- A dashboard with live readings, aggregates, device health and data-quality panels.
- Data quality checks with Great Expectations, pipeline monitoring metrics and pytest automated tests.
- Docker Compose deployment, GitHub repository with README, and all documents from the guidelines.
- Airflow orchestration: five DAGs for stream health, daily data-quality reporting, lake compaction, gold-layer backfill and warehouse maintenance.

**Out of scope**

- Real physical devices or hardware firmware (data is simulated).
- Paid or cloud-only services, including paid Azure streaming services.
- Machine learning or predictive maintenance models (so the infographic has no AI components section).
- Multi-node production clusters, Kubernetes, and high-availability failover.
- Full user authentication system and mobile apps.
- Alert delivery to external channels (email, SMS). Threshold alerts appear on the dashboard only.

## 1.5 Proposed technology stack

| Layer | Tool | Role |
|---|---|---|
| Data source | Python simulator | Generates sensor events with fault injection |
| Messaging | Apache Kafka | Durable, partitioned event log; raw topic keeps 7 days, plus a dead-letter topic |
| Stream processing | PySpark Structured Streaming | Per-event validation, deduplication, watermarks, windows |

| Layer | Tool | Role |
|---|---|---|
| Lake storage | Apache Parquet files | Raw and clean layers for history and replay |
| Serving layer | SQL Server Developer | Relational tables for the dashboard and analysts |
| Data quality | Great Expectations | Expectation suites on the stored clean Parquet and SQL Server tables, validation results, daily quality report |
| Orchestration | Apache Airflow | Five DAGs: stream_health_check, dq_daily_report, lake_compaction, gold_backfill, warehouse_maintenance |
| Dashboard | Grafana | Live visualization on the SQL Server serving tables |
| Testing | pytest | Unit, integration and quality tests |
| DevOps | Docker Compose (local), GitHub | One-command run, version control |

## 1.6 Expected deliverables

| Stage | Deliverables | Due |
|---|---|---|
| 1. Planning and management | Proposal, plan, roles, risks, KPIs | 19 Oct 2026 |
| 2. Literature review | Related work and tool comparison, lecturer sections | 19 Oct 2026 |
| 3. Requirements gathering | Stakeholders, user stories, functional and non-functional requirements | 19 Oct 2026 |
| 4. System analysis and design | Diagrams, schema, wireframes | 6 Nov 2026 |
| 5. Implementation | Source code, repository, README, Docker Compose | 30 Nov 2026 |
| 6 and 7. Testing, final presentation and reports | Test plan and report, technical documentation, user manual, presentation, infographic, optional demo video | 4 Dec 2026 |

## 1.7 Assumptions and constraints

- Free-to-use tools only, no budget.

- Low resources.
- The pipeline runs on team laptops with Docker, so throughput targets are sized for a laptop.
- All sensor data is simulated, so no personal or sensitive data is involved.
- Everything is uploaded to GitHub.

## 2. Project Plan

### 2.1 Milestones

| Date | Milestone | Exit criteria |
|---|---|---|
| 19 Oct 2026 | Planning, literature review and requirements submitted | All three documents on GitHub |
| 6 Nov 2026 | System analysis and design submitted | All required diagrams, schema and wireframes reviewed |
| 23 Nov 2026 | Feature freeze (internal) | End-to-end flow runs; only fixes after this date |
| 30 Nov 2026 | Implementation submitted | Code, README and one-command Docker Compose setup on GitHub |
| 4 Dec 2026 | Testing, final presentation and reports submitted | Test report, technical docs, manual, presentation, infographic |

### 2.2 Gantt chart

Each block marks a week in which the activity is active. Build activities end by 22 Nov, before the 23 Nov feature freeze.

| Activity | 19 Oct | 17-23 Oct | 24-30 Oct | 31 Oct-6 | 7-13 Nov | 14-20 Nov | 21-30 Nov | 1-4 Dec |
|---|---|---|---|---|---|---|---|---|
| Planning, literature review, requirements | ■ | | | | | | | |
| System analysis and design | | ■ | ■ | ■ | | | | |
| Event contract and interface agreement | | ■ | | | | | | |
| Repository, branching, Docker Compose skeleton | | ■ | | | | | | |
| Test plan (draft in design, final in testing) | | | | ■ | | | ■ | |
| Simulator, Kafka producers and topics | | | | | ■ | ■ | | |

| Activity | 19 Oct | 17-23 Oct | 24-30 Oct | 31 Oct-6 | 7-13 Nov | 14-20 Nov | 21-30 Nov | 1-4 Dec |
|---|---|---|---|---|---|---|---|---|
| Spark streaming jobs | | | | | | ■ | ■ | |
| Great Expectations suites | | | | | | ■ | ■ | |
| Storage layers (Parquet and SQL Server) | | | | | | ■ | ■ | |
| Airflow setup and DAGs | | | | | | ■ | ■ | |
| Dashboard (Grafana) | | | | | | ■ | ■ | |
| Automated tests and optional CI | | | | | | ■ | ■ | |
| README and one-command setup | | | | | | ■ | ■ | |
| Integration, KPI benchmark, bug fixing | | | | | | | ■ | |
| Test execution and test report | | | | | | | ■ | ■ |
| Technical documentation and user manual | | | | | | | ■ | ■ |
| Presentation, infographic, optional demo video | | | | | | | | ■ |

## 2.3 GitHub repository

All project files are uploaded to GitHub

| Folder | Contents |
|---|---|
| docs/planning | Planning document and literature review |
| docs/requirements | Requirements document |
| docs/design | All diagrams, schema, wireframes |
| src | Producers, streaming jobs, serving layer, dashboard, Airflow DAGs, Great Expectations suites |
| tests | Automated tests and data quality checks |
| docs/testing | Test plan, test report, bug reports |
| docs/final | Technical documentation, user manual, presentation, infographic, demo video or link |
| Repository root | README.md (installation, configuration, execution), docker-compose.yml, .env.example without credentials, .gitignore |

## 3. Task Assignment and Roles

| Member | Role | Responsibilities | Main deliverables | Backup |
|---|---|---|---|---|
| Member 1 | Team lead, documentation, presentation | Planning, coordination, submissions, README draft, final review | Proposal, Gantt plan, roles table, problem statement, presentation, infographic | Member 4 |
| Member 2 | Kafka and simulator | Device simulator, Kafka topics and producers, related-work note | Simulator, topics, sequence and activity diagrams, literature review, optional demo video | Member 3 |
| Member 3 | PySpark and data quality | Streaming jobs, validation, deduplication, windows, Great Expectations suites, KPI measurement | Streaming code, DFD, architecture (with Member 2), KPI definitions | Member 2 |
| Member 4 | Storage, ER and dashboard | Requirements, storage layers, SQL Server schema, dashboard | Requirements document, use case diagram, ER diagram and schema, wireframes, dashboard, technical documentation, user manual | Member 1 |
| Member 5 | QA, DevOps and GitHub | Repository, Docker Compose, Airflow deployment, tests, CI, risk register | Risk register, repo structure, deployment and component diagrams, test plan, test report | Member 3 |

## Working agreements

- One feature branch per task, merged through a pull request.
- Meaningful commit messages and PR descriptions.

- Weekly sync, plus a short check-in at each interface point (simulator to Kafka, Kafka to Spark, Spark to storage, storage to dashboard).
- Interfaces are fixed early: event schema, topic names, table names. Changes go through an issue and a PR.
- Blockers are raised the same day in the team channel.

## 4. Risk Assessment and Mitigation

Likelihood (L) and impact (I) are rated Low, Medium or High. Member 5 keeps this register and reviews it at each weekly sync.

| ID | Risk | L | I | Mitigation | Owner |
|---|---|---|---|---|---|
| R1 | Data loss between broker, processor and storage | Medium | High | Kafka replication settings and offsets committed after successful write; checkpointing in Spark; raw layer kept for replay; completeness check comparing counts | Member 3 |
| R2 | Consumer lag grows under load | Medium | High | Partition topics by device; tune batch interval and shuffle partitions; monitor lag; run load tests before the freeze | Member 3 |
| R3 | Schema changes break the pipeline | Medium | Medium | Versioned event schema with explicit fields; schema validation at entry; unknown sensor types and missing required fields routed to the dead-letter queue, extra fields dropped and counted; schema changes only through PR | Member 2 |
| R4 | Tool setup problems on different laptops | High | Medium | Docker Compose with pinned image versions; setup guide; early environment test in week 1; shared troubleshooting notes | Member 5 |
| R5 | Laptops lack resources for the full stack | Medium | Medium | Resource limits per container; reduced demo profile; scaled-down simulator settings | Member 5 |

| ID | Risk | L | I | Mitigation | Owner |
|---|---|---|---|---|---|
| R6 | Duplicate or late events corrupt aggregates | High | Medium | Deduplicate on event ID with a watermark; event-time windows; late-event tests | Member 3 |
| R7 | Integration problems discovered late | Medium | High | Fixed interfaces in week 1; thin end-to-end slice early; feature freeze on 23 Nov | Member 1 |
| R8 | Scope creep (alerting, extra dashboards) | Medium | Medium | Out-of-scope list; extras only after KPIs are met; lead approves additions | Member 1 |
| R9 | Team member unavailable | Medium | Medium | Backup owner per role; documented handoffs; small tasks with clear acceptance criteria | Member 1 |
| R10 | Missed deadline for a document stage | Low | High | Weekly schedule with owners; draft one week before each due date; lead reviews before submission | Member 1 |
| R11 | Dashboard shows stale or wrong data | Medium | Medium | Freshness metric on the dashboard; data quality panel; reconcile dashboard numbers with serving tables | Member 4 |
| R12 | Repository mess (large files, secrets, bad history) | Low | Medium | .gitignore, no data dumps or credentials committed, environment files via examples, PR reviews | Member 5 |
| R13 | SQL Server Developer container is memory-hungry next to Kafka, Spark and Airflow | High | Medium | Set memory limits per container; test the full stack early on every laptop; keep a reduced demo profile; Developer edition only for development and demo | Member 5 |

| ID | Risk | L | I | Mitigation | Owner |
|---|---|---|---|---|---|
| R14 | The starting 2-minute watermark may suit the data badly (unstable aggregates or too much state) | Medium | Medium | Test several lateness thresholds with the simulator before the feature freeze; record the results; the value changes only through a pull request with test evidence | Member 3 |
| R15 | Airflow deployment complexity delays the five required DAGs | Medium | Medium | Pinned Airflow image in Docker Compose; set up early; build the simplest DAG first (stream_health_check) and add the others one by one | Member 5 |
| R16 | Great Expectations does not fit a streaming flow directly | Medium | Medium | Great Expectations validates the stored clean Parquet and SQL Server tables; fast structural checks stay in Spark; run an early spike to confirm the setup | Member 3 |
| R17 | Closed decisions drift (dashboard tool, event contract, ranges, watermark) | Medium | High | Any change goes through an issue and a pull request and is recorded with its date | Member 1 |

## 5. KPIs

Targets are initial values. They are validated in the benchmark run in the last implementation week and reported in the test report.

| KPI | Definition and measurement boundary | Target | Acceptance test |
|---|---|---|---|
| Processing latency | Time from Kafka ingest time to served time (row queryable in SQL Server). | p95 of 10 s or less; | 10-minute normal-load run; percentiles |

| KPI | Definition and measurement boundary | Target | Acceptance test |
|---|---|---|---|
| | Event-time delay (event time to ingest time) is reported separately, and injected late events are excluded | median of 5 s or less | computed from stored timestamps |
| Throughput | Valid events processed per second by the streaming job; rejected and duplicate events counted separately | 500 events/s sustained; 1,000 events/s peak | 10-minute sustained run and a peak run; pass if the target rate is met and consumer lag does not keep growing; record hardware and container limits |
| Data freshness | Current UTC time minus the served time of the newest successfully served event per site, on one host clock. A device that stops sending is shown as silent, not as stale pipeline data | 15 s or less | Dashboard panel checked during a normal-load run with timestamped screenshots |
| Error or dead-letter rate | Share of injected invalid events captured with a reason, and share of valid events lost to pipeline failures after retries | 100% of injected invalid events captured; under 0.1% pipeline-caused failures | Fault-injection run; compare injected counts with dead-letter counts |
| Pipeline uptime (availability) | Share of health-check samples (every 10 s) in which all required services are healthy: Kafka, streaming job, SQL Server, Airflow and dashboard | 99% or more over a 2-hour soak | 2-hour soak test; recovery time measured separately for each service restart |
| Recovery time | Time from a service restart until processing resumes with no data loss | 60 s or less per tested service | Restart each of Kafka, the streaming job and SQL Server once during a run |

| KPI | Definition and measurement boundary | Target | Acceptance test |
|---|---|---|---|
| Data completeness (extra) | Valid unique events produced by the simulator versus events stored in the clean layer and SQL Server; intentional duplicate suppression is excluded | 100% | Reconciliation query after each test run, covering retried writes |
| Duplicate rate (extra) | Duplicate event IDs in the clean layer and the serving table | 0 | SQL and Parquet duplicate check |
| Consumer lag (extra) | Age of the oldest unprocessed message (now minus its Kafka timestamp), tracked beside lag in messages | 5 s or less under normal load | Kafka consumer group metrics during a normal-load run |

## Measurement plan

- Every record carries four timestamps in UTC: event time, ingest time (Kafka append time), processed time and served time.
- All services run on one host clock, so timestamp differences are comparable.
- Latency, throughput, freshness and lag are computed from these timestamps and shown on a monitoring panel.
- The benchmark runs three scenarios: normal load, peak load, and a fault-injection run with late, duplicate and malformed events.
- Results go into the test report with the machine specification used.

# Requirements Gathering

This document covers the four Requirements Gathering deliverables from the project guidelines: stakeholder analysis, user stories and use cases, functional requirements, and non-functional requirements. Priorities use MoSCoW (Must, Should, Could). Targets match the KPIs in the Planning document.

## 1. Stakeholder Analysis

| Stakeholder | Role | Needs from the system | Influence | Interest |
|---|---|---|---|---|
| Data engineers (the team) | Build, run and maintain the pipeline | Clear setup, monitoring metrics, replay of raw data, simple debugging | High | High |
| Data analysts | Query the clean and aggregated data | Trusted, deduplicated data in a relational schema, documented columns | Medium | High |
| Dashboard consumers (operations or facility managers) | Watch device and site status | Live readings, device health, clear data-quality indicators | Medium | High |
| Device and field technicians | Respond to faults | Clear view of offline devices and out-of-range readings | Low | Medium |
| Lecturers and assessors | Evaluate the project | Complete documents, working demo, measured KPIs, clean GitHub repository | High | High |
| Platform and DevOps support (the team) | Deploy and operate the stack | One-command setup, pinned versions, health checks | Medium | Medium |

## 2. User Stories and Use Cases

## 2.1 User stories

| ID | As a | I want | So that | Related FR | Priority |
|---|---|---|---|---|---|
| US-01 | Data engineer | to start the whole pipeline with one command | anyone can run it without manual setup | FR-21 | Must |
| US-02 | Data engineer | to simulate many devices with configurable rate and fault injection | I can test normal and bad-data conditions | FR-01, FR-02 | Must |
| US-03 | Data engineer | invalid events sent to a dead-letter store with the reason | bad data is never lost or silently dropped | FR-08, FR-09 | Must |
| US-04 | Data engineer | duplicate events removed | counts and averages are correct | FR-10 | Must |
| US-05 | Data engineer | late events handled by the approved watermark policy (2-minute start value) | windows stay correct without unbounded state | FR-11 | Must |
| US-06 | Data engineer | raw events kept unchanged | I can replay and reprocess after a bug fix | FR-12 | Should |
| US-07 | Data analyst | clean readings in a relational table with keys | I can query them with SQL | FR-13, FR-14 | Must |
| US-08 | Data analyst | per-minute and per-site aggregates | I can analyze trends quickly | FR-15 | Must |
| US-09 | Dashboard consumer | to see device readings within seconds of arrival | I can react to what is happening now | FR-16 | Must |
| US-10 | Dashboard consumer | to see which devices are offline or silent | I know where data is missing | FR-17 | Should |
| US-11 | Dashboard consumer | a data-quality panel showing rejected and late events | I know how far to trust the numbers | FR-18 | Should |
| US-12 | Operations manager | threshold alerts shown on the dashboard | I notice dangerous readings fast | FR-19 | Could |
| US-13 | Data engineer | latency, throughput and lag metrics | I can prove the KPIs are met | FR-20 | Must |

| ID | As a | I want | So that | Related FR | Priority |
|---|---|---|---|---|---|
| US-14 | Assessor | tests, documents and a README in GitHub | I can verify the work | FR-22, FR-23, FR-28 | Must |
| US-15 | Data engineer | data-quality rules defined as Great Expectations suites with a daily report | quality is checked repeatably and visible to everyone | FR-24 | Must |
| US-16 | Data engineer | Airflow DAGs for stream health, daily quality report, lake compaction, gold backfill and warehouse maintenance | routine operations run on schedule and on demand | FR-25 | Must |
| US-17 | Data engineer | failed writes retried without creating duplicates | no valid event is lost or stored twice | FR-26, FR-27 | Must |

## 2.2 Use cases

The use case diagram is part of the Design stage. These are the use cases it will show.

| ID | Use case | Actor | Summary |
|---|---|---|---|
| UC-01 | Generate sensor events | Simulator (system actor), data engineer | Simulator creates events at a configured rate, with optional faults, and publishes to Kafka |
| UC-02 | Validate and clean events | Streaming job | Parses events, checks schema and ranges, removes duplicates, routes bad events to the dead-letter topic |
| UC-03 | Aggregate readings | Streaming job | Computes windowed aggregates per device and per site using event time |
| UC-04 | Store and serve data | Streaming job, SQL Server | Writes raw, clean and aggregated layers and updates serving tables |
| UC-05 | View live dashboard | Dashboard consumer | Opens the dashboard and sees live readings, device health and quality indicators |
| UC-06 | Query historical data | Data analyst | Runs SQL on the clean and aggregate tables |

| ID | Use case | Actor | Summary |
|---|---|---|---|
| UC-07 | Monitor pipeline health | Data engineer | Reads latency, throughput, lag and error metrics |
| UC-08 | Inspect and replay rejected or raw data | Data engineer | Reviews dead-letter records and replays raw data after a fix |
| UC-09 | Run scheduled operations | Airflow, data engineer | Airflow runs stream health checks, the daily quality report, lake compaction, gold backfill and warehouse maintenance on schedule or on demand |

**UC-02 in detail (example)**

| Field | Description |
|---|---|
| Actor | Streaming job |
| Precondition | Raw events are available on the Kafka topic |
| Trigger | A micro-batch of events arrives |
| Main flow | 1. Parse the event. 2. Check required fields, types and value ranges. 3. Drop duplicates by event ID within the watermark. 4. Write valid unique events to the clean layer and the serving table. 5. Verify the required writes |
| Alternate flow: invalid | Parsing, schema or range check fails: send the original payload and the reason to the dead-letter topic, then continue |
| Alternate flow: duplicate | The event is suppressed from the clean and serving layers and counted |
| Alternate flow: late | Events later than the 2-minute watermark go to the late-events Parquet path and are corrected by the gold_backfill DAG |
| Alternate flow: infrastructure failure | The write is retried with idempotent writes; the event is not counted as persisted until the required writes are verified |
| Postcondition | Every event is accounted for as stored, rejected to the dead-letter store, suppressed as a duplicate, |

| Field | Description |
|---|---|
| | handled as late under the approved policy, or still being retried |

## 3. Functional Requirements

| ID | Area | Requirement | Priority |
|---|---|---|---|
| FR-01 | Ingestion | The simulator shall generate events for a configurable number of devices and sites at a configurable rate | Must |
| FR-02 | Ingestion | The simulator shall inject late, duplicate, malformed and out-of-range events at configurable percentages | Must |
| FR-03 | Ingestion | Each event shall carry a unique event ID, device ID, site ID, sensor type, value, unit and event timestamp | Must |
| FR-04 | Ingestion | Events shall be published to a Kafka topic partitioned by device ID | Must |
| FR-05 | Ingestion | A separate Kafka dead-letter topic shall receive rejected events | Must |
| FR-06 | Processing | The streaming job shall consume the raw topic and parse events against a defined schema | Must |
| FR-07 | Processing | The job shall enrich events with device and site reference data | Should |
| FR-08 | Processing | The job shall validate required fields, types and value ranges per sensor type | Must |
| FR-09 | Processing | A consumer shall persist records from the dead-letter topic to durable dead-letter storage with the failure reason and original payload | Must |
| FR-10 | Processing | The job shall remove duplicate events by event ID | Must |
| FR-11 | Processing | The job shall use event-time windows with a watermark to handle late events; the watermark starts at 2 minutes and changes only through a pull request with test evidence, and later events go to the late-events Parquet path and are corrected by gold_backfill | Must |
| FR-12 | Storage | Raw events shall be stored unchanged in the raw Parquet layer; the Kafka raw topic keeps 7 days and | Should |

| ID | Area | Requirement | Priority |
|---|---|---|---|
| | | the raw Parquet layer is kept for the whole project, so replay after 7 days uses Parquet | |
| FR-13 | Storage | Validated events shall be stored in the clean Parquet layer and in a SQL Server Developer table | Must |
| FR-14 | Storage | The serving schema shall use primary and foreign keys for devices, sites and readings | Must |
| FR-15 | Storage | Windowed aggregates (average, minimum, maximum, count) shall be stored per device and per site | Must |
| FR-16 | Serving | The Grafana dashboard shall show live readings and aggregates, refreshing at an interval no longer than the freshness target | Must |
| FR-17 | Serving | The dashboard shall show device status (active or silent) based on last event time | Should |
| FR-18 | Serving | The dashboard shall show data-quality indicators: rejected, duplicate and late event counts | Should |
| FR-19 | Alerting | The dashboard shall highlight readings that cross configured thresholds | Could |
| FR-20 | Operations | The pipeline shall record event, ingest, processed and served timestamps and expose latency, throughput and consumer lag | Must |
| FR-21 | Operations | The full stack shall start with one Docker Compose command and stop cleanly | Must |
| FR-22 | Quality | The project shall include pytest unit tests and data quality checks | Must |
| FR-23 | Documentation | The repository shall include a README with installation, configuration and execution steps | Must |
| FR-24 | Quality | Data quality rules shall be defined as Great Expectations expectation suites that validate the stored clean Parquet and SQL Server tables, run on a schedule and on demand, with stored validation results and a daily report | Must |
| FR-25 | Orchestration | Airflow shall run five DAGs: stream_health_check, dq_daily_report, lake_compaction, gold_backfill and warehouse_maintenance | Must |

| ID | Area | Requirement | Priority |
|---|---|---|---|
| FR-26 | Reliability | Failed writes shall be retried, writes shall be idempotent so retries create no duplicates, and an event counts as persisted only after the required writes are verified | Must |
| FR-27 | Operations | A reconciliation check shall compare produced, stored, rejected and duplicate-suppressed event counts | Should |
| FR-28 | Documentation | All project files (documents, diagrams, source code, Airflow DAGs, Great Expectations suites, tests, reports, presentation, infographic) shall be uploaded to the GitHub repository using the folder structure in the Planning document, section 2.3 | Must |

## Event data requirements

| Field | Type | Rule |
|---|---|---|
| event_id | string | Required; UUID created by the producer, globally unique, reused when a send is retried |
| device_id | string | Required; must exist in the device registry |
| site_id | string | Required; must match the site registered for the device, otherwise dead-letter |
| sensor_type | string | One of temperature, humidity, co2, power; unknown types go to the dead-letter queue |
| value | double | Required, not null; temperature -40 to 85 °C, humidity 0 to 100 %, CO2 0 to 5,000 ppm, power 0 to 5,000 W |
| unit | string | Matches the sensor type (°C, %, ppm, W) |
| event_ts | timestamp | Required; ISO 8601 in UTC with Z; rejected if more than 5 s in the future |

Other rules: missing or null required fields go to the dead-letter queue, and extra fields are dropped and counted. Planned simulation size: 500 devices sending one reading per second, which is about 500 events per second, with peak tests at 1,000 events per second.

## Acceptance evidence

Each Must requirement needs a testable outcome. These are suggested evidence standards; the project guidelines and lecturer instructions remain authoritative. Test IDs are assigned in the test plan.

| Requirements | Suggested acceptance evidence | Test ID |
|---|---|---|
| FR-01 to FR-06 | Simulator configuration, Kafka topic configuration (raw and dead-letter) and a measured production-rate test | To be assigned |
| FR-08, FR-09 | Test fixtures showing invalid records captured with correct rejection reasons | To be assigned |
| FR-10 | SQL and Parquet checks showing no duplicate event IDs in the clean and serving layers | To be assigned |
| FR-11 | Tests for events inside and outside the 2-minute watermark | To be assigned |
| FR-13 to FR-15 | Database schema, successful writes and verified aggregate calculations | To be assigned |
| FR-16 to FR-20 | Dashboard screenshots plus timestamped latency, freshness and throughput measurements | To be assigned |
| FR-21 | Clean-start test using the documented Docker Compose command | To be assigned |
| FR-22, FR-24 | Automated test results and the Great Expectations validation report | To be assigned |
| FR-23, FR-28 | README walkthrough completed by a team member other than its author; repository checked against the folder structure with every deliverable linked | To be assigned |
| FR-25 | Each of the five DAGs run on schedule and on demand with logged results | To be assigned |
| FR-26, FR-27 | Forced write failure and service restart showing retries without duplicates, and a passing reconciliation | To be assigned |

## 4. Non-Functional Requirements

| ID | Category | Requirement | Target | Priority |
|---|---|---|---|---|
| NFR-01 | Performance | Processing latency from Kafka ingest time to the serving layer, with event-time delay reported separately | p95 of 10 s or less | Must |
| NFR-02 | Performance | Sustained throughput on a laptop | 500 events/s, with a 1,000 events/s peak test | Must |
| NFR-03 | Performance | Dashboard data age | 15 s or less | Must |
| NFR-04 | Reliability | No data loss between broker and storage | 100% of valid, unique events stored (intentional duplicate suppression excluded) | Must |
| NFR-05 | Reliability | Pipeline availability and recovery | 99% over a 2-hour soak; restart recovery within 60 s | Should |
| NFR-06 | Reliability | Failed records handled without stopping the job | Zero job crashes from bad records | Must |
| NFR-07 | Scalability | Throughput grows by adding Kafka partitions and Spark resources | Documented scaling path; tested with at least two partition counts, recording partition counts, resources, test duration and throughput and lag results | Should |
| NFR-08 | Data quality | Duplicates in clean and serving layers | 0 | Must |
| NFR-09 | Data quality | Invalid injected events captured in the dead-letter store | 100% with a reason | Must |

| ID | Category | Requirement | Target | Priority |
|---|---|---|---|---|
| NFR-10 | Security | No credentials in the repository; secrets in environment files not committed; services reachable only on the local network | Checked in code review | Must |
| NFR-11 | Maintainability | Modular, commented code with consistent naming and PR review | Every merge through a reviewed PR | Should |
| NFR-12 | Portability | Runs on Windows, macOS or Linux with Docker | Setup tested on at least two operating systems | Should |
| NFR-13 | Usability | A new user can start the pipeline and read the dashboard from the manual | Setup in 15 minutes or less | Should |
| NFR-14 | Observability | Pipeline health visible without reading logs | Metrics panel on the dashboard | Should |

## 5. Traceability

| Objective (Planning document) | Requirements |
|---|---|
| O1 Ingest at 500 events/s | FR-01 to FR-05, NFR-02 |
| O2 Streaming validation, deduplication, windows | FR-06 to FR-11, NFR-06, NFR-08 |
| O3 Dead-letter handling | FR-05, FR-09, FR-24, NFR-09 |
| O4 Layered storage and relational serving | FR-12 to FR-15, FR-26 |
| O5 Live dashboard | FR-16 to FR-19, NFR-03 |
| O6 Measured KPIs | FR-20, NFR-01 to NFR-05 |
| O7 Full guideline deliverables | FR-21 to FR-23, FR-28, NFR-10 to NFR-14 |
| O8 Orchestration with Airflow | FR-25, FR-27 |