

Parallel and Concurrent Programming in Haskell

Lab Exercises

Simon Marlow
`simonmar@microsoft.com`
Microsoft Research Ltd., Cambridge, U.K.

May 18, 2012

1 Introduction

Lines beginning with `$` are commands that you type at the command-line (a terminal in Linux, or a command-prompt in Windows). For example:

```
$ ghc-pkg list
```

to see what Haskell packages are installed.

If that doesn't work, you may need to add the relevant directories to your `PATH`:

```
$ PATH=/export/opt/HASKELL/2011.4.0.0/bin:/export/opt/GHC/7.4.1/bin:$PATH
```

Next, install the extra packages that we'll need for the exercises using `cabal`:

```
$ cabal update
$ cabal install monad-par-0.1.0.3
$ cabal install remote-0.1.1
$ cabal install derive-2.5.8
$ cabal install parallel-3.2.0.2
$ cabal install HTTP-4000.2.3
$ cabal install xml-1.3.12
```

Next, get the sample code and unpack it.

```
wget http://community.haskell.org/~simonmar/par-tutorial-cadarache.tar.gz
tar xvzf par-tutorial-cadarache.tar.gz
```

Build the code. There is a `Makefile`, so you should be able to say `make` to build all the programs:

```
$ cd par-tutorial/code  
$ make
```

Alternatively, you can compile any individual program like this:

```
$ ghc -threaded -rtsops -eventlog -O2 sudoku1.hs
```

2 Lab 1: Parallel Haskell

Test that you can get parallel speedup. Compile `sudoku1` as above, and run it on one processor like so:

```
$ ./sudoku1 sudoku17.1000.txt +RTS -s
```

Next, the static parallel version:

```
$ ./sudoku2 sudoku17.1000.txt +RTS -s -N2
```

Next, the `parMap` version:

```
$ ./sudoku3 sudoku17.1000.txt +RTS -s -N2
```

(the last one should be the fastest)

Now try a larger example, a 16000-problem dataset:

```
$ ./sudoku1 sudoku17.16000.txt +RTS -s
$ ./sudoku3 sudoku17.16000.txt +RTS -s -N2
```

What speedup did you get? Can you explain the discrepancy? (hint: look at the `SPARKS` line in the `+RTS -s` output. GHC's spark pool can only hold about 8000 sparks, new sparks are discarded when the pool is full).

This example took a while to run, so let's simulate the problem on the smaller dataset by reducing the spark pool size to 500:

```
$ ./sudoku3 sudoku17.1000.txt +RTS -s -N2 -e500
```

Now, to avoid overflowing the spark pool we want to create fewer sparks, and so each spark needs to do more work. Hence we need to divide the work into fewer, but larger, chunks.

`Control.Parallel.Strategies` provides the following function:

```
parListChunk :: Int -> Strategy a -> Strategy [a]
```

The first argument to `parListChunk` is the chunk size in list elements, and the second is the `Strategy` to apply to the list elements.

Exercise 1.1. Modify `sudoku3.hs` to use `parListChunk`.

Try your version on the 1000-problem dataset with a spark pool size of 500:

```
$ ./sudoku3 sudoku17.1000.txt +RTS -s -N2 -e500
```

(if you want, try it on the 16000-problem dataset too)

What speedup did you get relative to `sudoku1`? Try a few different chunk sizes. Does it make any difference?

Exercise 1.2. The Strategies library includes another operation for parallelising list-based operations:

```
parBuffer :: Int -> Strategy a -> Strategy [a]
```

Rather than dividing the list into chunks, `parBuffer` processes the list in a stream-like way, sparking `N` elements of the list ahead of the current element. At any given point in time there should be no more than `N` active sparks.

Convert `sudoku3.hs` to use `parBuffer`, and try it on the 1000-problem dataset. What speedup did you get, and how does that compare to the results with `parListChunk`?

Try a few different buffer sizes - what difference do they make?

3 Lab 2: Concurrent Haskell

The sample code corresponding to the examples in the notes can be found in `par-tutorial/code`. Try the `fork` example from Section 3.1:

```
$ ghc -threaded -rtsopts -eventlog --make fork.hs
$ ./fork
ABABABABABABABABABABABABABABABA...
```

Exercise 2.1. In `par-tutorial/code/bingtranslator.hs` there is a program that translates a line of text into multiple languages using the Bing Translate API. For example:

```
$ ./bingtranslator "translate this"
"translate this" appears to be in language "en"
ar:
bg:
zh-CHS:
zh-CHT:
cs: peloit
da: overstte dette
... etc.
```

Compile the program - for this you may need to install the `xml` and `utf8-string` packages first:

```
$ cabal install xml utf8-string
$ ghc -threaded -rtsopts -eventlog --make bingtranslator.hs
```

When the program is compiled, run it yourself with some sample text.¹ Note how the translations appear slowly - the program queries the Bing API for each translation in sequence.

Exercise 2.1. Convert the program to perform all the translations concurrently. Use the `Async` API (the code is in the `bingtranslator.hs` source file).

Exercise 2.2. The program also makes two initial queries to the Bing API: one to get the list of supported languages, and another to detect the language in which the initial text is written. Make these two queries concurrently.

A sample solution can be found in `bingtranslatorconc.hs`.

¹On Windows you may not see the international characters appear correctly on the console. First, switch the codepage to UTF-8 with `chcp 65001`. Then redirect the output of `bingtranslator` to a file, and open the file in Notepad to see the output correctly.

Exercise 2.3. Write a simple game in which the user is presented with a random arithmetic question, and they have to type in the correct answer within ten seconds.

Hint: random integers can be generated using `System.Random.randomIO`. (keep your solution to this exercise; it will become the basis for Exercise 4.2).

4 Lab 3: Software Transactional Memory (STM)

Exercise 3.1. Implement a bounded channel type, with the following signatures:

```
data BoundedChan
newBoundedChan :: Int -> STM (BoundedChan a)
readBoundedChan :: BoundedChan a -> STM a
writeBoundedChan :: BoundedChan a -> a -> STM ()
```

`newBoundedChan` takes the size of the channel, and `writeBoundedChan` blocks if the channel is full.

(After you’ve done this, if you’re feeling very brave, try implementing it with `MVar` instead of `STM`. Obviously the functions must all be in the `IO` monad rather than `STM`.)

Exercise 3.2. (optional: for the performance-obsessed) Write a program in which two threads communicate over a channel, one writing a large number of items to the channel and the other reading them. Measure the time it takes, using (a) the `Chan` type, (b) the `TChan` type, (c) the bounded channel from Exercise 3.1 (choosing a suitable bound). Can you explain the differences in performance?

Exercise 3.3. Write a program that corrects your punctuation as you type.

In this exercise we are going to write a program that does the following:

- Accepts characters typed by the user, and echos them to the screen.
- Automatically applies a correction to the input string. The correction is required to happen in a separate thread, because in principle computing the correction might take time, and we want the input to remain responsive.

Use the following guidelines to structure the program:

- Store the current input string in a `TVar`.
- Use three threads:
 - The main thread reads characters from `stdin` and appends them to the string in the `TVar`.
 - The `render` thread watches for changes to the `TVar` (as in the windowing example in the lecture/notes). When a change is detected, it renders the new string. Hint: you will need to delete the old string by emitting the correct number of ‘\8’ backspace characters before printing the new string using `putStr`.

- The `correcter` thread also watches for changes to the `TVar`, and when it detects a new string it applies a correction function to it and writes the result back to the `TVar`. The correction function can do whatever you like; e.g. my correcter in the sample solution capitalises the first character after a full stop.

Note that you will need to set `stdin` and `stdout` to no-buffering mode, and disable echoing. Your `main` function should start like this:

```
import System.IO
import Control.Concurrent
import Control.Concurrent.STM

main = do
  hSetBuffering stdin  NoBuffering
  hSetBuffering stdout NoBuffering
  hSetEcho stdin False
  tvar <- newTVarIO ""
  forkIO (render tvar)
  forkIO (correcter tvar)
  ...
```

then you need to implement `render`, `correcter`, and the code at the end of `main` that reads the input characters.

Sample solution: `code/correcter.hs`

Exercise 3.4. Modify exercise 3.3 so that your text is automatically translated into Japanese as you type it, using the Bing translation service (see exercise 2.1) in the background.

5 Lab 4: Server applications

In this exercise we'll add some extensions to the sample chat server.

Compile the chat server like so:

```
$ cd code/chat
$ ghc --make -i.. Main.hs -o chat
[1 of 2] Compiling ConcurrentUtils ( ../ConcurrentUtils.hs, ../ConcurrentUtils.o )
[2 of 2] Compiling Main ( Main.hs, Main.o )
Linking chat ...
```

Check that you can run it and that it works properly.

```
$ ./chat
Listening on port 44444
```

Now switch to another window, and connect a client:

```
$ nc localhost 44444
What is your name?
a
*** a has connected
```

Now switch to a third window, and connect another client:

```
$ nc localhost 44444
What is your name?
b
*** b has connected
```

when you connect client **b**, you should see a message on client **a**'s session:
***** b has connected**. Now try typing messages into each client and check that the messages are broadcast properly. Try kicking a client with `/kick b`.

The following exercises (4.1.1–4.1.6) are to add various enhancements to the chat server, and they get progressively harder. Feel free to skip to exercise 4.2 at any time you like.

Exercise 4.1.1. Add a `/names` command to list the currently connected users.

Exercise 4.1.2. Add a timeout to the "What is your name?" question. You probably want to use `System.Timeout.timeout`.

Exercise 4.1.3. Add a timeout to the client loop: an inactive client should be automatically disconnected after a fixed time limit.

Exercise 4.1.4. `broadcast` is inefficient because it uses an unbounded transaction (see the section on performance of STM in the notes). Change the server to use a single broadcast channel; you can either use `TChan` with `dupTChan`, or alternatively build your own. Note that this will mean that `runClient` will need to check the broadcast channel in addition to its `clientSendChan` and the `clientKicked` variable.

Exercise 4.1.5. Add a `/nick` command to change the current client's name. Careful! The name is stored as an immutable value in the `Client` record, and it is the key of the `clients` map. Some refactoring of the program will be needed to make the name modifiable. Hint: give each client a unique number, and use this as the key in the map.

Exercise 4.1.6. Add flood prevention: prevent a client from issuing more than a certain number of messages in a given time.

Exercise 4.2. Take your solution to exercise 2.3 and make it a multiplayer game. The current question is presented to all connected users, and the first user to type the correct answer wins a point; if nobody answers correctly within ten seconds then another question is presented. After each question, the current scores are printed out.

You might want to start with the chat server as a basis for this program, since some of the functionality is similar: clients need to connect and tell the server their name.

6 Lab 5: Distributed programming

A key-value store is a simple database that supports only operations to store and retrieve values associated with keys. Key-value stores have become popular over recent years because they offer scalability advantages over traditional relational databases, in exchange for supporting fewer operations (in particular, database joins).

This exercise is to use the `remote` framework to implement a *distributed fault-tolerant key-value store* in several stages. You probably won't get to the end in the time available, but I think it's a fun exercise and I hope you enjoy it nonetheless!

The interface exposed to clients is the following:

```
type Database
type Key     = String
type Value   = String

createDB :: ProcessM Database
set      :: Database -> Key -> Value -> ProcessM ()
get      :: Database -> Key -> ProcessM (Maybe Value)
```

where `createDB` creates a database, and `set` and `get` perform operations on it. The `set` operation sets the given key to the given value, and `get` returns the current value associated with the given key, or `Nothing` if the key has no entry.

Exercise 5.1. In `remote-db/db.hs` I have supplied a sample `main` function that acts as a client for the database, and you can use this to test your database. The skeleton for the database code itself is in `Database.hs` in the same directory: the first exercise is to implement a single-node database by modifying `Database.hs`. That is:

- `createDB` should spawn a process to act as the database. It can spawn on the current node.
- `get` and `set` should talk to the database process via messages; you need to define the message type and the operations.

When you run `db.hs`, it will call `createDB` to create a database, and then populate it using the `Database.hs` source file itself; every word in the file is a key that maps to the word after it. The client will then lookup a couple of keys, and then go into an interactive mode where you can type in keys that are looked up in the database. Try it out with your database implementation, and satisfy yourself that it is working.

Exercise 5.2. The second stage is to make the database *distributed*. The basic plan is that we are going to divide up the key space uniformly, and store

each portion of the key space on a separate node. For example, operations on the key "Simon" might go to node 1, whereas operations on key "Andres" go to node 2, and "Ralf" is handled by node 3. The exact method you use for splitting up the key space is up to you, but one simple scheme is to take the first character of the key modulo the number of workers.

There will still be a single process handling requests from clients, so we still have `type Database = ProcessId`. However, this process needs to delegate requests to the correct worker process according to the key.

- Arrange to start worker processes on each of the nodes with `WORKER` role. (for how to do this, see the example code for multi-node ping in the notes, which is also in `remote-ping/ping-multi.hs`).
- Write the code for the worker process. You probably need to put it in a different module (e.g. called `Worker`), due to restrictions imposed by Template Haskell. The worker process needs to maintain its own `Map`, and handle get and set requests.
- Make the main database process delegate operations to the correct worker. You should be able to make the worker reply directly to the original client, rather than having to forward the response from the worker back to the client.

Compile `db.hs` against your distributed database, and make sure it still works.

Sample solution: `db2.hs`, `DatabaseDistrib.hs`, `Worker.hs`

Exercise 5.3. Make the main database process monitor all the worker processes. Detect failure of a worker and emit a message using `say`. You will need to use `receiveWait` to wait for multiple types of message; see the `ping-fail.hs` example for hints.

Note that we can't do anything sensible if a worker dies yet, that is the next part of the exercise...

Exercise 5.4. Implement *fault tolerance by replication*.

- Instead of dividing the key space evenly across workers, put the workers in pairs and give each pair a slice of the key space. Both workers in the pair will have exactly the same data.
- Forward requests to both workers in the pair (it doesn't matter that there will be two responses in the case of a `get`).

- If a worker dies, you will need to remove the worker from your internal list of workers so that you don't try to send it messages in the future.²

This *should* result in a distributed key-value store that is robust to individual nodes going down, at least if we don't kill too many nodes too close together.

Try it out - kill a node while the database is running, and check that you can still look up keys. If you got this far, well done!

Sample solution: `db4.hs`, `DatabaseRepl.hs`, `Worker.hs`

²A real fault-tolerant database would restart the worker on a new node and copy the database slice from its partner - by all means have a go at doing this but the provided solutions don't do this.

7 Lab 6: GPU programming

Your goal in this exercise is to **crack my password**.

My password is a dictionary word that can be found in the file

`/usr/share/dict/american-english`

I have hashed the password using a checksum algorithm called CRC32 (32-bit Cyclic Redundancy Check), and the hash of my password is

0xb4967c42

In order to find the password, you will have to compute the CRC32 value for every word in the file `/usr/share/dict/american-english`, and then find the word that has the CRC32 value `0xb4967c42`.

Some ordinary sequential Haskell code for computing CRC32 can be found in `code/crc32/CRC32.hs`. You can try it out by hand on a few words:

```
> :load CRC32.hs
[1 of 1] Compiling CRC32          ( CRC32.hs, interpreted )
Ok, modules loaded: CRC32.
*CRC32> crc32String "hello"
3387906425
```

You can see the value in hex using `printf`:

```
*CRC32> import Text.Printf
*CRC32 Text.Printf> printf "%x\n" crc32String "hello"
c9ef5979
*CRC32 Text.Printf> printf "%x\n" (crc32String "hello")
c9ef5979
```

The CRC32 code is quite simple:

```
crc32 :: [Word8] -> Word32
crc32 msg = go 0xffffffff msg
  where go crc []      = crc
        go crc (w:ws) = go crc' ws
          where crc' = (crc `shiftR` 8) `xor`
                        (crc32_tab !! fI (fI crc `xor` w))
          fI x = fromIntegral x
```

It's basically a loop over the bytes of the input string, performing a few bitwise operations at each stage. It uses a 256-entry lookup table `crc32_tab :: [Word32]`, which can also be found in the file `CRC32.hs`, you can just import this module to gain access to it.

Our aim is to compute the CRC32 in parallel on all the words in the dictionary, using the GPU. The rest of this section will lead you to the solution in several stages and give lots of hints along the way; if you want a challenge then stop reading now and try to solve the problem on your own!

Exercise 6.1. write the following function:

```
crc32_one :: Acc (Vector Word32) -> Exp Word32 -> Exp Word8
          -> Exp Word32
```

This performs one iteration of the CRC32 calculation. The first parameter is the lookup table, the second parameter is the current CRC value, the third parameter is the byte of the input string, and the output should be the new CRC32 value.

There is one extra criterion: *if the input byte is zero, then the output CRC must be the same as the input*. This will enable us to run `crc32_one` in parallel on multiple strings even though the strings vary in length: we'll just pad the shorter strings with zeros.

Exercise 6.2. Using `crc32_one`, write the following function to compute the CRC32 values for a list of strings:

```
crcAll :: [String] -> Acc (Vector Word32)
```

We're going to do this by mapping `crc32_one` over a *slice* of the input strings. That is, first we map over all the first characters, then over all the second characters, and so on until we have reached the maximum string length.

Start by bringing the lookup table `crc32_tab` into the `Acc` world:

```
table :: Acc (Vector Word32)
table = ...
```

Next, you should calculate both the number of strings (call this `n`), and their maximum length (call this `width`).

```
n = ...
width = ...
```

Then create a vector of length `n` containing the initial CRC values, which are all `0xffffffff`. Hint: use `fill`.

```
init_crcs :: Acc (Vector Word32)
init_crcs = ...
```

Write a function `one_iter`, which performs one iteration over a vector of input characters. In here you will call `crc32_one`:

```
one_iter :: Acc (Vector Word32) -> Acc (Vector Word8)
          -> Acc (Vector Word32)
```

Finally, we want to write a function to perform all the iterations:

```
all :: Int -> Acc (Array Word32) -> [String]
    -> Acc (Array Word32)
all 0 crcs words = crcs
all x crcs words = ...
```

The first argument is a counter, which starts at `width` and counts down to zero. The second argument is the vector of current CRC values, and the third argument is the current list of strings, where the first character of each is the next to process (at each iteration we will remove one character from the head of each string).

In order to complete this function, you will need to create an `Acc (Vector Word8)` consisting of the first character from each string (or zero if the string is already empty). Then pass this to `one_iter` to calculate the new CRC values, and finally recursively call `all` with the new CRC values and the remainder of each string.

Test this out by calling it from GHCi with a few sample strings, and test that you get the same results as calling the pure Haskell version `crc32String`.

Exercise 6.3. Find the index of the element in the array that has the correct CRC32 value.

We want to write this function:

```
find :: Acc (Vector Word32) -> Acc (Scalar Int)
```

which takes the array produced by `crcAll`, and returns the index of the element that has the value we are looking for.

You could do this in two stages: first map every element to either (a) its index if it has the correct value or (b) zero otherwise, and then fold the `max` function over the resulting array. NB. there appears to be a bug in Accelerate such that `max` doesn't work on the GPU with `Int` arguments, so we have to use `Int32`.

Hint: an array of the same shape as an input array `arr`, in which every element contains its index as an `Int32` is given by:

```
generate (shape arr) (A.fromIntegral . unindex1)
```

Exercise 6.4. Having done all this, you should be able to use this `main` wrapper to find the answer:

```
main = do
  s <- readFile "/usr/share/dict/american-english"
  let ls = lines s
  let [r] = toList $ run $ find $ crcAll ls
  print (ls !! r)
```

You can run it with the interpreter, and it will take a few seconds. To actually run it on the GPU, make sure you replace

```
import Data.Array.Accelerate.Interpreter
```

with

```
import Data.Array.Accelerate.CUDA
```

at the top of your program. Does it go faster on the GPU?

Sample solution: `code/crc32/crc32_acc.hs`