Особенности GNU Make

АРГУМЕНТЫ

Основные аргументы:

`<переменная>=<значение>` `-n`

Аргумент `<переменная>=<значение>`

Служит для переопределения переменных, объявленных в Makefile.

ПРИМЕРЫ

```
make WAVES=0
```

```
make SIM_OPTS=-gui
```

Аргумент `-n`

Служит для вывода всех команд, которые были бы исполнены при вызове, в терминал. Сами команды не исполняются.

ПРИМЕРЫ

```
make -n
```

```
make -n SIM_OPTS=-gui
```

ПОЛЬЗОВАТЕЛЬСКИЕ ПЕРЕМЕННЫЕ ОСНОВНОГО MAKEFILE КУРСА

ВЫЗОВ

```
make help
```

Выведет список пользовательских переменных.

> **Обратите внимание,** что у GNU Make нет опции `help`, автор собственноручно ее реализует в виде отдельной цели `help` в Makefile.

ВЫВОД

```
This is common examples/tasks Makefile.

You can run concrete example/task from directory of this Makefile via:
  | make EXAMPLE=<example-directory>

Available arguments:

  * EXAMPLE  - example directory
               default is ''

  * SIM_OPTS - simulation options
               default is '-gui'

  * COMP_OPTS - compilation options
               default is ''

  * RTL_FILE - file with list of all RTL sources
               default is '$(EXAMPLE)/dv/build/rtl.f'

  * TB_FILE  - file with list of all DV sources
               default is '$(EXAMPLE)/dv/build/tb.f'

  * CONFIG   - additional configuration files
               default is ''

  * INCLUDE  - include files (in package for example);
               these files are tracked but not compiled
               default is ''

  * TOP      - top module for simulation
               default is 'testbench'

  * OUT      - simulation logs directory
               default is '$(EXAMPLE)/out'

  * WAVES    - waveform save enable
               default is '1'

Examples:

  * Run example 02_sum with batch
    | make EXAMPLE=02_sum SIM_OPTS=-c

  * Run example 03_sum with batch with randomization seed 12345
    | make EXAMPLE=03_sum SIM_OPTS="-c -sv_seed 12345"

  * Run example 10_initial with GUI with no waveform saving
    | make EXAMPLE=10_initial WAVES=0

  * Run example 06_alu with batch and passing define VERSION_4
    to the compilation
    | make EXAMPLE=06_alu SIM_OPTS=-c COMP_OPTS=+define+VERSION_4
```