## SUB Aqua Pro, Digital Unstirred Water Bath



## DESCRIPTION

Built to the highest standard and specifications and incorporating the latest technology the SUB Aqua Pro advanced water bath range supports even the most demanding applications requiring accurate temperature control. Choose from eight models with base tray and lid included as standard.

- Ambient +5°C to 99°C operation
- Set and Forget™ technology fast heat-up, accurate temperature control
- Stability ±0.2°
- Adjustable over temperature alarm protect samples from over heating
- Advanced dry start and run dry protection
- Three programmable temperature presets
- 3 year warranty



Temperature range	ambient +5 to 99°C
Temp. display and setting resolution	0.1°C
Temp stability (DIN 12876) @ 70°C	±0.2°C
Temperature setting/energy regulation	digital
User adjustable over temp. alarm	+
Fixed thermal cut-out	+
Dry start/boil dry protection	+
Programmable temp. presets	3
Countdown timer with audible alarm	1 to 999 mins
Nominal operating voltage	120 or 230 V



	DAPE	10091	1989	1850	20718	19770	5894	1/4
	100.7	20733	1000	100-10	100/10	100.00	100-01	
	444		and the	-0	460	460	-40	400
	-	Allina	-		- 10	-	-37	
	· **/	- 10	190	190	100	100	100	-
Capacity	2.	D.	N.	15.	18)	195	94.	0.441
	Replacement	i polycarkonali	a le ampuranti	W/	_	_	_	
	AGUS	AGLE	10.0	AGUS	AGUSE	10.76		AGLS
	Directs complete	ation years from	-	make maked	ratio, related to	mode at a		-
.00	Market de	of display like	,					
	-	1.6	148	14/14	U-01	1408	LANGE	918.14
-	FM NAC							
1000	-		179	9711	1756	1758	1/56	9919
Francisco			Chiquest			ill inquest	\$100 MID	2412
		Frontile Note do		rodate/of record	erital reducing	парияйл		
1000	Polymopphe	e spherer' go	erka pur kurtij					
	11750	11/500	1 = P600	Fit PEDD	2+7636	3 1/4500	3 = H00	2 x P62
F. 6	Standard adjunction	4000,000	on repositors	nd had been eith	il dissiprate	com/s mark/	e-ter bath parts	drivate
	Rahad shahi	es : www.dida	affron her o	half-dopthrs. It	s shall height.	described has	u jerej	
and the same				P0148	Alinen	Miles	Miles.	7614
100				0.00	0-40 o 135	0.45 + 100	140 4 100	0-6 m.
4				half-gross of	matters or	fact street	half-area of	Traff error
	_	_		SATE	5679	5491	5959	541
105504	Balki" po							
10000			11.00	21.0	41-8	4147	81.0	1:00
4	Debroit of	90 to 20.00mg	con dheet ta	e done tro	HUMber (see )	1010		
	Replacement	Abase Napa						
	AURTY.	AURTS	AGETS	AUSTY:	AURTYS	AGETS	serm	AGES
-0	Street of Files.	terrent hadro	es to be placed a	mark or forte	and to bath an	to completion	winesonie in	tulum
_	Date times	,						
-8	_	_	_	UNRIGHT.	UNE 01	UNREST.	UMB CO.	UMB C
				0.00	Desired St	949.65	0.000	East of

## CAT. NR.

SAP2	230VAC 50/60Hz Euro plug
SAP2 US	120VAC 60Hz US plug
SAP2S	230VAC 50/60Hz Euro plug
SAP2S US	120VAC 60Hz US plug
SAP5	230VAC 50/60Hz Euro plug
SAP5 US	120VAC 60Hz US plug
SAP12	230VAC 50/60Hz Euro plug
SAP12 US	120VAC 60Hz US plug
SAP18	230VAC 50/60Hz Euro plug

Biosan SIA., Ratsupites 7, build. 2, Riga, LV-1067, Latvia, Phone: +371 674 261 37, Fax: +371 674 281 01, E-mail: marketing@biosan.lv, <a href="http://www.biosan.ly">http://www.biosan.ly</a>



## **SUB Aqua Pro, Digital Unstirred Water Bath**

SAP18 US	120VAC 60Hz US plug
SAP26	230VAC 50/60Hz Euro plug
SAP26 US	120VAC 60Hz US plug
SAP34	230VAC 50/60Hz Euro plug
SAP34 US	120VAC 60Hz US plug
SAPD	230VAC 50/60Hz Euro plug
SAPD US	120VAC 60Hz US plug