



FG12_4CH GMSL相机平台是一个扩展板，允许多达4个相机连接到Jetson® Orin™/Xavier™ NX模块，它与NVIDIA Jetson® Orin™/Xavier™ NX Devkit开发套件完全兼容。自适应的工作在不同频率即通过软件配置同时兼容GMSL1与GMSL2协议接口从而可以采用市面上许多不同类型的GMSL相机。GMSL相机的电源由PoC(PoweroverCoax)提供，因此所有数据、控制信号和电源都通过一根50欧姆同轴电缆发送，这使得相机的电缆布线灵活且具备较强的电磁抗干扰能力，易于在自主移动机器人（AMR）机器人技术、无人机（UAV）及汽车等应用中安装及使用。



特点 FEATURES
GMSL2 和 GMSL1 协议兼容
Power over Coax 同轴供电
相机供电外部输出支持宽压输出
电路内置过压及短路保护
软件可控制相机的供电
尺寸小巧适配 Jetson Orin™/Xavier™ NX Devkit

SPECIFICATIONS 规格书			
SIZE 尺寸	80mm x 53 mm	Weight 重量	50g
Jetson Devkit 开发套件接口	Molex22PinZIF连接器 (4LaneCSI)	Camera Inputs相机数量输入	4路GMSL2或GMSL1相机 (RGB/RGBD等均兼容支持)
Deserializer解串器	ADI MAX96712	MIPI Output MIPI输出	支持2/4-Lane CSI-2 v1.3
Camera Connector 相机连接器	安费诺单端卧式同轴FAKRA连接器	PoC(Power-Over-COAX) 供电	4路相机供电是由GMSL板提供的 PoC 12V电压 (DC Input >12V)
Power 供电	支持外接12V~24V @ 4A MAX	Operating Temperature 工作温度	-20°C to +65°C (-4°F to +149°F)
质保和支持 Warranty and Support	一年质保和技术支持		



FG12_4 CH GMSL Camera Platform is an expansion board that allows up to 4 cameras to be connected to Jetson® AGX Orin™/Xavier™ modules, and it is fully compatible with the NVIDIA Jetson® AGX Orin™/Xavier™ development kit. It operates adaptively at different frequencies, i.e., it is compatible with both GMSL1 and GMSL2 protocol interfaces via software configuration, enabling the use of many different types of GMSL cameras available on the market. The power supply for GMSL cameras is provided by PoC (Power over Coax), so all data, control signals and power are transmitted through a single 50-ohm coaxial cable. This makes the camera cable wiring flexible and provides strong electromagnetic interference resistance, facilitating installation and use in applications such as Autonomous Mobile Robots (AMR), Unmanned Aerial Vehicles (UAV) and automotive systems.



FEATURES
Compatible with GMSL2 and GMSL1 protocols
Power over Coax
Wide voltage output support for external camera power supply
Built-in overvoltage and short-circuit protection for the circuit
Software-controllable camera power supply
Compact size, compatible with AGX Orin/Xavier Devkit

SPECIFICATIONS			
SIZE	68mm x 6 5 mm	Weight	50g
Jetson Devkit Interface	Molex 22Pin ZIF connector (4-Lane CSI)	Camera Inputs	4 channels of GMSL2 or GMSL1 cameras (compatible with RGB/RGBD, etc.)
Deserializer	ADI MAX96712	MIPI Output	Supports 2/4-Lane CSI-2 v1.3
Camera Connector	Amphenol single-ended horizontal coaxial FAKRA connector	PoC(Power-Over-COAX)	4-channel camera power supply with 12V PoC from the GMSL board (DC Input > 12V)
Power	Supports external 12V~24V @ 4A MAX	Operating Temperature	-20℃ to +65℃(-4°F to +149°F)
Warranty and Support	One-year warranty and technical support		