

## Pressure Gauge



HT-305

### Features

- Thread Size : 1/4" BSP Male
- Economical Version
- General Purpose Application
- Warranty : 12 months
- Dial : 2"



HT-310

### Features

- Thread Size : 1/4" BSP Male
- General Purpose Application
- Warranty : 12 months
- Dial : 2 1/2"



HT-320

### Features

- Thread Size : 1/4" BSP Male
- Rugged Construction
- Glycerine Filled
- Standard followed in General EN 837-1 / General EN 837-1
- Warranty : 12 months
- Dial : 2 1/2"

## Lateral Valve



### Barb x Barb

12mm x 12mm  
12mm x 16mm  
12mm x 20mm



### Barb x Barb

16mm x 16mm  
16mm x 20mm  
20mm x 20mm



### 1/2" Male Thread x Barb

1/2" Male Thread x 12mm  
1/2" Male Thread x 16mm  
1/2" Male Thread x 20mm



### 3/4" Female Thread x Barb

3/4" Female Thread x 12mm  
3/4" Female Thread x 16mm  
3/4" Female Thread x 20mm



### 3/4" Male Thread x Barb

3/4" Male Thread x 12mm  
3/4" Male Thread x 16mm  
3/4" Male Thread x 20mm



### Male Thread x Male Thread

1/2" Male Thread x 1/2" Male Thread  
3/4" Male Thread x 3/4" Male Thread

## Compression Drip Fittings



Compression Coupler



Compression Tee



Compression x MPT Adaptor



Compression Elbow

### Features

- Color Coded gripper for easy identification.
- Faster and easier to install, simply push drip tubing into fittings for tight connection and get unobstructed flow.
- Full flow and no pressure drop.
- Very tight fit with no tools, gluing or clamps required.
- Superb gripping of PE tubing, no slipping at high pressure and no leakage at low pressure.
- Ultra sonic welded grippers for no leakage and longer life.
- Impact, UV and Chemical Resistant.