Micro sprinkler (HT-205 series)

माईक्रो स्प्रिंकलर









Applications

- For overhead irrigation of Orchard, nurseries, Green houses and vegetable crops
- For irrigation of widely spaced plants upto 6x6m spacing at Agri-Stand
- · Ideal for frost protection and overhead cooling

Features & Specifications

- Sturdy Structure and User Friendly
 Push-Fit, 3/8" and 1/2" male threaded connection
 Insect proof Pop-up Swivel
- Range of operating Pressure: 1.5 3.0kg/cm²
 Flow Rate Range: 28 449 LPH
- Recommended Spacing 4x4m & 5x5m

Connection: Pushfit Type

	Swivel Color	Nozzle Color	Nozzle (mm)	1.5 kg/cm ²		2.0 kg/cm ²		2.5 kg/cm ²	
				Flow lph	Dia. m	Flow lph	Dia. m	Flow lph	Dia. m
	Black	Violet	0.8	28	5.5	36	6.0	41	6.2
		Brown	0.94	42	6.0	52	6.5	57	6.7
	Blue	Grey	1.14	62	7.2	71	8.0	80	8.2
		Green	1.4	90	8.2	102	8.4	118	8.5
	Green	Orange	1.5	105	8.5	122	9.0	136	9.4
		Black	1.78	140	9.0	162	9.4	180	9.8
		Blue	1.98	174	9.7	202	10.0	225	10.3
		Yellow	2.2	210	10.0	245	10.5	295	10.7
		Red	2.4	245	10.2	290	10.8	350	11.0

^{*} Tested at 25cm height above ground

Connection: 3/8" Male Threaded

	Nozzle Color	Nozzle (mm)	1.5 kg/cm ²		2.0 kg/cm ²		2.5 kg/cm ²	
Swivel Color			Flow lph	Dia. m	Flow lph	Dia. m	Flow lph	Dia. m
Blue	Grey	1.14	62	7.6	71	8.2	80	8.5
Dide	Green	1.4	90	8.4	102	8.7	118	9.0
	Orange	1.5	105	8.7	122	9.2	136	9.6
	Black	1.78	140	9.2	162	9.5	180	10.0
Green	Blue	1.98	174	9.8	202	10.2	225	10.4
	Yellow	2.2	210	10.2	245	10.6	295	11.0
	Red	2.4	245	10.5	290	11.0	350	11.4

^{*} Tested at 1m height above ground

Connection: 1/2" Male Threaded

	Swivel Color	Nozzle Color	Nozzle (mm)	1.5 kg/cm ²		2.0 kg/cm ²		2.5 kg/cm ²	
				Flow lph	Dia. m	Flow lph	Dia. m	Flow lph	Dia. m
Carr	Green	Blue	1.98	174	10.6	202	11.0	225	11.5
Gre		White	2.8	350	12.0	402	12.5	449	12.8

^{*} Tested at 1m height above ground