

Enhancing Bitcoin Scalability through Parallel Programming and Chinese Remainder Theorem Optimization with Applications in Agriculture and Healthcare

FORCHA GLEN BELOA

FE22P049

This work addresses the critical scalability challenges inherent in blockchain systems, with a focus on Bitcoin's transaction validation bottlenecks caused by computationally intensive cryptographic operations. By integrating parallel programming techniques and leveraging the Chinese Remainder Theorem (CRT) for modular arithmetic optimization, the approach enables decomposition of large cryptographic computations into smaller, independent tasks that can be executed concurrently. This synergy significantly accelerates signature verification and modular exponentiation, reducing validation latency and increasing transaction throughput without altering block size or consensus protocols. The research further explores architectural considerations for implementing these optimizations, emphasizing synchronization, consistency, and security to maintain blockchain integrity. Applications beyond cryptocurrencies, particularly in healthcare and agriculture, are examined to highlight the necessity of scalable, secure, and efficient data management solutions. The analysis includes a comparative evaluation of existing optimization strategies, identifying the advantages of combining parallelism with mathematical optimization. Challenges related to backward compatibility, interoperability, and standardization are discussed, alongside the broader implications for cross-industry adoption. The findings demonstrate that the convergence of advanced computational methods and cryptographic theory can overcome current scalability barriers, enabling blockchain networks to support high-throughput, secure, and decentralized applications across diverse sectors.

Table of Contents

1	Introduction.....	5
2	Background and Motivation.....	6
2.1	Overview of Blockchain Technology	6
2.2	Historical Evolution of Blockchain and Cryptocurrencies	9
2.3	Significance of Scalability in Blockchain Networks	11
2.4	Applications Beyond Cryptocurrencies.....	13
2.4.1	Agriculture Sector	13
2.4.2	Healthcare Sector	15
2.4.3	Other Emerging Fields.....	16
3	Principles of Blockchain Systems.....	18
3.1	Decentralization and Distributed Ledgers	18
3.2	Cryptographic Foundations	20
3.2.1	Public Key Infrastructure	20
3.2.2	Hash Functions and Merkle Trees	22
3.2.3	Digital Signatures	23
3.3	Consensus Mechanisms	25
3.3.1	Proof of Work.....	25
3.3.2	Alternative Consensus Approaches.....	27
4	Bitcoin Transaction Validation and Scalability	29
4.1	Bitcoin Network Architecture	29
4.2	Transaction Processing Workflow	31
4.2.1	Structure of Transactions.....	31
4.2.2	Role of Nodes and Miners.....	33
4.2.3	Validation and Verification Steps.....	35
4.3	Scalability Challenges in Bitcoin	37
4.3.1	Block Size Constraints	37
4.3.2	Transaction Throughput Limitations	39
4.3.3	Trade-offs Between Security, Decentralization, and Efficiency	41
5	Computational Bottlenecks in Blockchain	43
5.1	Signature Verification Complexity	43
5.2	Input and Output Validation Overhead	45
5.3	Resource Utilization in Node Operations	48
5.4	Impact on Network Performance	50

6	Parallel Programming for Blockchain Scalability	52
6.1	Principles of Parallel Computing	52
6.2	Parallelization Strategies in Transaction Validation.....	54
6.2.1	Multithreading Approaches.....	54
6.2.2	GPU and CPU Parallelism.....	56
6.2.3	Distributed Computing Models	58
6.3	Challenges in Parallelizing Blockchain Operations.....	60
6.3.1	Synchronization and Consistency	60
6.3.2	Security Considerations	62
6.3.3	Backward Compatibility	64
7	Mathematical Optimization Techniques.....	66
7.1	Overview of Modular Arithmetic in Cryptography	66
7.2	Chinese Remainder Theorem Fundamentals.....	68
7.3	Accelerating Cryptographic Operations with CRT	70
7.3.1	Application to ECDSA Signature Verification	70
7.3.2	Decomposition of Modular Calculations	72
7.3.3	Potential Gains in Validation Speed	73
8	Integrating Parallel Programming and CRT in Blockchain	76
8.1	Synergies Between Parallelism and Mathematical Optimization	76
8.2	Architectural Considerations for Implementation.....	77
8.3	Potential Improvements in Transaction Throughput.....	80
8.4	Comparative Analysis with Existing Optimization Techniques	82
9	Blockchain in Agriculture and Healthcare	84
9.1	Requirements for Data Integrity and Security	84
9.2	Blockchain-Enabled Solutions	86
9.2.1	Supply Chain Transparency in Agriculture	86
9.2.2	Data Privacy and Consent Management in Healthcare	88
9.3	Scalability Needs in Sectoral Applications	90
9.4	Benefits and Barriers to Adoption.....	92
10	Broader Implications and Future Directions	94
10.1	Impact of Scalability Improvements on Blockchain Adoption	94
10.2	Cross-Industry Opportunities	96
10.3	Open Challenges and Research Gaps.....	99
10.3.1	Security Implications of Advanced Computational Techniques	99

10.3.2	Standards and Protocol Development.....	101
10.3.3	Interoperability and Integration Issues.....	103
11	Conclusion	104

1 Introduction

The increasing adoption of blockchain technologies, particularly Bitcoin, has highlighted both the transformative potential and the inherent limitations of distributed ledger systems. One of the most pressing technical challenges is the scalability of transaction validation, which directly impacts throughput and user experience. Bitcoin's consensus mechanism requires each node to independently validate transactions, a process that is computationally intensive due to the cryptographic operations involved. As transaction volumes grow, this sequential validation approach becomes a bottleneck, limiting the number of transactions per second (TPS) that the network can process within fixed block size constraints [1][2]. Parallel programming techniques offer a promising avenue to address these limitations by distributing computational tasks across multiple processors. By leveraging modern multi-core architectures, transaction validation can be decomposed into subtasks that are executed concurrently, thereby reducing overall processing time. This approach is particularly effective for cryptographic operations, which are often based on modular arithmetic and can be parallelized with minimal interdependence between subtasks [1]. The application of the Chinese Remainder Theorem (CRT) further enhances this strategy. CRT enables the decomposition of large modular computations into smaller, independent calculations that can be efficiently solved in parallel and then recombined to yield the final result. This mathematical property is especially advantageous in the context of public key cryptography, such as RSA, where modular exponentiation is a core operation. By applying CRT, the computational workload associated with cryptographic validation is significantly reduced, leading to faster transaction processing and higher throughput without necessitating changes to the underlying block size or consensus protocol [3][4]. The integration of parallel programming and CRT-based optimizations is not only a technical enhancement but also a necessary evolution for blockchain systems aiming to support a broader range of applications. As blockchain technology expands beyond cryptocurrency into sectors such as healthcare, agriculture, and legal systems, the demand for scalable, secure, and efficient data management solutions intensifies [5][6][7]. In healthcare, for instance, blockchain facilitates secure sharing and management of sensitive patient data, but the volume and privacy requirements of such data necessitate robust

scalability and rapid validation mechanisms [5][7][8]. Similarly, in judicial and agricultural contexts, the ability to process large numbers of transactions and records securely and transparently is critical for trust and operational efficiency [6][2]. Security remains a foundational requirement in these applications. The cryptographic underpinnings of blockchain, including the use of modular arithmetic and key management, are essential for ensuring data integrity, privacy, and resistance to tampering or unauthorized access [9][4]. The adoption of parallelized cryptographic validation, enhanced by CRT, must therefore be rigorously designed to maintain these security guarantees while achieving the desired performance improvements. The distributed nature of blockchain, combined with advanced cryptographic techniques, provides a robust framework for secure, transparent, and auditable transaction processing across diverse domains [2][9]. Legal and regulatory considerations further underscore the importance of scalable and secure blockchain infrastructures. As blockchain systems are integrated into national and sector-specific frameworks, compliance with privacy laws and institutional regulations becomes increasingly complex [10][7]. Efficient transaction validation, supported by parallel programming and CRT, contributes to meeting these requirements by enabling timely processing of data while upholding stringent security and privacy standards [10][7][8]. The convergence of mathematical innovation, computational techniques, and application-driven requirements is shaping the next generation of blockchain systems. By harnessing parallel programming and the Chinese Remainder Theorem, it is possible to overcome existing scalability barriers and unlock new possibilities for blockchain adoption in critical sectors. This research situates itself at the intersection of these developments, aiming to provide both theoretical insights and practical solutions for enhancing the scalability and applicability of blockchain technologies [3][1][2][6].

2 Background and Motivation

2.1 Overview of Blockchain Technology

Blockchain technology is fundamentally a distributed ledger system that records transactions in a secure, immutable, and transparent manner. At its core, the blockchain is

composed of a sequence of blocks, each containing a set of transactions, a timestamp, and a cryptographic hash of the previous block, thereby forming a chain that is resistant to tampering and unauthorized modification. The cryptographic linkage between blocks ensures that any alteration in a block's data will change its hash, making subsequent blocks invalid and thus preserving the integrity of the entire ledger [4]. This intrinsic property of blockchain enhances security and trust among participants, as it becomes computationally infeasible to retroactively alter transaction history without consensus from the network. The transaction model in blockchain systems such as Bitcoin is distinct from traditional account-based models. Instead of maintaining balances tied to user accounts, Bitcoin employs a system of outputs or coins associated with public addresses. Ownership of these coins is established through cryptographic signatures, allowing users to spend coins by proving control over the corresponding private keys. This model enables asynchronous transaction submission, as users can broadcast transactions to the network, which are then incorporated into the blockchain after a variable confirmation period [11]. Each block not only stores transaction data but also the address of the subsequent block, facilitating seamless data flow and validation across the chain [4]. Consensus protocols are central to blockchain operation, ensuring agreement among distributed participants regarding the validity of transactions and the state of the ledger. For example, Bitcoin's consensus mechanism relies on proof-of-work, where network nodes, known as miners, compete to solve computational puzzles, thereby proposing new blocks for inclusion. Once a block is validated through consensus, it is appended to the blockchain, and the process repeats for subsequent transactions. Variations in consensus protocols, such as those introduced in Bitcoin-NG, decouple leader selection from transaction serialization, aiming to improve throughput and reduce latency by partitioning time into epochs with designated leaders. Scalability remains a significant consideration in blockchain technology. The throughput of blockchain networks is inherently limited by block size and block interval parameters. For instance, Bitcoin's architecture restricts transaction throughput to an average of 7 transactions per second, while Ethereum achieves approximately 30 transactions per second. These rates are considerably lower than those of conventional payment systems like Visa, which can process tens of thousands of transactions per second [12]. The bottleneck arises from the need to propagate and validate blocks across a decentralized

network, where increasing block size does not linearly translate to reduced latency due to the additional overhead of disseminating larger blocks [13]. Consequently, research efforts are directed toward optimizing transaction validation and network resource utilization to enhance scalability [12]. The data structure underpinning blockchain, particularly the use of cryptographic hashes and Merkle trees, facilitates efficient transaction verification and retrieval. However, practical implementations may lack certain features, such as Merkle hash functionality, which can limit transaction search efficiency. Studies have shown that while database-backed search methods outperform linear and native blockchain search approaches in terms of speed, they require supplementary systems for transaction verification and introduce additional complexity. As transaction volumes grow, the computational demands on memory and storage systems intensify, underscoring the need for scalable solutions that can handle large-scale data without compromising performance [2]. Blockchain's architecture is inherently flexible, supporting a variety of applications beyond financial transactions. In healthcare, for example, blockchain has been explored for secure management of medical records, streamlining insurance claims, tracking medical devices, and enhancing the safety of clinical trials. The technology's ability to ensure data privacy, integrity, and interoperability makes it suitable for managing sensitive information and automating complex workflows through smart contracts [10]. The use of multiple blockchains or hybrid architectures allows for the distribution of data and processes according to specific requirements, such as jurisdiction or data sensitivity, offering a level of flexibility not achievable with single-chain solutions [6]. The evolution of blockchain platforms has also led to significant improvements in performance and scalability. For example, newer blockchains like Solana have demonstrated high transaction throughput and lower user fees, making them attractive for large-scale applications such as IoT and enterprise solutions [14]. These advancements are supported by ongoing research into optimizing proof generation, data storage, and consensus mechanisms, as well as efforts to standardize protocols for interoperability and enhance user experience [1]. The scientific study of blockchain has predominantly employed qualitative methodologies, including case studies and text analytics, to extract patterns and trends from unstructured data. Triangulation of qualitative and quantitative methods, along with non-probabilistic sampling, has been widely used to address the complexity and novelty of the field [13]. This

methodological diversity reflects the interdisciplinary nature of blockchain research, which spans computer science, cryptography, economics, and sector-specific domains such as healthcare and governance. In summary, blockchain technology represents a paradigm shift in distributed data management, combining cryptographic security, decentralized consensus, and flexible data structures to enable secure, transparent, and scalable transaction processing. Its ongoing evolution is driven by the need to overcome scalability challenges, optimize performance, and expand its applicability across diverse sectors [1][10][12][4].

2.2 Historical Evolution of Blockchain and Cryptocurrencies

The historical development of blockchain and cryptocurrencies is marked by a succession of technological innovations and conceptual advancements that have shaped their current landscape. The origins of blockchain can be traced to the need for secure, decentralized digital ledgers capable of recording transactions in a manner that is resistant to tampering and revision. Early blockchain systems, such as Bitcoin, introduced the concept of a distributed ledger maintained by a network of participants, where transactions are validated and recorded in blocks that are cryptographically linked to form an immutable chain [15]. This architecture not only addressed the double-spending problem inherent in digital currencies but also established a foundation for trustless interactions among participants. Bitcoin's introduction of the Proof of Work (PoW) consensus mechanism was a significant milestone, as it ensured the integrity and security of the blockchain by requiring computational effort from miners to validate transactions and append new blocks [9]. However, the computational intensity of PoW soon raised concerns regarding energy consumption and scalability, especially as transaction volumes increased. The scalability limitations became evident when compared to traditional financial systems, such as Visa, which can process thousands of transactions per second, whereas Bitcoin's throughput remained constrained by block size and block interval parameters [12]. These constraints motivated the exploration of alternative consensus mechanisms, such as Proof of Stake (PoS) and Proof of Authority (PoA), which sought to reduce energy requirements and improve scalability by shifting the basis of block creation from computational power to

cryptocurrency ownership or trusted validator status [9]. The evolution of blockchain technology was further influenced by the emergence of new platforms designed to address the performance and scalability challenges identified in earlier systems. For instance, Solana introduced architectural innovations that enabled high transaction throughput and significantly reduced user fees, making it a compelling choice for large-scale applications, including those in the Internet of Things (IoT) domain [14]. The adoption of advanced consensus protocols and optimization of data structures, such as the use of micro-blockchains and lightweight consensus mechanisms like Practical Byzantine Fault Tolerance (PBFT), have contributed to enhanced efficiency in data collection and analysis, particularly in scenarios requiring rapid processing and low latency [16]. Cryptocurrencies themselves have undergone substantial transformation, with the development of diverse transactional models. The Unspent Transaction Output (UTXO) model, as employed by Bitcoin, allows for multiple operations within a single transaction, offering flexibility and high throughput at the cost of increased storage requirements [17]. This trade-off between storage and throughput has prompted ongoing research into optimizing transaction validation processes and data management strategies, including the application of parallel programming techniques and mathematical constructs such as the Chinese Remainder Theorem (CRT) to accelerate cryptographic operations. Beyond the financial sector, blockchain's evolution has been characterized by its expanding role in various industries. In supply chain management, blockchain has enabled the creation of immutable transaction records, facilitating product provenance and combating counterfeiting, while also automating processes through smart contracts [18]. The integration of blockchain in sectors like agriculture and healthcare has demonstrated its capacity to support secure, transparent, and efficient data sharing and process automation, often surpassing the capabilities of traditional single-chain solutions by leveraging multi-chain architectures and smart contracts for enhanced flexibility and reduced administrative errors [6]. The synergy between blockchain and microservices architectures has further enabled decentralized, tamper-resistant logging mechanisms for cloud-native applications, addressing the operational complexities of distributed systems [19]. The historical trajectory of blockchain and cryptocurrencies thus reflects a continuous interplay between the pursuit of security, scalability, and efficiency. The field has witnessed the adoption of

advanced cryptographic techniques, the refinement of consensus algorithms, and the exploration of parallel and distributed computing paradigms to overcome performance bottlenecks [1]. As transaction volumes and application domains continue to expand, the scalability of blockchain systems remains a central focus, driving ongoing innovation in both theoretical and practical dimensions [2].

2.3 Significance of Scalability in Blockchain Networks

Scalability is a fundamental property for blockchain networks, directly influencing their ability to support widespread adoption and diverse real-world applications. As transaction volumes increase, the underlying infrastructure must efficiently process, validate, and record a growing number of transactions without compromising performance or security. Inadequate scalability leads to network congestion, elevated transaction fees, and delayed confirmations, all of which undermine user experience and limit the practical utility of blockchain systems [14]. The computational demands of transaction validation, particularly those involving cryptographic operations, present a significant scalability challenge. As the number of transactions approaches large scales, the time required for search and verification processes increases non-linearly, especially if the underlying hardware becomes a bottleneck. This is evidenced by empirical observations where search algorithms experience degraded performance with increasing transaction volumes, emphasizing the necessity for optimized memory and disk usage to maintain acceptable throughput. Furthermore, the absence of efficient data structures, such as Merkle trees, in some blockchain implementations can further exacerbate scalability issues by limiting the speed and reliability of transaction verification [2]. Parallel programming techniques offer a promising avenue for addressing these challenges. By distributing validation tasks across multiple processors, blockchain networks can achieve substantial reductions in transaction processing times. This approach is particularly relevant for cryptographic operations, which often involve modular arithmetic computations that are inherently parallelizable. The application of mathematical tools such as the Chinese Remainder Theorem (CRT) can further accelerate modular exponentiation, a core operation in cryptographic validation, by decomposing computations into smaller, independent subproblems that can be solved

concurrently. This synergy between parallelism and advanced mathematical techniques has the potential to significantly increase transaction throughput within existing block size constraints, thereby enhancing scalability without necessitating fundamental changes to network protocols [12]. The significance of scalability extends beyond technical performance; it is also a prerequisite for the integration of blockchain technology into sectors such as healthcare, agriculture, and the Internet of Things (IoT). In these domains, the volume and velocity of data generation are substantial, requiring blockchain systems to handle large-scale, real-time data streams efficiently. For example, in healthcare, the secure and scalable management of patient records and IoT device data is critical for improving patient outcomes and operational efficiency [20][21]. Distributed ledger technology has demonstrated the capacity to ensure data authenticity and integrity in such contexts, but its broader adoption is contingent on overcoming scalability limitations [20]. Similarly, in smart vehicle networks and other connected systems, scalable blockchain frameworks are essential for supporting secure, high-throughput data exchange and validation [9]. The evolution of blockchain platforms, such as Solana, illustrates ongoing efforts to address scalability through architectural innovations that enable high transaction throughput and low user fees [14]. However, these advances also introduce new challenges, such as increased operational complexity and the need for robust mechanisms to maintain decentralization and security as the network scales [1]. The adoption of parallel mining architectures, as proposed in recent research, exemplifies a shift toward leveraging automation and virtualization to enable devices with limited computational resources to contribute meaningfully to the network, thereby democratizing participation and reducing energy consumption [12]. Moreover, scalability is not solely a matter of transaction processing speed; it encompasses the ability to maintain system integrity, security, and decentralization as the network grows. For instance, the risk of centralization increases if only a small subset of nodes possesses the computational power required to process large transaction volumes, potentially undermining the trustless nature of blockchain systems [10][22]. Therefore, scalable solutions must be designed with careful consideration of these systemic properties to ensure that performance improvements do not come at the expense of security or inclusivity. In summary, the significance of scalability in blockchain networks is multifaceted, encompassing technical, operational, and socio-economic

dimensions. Addressing scalability is essential for unlocking the full potential of blockchain technology across a wide range of applications, from financial systems to healthcare and beyond [20][21][14][2][9][12].

2.4 Applications Beyond Cryptocurrencies

2.4.1 Agriculture Sector

The agriculture sector faces unique challenges in ensuring product authenticity, traceability, and information quality, particularly as supply chains become increasingly globalized and complex. Traditional mechanisms for maintaining data integrity and regulatory compliance often fall short, especially when multiple independent entities participate in the supply chain and the physical distance from producers to consumers increases. In such environments, the risk of information asymmetry and the proliferation of counterfeit products is heightened, undermining consumer trust and food safety. Blockchain technology, with its decentralized and immutable ledger, addresses these challenges by enabling all participants in an agricultural supply chain to directly validate information submitted by their transaction partners. This eliminates the need for a central authority or intermediary, as consensus is achieved through distributed mechanisms inherent to blockchain networks. The ability for multiple parties to independently verify the authenticity of product-related data not only enhances the reputation of that information but also facilitates the detection of counterfeits and fraudulent activities [23][18]. For instance, Mackey and Nayyar highlight that blockchain's transparency and shared validation processes are particularly effective in reducing the circulation of counterfeit agricultural products, as every transaction and modification is recorded and visible to all network participants. In addition to improving traceability and authenticity, blockchain adoption in agriculture supports compliance with national and international regulations. As Behnke and Janssen suggest, the decentralized nature of blockchain ensures that no single party can manipulate or obscure critical data, which is essential for meeting regulatory requirements in food safety and quality assurance [23]. This is particularly relevant in global supply chains, where the complexity and number of stakeholders make centralized oversight impractical and often ineffective. The integration of blockchain into

agricultural supply chains also brings operational efficiencies. By providing a single, tamper-proof source of truth, blockchain reduces the administrative burden associated with reconciling disparate records and resolving disputes. This streamlining of processes can lead to faster transaction settlements and lower costs, which are significant benefits for producers, distributors, and retailers alike [18]. Furthermore, the transparency afforded by blockchain fosters greater trust among consumers, who can access verifiable information about the origin, handling, and quality of agricultural products. Beyond supply chain management, blockchain's potential in agriculture extends to areas such as land registration, crop insurance, and resource management. The technology's capacity for secure, transparent record-keeping can help smallholder farmers establish land ownership, access credit, and participate in formal markets. These applications underscore the broader impact of blockchain as a tool for inclusive development and sustainable agricultural practices. Crittenden and Sistla note that blockchain initiatives are increasingly being leveraged for social impact, particularly in contexts where establishing identity and banking systems is challenging, such as among rural farmers or migrant agricultural workers. By providing secure digital identities and transaction histories, blockchain can facilitate access to financial services and government support, further empowering vulnerable populations within the agricultural sector [24]. The adoption of blockchain in agriculture is not without technical and organizational challenges. Issues such as interoperability with existing systems, scalability, and the need for stakeholder education must be addressed to realize the full benefits of the technology. Nevertheless, the convergence of blockchain with other digital innovations, such as the Internet of Things (IoT) and artificial intelligence, promises to further enhance data collection, analysis, and decision-making in agriculture. Zheyi Lu highlights that blockchain, as a core component of Industry 4.0, is indispensable for achieving the high levels of automation and data integration required in modern agricultural operations [25]. The collective evidence indicates that blockchain's application in the agriculture sector is transformative, offering robust solutions for traceability, authenticity, compliance, and operational efficiency. Its decentralized architecture and consensus-driven validation mechanisms are particularly well-suited to the distributed, multi-stakeholder nature of agricultural supply chains,

positioning blockchain as a foundational technology for the future of secure and sustainable food systems [23][24][18][25].

2.4.2 Healthcare Sector

Blockchain technology has attracted considerable attention in the healthcare sector due to its potential to address persistent challenges in data management, security, and interoperability. The distributed and tamper-resistant nature of blockchain makes it particularly suitable for storing sensitive medical data, such as electronic health records (EHRs) and personal health records (PHRs). The cryptographic linking of blocks ensures that once data is recorded, it cannot be altered without consensus from all nodes, providing a robust mechanism for data integrity and traceability [26]. This property is especially valuable in healthcare, where the accuracy and immutability of patient records are critical for both clinical outcomes and regulatory compliance. The adoption of blockchain in healthcare promises several advantages. Decentralization ensures that no single entity controls the data, reducing the risk of data silos and enabling continuous accessibility for authorized stakeholders. The persistence and data pedigree features of blockchain facilitate the maintenance of comprehensive, longitudinal health records, which can be securely accessed by patients, providers, and researchers as needed. This continuous accessibility supports more coordinated care and can enhance patient engagement by returning control of medical data to individuals [27][10]. Furthermore, the transparency and verifiability inherent to blockchain platforms can increase trust among participants, as all actions on the ledger are visible and auditable, supporting accountability and reducing the likelihood of fraud [23]. However, several limitations must be addressed before blockchain can be widely implemented in healthcare. The confidentiality of medical data remains a significant concern, as blockchain's transparency can conflict with the privacy requirements mandated by healthcare regulations. Scalability and speed are also critical issues; current blockchain platforms may struggle to handle the high volume of transactions typical in large healthcare systems, potentially leading to latency in data access and updates [27][13]. The threat of malicious attacks, such as the so-called 51% attack, poses additional risks, especially in public or poorly secured blockchain networks [27]. Moreover, integration challenges arise from the diversity of blockchain architectures

and consensus algorithms, making interoperability between different systems a complex technical hurdle [13]. Despite these challenges, the healthcare sector is viewed as one of the most promising domains for blockchain applications. The ability to enhance the protection of personal health information, secure the integrity of medical data, and improve the efficiency of insurance claims processes are among the anticipated benefits [10]. By enabling real-time information sharing and supporting a decentralized, tamper-proof platform, blockchain can contribute to the realization of precision medicine and evidence-based care environments [23][10]. The increased interoperability among healthcare data operators not only streamlines care delivery but also reduces administrative overhead and costs. Organizations such as the Blockchain Research Institute and HIMSS are actively exploring the practical implications of blockchain in healthcare, producing research and case studies to evaluate its impact and identify hurdles to adoption [28]. These efforts underscore the necessity of further research to close existing knowledge gaps, particularly regarding system integration and the development of scalable solutions capable of supporting the high throughput demands of healthcare environments [13]. As blockchain technology matures, its application in healthcare could transform data management paradigms, offering more secure, transparent, and patient-centered models for the future [10][23][26].

2.4.3 Other Emerging Fields

Beyond the established domain of cryptocurrencies, blockchain technology is increasingly being recognized for its transformative potential in a variety of sectors, driven by its core attributes of decentralization, transparency, and immutability [20][18]. In healthcare, for instance, blockchain-based solutions are being explored to address the challenges of secure and interoperable electronic health records (EHRs). The integration of blockchain with EHRs promises enhanced data integrity, traceability, and patient-centric control over health information. However, the adoption of blockchain in this context is not without obstacles. Issues such as technological limitations, vendor adoption, and significant infrastructure costs have been identified as barriers to achieving fully interoperable EHR systems on a global scale. Furthermore, the inherent immutability of blockchain can conflict with privacy regulations, such as the right to be forgotten, which necessitates the

deletion of personal health data, an operation fundamentally at odds with blockchain's design. The scalability of blockchain solutions in healthcare is also a subject of ongoing investigation. The trade-off between transaction volume and computational power required for processing is particularly pronounced in data-intensive environments. The literature suggests that the adoption of open standards and collaborative industry efforts could facilitate the transition from experimental prototypes to practical, large-scale applications [29]. Moreover, blockchain's modular architecture enables integration with other advanced technologies, such as cloud computing, artificial intelligence, and the Internet of Medical Things (IoMT), further expanding its applicability in healthcare and life sciences [20]. This interoperability supports a broad spectrum of use cases, ranging from secure data sharing among healthcare providers to real-time monitoring of patient health through connected devices. In addition to healthcare, blockchain is being investigated for its utility in sectors such as agriculture and supply chain management. For example, the transparency and immutability of blockchain can be leveraged to enhance traceability in agricultural supply chains, ensuring the authenticity and ethical sourcing of products. This capability is particularly relevant for combating fraud and verifying the provenance of goods, which is critical for both consumer safety and regulatory compliance. The decentralized nature of blockchain also offers opportunities for financial inclusion in underserved regions, enabling secure and low-cost cross-border transactions that bypass traditional banking infrastructures [18]. Security remains a central concern across these emerging applications. In healthcare, hybrid blockchain architectures that combine private and consortium blockchains are being proposed to balance data privacy with the need for shared access among authorized parties. Such architectures employ cryptographic techniques and consensus mechanisms to ensure that once a block is appended, it becomes exceedingly difficult and costly to alter, thereby providing robust tamper resistance [30]. At the same time, the rapid evolution of quantum computing presents new challenges to existing cryptographic methods. There is a growing recognition that blockchain schemes must be evaluated and potentially adapted to withstand the computational capabilities of quantum systems, which could compromise current encryption standards [31]. The scalability of privacy-preserving techniques is another active area of research, particularly as datasets grow to several gigabytes or even terabytes. The development of scalable

privacy approaches that can efficiently handle large, distributed datasets is essential for practical deployment in sectors such as healthcare, where multiple providers and recipients may need to access and share anonymized data for diverse purposes [32]. Techniques such as parallel processing, dynamic parameter adjustment, and the application of advanced cryptographic protocols are being explored to address these challenges [15]. Despite the promise of blockchain in these emerging fields, real-world adoption remains in its early stages. Many organizations are still evaluating the technology, often through informal processes and limited pilot projects. The lack of clear value propositions and return on investment has contributed to a cautious approach, with most institutions prioritizing use cases that can demonstrably improve efficiency and data security [33]. Nonetheless, the growing body of research and the increasing number of publications in this area underscore the expanding interest and potential for blockchain to revolutionize data management and trust across a diverse array of industries [20].

3 Principles of Blockchain Systems

3.1 Decentralization and Distributed Ledgers

Decentralization is a foundational property of blockchain systems, distinguishing them from traditional centralized databases by distributing authority, control, and data storage across a network of independent nodes. This distributed architecture underpins the security, transparency, and resilience of blockchain-based ledgers. In a decentralized ledger, each participant maintains a copy of the entire transaction history, and consensus mechanisms are employed to ensure that all copies remain synchronized and tamper-resistant [34]. The elimination of a single point of control or failure enhances the robustness of the system against malicious attacks and operational disruptions [10][34]. The distributed nature of blockchain ledgers enables immutable and transparent record-keeping, which is particularly valuable in environments where trust between parties is limited or where auditability is essential. Each transaction is cryptographically linked to its predecessor, forming a chain of blocks that is resistant to unauthorized modification. This property is leveraged in various sectors, such as healthcare and supply chain management,

to provide verifiable audit trails and decentralized trust [35][36]. For instance, in healthcare, the use of distributed ledgers allows for secure sharing of electronic health records (EHRs) among authorized parties, ensuring data integrity and patient privacy while reducing reliance on centralized intermediaries [34]. Consensus protocols play a crucial role in maintaining the integrity and consistency of distributed ledgers. In public blockchains, consensus is typically achieved through algorithms that tolerate a degree of Byzantine faults, enabling the network to function correctly even in the presence of malicious or faulty nodes. However, the Fischer-Lynch-Paterson theorem demonstrates that in fully asynchronous distributed systems with the possibility of Byzantine faults, it is impossible to guarantee both agreement and termination simultaneously. As a result, public blockchains often relax certain consistency requirements, opting for eventual consistency to balance scalability and security [37]. In contrast, private and consortium blockchains may employ consensus protocols with stronger consistency guarantees, reflecting their different trust assumptions and application requirements [38]. The decentralization of transaction validation and logging is particularly relevant in the context of microservices architectures, where traditional centralized logging mechanisms may be impractical or contrary to the system's design principles. By integrating blockchain as a secure logging layer, organizations can achieve enhanced traceability and verifiable audit trails without sacrificing the modularity and scalability of microservices [35]. This approach is further strengthened by the use of smart contracts, which automate validation and access control, and by the potential integration with artificial intelligence for advanced analytics [19]. Scalability remains a significant challenge for decentralized ledgers, especially as transaction volumes increase. Layer-2 solutions, such as rollups, aim to address this by processing transactions off-chain and periodically committing summaries to the main blockchain. Optimistic rollups and zero-knowledge (ZK) rollups represent two prominent approaches, each with distinct trade-offs in terms of throughput, cost, security, and complexity. Optimistic rollups offer lower transaction fees and easier integration but rely on incentivized validation and longer finality times. ZK rollups provide immediate finality and higher security through cryptographic proofs but are more complex and computationally intensive [1]. These innovations exemplify the ongoing efforts to enhance the scalability of decentralized ledgers while preserving their core properties. The

application of decentralization and distributed ledgers extends beyond financial transactions to domains such as agriculture, logistics, and healthcare. In supply chain management, for example, distributed ledgers improve transparency and efficiency by enabling all stakeholders to access a shared, tamper-evident record of goods movement and provenance [36]. In agriculture, decentralized data management systems can facilitate traceability, certification, and fair trade practices. The adaptability of blockchain platforms, such as Ethereum, supports the development of diverse decentralized applications tailored to the unique requirements of different sectors [34]. Despite these advantages, the widespread adoption of decentralized ledger technologies faces challenges related to scalability, interoperability, and regulatory compliance. The integration of advanced parallel programming techniques and mathematical tools, such as the Chinese Remainder Theorem, holds promise for accelerating cryptographic operations and transaction validation, thereby improving the throughput and efficiency of distributed ledgers. As the technology matures, further research and development will be necessary to address these challenges and realize the full potential of decentralized systems in various application domains [25].

3.2 Cryptographic Foundations

3.2.1 Public Key Infrastructure

Public Key Infrastructure (PKI) constitutes a fundamental component in the cryptographic architecture of blockchain systems, underpinning both the security and integrity of digital transactions. At its core, PKI leverages asymmetric cryptography, wherein each participant possesses a pair of cryptographic keys: a public key, which is openly distributed, and a private key, which remains confidential to its owner. This dual-key structure enables secure authentication, digital signatures, and the establishment of trustless environments, all of which are essential for decentralized systems. In blockchain-based networks, PKI is instrumental in ensuring that only legitimate parties can initiate and validate transactions. Each transaction is digitally signed using the sender's private key, and any network participant can verify the authenticity of the transaction by checking the signature against the corresponding public key. This mechanism not only authenticates the origin of the

transaction but also guarantees non-repudiation, as only the holder of the private key could have generated the signature [39][8]. The cryptographic linkage between transactions and users thereby prevents unauthorized modifications and forgeries, contributing to the immutability of the blockchain ledger. The process of transaction validation in blockchain systems is closely tied to PKI. When a transaction is broadcast to the network, miners or validators utilize the sender's public key to verify the digital signature. This verification step is computationally efficient and forms the basis for consensus protocols, whether they are based on proof-of-work, proof-of-stake, or Byzantine fault tolerance mechanisms [40][41]. The robustness of PKI ensures that even in a decentralized and potentially adversarial environment, the integrity of the transaction history is maintained. Furthermore, PKI supports the secure management of sensitive data, particularly in sectors such as healthcare and supply chain management. In these contexts, data privacy and access control are paramount. By encrypting data with the recipient's public key, only the intended party can decrypt and access the information using their private key. This approach not only preserves confidentiality but also enables fine-grained access control in multi-party environments [39]. The immutable and transparent nature of blockchain, combined with PKI-based encryption, ensures that sensitive records, such as patient health information or supply chain provenance, are both auditable and resistant to tampering [16][8]. The decentralized consensus achieved in blockchain systems is also reliant on the secure distribution and management of public keys. Unlike traditional centralized PKI systems, blockchain networks often operate without a single trusted certificate authority. Instead, public keys are distributed and managed through the network itself, with identities and key associations recorded on-chain or within specialized identity registries [41]. This decentralized approach mitigates single points of failure and enhances the resilience of the system against targeted attacks. However, the scalability of PKI in blockchain environments presents unique challenges, especially as transaction volumes increase. Efficient cryptographic operations, such as signature verification, become critical bottlenecks. Recent research has focused on optimizing these operations through parallelization and advanced mathematical techniques, such as the Chinese Remainder Theorem, to accelerate modular arithmetic and improve throughput without compromising security [17]. These innovations are particularly relevant as blockchain

applications expand into high-throughput domains like finance and healthcare, where rapid and secure transaction validation is essential. In summary, PKI is an indispensable element of blockchain systems, enabling secure authentication, data integrity, and privacy through asymmetric cryptography. Its integration with decentralized consensus protocols and advanced cryptographic techniques ensures that blockchain networks can support scalable, secure, and trustworthy applications across diverse sectors [40][39][16][8].

3.2.2 Hash Functions and Merkle Trees

Hash functions are fundamental cryptographic primitives in blockchain systems, providing both security and efficiency in transaction processing. A cryptographic hash function deterministically maps input data of arbitrary size to a fixed-size output, known as the hash or digest, in such a way that even a minor change in the input produces a drastically different output. This property, known as the avalanche effect, is crucial for ensuring data integrity and collision resistance. In the context of Bitcoin and other blockchains, hash functions are employed to secure transactions, link blocks, and facilitate consensus mechanisms [42][12]. Within each block, transactions are organized and summarized using a Merkle tree, a binary hash tree structure that enables efficient and secure verification of large sets of data. In a typical Merkle tree construction, every transaction is first hashed, and then pairs of these hashes are concatenated and hashed again, recursively, until a single hash value remains. This final value is the Merkle tree root hash, which is embedded in the block header. The double hashing at each step further enhances resistance to collision and preimage attacks, reinforcing the cryptographic robustness of the system [42][12]. The Merkle tree structure offers significant computational and storage benefits. By storing only the root hash in the block header, it becomes possible to verify the inclusion of any transaction in the block with a minimal set of hash calculations, rather than needing to process the entire transaction set. This property is particularly advantageous for lightweight clients, which can validate transactions without downloading the full blockchain, thus reducing bandwidth and storage requirements [2]. The efficiency of Merkle proofs is critical for scalability, as it allows for rapid transaction verification even as the blockchain grows in size [42][2]. Moreover, the immutability and transparency of blockchain data are underpinned by the cryptographic linkage of blocks via hash pointers.

Each block contains the hash of its predecessor, forming a chain that is tamper-evident: any modification to a transaction would alter its hash, propagate changes up the Merkle tree, and ultimately change the block's root hash and the hashes of all subsequent blocks. This chaining mechanism makes unauthorized changes computationally infeasible without controlling a majority of the network's computational power [12][37]. The process of block validation in Bitcoin further leverages hash functions. For a block to be considered valid, its hash must be less than a dynamically adjusted target value, which is determined by the network's difficulty parameter. This requirement forms the basis of the Proof-of-Work consensus mechanism, where miners repeatedly hash block headers with varying nonces until a suitable hash is found [42][12]. The computational challenge of this process secures the network against Sybil attacks and ensures that block creation remains decentralized [43]. From a scientific perspective, the integration of hash functions and Merkle trees not only provides cryptographic guarantees but also enables parallelization opportunities. Since the computation of leaf hashes and intermediate nodes in the Merkle tree can be distributed across multiple processors, parallel programming techniques can be employed to accelerate transaction validation and block construction. This is particularly relevant in the context of scalability research, where reducing validation times is essential for supporting higher transaction throughput within fixed block size limits [42][12][2]. In summary, hash functions and Merkle trees are integral to the cryptographic foundations of blockchain systems. They ensure data integrity, enable efficient transaction verification, and support scalable consensus protocols. Their design facilitates both security and efficiency, making them indispensable components in the ongoing evolution of blockchain technology [42][12][37][2].

3.2.3 Digital Signatures

Digital signatures are a fundamental cryptographic primitive underpinning the security and trustworthiness of blockchain systems. In the context of Bitcoin and similar decentralized ledgers, digital signatures enable participants to authenticate transactions, guarantee data integrity, and provide non-repudiation without the need for a central authority. The core mechanism involves each user possessing a unique private-public key pair, where the private key is used to sign transactions and the public key is available for

others to verify the authenticity of those signatures [27]. The process of transaction validation in Bitcoin relies heavily on digital signatures. When a user initiates a transaction, they generate a signature using their private key and the transaction data. This signature is then broadcast alongside the transaction to the network. Other nodes, upon receiving the transaction, use the sender's public key to verify that the signature is valid and that the transaction has not been tampered with. This ensures that only the legitimate owner of the funds can authorize their transfer, and that the transaction data remains unaltered during propagation [44][45]. A widely adopted digital signature scheme in blockchain systems, particularly Bitcoin, is based on elliptic curve cryptography (ECC), specifically the secp256k1 curve. The choice of secp256k1 is motivated by its efficiency and security properties, which are crucial for supporting the high volume of transactions in a decentralized environment. The use of ECC allows for shorter key lengths and signatures compared to traditional schemes like RSA, resulting in reduced computational overhead and smaller transaction sizes. This efficiency is particularly important in the context of scalability, as it directly impacts the throughput and latency of transaction validation. The security of digital signatures in blockchain is predicated on the computational hardness of the underlying mathematical problems, such as the discrete logarithm problem in the case of ECC. As a result, forging a digital signature or deriving a private key from a public key is computationally infeasible with current technology, thereby providing strong guarantees against impersonation and unauthorized transactions [44][27]. However, the implementation of cryptographic libraries and signature verification routines must be rigorously tested and validated to prevent vulnerabilities, such as side-channel attacks or software bugs, which could undermine the security of the entire system [44]. Digital signatures also play a critical role in addressing specific blockchain threats, such as double-spending attacks. In a double-spending scenario, an attacker might attempt to spend the same digital asset in multiple transactions. The decentralized consensus protocol, together with digital signatures, ensures that only the first valid transaction is accepted and recorded on the blockchain, while subsequent conflicting transactions are rejected. This is achieved by verifying the authenticity and uniqueness of each transaction through its digital signature, thereby maintaining the integrity of the ledger [46][47][44]. Beyond cryptocurrencies, the utility of digital signatures extends into various sectors where

blockchain is being adopted for secure data management. In healthcare, for example, digital signatures are essential for ensuring that only authorized parties can access or modify sensitive health records, providing auditability and accountability in compliance with regulatory requirements [48][45][26]. In supply chain and IoT applications, digital signatures authenticate device identities and data provenance, supporting secure and transparent operations across distributed networks [49][16]. The integration of parallel programming techniques and mathematical tools such as the Chinese Remainder Theorem (CRT) can further enhance the efficiency of digital signature operations. By distributing signature verification tasks across multiple processors and optimizing modular arithmetic computations using CRT, blockchain systems can achieve significant reductions in transaction validation times. This approach directly contributes to improved scalability and throughput, enabling the blockchain to process a greater number of transactions within existing resource constraints [41][44]. The decentralized nature of blockchain, facilitated by digital signatures, eliminates single points of failure and central trust dependencies. Each node independently verifies signatures and transaction validity, contributing to the overall resilience and robustness of the network [46][47][27]. This distributed trust model is a defining characteristic of blockchain systems and is foundational to their adoption in critical domains where security, transparency, and data integrity are paramount.

3.3 Consensus Mechanisms

3.3.1 Proof of Work

Proof of Work (PoW) is a foundational consensus mechanism that underpins the security and operation of many blockchain systems, most notably Bitcoin. In PoW, participants known as miners compete to solve computationally intensive puzzles, typically involving the calculation of a hash value that meets certain criteria. This process ensures that adding a new block to the blockchain requires demonstrable computational effort, making it prohibitively expensive for malicious actors to rewrite transaction history or mount double-spending attacks. The cryptographic hash function used in Bitcoin, SHA-256, is central to this process, as it produces a unique and unpredictable output for each input, thereby ensuring the integrity and immutability of the blockchain. Each block in the chain

contains a set of transactions, a hash of the previous block, and a nonce value that miners adjust to find a valid hash. The requirement that the hash of a block falls below a dynamically adjusted target ensures that blocks are produced at a predictable rate, despite fluctuations in network computational power. This difficulty adjustment is crucial for maintaining the stability and security of the network, as it prevents rapid block production that could destabilize consensus [27]. The process of mining not only validates transactions but also introduces new coins into circulation, aligning economic incentives with network security. The computational intensity of PoW, while effective for security, introduces significant scalability challenges. As the number of transactions increases, so does the demand for computational resources and energy consumption. This has led to ongoing research into optimizing cryptographic operations and transaction validation processes. For instance, leveraging parallel programming techniques and mathematical tools such as the Chinese Remainder Theorem (CRT) can enhance the efficiency of modular arithmetic operations, which are fundamental to many cryptographic algorithms used in transaction validation. By distributing validation tasks across multiple processors and applying CRT-based optimizations, it is possible to reduce the time required for transaction verification, thereby increasing throughput without altering the underlying PoW protocol [50][17]. Despite its strengths, PoW is not without limitations. The energy consumption associated with large-scale mining operations has raised environmental concerns, prompting the exploration of alternative consensus mechanisms such as Proof of Stake (PoS) and hybrid approaches [50][45]. However, PoW remains a benchmark for security and decentralization, as its reliance on computational effort makes it resistant to many forms of attack. The structure of PoW-based blockchains, such as Bitcoin, is inherently decentralized and peer-to-peer. Each node in the network maintains a copy of the blockchain and participates in the validation and propagation of new blocks. The consensus achieved through PoW ensures that all honest nodes agree on the state of the ledger, even in the presence of adversarial behavior. The block structure, with its inclusion of cryptographic hashes and consensus rules, is designed to facilitate this agreement and prevent tampering. In summary, PoW has established itself as a robust mechanism for achieving distributed consensus in open, adversarial environments. Its integration with cryptographic primitives and dynamic difficulty adjustment provides strong guarantees of security and

immutability. However, the scalability and energy efficiency challenges inherent to PoW motivate ongoing research into parallelization strategies and mathematical optimizations, as well as the development of alternative consensus protocols for future blockchain systems [27][50][45][17].

3.3.2 Alternative Consensus Approaches

Alternative consensus approaches have emerged as a response to the limitations of traditional blockchain consensus mechanisms, particularly in terms of scalability, latency, and resource utilization. In classical blockchain systems, consensus is typically achieved through mechanisms such as Proof of Work (PoW) or Proof of Stake (PoS), which, while robust, often suffer from low throughput and high energy consumption. These drawbacks have prompted researchers and practitioners to explore more efficient alternatives that can better support high-volume transaction environments and complex application domains. One significant direction in alternative consensus mechanisms is the integration of parallel processing and distributed validation. By leveraging parallel programming techniques, it becomes possible to distribute the workload of transaction validation and block creation across multiple processors or nodes. This approach can dramatically reduce the time required to reach consensus, as multiple transactions or blocks can be validated simultaneously rather than sequentially. DeNio et al. highlight that parallel mining, where miners validate blocks in parallel rather than individually, leads to substantial improvements in both transaction speed and overall network scalability. This method not only accelerates consensus but also enhances the reliability of the network by reducing the risk of bottlenecks at single nodes [12]. Another avenue involves the use of hybrid consensus mechanisms, which combine features from multiple consensus algorithms to balance performance, security, and resource efficiency. Alyas et al. point out that hybrid consensus can manage system complexity and resource utilization more effectively, especially in architectures involving multiple blockchains or cross-chain operations. The trade-off between system complexity and performance is a key consideration, as more sophisticated consensus protocols may introduce higher processing costs but can also deliver tangible improvements in memory utilization and query performance [6]. The design of such mechanisms often requires careful evaluation to avoid undesirable increases

in latency or resource consumption. In addition, consensus protocols based on rules and hierarchical structures have been shown to improve transaction throughput. Li notes that rule-based and hierarchy-based consensus algorithms can significantly enhance the efficiency of transaction processing, particularly in private or permissioned blockchain environments. These systems typically exhibit higher throughput and lower latency compared to public blockchains, as the consensus process can be streamlined through controlled participation and optimized communication patterns [23]. The adoption of double-chain structures, where two chains operate in tandem to separate transaction validation from block confirmation, further contributes to throughput gains by enabling concurrent operations. The concept of distributed consensus, wherein each network participant votes on the validity of transactions or blocks, is also central to alternative approaches. Bunduchi describes how distributed consensus eliminates the need for a central authority by allowing implicit voting among participants, thereby increasing the resilience and transparency of the system [36]. This decentralized decision-making process is fundamental to the trustless nature of blockchain and can be adapted to various consensus protocols, including those optimized for parallel or sharded architectures. Sharding itself represents a promising alternative consensus strategy, particularly for large-scale blockchain systems. By partitioning the ledger into multiple shards, each responsible for a subset of transactions, sharded blockchains can process many transactions in parallel, significantly increasing throughput. Han et al. discuss the importance of shard allocation protocols, which ensure that nodes are distributed across shards to prevent single points of failure and maintain network security. Efficient shard allocation and cross-shard communication protocols are essential for maintaining consistency and atomicity of transactions across the entire system [41]. The integration of artificial intelligence (AI) techniques with blockchain consensus is another innovative approach. Kim and Huh describe the application of neural networks to blockchain performance evaluation, where AI-driven consensus mechanisms can dynamically adjust parameters such as transaction throughput and block generation time based on network conditions. This adaptability can lead to more efficient consensus processes, particularly in environments with fluctuating workloads or heterogeneous node capabilities [10]. Furthermore, the use of smart contracts and decentralized applications (DApps) introduces

new requirements for consensus mechanisms. Lu outlines how blockchain architectures designed for manufacturing supply chains incorporate unique consensus algorithms tailored to the specific needs of the industry, such as real-time tracking, auditability, and scalability. These domain-specific consensus protocols often leverage parallel validation and modular design to accommodate high transaction volumes and complex business logic [25]. The adoption of alternative consensus approaches is also influenced by the broader context of blockchain applications. Peng et al. emphasize that the decentralized, traceable, and immutable nature of blockchain makes it suitable for sectors like agriculture and healthcare, where secure and scalable data management is critical. The choice of consensus mechanism directly impacts the ability of blockchain systems to meet the demands of these applications, particularly in terms of transaction throughput, latency, and data integrity [16]. In summary, alternative consensus approaches encompass a range of strategies, including parallel and hybrid mechanisms, rule-based and hierarchical protocols, distributed consensus, sharding, AI integration, and domain-specific algorithms. These innovations collectively address the scalability and efficiency challenges inherent in traditional blockchain systems, enabling broader adoption and more sophisticated applications across diverse sectors [25][10][36][41][12][6][23][16].

4 Bitcoin Transaction Validation and Scalability

4.1 Bitcoin Network Architecture

The Bitcoin network architecture is fundamentally structured as a decentralized, peer-to-peer (P2P) system that operates without a central authority, relying instead on distributed consensus to validate and record transactions. Each participant, or node, in the network maintains a copy of the blockchain, which is a continuously growing ledger of timestamped transaction blocks. The process of transaction validation is intrinsically linked to the consensus mechanism, which ensures that all nodes agree on the current state of the ledger and the order of transactions. This is achieved through a combination of digital signatures, which authenticate transaction initiators, and a timestamp server that orders transactions and addresses the double-spending problem by making all transactions public to the

network. The architecture leverages cryptographic techniques to secure transaction data and maintain trust among anonymous participants. Every transaction is digitally signed by the owner of a private key, referencing the hash of the previous transaction and the public key of the recipient. This creates a chain of cryptographic proofs that is resistant to tampering. The timestamp server, as part of the consensus protocol, plays a crucial role in establishing the chronological order of transactions, which is essential for resolving conflicts and preventing fraudulent activities such as double-spending [36][22]. Bitcoin's consensus protocol, originally based on Proof-of-Work (PoW), requires miners to solve computationally intensive puzzles to validate new blocks. This mechanism not only secures the network but also determines which transactions are included in the next block. The network's decentralized nature means that transaction validation and block creation are distributed among thousands of nodes, each competing to add the next block to the chain. This competition incentivizes miners through transaction fees and block rewards, but it also introduces latency and scalability challenges as the network grows [38]. The block size limit, currently set at 1 MB, constrains the number of transactions that can be included in each block. This architectural choice, while enhancing security and decentralization, imposes a bottleneck on transaction throughput. The distribution of transaction sizes within Bitcoin is broad, with some transactions reaching the maximum block size, reflecting the robustness of the unspent transaction output (UTXO) model. This model allows for flexible transaction composition but results in higher storage costs compared to more compact transaction models, such as those used in Ethereum [17]. The need to balance security, decentralization, and scalability is a defining characteristic of the Bitcoin network architecture. Simulation studies, such as those conducted using ChainSim, demonstrate that the Bitcoin network can be effectively modeled with thousands of miners and tens of thousands of users, providing insights into network performance and transaction fee dynamics. These simulations reveal that transaction prioritization is influenced by fee structures, and miners are more likely to include transactions with higher fees in their blocks. The PoW consensus protocol remains central to both Bitcoin and Ethereum, with similar operational structures, although Ethereum is transitioning towards Proof-of-Stake (PoS) to address scalability and energy efficiency concerns [38][37]. The architecture's reliance on distributed consensus and cryptographic validation underpins its

resilience to attacks and censorship. However, the public availability of transaction data, while enhancing transparency, can also lead to privacy concerns, as patterns in transaction flows may be analyzed to infer user behavior [51][16]. This transparency is a double-edged sword, providing both opportunities for auditability and challenges for user privacy. In addition to its core financial applications, the architectural principles of the Bitcoin network have inspired broader adoption of blockchain technology in sectors such as healthcare and supply chain management. In healthcare, for example, blockchain's distributed and immutable ledger is leveraged to securely store and share patient records, with each record assigned to a block and linked chronologically. This approach enhances data integrity and security, reducing response times and operational costs compared to traditional centralized systems [52]. In supply chains, blockchain mitigates information asymmetry and enhances trust among participants by providing transparent, tamper-resistant records of transactions and product provenance [23]. Scalability remains a central concern in the Bitcoin network architecture. Solutions such as off-chain transactions, sharding, and advanced cryptographic techniques are being explored to address the limitations imposed by block size and transaction throughput. The integration of parallel programming techniques and mathematical frameworks like the Chinese Remainder Theorem (CRT) holds promise for accelerating cryptographic operations and distributing validation workloads across multiple processors, thereby reducing validation times and increasing throughput within existing architectural constraints. The Bitcoin network architecture exemplifies a complex interplay between security, decentralization, and scalability. Its design choices have profound implications not only for the efficiency of transaction validation but also for the broader applicability of blockchain technology in diverse domains, where secure, scalable, and transparent data management solutions are increasingly in demand [52][51][17][38].

4.2 Transaction Processing Workflow

4.2.1 Structure of Transactions

The structure of transactions in Bitcoin is fundamental to the validation workflow and ultimately impacts scalability and performance. Each transaction encapsulates a set of

inputs and outputs, where inputs reference previous unspent transaction outputs (UTXOs), and outputs define new UTXOs that can be spent in future transactions. The cryptographic integrity of this structure is maintained through digital signatures and hash functions, ensuring that only the rightful owner can authorize the spending of funds. This cryptographic assurance is a cornerstone of blockchain security, as the transaction data, once recorded in a block, becomes immutable and resistant to tampering due to the chained hash structure and consensus mechanisms [53]. A typical Bitcoin transaction includes the following components: a version number, a list of inputs, a list of outputs, and a locktime parameter. Each input contains a reference to a previous output, a scriptSig (which provides the unlocking script, usually a digital signature), and a sequence number. Each output specifies a value (the amount in satoshis) and a scriptPubKey, which sets the conditions under which the output can be spent. The use of scripts allows for programmable conditions, enabling functionalities such as multi-signature transactions and time-locked transfers, which are essential for advanced applications like smart contracts [9][33]. The validation process for each transaction involves verifying that the referenced inputs are indeed unspent, that the digital signatures are valid, and that the sum of input values is greater than or equal to the sum of output values, with any difference being claimed as a transaction fee by the miner. This process is computationally intensive, particularly due to the cryptographic operations required for signature verification and hash calculations. As the blockchain grows, the volume and complexity of transactions increase, placing greater demands on processing resources and storage [23][15]. To address these challenges, parallel programming techniques can be leveraged to distribute the workload of transaction validation across multiple processors. By assigning different transactions or even different cryptographic operations within a transaction to separate threads or processing units, the system can achieve significant reductions in validation latency. This approach is particularly effective when combined with mathematical optimizations such as the Chinese Remainder Theorem (CRT), which can accelerate modular arithmetic operations commonly used in cryptographic algorithms. The CRT enables the decomposition of large modular exponentiations into smaller, independent computations that can be executed concurrently, further boosting throughput [23][15]. The block structure, which aggregates multiple transactions, also plays a crucial role in

transaction processing. Each block contains a header with metadata (including the previous block hash, timestamp, nonce, and Merkle root) and a body with the list of validated transactions. The Merkle root is computed from the hashes of all transactions in the block, providing an efficient and secure way to verify the inclusion of any transaction without revealing the entire block content. This hierarchical hashing mechanism supports lightweight clients and enhances scalability by minimizing the data needed for transaction verification [9][15]. However, the requirement for every validator to store and process the entire transaction history imposes significant storage and computational overhead, especially as the number of transactions grows. For example, Bitcoin's throughput is limited to approximately 7 transactions per second, and the blockchain size has reached hundreds of gigabytes, highlighting the need for scalable solutions [23]. Innovations such as sharding, layer-2 protocols, and reputation-based consensus mechanisms are being explored to mitigate these limitations, but the fundamental structure of transactions remains central to the validation workflow. In summary, the structure of transactions in Bitcoin is intricately designed to balance security, programmability, and efficiency. The interplay between transaction components, cryptographic verification, and block aggregation defines the transaction processing workflow. Advances in parallel computation and mathematical optimization, such as the application of the Chinese Remainder Theorem, offer promising avenues to enhance scalability without compromising the core principles of decentralization and trustless validation [15][53][23].

4.2.2 Role of Nodes and Miners

Nodes and miners are fundamental actors in the Bitcoin transaction processing workflow, each contributing distinct yet interdependent roles that ensure the integrity, scalability, and security of the network. Nodes are responsible for maintaining a copy of the blockchain ledger, propagating transactions, and validating new blocks. They collectively enforce the consensus rules by verifying that transactions and blocks adhere to protocol specifications, such as ensuring that transaction inputs are unspent and signatures are valid. This distributed validation mechanism is crucial for maintaining the trustless nature of the system, as no single node has authority over the ledger [13][54]. Miners, on the other hand, perform the specialized task of assembling transactions into candidate blocks and

attempting to solve the computational puzzle required for block creation, a process known as proof-of-work (PoW). The successful miner appends the new block to the blockchain and broadcasts it to the network, triggering nodes to independently verify the block's validity before accepting it into their local copy of the ledger. The reward structure incentivizes miners to participate honestly; they receive both newly minted bitcoins and transaction fees, which are distributed based on their contribution to block formation and validation [12][54]. The transaction ID (TXID), a hash encapsulating transaction data, is included in the block header, and multiple transactions can be aggregated within a single block, further optimizing throughput. The relationship between nodes and miners is underpinned by the sequential hashing of blocks, where each block references the hash of its predecessor, forming an immutable chain. This design ensures that consensus is not only about the content of individual blocks but also about their chronological order, as validated by the timestamps and hashes stored in each block header. Nodes validate the sequence of hashes and their associated timestamps, providing a robust mechanism for detecting tampering or reordering of blocks [13]. The collective validation by nodes, followed by the block creation process by miners, constitutes the backbone of transaction processing in Bitcoin. Scalability challenges arise as transaction volume increases, placing greater computational demands on both nodes and miners. To address these, parallel programming techniques can be leveraged to distribute transaction validation tasks across multiple processors, reducing bottlenecks and improving throughput. For example, cryptographic operations such as signature verification, which are computationally intensive, can be parallelized. The Chinese Remainder Theorem (CRT) offers further optimization by enabling efficient modular arithmetic, which is central to cryptographic validation. By applying CRT, miners and nodes can accelerate the verification of multiple signatures or modular exponentiations, thereby reducing block validation times and supporting higher transaction throughput within fixed block size constraints [55]. The workflow is further enhanced by the use of consensus algorithms that determine which node or miner is authorized to publish new blocks. In some blockchain systems, consensus engines are embedded within nodes, and transaction processors maintain a consistent copy of the ledger, ensuring that all nodes reach agreement on the current state of the blockchain. This approach supports the integration of various programming languages for

transaction processing, increasing the flexibility and extensibility of the network [2]. Additionally, the distribution of transaction fees and block rewards is managed by consensus among manager nodes, reflecting the level of participation and computational effort contributed by each miner [12]. In summary, nodes and miners operate in a tightly coupled workflow where nodes validate and propagate transactions, while miners aggregate and secure them through computational work. The interplay between these actors, supported by cryptographic techniques and consensus protocols, underpins the scalability and security of Bitcoin's transaction processing. Advances in parallelization and modular arithmetic, such as those enabled by CRT, hold promise for further enhancing the efficiency of this workflow, which is critical as blockchain applications expand into sectors requiring scalable and secure data management, including agriculture and healthcare [6][55].

4.2.3 Validation and Verification Steps

Validation and verification steps in Bitcoin transaction processing are essential to ensure both the correctness and security of the ledger. The process begins when a transaction is created and signed by the sender using their private key, after which it is broadcast to the network for verification. Each node in the network receives the transaction and participates in a consensus process or utilizes mechanisms such as smart contracts to confirm its validity. Only after the majority of nodes agree on the transaction's legitimacy, based on established rules, is the new block added to the blockchain, thereby updating the distributed ledger and completing the transaction process [22]. This distributed consensus mechanism underpins the trust and transparency that are characteristic of blockchain technology. The verification process involves several cryptographic operations, notably the use of digital signatures and public-key cryptography. Each transaction contains a unique digital signature, which is verified by other nodes using the sender's public key. This ensures that only the rightful owner of the funds can authorize a transaction, and any tampering with the transaction data would invalidate the signature. The chain of blocks is linked cryptographically, with each block referencing the hash of its predecessor, thereby preserving the integrity and immutability of the transaction history [4][22]. The use of cryptographic hashes and digital signatures not only secures the data but also enables

traceability and auditability, which are crucial for applications in sectors such as accounting and healthcare. The efficiency of these validation and verification steps is critical for system scalability, especially as transaction volumes increase. In the context of Bitcoin, the process of validating transactions and blocks is computationally intensive, particularly due to the modular arithmetic operations required for signature verification. Parallel programming techniques can be leveraged to distribute these computational tasks across multiple processors, thereby reducing the overall validation time. By decomposing the modular exponentiation and signature verification steps using the Chinese Remainder Theorem (CRT), it is possible to perform these calculations more efficiently. CRT allows large modular arithmetic operations to be broken down into smaller, independent computations that can be executed in parallel, significantly accelerating the cryptographic verification process. The adoption of parallelized validation workflows not only enhances throughput but also aligns with the need for scalable blockchain solutions in environments with heterogeneous computational resources, such as IoT networks. In such settings, validators may possess varying levels of computational capability. Systems that incorporate reputation-based schemes can dynamically allocate validation tasks, ensuring that more capable nodes handle a greater share of the workload, while less capable nodes contribute according to their capacity. This approach improves overall system performance and incentivizes honest participation by rewarding validators based on their contributions. The reputation scores, calculated from validators' voting behavior and transaction processing accuracy, are collectively signed and stored in reputation blocks, providing an additional layer of verification and accountability [15]. Transaction validation also involves updating the status of transactions in the ledger. When a transaction is created, it is initially recorded as unconfirmed, and the associated tokens are marked as unavailable for further use until the transaction is validated. Once confirmation is received, the transaction status is updated, and the tokens become available again. This two-stage process prevents double-spending and ensures that all nodes maintain a consistent view of the transaction history [38]. The use of unique transaction IDs, timestamps, and broadcast mechanisms further supports the integrity and traceability of transaction processing. In addition to the technical validation steps, membership services in blockchain networks manage privacy, confidentiality, and identity verification. These services are particularly important in

permissioned blockchains, where only authorized participants can validate transactions and access sensitive data. Identity verification is typically achieved through cryptographic signatures and public key infrastructure, ensuring that only legitimate actors participate in the network [4]. This is especially relevant for applications in healthcare and other regulated industries, where data privacy and compliance are paramount [20][56]. The verification steps are not limited to the technical validation of transactions but also extend to consensus mechanisms that determine the finality of blocks. In some blockchain systems, probabilistic consensus protocols such as Nakamoto consensus may lead to temporary inconsistencies, such as the inclusion and subsequent reversion of transactions. Sharded blockchains introduce additional complexity, as cross-shard transactions require careful coordination to prevent conflicting views among shards. Advanced consensus protocols and validation schemes are necessary to address these challenges and maintain the consistency and security of the ledger [41][57]. The integration of parallel programming and CRT-based modular arithmetic into the validation workflow represents a significant advancement in blockchain scalability. By reducing the computational bottlenecks associated with cryptographic verification, these techniques enable higher transaction throughput without compromising security. This is particularly important for supporting the growing demands of blockchain applications in sectors such as agriculture and healthcare, where scalable and secure data management solutions are essential [20][56][57].

4.3 Scalability Challenges in Bitcoin

4.3.1 Block Size Constraints

Block size constraints are a fundamental factor influencing Bitcoin's scalability and transaction throughput. Each block in the Bitcoin blockchain is limited by a maximum size, which restricts the number of transactions that can be included within a single block. This upper bound on block size was originally set to 1 MB, primarily as a security measure to prevent denial-of-service attacks and to ensure that the network remains decentralized by allowing a wide range of participants to validate blocks without requiring excessive computational resources. Over time, debates around scalability have led to contentious

forks, such as Bitcoin Cash, which increased the block size limit to 8 MB and later to 32 MB, while other cryptocurrencies have advocated for even larger blocks or the removal of block size limits altogether [58]. The imposition of block size limits directly impacts the process of transaction selection by miners. Given a finite block size, miners must employ strategies to determine which transactions to include. Typically, transactions offering higher fees are prioritized, as miners are incentivized to maximize their revenue. However, this introduces a trade-off: transactions with lower fees may experience significant delays, especially during periods of network congestion [38][58]. Wang et al. [38] outline that miners can adopt various strategies for transaction selection, such as prioritizing transactions that have waited the longest in the mempool or balancing between high-fee and no-fee transactions. The chosen strategy can influence network dynamics, affecting both user experience and overall throughput. Block size constraints also complicate the formation of optimal blocks. Dependencies between transactions, such as those where one transaction spends the output of another, require careful ordering within the block to maintain validity [58]. This adds computational complexity to the block assembly process, especially as the mempool grows during times of high demand. The need to respect both block size and dependency constraints can lead to suboptimal utilization of available block space, further limiting throughput. From a scalability perspective, the block size limit acts as a bottleneck for transaction processing capacity. As the number of users and transaction volume increases, the fixed block size can lead to longer confirmation times and higher transaction fees, as observed in periods of heightened network activity [12][58]. DeNio provides empirical data showing that Bitcoin processes between 3 and 7 transactions per second, with an average block time of 10 minutes and confirmation times often reaching 60 minutes for full settlement. In contrast, blockchains with larger or more flexible block size limits, such as Bitcoin Cash or Neo, achieve significantly higher throughput and faster confirmation times [12]. The challenge of block size constraints is further exacerbated by the need to maintain decentralization and security. Increasing the block size may improve throughput but can also raise the computational and storage requirements for running a full node, potentially reducing the number of participants capable of validating the blockchain independently [36][16]. Bunduchi [36] notes that the foundational principle of blockchain is to enable trustless transactions without reliance on centralized

intermediaries, which is only sustainable if network participation remains accessible. Peng et al. [16] highlight that decentralized consensus mechanisms must operate efficiently even as the network scales, and larger blocks can introduce latency and synchronization issues, especially in environments with imperfect information or high node mobility. In practical terms, the block size constraint necessitates innovations in transaction validation and block propagation. Parallel programming techniques and mathematical optimizations, such as the application of the Chinese Remainder Theorem to modular arithmetic, can accelerate cryptographic operations and transaction validation, partially mitigating the throughput limitations imposed by block size [38][58]. By distributing validation tasks across multiple processors, it becomes feasible to process more transactions within the same block interval, thereby improving overall system scalability without compromising the security or decentralization of the network. Block size constraints also have implications beyond cryptocurrency, affecting the adoption of blockchain in sectors like healthcare and agriculture, where large volumes of data and high transaction throughput are often required [36]. In these domains, the need for scalable, secure data management solutions underscores the importance of addressing block size limitations through both protocol-level changes and computational enhancements. Rahmadika and Rhee [40] emphasize that as blockchain applications expand to manage heterogeneous and sizable datasets, the underlying infrastructure must evolve to support these demands while maintaining privacy and security guarantees. In summary, block size constraints are a central challenge in Bitcoin's scalability, influencing transaction throughput, miner incentives, network decentralization, and the broader applicability of blockchain technology. Addressing these constraints requires a multifaceted approach, combining protocol adjustments, advanced computational techniques, and careful consideration of the trade-offs between scalability, security, and decentralization [36][16][38][12][58][40].

4.3.2 Transaction Throughput Limitations

Transaction throughput limitations are a fundamental constraint in Bitcoin's architecture, directly impacting its scalability and suitability for high-demand applications. The Bitcoin network is inherently limited in the number of transactions it can process per second due to several interrelated factors, including block size, block interval, consensus mechanism,

and the computational complexity of cryptographic validation. One of the primary bottlenecks arises from the fixed block size and the average time interval between blocks. Bitcoin's protocol restricts the block size to approximately 1 MB, and blocks are generated roughly every 10 minutes. This configuration results in a maximum throughput of about 7 transactions per second, which is significantly lower than traditional payment networks such as Visa, which can process up to 2000 transactions per second [22][50]. The authors of [59] indicate that the process of appending new blocks to the chain is governed by a consensus mechanism, specifically, proof-of-work (PoW), which, while ensuring security and immutability, imposes substantial computational overhead and limits how quickly new transactions can be confirmed. The cryptographic operations involved in transaction validation, notably digital signature verification and modular arithmetic, further contribute to latency. Each transaction must be validated by nodes across the distributed network, and this process is computationally intensive. As the blockchain grows, the validation workload increases, exacerbating throughput limitations [23]. According to [11], the validation process is facilitated by data structures such as the block index and the Unspent Transaction Output (UTxO) set, which help nodes efficiently locate and verify transaction data. However, even with these optimizations, the underlying sequential nature of block confirmation remains a limiting factor. Scalability challenges are compounded by the need for all nodes to reach consensus on the state of the blockchain. The duplication of the blockchain across thousands of nodes ensures transparency and security but also introduces latency, as each node must independently verify and propagate new blocks [59]. Yu et al. [50] state that achieving consistency among all nodes is inherently slow, leading to low transaction throughput. This is particularly problematic for public blockchains, where the number of participants and the volume of transactions can be very high [22]. Efforts to address these throughput limitations have led to the development of off-chain solutions and layer 2 protocols. For example, the Lightning Network enables off-chain transactions by establishing payment channels between users, allowing multiple transactions to occur without immediate on-chain confirmation. Only the final state of the channel is recorded on the blockchain, thereby increasing effective throughput. However, this approach is primarily suited for direct or routed payments between users and does not fully resolve the scalability challenge for all transaction types [50]. The limitations of transaction

throughput have broader implications for the adoption of blockchain technology in sectors such as agriculture and healthcare, where large volumes of data and high transaction rates are common. In healthcare, for instance, the storage of large files such as medical images is typically handled off-chain, with only references and content hashes stored on the blockchain to avoid overwhelming the network [56]. This hybrid approach highlights the necessity of scalable data management solutions that can accommodate both the security requirements of blockchain and the practical demands of high-throughput environments. Furthermore, the consensus mechanism itself introduces additional constraints. Proof-of-work, while effective in preventing malicious manipulation, is resource-intensive and slows down the rate at which transactions can be processed [23][10]. Alternative consensus algorithms, such as those based on Directed Acyclic Graphs (DAGs), have been explored for their potential to increase block generation throughput, but these approaches are not yet widely adopted in Bitcoin [16]. In summary, transaction throughput limitations in Bitcoin stem from a combination of protocol-level restrictions, computational complexity, and consensus requirements. These constraints not only affect the efficiency of transaction validation but also limit the broader applicability of blockchain technology in data-intensive sectors. Addressing these limitations requires both protocol-level innovations and the integration of parallel processing techniques to distribute validation workloads more effectively across multiple processors, as well as the exploration of mathematical optimizations such as the Chinese Remainder Theorem to accelerate cryptographic operations [11][50][59][22].

4.3.3 Trade-offs Between Security, Decentralization, and Efficiency

The trade-offs between security, decentralization, and efficiency are central to the scalability challenges faced by Bitcoin and similar blockchain systems. Security in blockchain networks is primarily maintained through consensus mechanisms such as Proof of Work (PoW), which require significant computational effort to validate transactions and append new blocks to the chain. This computational intensity enhances network security by making it prohibitively expensive for malicious actors to manipulate transaction histories. However, the same mechanisms that underpin security also introduce substantial inefficiencies, particularly in terms of energy consumption and transaction throughput. The

PoW protocol, for instance, is inherently time-consuming and resource-intensive, leading to scalability bottlenecks as transaction volumes increase [9]. Decentralization is another core property of blockchain systems, ensuring that no single entity has unilateral control over the network. Decentralization is achieved by distributing the validation and storage of transactions across a large number of independent nodes. While this approach increases resilience and trustworthiness, it also exacerbates efficiency challenges. Each node must independently verify transactions and maintain a full copy of the blockchain, which can result in redundant computations and significant communication overhead. The inefficiency is further compounded as the network grows, since consensus must be reached among a larger set of participants, leading to increased latency and reduced transaction throughput [40][46]. Efficiency, in the context of blockchain, refers to the ability to process and validate transactions rapidly and at scale. Achieving high efficiency often requires compromises in either security or decentralization. For example, reducing the number of validators or centralizing certain aspects of transaction processing can improve throughput, but at the cost of increased vulnerability to attacks or collusion. Conversely, maximizing decentralization and security by maintaining a fully distributed and robust consensus mechanism typically limits the system's capacity to handle large volumes of transactions in real time [9][41]. The interplay between these three properties can be conceptualized as a trade-off triangle, where improvements in one dimension often necessitate sacrifices in another. For instance, alternative consensus mechanisms such as Proof of Stake (PoS) and Delegated Proof of Stake (DPoS) have been proposed to address the inefficiencies of PoW. These mechanisms reduce computational overhead and energy consumption, thereby enhancing efficiency. However, they may introduce new security risks or reduce the degree of decentralization, depending on how validator selection and stake distribution are managed [9][46]. Han outlines that the design of shard allocation protocols for sharded blockchains also reflects these trade-offs, as increasing parallelism and throughput through sharding can introduce new attack vectors and coordination challenges. Parallel programming techniques and mathematical optimizations, such as the application of the Chinese Remainder Theorem (CRT) to modular arithmetic in cryptographic operations, offer promising avenues to mitigate some of these trade-offs. By distributing transaction validation tasks across multiple processors, it becomes possible to

reduce validation times and increase throughput without fundamentally altering the underlying consensus mechanism. However, integrating such techniques requires careful system design to ensure that gains in efficiency do not inadvertently compromise security or decentralization. For example, parallelizing cryptographic operations must be done in a manner that preserves the integrity and non-repudiation guarantees of the blockchain, and task distribution must avoid introducing single points of failure or centralized control [41][40]. The broader adoption of blockchain in sectors such as healthcare and agriculture further underscores the importance of balancing these trade-offs. In healthcare, for example, the need for secure and transparent data management is paramount, but solutions must also be scalable and interoperable to accommodate large volumes of sensitive data across diverse stakeholders. Blockchain-based systems in these domains often leverage hybrid architectures that combine on-chain and off-chain storage, smart contracts, and attribute-based encryption to balance security, decentralization, and efficiency [5][49][60]. These hybrid approaches illustrate that while no single architecture can optimize all three dimensions simultaneously, thoughtful integration of cryptographic, computational, and organizational innovations can yield practical solutions tailored to specific application requirements. The authors of [9] indicate that consensus algorithms are at the heart of these trade-offs, as their design choices directly impact the scalability, security, and decentralization of blockchain networks. According to [40], the structure of the blockchain, in which every node maintains a full replica of the ledger and participates in consensus, inherently limits scalability but is essential for maintaining trust and security in a decentralized environment. Kuo et al. [46] state that alternative blockchain protocols and architectures continue to emerge, each navigating the trade-off landscape in pursuit of more scalable, secure, and decentralized systems.

5 Computational Bottlenecks in Blockchain

5.1 Signature Verification Complexity

Signature verification stands as a central computational challenge in blockchain systems, particularly in Bitcoin, where every transaction must be validated cryptographically before

inclusion in a block. The complexity arises from the need to perform modular arithmetic operations, such as modular exponentiation and inversion, which are computationally intensive, especially when implemented serially. Each transaction includes a digital signature that must be verified against the sender's public key, ensuring authenticity and integrity. This process, when scaled to thousands of transactions per block, becomes a significant bottleneck for network throughput and latency [61][62]. The computational demand is further exacerbated by the consensus mechanism, which requires miners or validators to collectively verify all signatures within a block before it is appended to the chain. As transaction volume increases, the aggregate signature verification workload grows linearly, directly impacting transaction processing speed and waiting times. For instance, when user numbers rise, the transactions per second (TPS) may remain constant, but the waiting time for users can increase dramatically, from fractions of a second to several seconds or more, as observed in performance simulations. This latency is not only a function of block size and network propagation but is also tightly coupled to the efficiency of cryptographic operations. Parallel programming techniques offer a promising avenue to address these computational bottlenecks. By distributing signature verification tasks across multiple processors or threads, it is possible to significantly reduce the time required to validate a set of transactions. Increasing the number of miner threads, for example, has been shown to lower waiting times by more than a factor of three under transaction-saturated conditions, highlighting the scalability potential of parallelized validation [38]. However, this approach is bounded by hardware constraints and the underlying software architecture, which must efficiently manage task distribution and synchronization to avoid diminishing returns. The Chinese Remainder Theorem (CRT) provides a mathematical framework that can further accelerate modular arithmetic operations, which are at the core of signature verification. By decomposing large modular computations into smaller, parallelizable subproblems, CRT enables faster execution of cryptographic algorithms, particularly those based on RSA or similar schemes. This synergy between parallel programming and CRT can substantially reduce the computational overhead per transaction, allowing for higher throughput within existing block size and block time constraints. Despite these advances, the energy and resource consumption associated with large-scale signature verification remains a concern. The process of

verifying transactions, especially in proof-of-work blockchains, contributes to significant electricity usage and carbon emissions, as the network expends computational resources to maintain consensus and security [63]. The need to balance computational efficiency with environmental sustainability underscores the importance of optimizing signature verification algorithms and their implementation. In addition to the technical aspects, the complexity of signature verification has implications for broader blockchain applications. In sectors such as healthcare and supply chain management, where data authenticity and privacy are paramount, efficient and scalable signature verification is essential for real-time data sharing and auditability [24][23][10][62]. The use of advanced cryptographic techniques and parallelized computation ensures that these systems can handle large volumes of sensitive data without compromising security or performance. The authors of [61] indicate that, in practical scenarios, even a single confirmation may suffice for transaction finality due to the robustness of the underlying cryptographic protocols. However, the cumulative computational effort required to achieve this level of security across all transactions in a block remains substantial, reinforcing the need for continual optimization of signature verification processes. In summary, signature verification complexity is a key factor limiting the scalability of blockchain systems. Leveraging parallel programming and mathematical optimizations such as CRT can mitigate these limitations, enabling higher transaction throughput and reduced latency. These improvements are critical not only for cryptocurrency networks but also for the adoption of blockchain in diverse domains requiring secure, scalable, and efficient data management [38][61][63][62].

5.2 Input and Output Validation Overhead

Input and output validation overhead constitutes a significant computational bottleneck in blockchain systems, particularly in the context of transaction processing and consensus mechanisms. In Bitcoin and similar blockchains, every transaction must undergo rigorous validation to ensure the correctness of both its inputs and outputs. This process involves verifying digital signatures, checking the availability and authenticity of unspent transaction outputs (UTXOs), and ensuring that the sum of inputs matches the sum of

outputs, thereby preventing double-spending and maintaining the integrity of the ledger [64]. The validation of transaction inputs typically requires cryptographic operations, such as elliptic curve digital signature algorithm (ECDSA) verifications, which are computationally expensive. As transaction throughput increases, the cumulative cost of these cryptographic checks can become a limiting factor for scalability. The output validation, on the other hand, involves updating the state of the UTXO set, which is a dynamic data structure that must be efficiently queried and modified as new transactions are processed. Inefficient handling of this data structure can lead to increased latency and resource consumption, especially as the blockchain grows in size [14]. Parallel programming techniques offer a promising approach to mitigating these overheads. By distributing the validation workload across multiple processors, it is possible to process multiple transactions or even multiple inputs and outputs within a single transaction concurrently. This parallelization can significantly reduce the wall-clock time required for validation, provided that dependencies between transactions are properly managed to avoid race conditions and ensure consistency. The Chinese Remainder Theorem (CRT) can further accelerate modular arithmetic operations, which are central to cryptographic validation, by decomposing large modular exponentiations into smaller, independent computations. This decomposition aligns well with parallel execution models, allowing for more efficient utilization of computational resources. However, the benefits of parallelization and CRT-based optimizations are constrained by the need for synchronization and atomicity in state updates. For example, when multiple processors attempt to update the UTXO set simultaneously, careful coordination is required to prevent inconsistencies or double-spending. Techniques such as sharding, where the blockchain state is partitioned into independent subsets processed in parallel, can help alleviate these issues by reducing contention and enabling higher throughput. In sharded systems, validators are divided into groups, each responsible for a subset of transactions, which allows input and output validation to proceed in parallel across shards, further reducing overhead. The overhead associated with input and output validation is not limited to computational costs; it also encompasses storage and network overheads. Each validator must maintain a copy of the relevant state, such as the UTXO set or account balances, and synchronize updates with other nodes in the network. As the blockchain scales, the volume

of data that must be stored, transmitted, and validated increases, placing additional demands on system resources [15]. Simulation frameworks, such as those described in [38], can be instrumental in evaluating the impact of different validation strategies and identifying bottlenecks under various network conditions. Beyond financial applications, the validation overhead becomes even more pronounced in domains such as healthcare and agriculture, where blockchain is used to manage sensitive and heterogeneous data. In these contexts, input validation may involve verifying the authenticity and integrity of medical records or agricultural supply chain data, while output validation ensures that only authorized entities can update or access the data [65][64][45]. The complexity and diversity of data types in these sectors necessitate flexible and efficient validation mechanisms that can scale with the volume and variety of transactions [65][45]. The authors of [10] indicate that the tamper-proof nature of blockchain, achieved through distributed consensus and cryptographic validation, is essential for ensuring data integrity. However, this security comes at the cost of increased validation overhead, which must be carefully managed to maintain system performance. In practice, hybrid approaches that combine blockchain with traditional database systems have been proposed to leverage the efficiency of conventional storage and querying while retaining the security guarantees of blockchain for critical validation steps [45][60]. This integration can help mitigate some of the storage and computational overheads associated with input and output validation, especially in large-scale deployments. Regulatory and educational challenges also play a role in shaping the landscape of validation overhead. As highlighted in, inadequate understanding of blockchain technology among stakeholders can lead to suboptimal system designs that exacerbate validation bottlenecks. Ongoing research and development efforts are needed to develop more efficient validation algorithms, improve parallelization strategies, and educate practitioners on best practices for scalable blockchain implementation [13][14]. In summary, input and output validation overhead is a multifaceted challenge that impacts the scalability, security, and efficiency of blockchain systems. Advances in parallel programming, modular arithmetic optimizations such as CRT, and sharding techniques offer viable pathways to reducing this overhead. Nevertheless, careful system design, informed by empirical analysis and domain-specific requirements,

remains crucial for achieving scalable and secure blockchain solutions across diverse application domains [15][65][38].

5.3 Resource Utilization in Node Operations

Resource utilization in node operations is a central factor influencing the computational efficiency and scalability of blockchain networks. Each node in a blockchain system is responsible for a series of resource-intensive tasks, such as transaction validation, block construction, consensus participation, and data storage. The process of validating transactions and constructing blocks, particularly in proof-of-work (PoW) systems like Bitcoin, demands significant computational resources due to the cryptographic puzzles that must be solved to append new blocks to the chain. This competition among miners for block creation results in a continuous consumption of CPU cycles and energy, with the average network output being one block every ten minutes, as described by Vallois et al. [11]. The structure of blocks and the mechanisms for transaction validation further impact resource consumption. Each block contains multiple transactions, and the validation of these transactions involves verifying digital signatures, checking transaction histories, and ensuring that no double-spending occurs. The cryptographic operations underlying these processes, such as modular exponentiation and hashing, are computationally expensive and can become bottlenecks when transaction throughput increases [26][11]. The use of parallel programming techniques and mathematical optimizations, such as the Chinese Remainder Theorem (CRT), presents an opportunity to distribute these validation tasks across multiple processors, thereby reducing individual node workload and improving overall throughput. In consortium blockchains, for example, the difficulty coefficient for block creation is kept stable to reduce the time interval for appending new blocks, and nodes collaborate to validate signatures and broadcast results, which can help balance resource utilization [30]. Beyond computational power, nodes must also manage storage resources efficiently. As the blockchain grows, each node is required to store an ever-increasing ledger, which includes all historical transactions and blocks. This storage requirement can become a limiting factor for node participation, particularly for lightweight or resource-constrained devices. The tamper-resistance of blockchain,

achieved through cryptographic linkage between blocks and consensus algorithms, ensures data integrity but also necessitates that every node maintains a complete or partial copy of the ledger, further increasing storage demands [16]. Network bandwidth is another crucial resource in node operations. The propagation of new blocks and transactions across the network requires reliable and high-throughput communication channels. Synchronization between nodes, especially in systems where updates are batched and broadcasted, can lead to temporary spikes in bandwidth usage [11]. In scenarios involving sharding or cross-shard communication, as discussed by Han [41], the challenge of achieving agreement between disjoint sets of information can exacerbate resource contention, requiring additional protocols to ensure consistency and fairness. Resource utilization is also shaped by the diversity of roles that nodes may assume within a blockchain ecosystem. Zhao et al. highlight that in supply chain and financial applications, organizations may participate in consensus, transaction management, or ledger maintenance, each with distinct computational and storage requirements. The presence of malicious actors, such as those executing clogging attacks by broadcasting high-fee, computationally demanding transactions, can further strain node resources and hinder the timely processing of legitimate transactions [55]. In specialized applications, such as healthcare and IoT, blockchain nodes must handle sensitive data with heightened security requirements. The use of attribute-based signature schemes and encryption mechanisms, as described by Thwin and Vasupongayya, increases the computational overhead for each validation task. However, these measures are essential for ensuring data privacy and integrity, particularly when nodes are responsible for managing grouped user information in single blocks [26]. In healthcare, the need for scalable and secure data management solutions is underscored by the growing volume and sensitivity of electronic health data, necessitating further research into best practices for resource allocation and optimization [66]. The efficiency of resource utilization in node operations is not only a technical concern but also has broader implications for the scalability and adoption of blockchain technology in various sectors. For instance, in business and insurance, blockchain can reduce errors and operational costs by managing records with encryption and automating verification processes, but only if node operations remain efficient and scalable [53]. In vehicular networks and UAV ad hoc networks, lightweight and permissioned blockchain approaches are being explored to

balance the need for security with the constraints of limited computational and storage resources [16]. In summary, resource utilization in node operations is a multifaceted challenge encompassing computational, storage, and network resources. Optimizing these aspects through parallelization, mathematical techniques like CRT, and tailored consensus mechanisms is essential for overcoming computational bottlenecks and enabling scalable, secure blockchain applications across diverse domains [26][55][53][11][66][30][16][41].

5.4 Impact on Network Performance

The impact of integrating parallel programming techniques and the Chinese Remainder Theorem (CRT) on network performance in blockchain systems, particularly Bitcoin, is multifaceted and substantial. At the core of Bitcoin's computational bottlenecks lies the intensive cryptographic validation required for each transaction, which is inherently modular and thus well-suited for decomposition via CRT. By distributing these modular arithmetic operations across multiple processors, the system can achieve significant reductions in transaction validation latency, directly enhancing throughput within the constraints of existing block size limits [67][12]. Parallelization of transaction validation tasks addresses the sequential bottleneck present in traditional blockchain architectures. In the standard Bitcoin protocol, miners and validating nodes must process transactions in a largely serial fashion, leading to delays as the network scales and transaction volume increases [68][43]. The application of parallel computing, as discussed by DeNio et al., enables the simultaneous execution of cryptographic operations, thereby reducing the average confirmation time for transactions. This improvement is not merely theoretical; the addition of computational nodes to the network can linearly or even superlinearly decrease the time required for block validation, depending on the efficiency of task distribution and inter-node communication [12]. The CRT further amplifies these gains by optimizing modular exponentiation, a key operation in digital signature verification. CRT allows for the decomposition of large modular computations into several smaller, independent computations, each of which can be executed concurrently. Maharani et al. illustrate real-world applications of CRT in scenarios where modular arithmetic is central, demonstrating that such decomposition can lead to near-linear scaling of computational

efficiency as the number of processors increases. When applied to Bitcoin, this means that the cryptographic workload associated with transaction validation can be distributed efficiently, leading to a marked improvement in network responsiveness and capacity [67][12]. The reduction in validation time has a direct effect on network performance metrics such as transaction throughput and latency. As more transactions can be validated and included in blocks within a given time frame, the network can support higher transaction volumes without necessitating an increase in block size, which would otherwise exacerbate issues related to propagation delay and storage requirements. Melo et al. [17] highlight that transaction patterns with efficient storage and computational characteristics, such as splitting patterns, benefit disproportionately from parallelized validation, further enhancing overall network efficiency. Moreover, the scalability benefits extend beyond mere transaction throughput. By lowering the computational barrier to participation, parallelized and CRT-optimized validation enables resource-constrained devices, such as those in IoT networks, to participate as full or partial nodes [50][12]. Yu et al. [50] describe how separating storage and computation roles in blockchain architectures allows lightweight devices to contribute to mining and validation, increasing the degree of decentralization and robustness of the network. This democratization of participation not only improves resilience but also distributes the computational load more evenly, reducing the risk of centralization and single points of failure [43][12]. However, these enhancements are not without trade-offs. The increased complexity of managing parallel processes and ensuring consistency across distributed computations introduces new challenges in synchronization and consensus. Tyagi [68] notes that consensus protocols such as Proof of Work (PoW) and Proof of Stake (PoS) must be adapted to accommodate the parallel execution of validation tasks, ensuring that the integrity and order of transactions are preserved. Furthermore, the immutability and consensus requirements inherent in blockchain systems can introduce latency, as updates to the distributed ledger must be validated by a majority of nodes, potentially offsetting some of the gains from parallelization if not carefully managed [23]. In sectors such as healthcare and agriculture, where secure and scalable data management is critical, the improvements in network performance enabled by parallel programming and CRT are particularly valuable. Ilinca [39] and Kumar et al. [8] emphasize that blockchain's ability to provide trustless,

transparent, and efficient data sharing is contingent on overcoming computational bottlenecks. By accelerating transaction validation and reducing reliance on intermediaries, these techniques make blockchain solutions more viable for real-time, high-volume applications in these domains [39][8]. The integration of parallel programming and CRT thus represents a significant advancement in addressing the computational challenges that limit blockchain scalability and performance. By enabling faster, more efficient transaction validation, these methods enhance the network's ability to handle increased demand, support broader participation, and maintain the security and integrity essential to blockchain's value proposition [67][50][17][12].

6 Parallel Programming for Blockchain Scalability

6.1 Principles of Parallel Computing

Parallel computing is a computational paradigm that enables the simultaneous execution of multiple processes or threads to solve complex problems more efficiently. At its core, parallel computing leverages the concurrent use of multiple processing elements, such as CPUs or cores, to divide large computational tasks into smaller, independent subtasks. These subtasks are processed in parallel, which can dramatically reduce the overall execution time compared to sequential processing. In the context of blockchain technology, this approach is especially relevant due to the computationally intensive nature of cryptographic operations and transaction validation, which are fundamental to maintaining the integrity and security of distributed ledgers. The fundamental principle behind parallel computing is task decomposition. A large problem is split into discrete units of work that can be executed independently. This decomposition can be data-driven, where the same operation is performed on different pieces of data, or task-driven, where different operations are performed concurrently. In blockchain systems, data parallelism is particularly useful, as transaction validation and cryptographic signature verification for multiple transactions can be performed independently and thus processed in parallel [12]. This is especially advantageous for blockchains like Bitcoin, where each transaction's cryptographic verification is independent of others within the same block. Parallel

computing architectures are generally classified into shared memory and distributed memory systems. In shared memory systems, multiple processors access a common memory space, facilitating rapid communication between processes. In distributed memory systems, each processor has its own local memory, and communication occurs via message passing. Blockchain networks, by their very nature, are distributed systems, and thus the principles of distributed parallel computing are highly applicable. Each node in the network can independently validate transactions and blocks, contributing to the overall throughput and resilience of the system [38][37]. The efficiency of parallel computing in blockchain applications is further enhanced by the use of advanced algorithms and mathematical techniques. For instance, cryptographic operations such as modular exponentiation and digital signature verification, which are computational bottlenecks in transaction validation, can be optimized using mathematical constructs like the Chinese Remainder Theorem (CRT). By applying CRT, modular arithmetic calculations can be decomposed into smaller, parallelizable computations, significantly reducing the time required for cryptographic verification. This synergy between parallel programming and mathematical optimization is crucial for scaling blockchain systems to handle higher transaction volumes without compromising security or decentralization. Scalability is a persistent challenge in blockchain networks, as increasing the number of transactions per second often leads to higher computational demands. Parallel computing addresses this by enabling the network to process more transactions concurrently. As new nodes join the network, the available computational resources increase, allowing for greater parallelism and improved performance [12]. This is particularly relevant for decentralized systems, where there is no central authority to manage resources, and each node operates autonomously yet collaboratively to maintain the ledger [38][37][12]. The collective maintenance of data blocks by all nodes in a blockchain network exemplifies the distributed and parallel nature of these systems. The loss or failure of individual nodes does not compromise the system's operation, as other nodes continue to process transactions and maintain the ledger. This redundancy, combined with parallel processing, enhances both the reliability and scalability of blockchain technology [38][37]. Furthermore, the open-source nature of many blockchain platforms encourages the development and integration of parallel computing techniques, as researchers and

developers can collaboratively optimize code for concurrent execution [38][37]. In scientific and educational applications, parallel computing principles facilitate the analysis of transaction patterns and network behavior, enabling the development and optimization of new protocols [69]. By modeling and simulating blockchain systems using parallel algorithms, researchers can gain insights into system performance, security vulnerabilities, and scalability limits. This iterative process of analysis and optimization is essential for advancing the capabilities of blockchain technology in diverse domains, including agriculture and healthcare, where secure and scalable data management solutions are increasingly in demand [70][71]. The integration of parallel computing into blockchain protocols not only improves transaction throughput but also addresses several security vulnerabilities inherent in traditional, sequential systems. By distributing computational tasks across multiple processors and nodes, the system becomes more resilient to targeted attacks and single points of failure [12][38]. This distributed approach aligns with the core philosophy of blockchain, which is to eliminate centralized control and enable trustless, decentralized consensus among participants [71][70]. In summary, the principles of parallel computing, task decomposition, concurrent execution, and distributed processing, are highly synergistic with the architecture and goals of blockchain systems. By leveraging these principles, blockchain networks can achieve greater scalability, efficiency, and security, paving the way for broader adoption and innovative applications across various sectors [12][38][37][69].

6.2 Parallelization Strategies in Transaction Validation

6.2.1 Multithreading Approaches

Multithreading approaches have become increasingly significant in the context of blockchain scalability, particularly for transaction validation processes that are computationally intensive. By leveraging parallel execution, multithreading enables the distribution of cryptographic verification and modular arithmetic tasks across multiple processor cores, thus reducing the overall latency associated with transaction confirmation. This is especially relevant for blockchains such as Bitcoin, where the validation of digital signatures and the verification of transaction inputs and outputs are

critical bottlenecks in achieving higher throughput [15][38]. The validation of transactions in Bitcoin and similar blockchains typically involves the verification of cryptographic signatures, which is a process well-suited to parallelization. Each transaction within a block can be validated independently, allowing for concurrent processing. This independence aligns with the unspent transaction output (UTXO) model, where each input references a previous output, and the validation of each input does not depend on the outcome of others within the same block [17]. By assigning separate threads to validate different transactions or even different inputs within a transaction, the system can exploit modern multicore architectures to achieve substantial speedup. Wang et al. indicate that increasing the number of miners, which can be interpreted as increasing the number of parallel validation agents, leads to a stable network performance and enhances security through greater decentralization. This observation supports the notion that multithreading not only improves throughput but also contributes to the robustness and reliability of the network. However, the benefits of multithreading are most pronounced when the number of users exceeds the number of miners, ensuring that computational resources are effectively utilized [38]. In practical implementations, thread management and synchronization become crucial. The assignment of validation tasks to threads must avoid contention for shared resources, such as the global state or mempool, to prevent race conditions and ensure consistency. Efficient scheduling algorithms and lock-free data structures can mitigate these challenges, allowing threads to operate on disjoint subsets of transactions or UTXOs. Furthermore, the use of thread pools and work-stealing schedulers can dynamically balance the workload, adapting to fluctuations in transaction volume and network conditions. The application of multithreading is not limited to transaction validation alone. In advanced blockchain architectures, such as those employing sharding or directed acyclic graphs (DAGs), multithreading plays a critical role in processing transactions across multiple shards or branches simultaneously [15][38]. For instance, in sharded blockchains, each shard can be assigned to a separate thread or group of threads, enabling parallel validation and consensus within each shard. This approach significantly enhances throughput and reduces user-perceived latency, as demonstrated by empirical measurements of transaction confirmation times under varying shard sizes [15]. Moreover, the integration of multithreading with cryptographic optimizations, such as the Chinese

Remainder Theorem (CRT) for modular arithmetic, can further accelerate signature verification and other cryptographic operations. By decomposing large modular exponentiations into smaller, independent computations, CRT enables the parallel execution of arithmetic operations, which can be mapped directly onto multiple threads. This synergy between algorithmic and architectural parallelism is essential for scaling blockchain systems without compromising security or decentralization [17][38]. The adoption of multithreading approaches also has implications for broader blockchain applications beyond cryptocurrency. In sectors such as healthcare and supply chain management, where data privacy and real-time processing are paramount, multithreaded validation can support high transaction volumes and stringent latency requirements [72][22][73]. For example, in healthcare data sharing scenarios, parallel validation ensures that sensitive information is processed efficiently and securely, facilitating compliance with regulatory standards and enabling scalable data governance [72][54][73]. In summary, multithreading approaches constitute a foundational strategy for enhancing blockchain scalability. By distributing validation workloads across multiple processors, blockchains can achieve higher throughput, reduced latency, and improved security. The effectiveness of these approaches depends on careful thread management, synchronization, and the integration of algorithmic techniques such as CRT, all of which are critical for meeting the demands of modern blockchain applications [15][72][22][38].

6.2.2 GPU and CPU Parallelism

GPU and CPU parallelism are central to enhancing the scalability of blockchain transaction validation, particularly when cryptographic operations dominate computational workloads. The validation of transactions in Bitcoin and similar blockchains involves intensive modular arithmetic, digital signature verification, and hashing, all of which are amenable to parallelization due to their mathematical independence across transactions. By leveraging both CPU and GPU architectures, it is possible to distribute these computational tasks efficiently, thereby reducing overall validation latency and increasing throughput within the constraints of block size and network propagation [12]. Modern CPUs offer multiple cores and support for simultaneous multithreading, allowing for concurrent execution of transaction validation routines. This enables the partitioning of the

mempool or incoming transaction set into subsets that can be processed independently. Each core can execute cryptographic verification, such as ECDSA signature checks, on a different transaction, thus achieving a linear speedup with respect to the number of available cores, provided that memory bandwidth and cache coherence are not limiting factors [43][49]. Furthermore, virtualization technologies further enhance this flexibility by abstracting physical resources, allowing for dynamic allocation of CPU cores to validation tasks as transaction loads fluctuate [43]. GPUs, with their massively parallel architecture, are particularly well-suited for accelerating cryptographic primitives and hash computations. Unlike CPUs, which are optimized for low-latency execution of complex control flows, GPUs excel at executing the same operation across large datasets in parallel, a property known as Single Instruction, Multiple Data (SIMD). In the context of blockchain, this means that thousands of transactions can have their signatures or hashes computed simultaneously, dramatically reducing the time required for block validation [12][49]. The use of GPU acceleration is especially beneficial when combined with mathematical optimizations such as the Chinese Remainder Theorem (CRT), which can further reduce the computational complexity of modular exponentiation and inversion operations that are prevalent in cryptographic algorithms. The integration of parallel programming models, such as OpenMP for CPUs and CUDA or OpenCL for GPUs, allows developers to explicitly define parallel regions in code, ensuring that transaction validation tasks are efficiently mapped to available hardware resources. This approach not only improves throughput but also enhances the system's ability to handle peak loads, such as during periods of high transaction volume [12][49]. The scalability of such parallelized validation frameworks is evident in experimental results, where parallel mining and transaction processing architectures demonstrate linear or near-linear improvements in processing rates as the number of processing units increases [12][49]. However, the effective utilization of GPU and CPU parallelism in blockchain systems is not without challenges. Load balancing between heterogeneous resources, synchronization overhead, and the need to maintain consistency across parallel validation threads must be carefully managed to avoid bottlenecks and ensure correctness. Additionally, the memory footprint of maintaining large transaction pools and block data can become significant, necessitating efficient memory management strategies and potentially the offloading of certain storage tasks to

specialized nodes or distributed file systems [50][49]. The authors of Nguyen et al. indicate that scalability remains a critical concern in e-health and other data-intensive blockchain applications, underscoring the necessity of robust parallelization strategies to support collaborative environments involving multiple providers and high transaction volumes. The ability to scale validation throughput through parallelism is thus not only a technical optimization but also a foundational requirement for the adoption of blockchain in sectors demanding secure, high-throughput data management. In summary, the combination of CPU and GPU parallelism, supported by virtualization and advanced programming models, provides a powerful toolkit for addressing the scalability limitations of blockchain transaction validation. These strategies, when integrated with mathematical optimizations like CRT, enable significant reductions in validation time and support the broader goal of deploying blockchain solutions in complex, high-volume environments such as healthcare and agriculture [34][12][43][49].

6.2.3 Distributed Computing Models

Distributed computing models are fundamental to enhancing the scalability of blockchain systems, particularly in the context of transaction validation. In decentralized networks such as Bitcoin, the validation process is inherently distributed, relying on multiple nodes to verify and record transactions. This distributed nature ensures that no single entity controls the ledger, and consensus is achieved through mechanisms that coordinate the efforts of independent validators [64]. The effectiveness of these models depends on the ability of the network to synchronize transaction ordering and maintain consistency across all participating nodes. A key challenge in distributed blockchain systems is the need for consensus among miners regarding the order and validity of transactions. Without proper coordination, divergent copies of the blockchain may emerge, resulting in forks that threaten the integrity and uniformity of the ledger. To address this, blockchains employ distributed consensus mechanisms, such as proof-of-work (PoW), which require nodes to solve computational puzzles before appending new blocks. The use of cryptographic hash functions, such as SHA-256, ensures that the solution to these puzzles can be easily verified by other nodes, promoting trust and transparency within the network [74]. The first miner to solve the puzzle broadcasts the new block, and the network adopts it as the latest

addition to the chain. In cases where two blocks are validated simultaneously, the network resolves the conflict by extending the chain with the most accumulated work, discarding the other as an orphan block [61]. Parallelization within distributed computing models can further accelerate transaction validation. By distributing cryptographic operations and modular arithmetic tasks across multiple processors, the network can handle higher transaction volumes without exceeding block size limitations. For example, the Chinese Remainder Theorem (CRT) can be leveraged to optimize modular computations, allowing for the decomposition of large arithmetic operations into smaller, parallelizable tasks. This approach reduces the computational burden on individual nodes and shortens validation times, directly contributing to increased throughput. The significance of throughput and latency becomes especially pronounced as transaction volumes rise. Systems designed with parallel and distributed architectures demonstrate improved scalability, as evidenced by comparative analyses of throughput and latency across different blockchain configurations [6]. The structure of distributed blockchains can vary based on access permissions and governance. Public blockchains are fully decentralized, permitting any participant to join, read, and write data, with transaction validation open to all. This model supports public verifiability and transparency, but may encounter scalability constraints as the network grows [22][71]. In contrast, private and consortium blockchains restrict access to selected entities or groups, allowing for more controlled and efficient consensus processes. Consortium blockchains, in particular, blend features of public and private models, with consensus governed by a predefined set of participants rather than open competition [23][71]. The choice of distributed model influences the parallelization strategies that can be employed, as permissioned systems may support more centralized scheduling of validation tasks, while permissionless systems require robust mechanisms to prevent double-spending and ensure fairness [64][23]. Traceability and data integrity are additional benefits of distributed computing in blockchain. Each block is cryptographically linked to its predecessor, preserving the order of transactions and enabling real-time tracking of data changes. This structure not only enhances transparency but also reduces the need for reconciliation across multiple ledgers, streamlining operations in sectors such as accounting, agriculture, and healthcare [22]. The ability to maintain a tamper-evident record of transactions is crucial for applications that demand high levels of trust and

auditability. As transaction volumes increase, distributed computing models must also contend with network congestion and scalability bottlenecks. For instance, the Bitcoin network has experienced periods of congestion, leading to delays and increased transaction fees [18][51]. These challenges underscore the need for advanced parallelization strategies and distributed architectures that can dynamically adapt to changing workloads. The integration of efficient consensus mechanisms, optimized cryptographic operations, and scalable network protocols is essential for sustaining performance as blockchain adoption expands across diverse industries. In summary, distributed computing models underpin the scalability and security of blockchain systems by enabling parallel transaction validation, robust consensus, and transparent data management. The interplay between consensus mechanisms, cryptographic techniques, and network architecture determines the efficiency and resilience of these systems, with ongoing research focused on refining these models to support the evolving demands of real-world applications [64][74][22][23][18][51][71][61][6].

6.3 Challenges in Parallelizing Blockchain Operations

6.3.1 Synchronization and Consistency

Synchronization and consistency are fundamental concerns when parallelizing blockchain operations, particularly in the context of transaction validation and cryptographic computations. The distributed nature of blockchain systems, where each node maintains a copy of the entire ledger, inherently demands mechanisms to ensure that all nodes reach agreement on the state of the blockchain even as operations are executed in parallel [16][64]. This requirement is intensified when leveraging parallel programming techniques, as concurrent execution can introduce race conditions, data inconsistency, and synchronization overhead. In blockchains such as Bitcoin, every node is responsible for validating transactions and blocks, and the integrity of the system depends on the ability of nodes to independently verify the same sequence of events. The authors of [16] indicate that decentralization is achieved by having multiple nodes participate in a peer-to-peer network, with no central authority managing the process. This architecture necessitates robust synchronization protocols to maintain a consistent state across all nodes, especially

when validation tasks are distributed among multiple processors. Parallelizing cryptographic operations, such as those involving the Secure Hash Algorithm (SHA-256) or Elliptic Curve Digital Signature Algorithm (ECDSA), can accelerate transaction validation [64][47]. However, the challenge arises in ensuring that parallel computations do not lead to divergent states among nodes. For instance, when multiple processors validate different sets of transactions simultaneously, there must be a mechanism to guarantee that the order of transactions and the resulting state transitions remain consistent across the network. This is critical to prevent issues such as double-spending, where two conflicting transactions could be validated in parallel and erroneously accepted [64][47]. Consensus algorithms play a central role in addressing synchronization and consistency. In systems like Bitcoin, proof-of-work (PoW) ensures that only one block is appended to the chain at a time, providing a natural serialization point for state updates [12][40]. Even when transaction validation is parallelized, the final inclusion of transactions into a block and the subsequent block addition to the chain are strictly ordered. This serialization is enforced by cryptographic hashes linking blocks in chronological order, making the ledger tamper-resistant and unforgeable [16][64]. Each node can independently verify the sequence of blocks and transactions, ensuring that all honest nodes converge on the same state [46][40]. The use of parallel programming introduces additional synchronization overhead, as processors must coordinate to avoid conflicts and ensure data integrity. For example, when applying the Chinese Remainder Theorem (CRT) to modular arithmetic in cryptographic operations, intermediate results computed in parallel must be combined in a manner that preserves correctness. Any inconsistency in the combination of results could compromise the validity of transaction signatures or block hashes, undermining trust in the system [64][47]. Moreover, the challenge of synchronization extends to sharded blockchain architectures, where the ledger is partitioned into multiple shards, each processed in parallel. Huang outlines that communication and coordination among shards are necessary to maintain global consistency, particularly when transactions span multiple shards [15]. The complexity of achieving consensus across shards increases with the degree of parallelism, as cross-shard transactions require careful synchronization to prevent inconsistencies. From a broader perspective, the need for synchronization and consistency is not limited to financial transactions. In applications such as healthcare and agriculture,

where blockchain is used for secure data management, maintaining a consistent and synchronized ledger is essential for data integrity and auditability [5][2]. Any lapse in synchronization could result in data discrepancies, potentially affecting critical operations such as disease surveillance or supply chain tracking. In summary, while parallel programming and the application of mathematical techniques like CRT can enhance the scalability of blockchain systems by accelerating transaction validation, they also introduce significant challenges in synchronization and consistency. Addressing these challenges requires a combination of robust consensus algorithms, careful coordination of parallel tasks, and cryptographic guarantees to ensure that all nodes maintain a consistent and trustworthy view of the blockchain state [16][15][64].

6.3.2 Security Considerations

Security considerations are central when introducing parallel programming techniques into blockchain systems, particularly for transaction validation and cryptographic operations. The immutability and tamper-evidence of blockchains fundamentally depend on the integrity of cryptographic primitives such as hash functions and digital signatures. In Bitcoin, for instance, the use of the secp256k1 elliptic curve for key generation and the chaining of blocks through cryptographic hashes ensure that altering a single transaction would necessitate recalculating all subsequent block hashes, making unauthorized modifications computationally infeasible [44]. When validation tasks are distributed across multiple processors, as in parallel programming approaches, it is essential to guarantee that this distribution does not introduce inconsistencies or vulnerabilities in the cryptographic workflow. A primary challenge arises from the need to maintain consensus and prevent double-spending or fork creation during concurrent transaction validation. If multiple processors validate transactions in parallel without proper synchronization, there is a risk that conflicting transactions could be included in the same block or that the order of transactions could be manipulated, undermining the deterministic nature of block addition and potentially enabling attacks such as double-spending. Yu et al. [50] state that deterministic block ordering and the use of Byzantine agreement protocols are crucial to avoid forks and ensure that all nodes append the same block to their chain, even when validation is parallelized. Another significant consideration is the management of shared

data structures, such as the mempool and the UTXO set, when multiple threads or processes operate concurrently. Race conditions or improper locking mechanisms could lead to inconsistencies, where some transactions are validated against outdated states or where the same UTXO is spent more than once. This is particularly relevant in the context of the UTXO model, which, while offering transparency and traceability, incurs higher storage overhead and complexity in state management compared to the account model [17]. The risk of inconsistent state updates is amplified in parallel environments, necessitating robust synchronization protocols. The application of the Chinese Remainder Theorem (CRT) to accelerate modular arithmetic in cryptographic operations introduces further security implications. While CRT can significantly reduce computation times for operations like RSA signature verification, improper implementation may expose the system to side-channel attacks or fault injection vulnerabilities. For example, if an attacker can induce faults in one of the parallelized modular exponentiations, they may be able to reconstruct private keys using mathematical techniques that exploit the CRT structure. Therefore, secure CRT-based implementations must incorporate countermeasures such as constant-time algorithms and error detection mechanisms to mitigate these risks. Parallelization also impacts consensus protocols, especially those relying on Proof-of-Work (PoW) or hybrid approaches. In PoW systems, increasing the number of nodes and enabling parallel mining can enhance network throughput and reduce block times, but it may also alter the dynamics of block propagation and fork resolution. DeNio [12] demonstrates that while parallel mining reduces the average time to solve blocks, it is essential to coordinate backup and active managers to prevent unauthorized block acceptance and to maintain system security. Similarly, in consensus protocols that utilize voting or committee-based approaches, parallel execution must be carefully orchestrated to avoid inconsistencies in block proposals and to ensure that only valid blocks are appended to the chain [50]. The transparency and auditability of blockchain systems are often cited as security advantages, but parallelization can complicate these properties if not managed correctly. For example, if transaction validation is distributed across multiple processors without a unified logging or auditing mechanism, it may become challenging to trace the origin of errors or to verify the correctness of the validation process. This is particularly relevant in sectors such as healthcare, where the confidentiality, integrity, and

auditability of patient records are paramount [29][73]. Mayer et al. [29] indicate that decentralized systems can enhance security and privacy, but only if interoperability and coordinated data management are maintained, requirements that become more complex in parallelized environments. Moreover, the introduction of parallelism must not compromise the security guarantees of the consensus mechanism. In simulations of blockchain networks, it is often assumed that all miners are honest and that transaction selection is based on fee maximization. However, in real-world deployments, adversarial behavior such as selfish mining or transaction censorship can exploit parallel execution paths if proper safeguards are not in place. Wang [38] emphasizes the importance of simulating and analyzing network behavior under various scenarios to identify potential vulnerabilities introduced by parallelism. Finally, the broader application of blockchain in domains like healthcare and agriculture necessitates heightened attention to security considerations. The distributed nature of blockchain can offer superior data protection compared to centralized systems, but only if the underlying parallel processing techniques do not introduce new attack vectors or undermine data integrity. Lawrence [73] outlines that blockchain's encryption and transparency are essential for secure data management, but these features must be preserved even as transaction throughput and validation speeds are increased through parallelization. In summary, while parallel programming and mathematical optimizations such as CRT can substantially enhance blockchain scalability, they also introduce complex security challenges. Ensuring the integrity of cryptographic operations, maintaining consensus consistency, safeguarding shared data structures, and preserving auditability are all critical to the secure adoption of parallelism in blockchain systems [50][17][29][12][38][44][73].

6.3.3 Backward Compatibility

Backward compatibility is a critical consideration when introducing parallel programming techniques and mathematical optimizations such as the Chinese Remainder Theorem (CRT) into existing blockchain systems like Bitcoin. The core challenge arises from the necessity to maintain interoperability with the current protocol rules and infrastructure, ensuring that nodes running legacy software continue to operate seamlessly alongside upgraded nodes that leverage parallelized validation or CRT-based cryptographic enhancements.

Bitcoin's security and consensus depend on strict adherence to protocol specifications, particularly in the cryptographic operations that underpin transaction validation. The use of Elliptic Curve Cryptography (ECC) and SHA-256 hashing is foundational, and any modification to the way these operations are computed, such as distributing modular arithmetic across multiple processors or applying CRT for efficiency, must not alter the output or observable behavior of the validation process [44]. This requirement constrains the design space for parallelization: while internal computation can be optimized, the external interface and results must remain identical to those produced by the original, sequential algorithms. The distributed nature of blockchain networks further complicates backward compatibility. All nodes must agree on the validity of blocks and transactions, and consensus mechanisms such as proof-of-work (PoW) or Byzantine fault tolerance (BFT) protocols rely on deterministic, reproducible computation [64][50]. If parallelized or CRT-optimized validation introduces non-determinism or subtle timing differences, it could lead to consensus failures or network forks. Therefore, any parallelization strategy must guarantee that, regardless of the number of processors or the internal scheduling of tasks, the output remains bitwise identical to the legacy implementation. Additionally, blockchains like Bitcoin are designed to be robust against adversarial manipulation. Attackers may attempt to exploit differences in node behavior introduced by parallelization, for example, by crafting transactions that trigger race conditions or inconsistencies in validation logic [64]. Ensuring backward compatibility thus requires rigorous testing and formal verification to demonstrate that the optimized system is functionally equivalent to the original, even under adversarial conditions. The challenge of backward compatibility is not unique to Bitcoin. In the context of permissioned blockchains for healthcare or other sectors, similar issues arise when integrating new validation mechanisms or data management schemes [75]. For example, when considering the adoption of parallelized validation or CRT-based optimizations in healthcare data blockchains, it is essential to ensure that existing data formats, access controls, and audit trails remain intact, so that previously validated data and transactions are still recognized as valid by the upgraded system. Moreover, the transition to new validation mechanisms must be carefully managed to avoid disrupting ongoing operations. This often necessitates a phased deployment, where nodes can opt-in to the new features while still participating

in the legacy protocol. During this period, the network must support heterogeneous nodes and guarantee that all blocks and transactions are validated consistently, regardless of the underlying implementation details. Ju et al. [43] indicate that changes to consensus or validation infrastructure, such as the shift from PoW to PoS in Ethereum, require extensive compatibility analysis to preserve decentralization and network integrity. Backward compatibility also intersects with regulatory and compliance requirements, particularly in sectors like healthcare and finance. Any change to the validation process must be auditable and transparent, ensuring that stakeholders can verify that the new system upholds the same guarantees as the original [13]. This is especially important when blockchain is used for sensitive data management, where legal and operational continuity is paramount. In summary, the integration of parallel programming and CRT-based optimizations into blockchain validation processes is constrained by the need for strict backward compatibility. This entails preserving the external behavior of transaction validation, ensuring deterministic and reproducible results across all nodes, and maintaining interoperability with legacy systems. The complexity of achieving these goals is amplified by the distributed and adversarial nature of blockchain networks, as well as by sector-specific requirements for data integrity and compliance [44][64][75][43][13][50].

7 Mathematical Optimization Techniques

7.1 Overview of Modular Arithmetic in Cryptography

Modular arithmetic forms the mathematical backbone of many cryptographic algorithms, particularly those employed in blockchain systems such as Bitcoin. At its core, modular arithmetic involves computations where numbers "wrap around" upon reaching a certain value, known as the modulus. This property is especially useful for constructing cryptographic primitives that require operations over finite fields or rings, ensuring both security and computational efficiency [30][63]. In public key cryptography, modular arithmetic is central to the security of algorithms like RSA and elliptic curve cryptography. For instance, RSA encryption and decryption processes rely on modular exponentiation, where a message m is transformed using an exponent e and a modulus n as $c = m^e \bmod n$.

The difficulty of reversing such operations without knowledge of the private key is rooted in the computational hardness of factoring large composite numbers, a problem inherently tied to modular arithmetic [30]. Similarly, digital signatures and key exchange protocols often depend on the intractability of discrete logarithms in modular groups. The blockchain's consensus mechanisms and transaction validation protocols also leverage modular arithmetic. In Proof of Work (PoW) systems, miners repeatedly compute cryptographic hashes, which are fundamentally based on modular operations, to find a nonce that satisfies a network-wide difficulty condition [63][12]. The efficiency of these computations directly impacts the throughput and scalability of the blockchain network. Therefore, optimizing modular arithmetic operations is crucial for improving transaction validation speeds and, consequently, the overall performance of the system [38][37]. Parallel programming techniques can further enhance the efficiency of modular arithmetic computations. By distributing modular exponentiations or multiplications across multiple processors, it becomes feasible to validate transactions concurrently, thereby reducing latency and increasing transaction throughput [38][55]. The Chinese Remainder Theorem (CRT) is particularly beneficial in this context, as it allows large modular computations to be decomposed into several smaller, independent computations modulo relatively prime numbers. These smaller computations can be executed in parallel and later recombined to yield the final result, significantly accelerating cryptographic operations [30]. The robustness of modular arithmetic in cryptography is not limited to financial applications. In healthcare and supply chain management, blockchain systems utilize modular arithmetic to secure sensitive data, enforce access controls, and ensure data integrity through cryptographic hashing and digital signatures [23][76][54]. The persistent, tamper-resistant nature of blockchain ledgers is maintained by cryptographic hash functions, which themselves are constructed using modular arithmetic to produce fixed-size outputs that are computationally infeasible to reverse or collide [76]. Moreover, modular arithmetic underpins the design of smart contracts and distributed ledgers, enabling the secure execution of programmable agreements without intermediaries [77]. The transparency and auditability of blockchain transactions are achieved through the immutable recording of cryptographically validated data, where modular arithmetic ensures that each transaction is uniquely and securely linked to its predecessor [16]. In summary, modular arithmetic is

an indispensable component of modern cryptographic systems, providing the mathematical structure necessary for secure, efficient, and scalable blockchain operations. Its integration with parallel processing and optimization techniques such as the CRT not only enhances computational performance but also broadens the applicability of blockchain technology across diverse sectors, from finance to healthcare and beyond [30][23][76][54].

7.2 Chinese Remainder Theorem Fundamentals

The Chinese Remainder Theorem (CRT) is a foundational result in number theory that provides a systematic approach for solving systems of simultaneous congruences with pairwise coprime moduli. At its core, CRT asserts that for a set of integers $n_1, n_2, \dots, n_k$ that are pairwise coprime, and for any given set of integers $a_1, a_2, \dots, a_k$, there exists a unique solution x modulo $N = n_1 n_2 \cdots n_k$ such that

$$\begin{cases} x \equiv a_1 \pmod{n_1} \\ x \equiv a_2 \pmod{n_2} \\ \vdots \\ x \equiv a_k \pmod{n_k} \end{cases}$$

This property enables the decomposition of complex modular arithmetic problems into simpler, independent computations over smaller moduli, which can be solved separately and then recombined to obtain the solution modulo N [67]. The CRT is not only limited to integer arithmetic but can also be extended to polynomial rings, where it facilitates the construction of polynomials with prescribed values at specific points. In polynomial form, CRT guarantees both the existence and uniqueness of solutions to systems of congruences involving polynomials, which is particularly useful in algebraic coding theory and cryptographic protocols. Luo et al. [3] highlight that the polynomial version of CRT allows for the explicit construction of polynomials that satisfy given modular constraints, and this approach can be generalized to prove various combinatorial identities and matrix propositions. A classic illustration of CRT in an applied setting is the so-called "bags problem," where one seeks an integer x that leaves prescribed remainders when divided by several moduli. For example, if x leaves a remainder of 1 when divided by 2, 3, and 4, the system can be written as:

$$\begin{cases} x \equiv 1 \pmod{2} \\ x \equiv 1 \pmod{3} \\ x \equiv 1 \pmod{4} \end{cases}$$

Such problems are directly addressed by CRT, which ensures that a unique solution exists modulo 24 (the product of 2, 3, and 4) [67]. The theorem's utility is evident in its ability to simplify the search for solutions by reducing the original problem to a set of smaller, independent congruences. The computational implications of CRT are significant, especially in the context of modular arithmetic operations that are central to cryptographic algorithms. By decomposing a large modular computation into several smaller ones, CRT enables parallel processing, which can substantially accelerate cryptographic operations such as modular exponentiation and inversion. This is particularly relevant in blockchain systems, where transaction validation often requires intensive modular arithmetic. The ability to distribute these computations across multiple processors, each handling a congruence modulo a small prime, can lead to marked improvements in validation speed and throughput [3]. Furthermore, the CRT's structure aligns well with parallel programming paradigms. Since each congruence in the system is independent, they can be solved concurrently without inter-process communication until the final recombination step. This property is crucial for optimizing transaction validation in blockchain networks, where latency and throughput are critical performance metrics [67]. For instance, in the context of time calculations, CRT can be used to efficiently compute the result of clock arithmetic, such as determining the hour on a 12-hour clock after a given number of hours, by reducing the problem to modular computations and then reconstructing the answer using the theorem. The generality of CRT also extends to more abstract algebraic structures, where it underpins the design of algorithms for error correction, secret sharing, and secure multiparty computation. Its role in ensuring the existence and uniqueness of solutions to modular systems makes it indispensable for constructing robust cryptographic schemes and optimizing mathematical operations in distributed environments [3]. In summary, the Chinese Remainder Theorem provides both a theoretical and practical framework for decomposing and efficiently solving modular arithmetic problems. Its applicability to both integers and polynomials, combined with its compatibility with

parallel computation, makes it a powerful tool for mathematical optimization in cryptography and blockchain technologies [67][3].

7.3 Accelerating Cryptographic Operations with CRT

7.3.1 Application to ECDSA Signature Verification

The process of verifying ECDSA signatures is computationally intensive due to the underlying modular arithmetic and elliptic curve operations. In the context of Bitcoin, each transaction must be validated by checking the ECDSA signature against the public key and transaction data, a process that involves modular exponentiation and inversion over large prime fields. The verification step is a bottleneck, especially as transaction throughput increases and block sizes approach their limits [40][68]. Applying the Chinese Remainder Theorem (CRT) to ECDSA signature verification offers a promising avenue for optimization. CRT allows the decomposition of modular arithmetic operations into smaller, independent computations modulo coprime integers, which can then be recombined to yield the result modulo the original large modulus. By leveraging CRT, the modular exponentiations and inversions required in ECDSA can be split into parallelizable subproblems, each operating on smaller moduli. This is particularly advantageous for hardware or multicore systems, where each processor can handle a subset of the computation, significantly reducing the overall verification time. Parallel programming techniques further amplify these gains. When the CRT is used to partition the modular arithmetic, each processor can independently perform operations such as modular multiplication, inversion, or exponentiation for its assigned modulus. After all processors complete their tasks, the partial results are recombined using the CRT reconstruction formula, yielding the final result modulo the original large prime. This approach not only accelerates the verification process but also aligns well with the architecture of modern multicore CPUs and GPUs, which are designed to handle concurrent workloads efficiently [67][41]. The security of ECDSA is not compromised by this optimization, as the CRT is mathematically equivalent to direct computation modulo the large prime. The correctness of the signature verification is preserved, provided that the CRT parameters are chosen appropriately and the recombination step is implemented securely. In fact, the use of CRT in cryptographic

operations is a well-established technique, commonly used in RSA implementations to speed up decryption and signing. Extending this approach to ECDSA signature verification in Bitcoin is a natural progression, given the similar mathematical structure of the modular operations involved [40][68]. The impact of these optimizations is substantial in high-throughput environments such as Bitcoin. By reducing the computational burden of signature verification, more transactions can be validated per unit time, directly increasing the effective transaction throughput without altering the block size or consensus protocol. This is particularly relevant as Bitcoin and other blockchain systems face scalability challenges due to the growing volume of transactions and the need for rapid validation to maintain network responsiveness [37][12]. Moreover, the application of CRT-based parallelization is not limited to Bitcoin. Other blockchain platforms that rely on ECDSA or similar elliptic curve cryptography can benefit from these techniques. In sectors such as healthcare and agriculture, where blockchain is increasingly used for secure data management and traceability, efficient cryptographic verification is essential to ensure both scalability and data integrity [67]. For example, healthcare applications that store sensitive patient data on-chain require rapid and secure verification of access rights and data provenance, which can be facilitated by accelerated ECDSA verification [7]. Similarly, agricultural supply chain systems benefit from fast validation of transactions and records, supporting real-time auditability and transparency [13][67]. The integration of CRT and parallel programming into ECDSA verification thus represents a significant advancement in blockchain scalability. It enables the validation of a larger number of transactions within the same computational and temporal constraints, supporting the broader adoption of blockchain technologies in diverse application domains [41][37]. The authors of [40] indicate that the unique structure of Bitcoin addresses, derived from ECDSA public keys, underscores the importance of efficient signature verification for both security and performance. According to [68], the combination of hash-chained storage and cryptographic validation mechanisms ensures the immutability and integrity of blockchain data, further highlighting the value of accelerating signature verification processes. By systematically applying mathematical optimization techniques such as CRT, and distributing the workload across multiple processors, blockchain systems can achieve substantial improvements in transaction validation speed and throughput, addressing one

of the central challenges in the evolution of decentralized digital infrastructures [67][41][40][68].

7.3.2 Decomposition of Modular Calculations

Decomposition of modular calculations is a fundamental strategy for optimizing cryptographic operations, particularly in the context of blockchain systems such as Bitcoin. Modular arithmetic underpins many cryptographic algorithms, including those used for transaction validation and digital signatures. The Chinese Remainder Theorem (CRT) offers a mathematically rigorous method to break down complex modular exponentiations into smaller, independent computations, which can be executed in parallel to achieve significant performance gains. The core idea of decomposition via CRT is to represent a large modulus N as a product of pairwise coprime integers, typically prime factors, such that $N = n_1 n_2 \cdots n_k$. For a given computation modulo N , such as $x \bmod N$, the CRT enables the transformation of this operation into a set of smaller modular calculations: $x \bmod n_1, x \bmod n_2, \dots, x \bmod n_k$. This decomposition is particularly advantageous because each smaller modular operation can be performed independently and concurrently, leveraging parallel programming paradigms to reduce overall computation time. In the context of cryptographic signature verification, such as RSA or ECDSA, this approach allows the most computationally intensive steps, modular exponentiations, to be distributed across multiple processors, thereby accelerating the validation process. Hash functions, which are central to blockchain immutability and security, also benefit from efficient modular arithmetic. High-quality hash functions like SHA-2 rely on fast and secure modular operations to produce unique and irreversible outputs. The security of these functions is grounded in the computational difficulty of reversing the modular transformations, which, when decomposed via CRT, maintain their cryptographic strength while enabling faster computation through parallelism [13]. This is especially relevant for blockchain networks where transaction throughput is constrained by the speed of cryptographic validation. Parallel execution of modular calculations not only improves speed but also enhances scalability. In a multi-peer blockchain network, distributing modular arithmetic tasks among peers allows for concurrent query processing, reducing the latency associated with transaction validation. For example, when multiple queries are processed in parallel, the

response time per query decreases as each peer handles a subset of the modular computations. This distributed approach aligns well with the decentralized architecture of blockchain, where no single node is a bottleneck for cryptographic operations. The decomposition strategy also addresses some of the storage and scalability challenges inherent in blockchain systems. By separating and parallelizing modular calculations, the computational burden on individual nodes is reduced, facilitating the management of large volumes of data, such as medical images or documents in healthcare applications [62][46]. This is crucial for sectors that require both high throughput and secure, tamper-resistant data management. Security considerations remain paramount when decomposing modular calculations. The use of CRT must ensure that the recombination of results preserves the integrity and confidentiality of the original computation. If implemented correctly, CRT-based decomposition does not introduce new vulnerabilities but rather maintains the robustness of the underlying cryptographic protocols [13]. However, care must be taken to protect private keys and manage consensus mechanisms, as the security of the entire system depends on the correct execution of modular arithmetic across distributed nodes [16]. In summary, decomposition of modular calculations using the Chinese Remainder Theorem represents a mathematically sound and practically effective optimization for cryptographic operations in blockchain systems. By enabling parallel execution of smaller modular tasks, this approach significantly accelerates transaction validation, supports higher transaction throughput, and addresses scalability challenges in data-intensive applications such as healthcare and finance [46][62][13][16].

7.3.3 Potential Gains in Validation Speed

The integration of the Chinese Remainder Theorem (CRT) into cryptographic operations within Bitcoin validation processes offers a promising avenue for substantial improvements in validation speed. Cryptographic algorithms, particularly those based on modular arithmetic such as RSA and ECDSA, are computationally intensive and represent a significant bottleneck in transaction verification. By decomposing large modular exponentiations into smaller, independent computations using CRT, it becomes feasible to distribute these tasks across multiple processors, thereby leveraging parallel programming techniques to accelerate the overall validation process. Bitcoin's consensus mechanism

relies on nodes verifying blocks and transactions, a process that involves repeated cryptographic checks and hash computations. The computational burden of these operations is evident in the current network, where transaction throughput is constrained by the time required for each node to validate cryptographic signatures and ensure the integrity of blocks [2][18]. The authors of [2] indicate that the validation of transactions is a meticulous process, requiring all nodes to authenticate and verify each transaction before consensus is reached. This inherently sequential approach, while secure, limits scalability and increases latency, especially as the volume of transactions grows. Parallelization of cryptographic operations, enabled by CRT, addresses this limitation by allowing independent computations on smaller moduli. For instance, in RSA signature verification, CRT can reduce the exponentiation modulo a large number n into two smaller exponentiations modulo p and q , where $n = pq$. These two computations can be executed concurrently on separate processors, and their results recombined using CRT to yield the final result. This approach not only reduces the computational complexity per processor but also minimizes the overall validation time, as the slowest operation among the parallel tasks determines the total duration rather than the sum of all sequential steps. The impact of such mathematical optimization is particularly pronounced when considering the constraints imposed by Bitcoin's block size and block interval. As block size remains fixed, increasing transaction throughput necessitates faster validation per transaction. Empirical studies have shown that block size directly affects the number of transactions that can be processed per second, with larger block sizes enabling higher throughput but also requiring more rapid validation to avoid network congestion [78]. By accelerating cryptographic checks through CRT-based parallelization, it becomes possible to process more transactions within the same block size, thus enhancing scalability without compromising security or decentralization. Moreover, the immutability and integrity of blockchain data are safeguarded by cryptographic techniques that link blocks in a deterministic order [50][18]. The cryptographic algorithm guarantees that once a block is appended to the chain, it cannot be tampered with. However, as the blockchain grows, the cumulative computational effort required for validation increases, further emphasizing the need for efficient validation mechanisms. The current storage size of the Bitcoin blockchain, for example, has reached several petabytes, with each node redundantly

storing and validating the entire transaction history [17]. In such an environment, any reduction in per-transaction validation time translates into significant aggregate time savings across the network. The consensus process, which requires the majority of participants to agree on the validity of new blocks, also benefits from faster cryptographic operations. According to [50], consensus protocols depend on the timely and trustworthy validation of blocks, with cryptographic techniques ensuring that only legitimate transactions are included. By expediting these cryptographic checks, CRT-based parallelization can reduce the time required for network-wide agreement, thereby decreasing block propagation delays and improving overall network responsiveness. Additionally, the incentive structure for miners, who compete to solve complex mathematical puzzles and add new blocks to the chain, is closely tied to the speed of validation [18]. Faster validation enables miners to process more transactions and potentially increase their rewards, while also contributing to the security and accuracy of the blockchain. The competitive nature of mining, combined with the need for rapid and reliable validation, underscores the practical benefits of optimizing cryptographic operations. Beyond the technical advantages, the broader applicability of scalable validation techniques extends to sectors such as agriculture and healthcare, where secure and efficient data management is critical [23][73]. In these domains, blockchain's distributed environment allows participants to access consistent information, reducing information asymmetry and facilitating trust among stakeholders [23]. The development of shared data pools across multiple blockchains further highlights the importance of scalable validation, as cross-chain compatibility and data aggregation require rapid and secure verification mechanisms [73]. In summary, the application of CRT in conjunction with parallel programming techniques holds significant promise for enhancing the speed of cryptographic validation in Bitcoin and other blockchain systems. By decomposing complex modular arithmetic into smaller, parallelizable tasks, it is possible to achieve higher transaction throughput within existing architectural constraints, thereby supporting the scalability and efficiency required for widespread adoption in diverse sectors [50][2][18][17].

8 Integrating Parallel Programming and CRT in Blockchain

8.1 Synergies Between Parallelism and Mathematical Optimization

The interplay between parallel programming techniques and mathematical optimization, particularly through the Chinese Remainder Theorem (CRT), presents a compelling pathway for enhancing the scalability of blockchain systems such as Bitcoin. At the core, parallelism enables the distribution of computationally intensive tasks, such as cryptographic operations and transaction validation, across multiple processors or nodes. This distribution is especially advantageous in blockchain environments where consensus and validation are inherently resource-demanding due to the need for redundancy, signature verification, and consensus mechanisms, all of which contribute to increased computational overhead and latency [26]. The CRT, a classical result in number theory, offers a means to decompose modular arithmetic operations into smaller, independent computations. In the context of cryptographic algorithms, such as those used in Bitcoin for transaction validation, CRT can be leveraged to split large modular exponentiations into several smaller ones, each corresponding to a different modulus. These smaller computations are naturally suited for parallel execution, as they are independent and can be assigned to separate processing units. By reconstructing the final result using the CRT, the overall computation time is significantly reduced compared to a sequential approach, which is particularly beneficial when blockchains are constrained by block size and transaction throughput [12][41]. Empirical studies of parallel blockchain architectures demonstrate that introducing additional nodes and distributing mining or validation tasks among them leads to measurable improvements in processing speed and system throughput. For example, the introduction of parallel mining managers and the allocation of hash computations to multiple nodes result in a decrease in block completion time and an increase in the number of hashes processed per second [12]. This evidence supports the notion that parallelism, when combined with mathematical techniques like CRT, can mitigate the bottlenecks imposed by sequential validation, thereby enabling higher transaction throughput without compromising security or decentralization. Moreover, the synergy between parallelism and mathematical optimization is not limited to the core

consensus or validation mechanisms. In sharded blockchain systems, where the network is partitioned into multiple shards that process transactions in parallel, mathematical optimization is crucial for ensuring that correctness and liveness properties are maintained despite the increased complexity of inter-shard communication. Han et al. [41] state that while sharding protocols can enhance scalability, they often encounter challenges related to communication complexity and fault tolerance, especially in the presence of Byzantine nodes. Here, mathematical frameworks, potentially including CRT-based optimizations, can be instrumental in designing robust shard allocation and leader election protocols that are both efficient and resilient. The practical implications of these synergies extend beyond the financial sector. In healthcare and supply chain management, where secure and scalable data management is essential, blockchain systems benefit from parallel and optimized validation processes. For instance, in healthcare, the need to process and verify large volumes of sensitive data securely and efficiently is paramount. Parallel processing, combined with mathematical optimizations, can address the latency and computational challenges associated with blockchain-based electronic health systems, as highlighted in studies of Hyperledger Fabric deployments and e-healthcare network simulations [62][45]. Similarly, in supply chain applications, the ability to rapidly validate and trace transactions across multiple participants enhances transparency and reduces costs, as demonstrated in BCT-enabled supply chains in the agriculture and food industries [23]. The integration of parallel programming and CRT-based optimization thus represents a strategic advancement in blockchain technology. By enabling the concurrent execution of modular arithmetic and validation tasks, these approaches collectively reduce transaction latency, increase throughput, and support the scalability required for broader adoption in diverse sectors. The ongoing exploration of these synergies is expected to yield further innovations in secure, decentralized data management systems [12][41][62][23].

8.2 Architectural Considerations for Implementation

Architectural considerations for integrating parallel programming and the Chinese Remainder Theorem (CRT) into blockchain transaction validation must address a complex interplay of performance, security, and scalability requirements. The design begins with

the decomposition of cryptographic operations, particularly modular arithmetic, into subtasks that can be distributed across multiple processors. By leveraging parallel programming paradigms, such as task-based or data-parallel models, the system can assign independent modular exponentiations or signature verifications to separate computational threads or cores. This distribution is especially effective when combined with CRT, which allows large modular computations to be split into smaller, independent congruences, each solvable in parallel before recombination using the theorem's reconstruction formula. Such an approach can dramatically reduce the latency of cryptographic validation, a known bottleneck in Bitcoin and similar blockchains [58]. The architectural blueprint must also consider the integration of a logging gateway or broker layer, which acts as an intermediary between microservices responsible for transaction validation and the underlying blockchain. This layer is tasked with aggregating, validating, and formatting logs or transaction results before their submission to the blockchain, thereby decoupling validation logic from business logic and preserving the autonomy of microservices. This modularity is essential for maintaining system flexibility and facilitating upgrades or optimizations in the validation pipeline without disrupting other components [19][35]. In practice, such a gateway could also orchestrate the distribution of validation tasks to available processors or nodes, monitor their execution, and handle error recovery or task rescheduling in case of failures. Selecting the appropriate blockchain infrastructure is another critical decision. Public blockchains, while offering maximal decentralization, often suffer from high latency and limited throughput due to consensus mechanisms like Proof of Work (PoW), which are computationally intensive and not easily parallelizable at the network level. In contrast, private or permissioned blockchains, such as Hyperledger Fabric or Quorum, provide more controlled environments where parallel validation strategies can be more readily implemented and optimized for enterprise use cases. These platforms allow for tailored consensus protocols and access controls, enabling finer-grained management of parallel task execution and resource allocation [19][35]. Kuo et al. [54] emphasize that the choice of consensus protocol significantly impacts energy consumption and processing efficiency; thus, architectures should favor consensus mechanisms that are compatible with parallel processing and do not introduce unnecessary computational overhead. The transaction processing pipeline must be carefully architected to avoid

vulnerabilities associated with transaction ordering and manipulation. Parallel validation introduces the risk of race conditions, where the order of validated transactions could impact the blockchain state or open avenues for adversarial strategies such as transaction reordering or sandwich attacks [55]. To mitigate these risks, the architecture should enforce deterministic ordering mechanisms and atomic commit protocols, ensuring that parallelized validation does not compromise the integrity or consistency of the ledger. Additionally, the use of smart contracts for orchestrating validation workflows can provide automated enforcement of validation rules and facilitate secure, auditable execution [8]. In domains such as healthcare and agriculture, where blockchain is increasingly applied for secure data management, architectural considerations extend to interoperability with existing systems, compliance with regulatory requirements, and support for high-throughput data streams. For example, in healthcare, integrating blockchain with cloud-based storage and data processing systems requires careful management of data privacy, access control, and auditability. Parallelized validation must be coordinated with secure data ingestion and retrieval mechanisms, ensuring that sensitive information is processed in compliance with legal and ethical standards [34][24][4][8]. The architecture should also support efficient error handling and rollback procedures, particularly when dealing with large-scale, real-time data flows. Furthermore, the system must incorporate robust benchmarking and monitoring tools to evaluate the effectiveness of parallelization and CRT-based optimizations under real-world workloads. Meybodi et al. [58] demonstrate the importance of live experiments and continuous performance tracking to identify bottlenecks and guide iterative improvements. Such monitoring should be integrated into the architectural design, providing feedback loops for dynamic resource allocation and adaptive scaling based on transaction volume and system load. Finally, the adoption of a mindful, context-aware approach to technology selection and integration is essential. As Bunduchi [36] argues, organizations should critically assess the suitability of blockchain and its architectural extensions, such as parallel processing and CRT, for their specific operational contexts rather than adopting them based on perceived hype. This involves rigorous evaluation of alternative technologies, consideration of local constraints, and alignment with organizational goals. Architectural implementation of parallel programming and CRT in blockchain thus requires a holistic design that balances

computational efficiency, security, scalability, and domain-specific requirements. By modularizing validation workflows, leveraging appropriate blockchain platforms and consensus protocols, and embedding robust monitoring and compliance mechanisms, the architecture can achieve substantial improvements in transaction throughput and system resilience [19][35][36][54].

8.3 Potential Improvements in Transaction Throughput

Enhancing transaction throughput is a central challenge in blockchain systems, especially for widely adopted networks like Bitcoin, where transaction validation is computationally intensive and constrained by block size. Integrating parallel programming techniques with the Chinese Remainder Theorem (CRT) offers a promising approach to address these limitations by accelerating cryptographic operations and distributing validation workloads across multiple processors. This strategy directly targets the bottlenecks in transaction processing, potentially enabling the network to handle a greater number of transactions per second without compromising security or decentralization. Parallel programming allows for the decomposition of transaction validation tasks into smaller, independent units that can be processed simultaneously. In the context of Bitcoin, this means that cryptographic verifications, such as digital signature checks and hash computations, can be distributed across several processing cores or even across a network of computational devices. DeNio outlines that leveraging a cloud environment for true parallel processing can dramatically improve transaction throughput and reduce the latency between transaction submission and confirmation. By assigning miners to work on the same transaction data with different nonce values, the system avoids redundant computation and ensures efficient use of computational resources [12]. This approach also reduces the risk of a single point of failure by distributing the management of nonce values and transaction assignments. The application of CRT further optimizes modular arithmetic operations, which are fundamental to cryptographic algorithms used in transaction validation. CRT enables the decomposition of large modular exponentiations into smaller, parallelizable computations, significantly reducing the time required for signature verification and other cryptographic checks. By combining CRT with parallel processing,

the system can achieve a synergistic effect, where both the algorithmic efficiency and hardware utilization are maximized. This dual optimization is particularly relevant given the direct relationship between transactional throughput and storage requirements, as identified by Melo et al. Increasing throughput often entails higher storage demands, but careful management of computational and storage resources can mitigate this trade-off [17]. Recent advancements in off-chain and sharding solutions also highlight the importance of parallelism in scaling blockchain throughput. Patel discusses how techniques like Optimistic Rollups, which process transactions off-chain and then batch-validate them on-chain, can achieve thousands of transactions per second by parallelizing transaction handling and reducing on-chain computational load [1]. While these solutions operate at a protocol level, the underlying principle of distributing validation tasks aligns closely with the benefits offered by parallel programming and CRT-enhanced cryptographic operations. Empirical studies have demonstrated that increasing the number of processing nodes or parallel transaction proposals can lead to higher throughput, though there are practical limits due to network overhead and coordination complexity. Jo et al. report that their network achieved throughput comparable to Ripple, with optimal performance observed at a specific node count, beyond which throughput gains diminished due to increased coordination costs [78]. This observation underscores the necessity of balancing parallelism with network efficiency, a consideration that must be addressed when designing parallel validation architectures for Bitcoin. In addition to throughput improvements, parallel and CRT-based validation can contribute to energy efficiency and broader network participation. DeNio notes that enabling even small computational devices to participate in transaction validation reduces reliance on large mining rigs and lowers overall power consumption [12]. This democratization of computational resources not only enhances network security by increasing the number of active validators but also supports the scalability required for expanding blockchain applications in sectors such as healthcare and agriculture, where secure and efficient data management is critical [24]. The integration of parallel programming and CRT into blockchain validation processes represents a significant step toward overcoming the inherent scalability limitations of current systems. By reducing validation times and increasing the number of transactions that can be processed within existing block size constraints, these techniques lay the

groundwork for more robust, scalable, and versatile blockchain networks. The direct correlation between throughput and storage highlighted in recent research suggests that future developments should also focus on optimizing storage management in tandem with computational enhancements to fully realize the potential of high-throughput blockchain systems [17].

8.4 Comparative Analysis with Existing Optimization Techniques

A comparative analysis of optimization techniques for blockchain transaction validation reveals a spectrum of approaches, each with distinct trade-offs in terms of throughput, energy efficiency, scalability, and security. Traditional blockchains such as Bitcoin rely on proof-of-work (PoW) consensus, where miners perform computationally intensive cryptographic operations to validate transactions and add new blocks. This process is inherently sequential and energy-consuming, with the base reward for miners being fixed by protocol rules and halving at predetermined intervals, as observed in Bitcoin's current structure [58]. While PoW ensures robust security, it imposes significant limitations on transaction throughput and resource utilization. Alternative consensus mechanisms have emerged to address these limitations. For example, protocols based on proof-of-stake (PoS) and delegated proof-of-stake (DPoS) shift the validation responsibility from computational power to stake or committee selection, often incorporating Byzantine Fault Tolerance (BFT) techniques. Yu et al. highlight that hybrid systems, such as PoQ, combine PoS with BFT to eliminate energy waste and improve fairness by allowing nodes with similar quality of service (QoS) to have comparable chances of being selected for block proposal. These deterministic protocols achieve higher transaction throughput and are more energy-efficient compared to PoW, but they introduce new challenges regarding committee selection and potential centralization risks [50]. Parallel programming techniques represent another avenue for optimization, particularly in the context of transaction validation and cryptographic computations. By distributing validation tasks across multiple processors, it becomes possible to process transactions concurrently, thereby reducing overall validation time and increasing throughput within the constraints of existing block size limits. This approach contrasts with linear search methods, where transactions are

verified sequentially, resulting in suboptimal performance as the blockchain grows [2]. The integration of parallelism is especially beneficial for modular arithmetic operations, which are fundamental to cryptographic algorithms used in blockchain systems. The Chinese Remainder Theorem (CRT) offers a mathematical tool to further accelerate modular arithmetic by decomposing large computations into smaller, independent subproblems that can be solved in parallel. When applied to cryptographic operations, CRT enables faster computation of modular exponentiations, which are prevalent in digital signature schemes and transaction validation. This synergy between parallel programming and CRT can substantially reduce the latency of transaction processing, offering a clear advantage over purely sequential or monolithic optimization strategies. In contrast, some optimization efforts focus on network-level or architectural changes. For instance, sharding techniques partition the blockchain into multiple shards, each processing a subset of transactions independently. While this increases concurrency and throughput, it introduces complexities related to cross-shard communication and atomic commit protocols. Han notes that optimistic concurrency control (OCC) and pessimistic concurrency control (PCC) make different assumptions about transaction conflict rates, with OCC allowing rollback mechanisms at the cost of increased protocol complexity [41]. These architectural optimizations, while effective in certain scenarios, may not directly address the computational bottlenecks inherent in cryptographic validation. Resource management and data availability are also critical considerations. Solutions such as the use of superpeers and replicated content, as described by Roehrs et al., enhance system availability even during periods of network communication issues by ensuring that nodes with replicated data remain accessible [56]. However, these approaches primarily target network resilience rather than computational efficiency. In the context of broader blockchain applications, especially in sectors like healthcare and agriculture, the need for scalable and secure data management is paramount. For example, efficient authentication schemes for blockchain-based electronic health records (EHRs) must balance security with performance, often relying on optimized cryptographic circuits and careful evaluation of computational overhead [79]. The integration of parallel programming and CRT into these systems can provide the necessary scalability without compromising security or data integrity. Comparing these techniques, it becomes evident that while consensus protocol

innovations and architectural changes address throughput and energy concerns at the system level, the combination of parallel programming and CRT directly targets the computational core of transaction validation. This approach not only accelerates cryptographic operations but also complements other optimization strategies, such as sharding and hybrid consensus, by alleviating their computational bottlenecks. The adoption of such mathematical and computational optimizations is particularly relevant as blockchain applications expand into domains requiring high throughput and low latency, reinforcing the importance of scalable, secure, and efficient validation mechanisms [58][41][56][50][2][79].

9 Blockchain in Agriculture and Healthcare

9.1 Requirements for Data Integrity and Security

Ensuring data integrity and security is fundamental when deploying blockchain-based solutions in agriculture and healthcare, where sensitive and mission-critical information is managed and exchanged. The distributed ledger architecture of blockchain inherently provides robust mechanisms for data validation, immutability, and access control, but specific requirements must be addressed to meet the stringent demands of these sectors. In healthcare, the integrity of patient records and medical transactions is paramount. Blockchain systems utilize cryptographic techniques to validate transactions, ensuring that once data is recorded, it cannot be altered retroactively without consensus from the network participants. This immutability is achieved through the chaining of blocks, where each block contains a cryptographic hash of the previous block, making unauthorized modifications computationally infeasible [80]. The authors of [9] indicate that compared to traditional distributed systems, blockchain offers enhanced security and transparency, which are crucial for managing critical information such as electronic health records (EHRs). The validation process in blockchain involves consensus algorithms, which ensure that only legitimate transactions are added to the ledger, thus maintaining data integrity [10][54]. The requirement for secure access control is especially pronounced in healthcare environments, where multiple stakeholders, including patients, healthcare providers,

insurers, and laboratories, need differentiated access to data. Smart contracts are employed to formalize and automate access permissions, specifying which entities can read, append, or share particular subsets of patient data. For example, patients may authorize specific hospitals to store and share their data, while restricting access for pharmacies or laboratories to only relevant information [8]. The distributed execution of smart contracts ensures that these permissions are enforced consistently across all nodes in the network, reducing the risk of unauthorized data exposure. Privacy preservation is another critical requirement. In cross-institutional collaborations, such as federated learning for predictive healthcare models, blockchain can facilitate secure model sharing without exposing patient-level data. Hospitals can collaboratively train models while retaining their data locally, sharing only the parameters or updates via the blockchain. This approach leverages the distributed, peer-to-peer nature of blockchain to eliminate single points of failure and minimize privacy risks [20]. The interoperability of EHR systems, a longstanding challenge due to heterogeneous data formats and siloed infrastructures, can be addressed by blockchain's standardized transaction protocols and consensus-driven data exchange [24]. Authentication and authorization mechanisms must be robust to prevent unauthorized access and ensure that only verified entities can participate in the network. Efficient authentication schemes, such as batch verification of digital signatures, can be implemented to streamline the validation of multiple transactions or access requests, as is often required in insurance claim processing or large-scale healthcare data management [79]. In these scenarios, the ability to verify multiple signatures from the same signer efficiently is essential for maintaining both security and system performance. The choice of consensus protocol also impacts the security and scalability of blockchain networks in healthcare and agriculture. Protocols such as Kafka and Proof of Elapsed Time offer low-energy consumption and can be tailored to the specific requirements of the application, including the need for rapid consensus or scalability to accommodate a growing number of participants [81]. Special hardware requirements, such as secure enclaves, may further enhance the security of sensitive applications, though they introduce additional deployment considerations [54]. In agricultural applications, similar requirements for data integrity and security arise, particularly in scenarios involving supply chain traceability, certification, and compliance. Blockchain's transparency and decentralized consensus

mechanisms ensure that records of agricultural products, from origin to distribution, are tamper-evident and auditable by all stakeholders [80]. This is particularly valuable in contexts where trust between parties is limited or regulatory compliance is mandatory. The implementation of blockchain in these sectors must also consider scalability challenges. As the number of transactions and participants increases, the network must maintain its ability to validate and record data securely without sacrificing performance. Solutions such as parallel processing of cryptographic operations and the application of mathematical techniques like the Chinese Remainder Theorem (CRT) can accelerate transaction validation, thereby supporting higher throughput within existing block size constraints. Ultimately, the requirements for data integrity and security in blockchain-based agriculture and healthcare systems encompass cryptographic validation, immutable record-keeping, fine-grained access control, privacy preservation, robust authentication, and scalable consensus protocols. These features collectively enable secure, transparent, and efficient data management, addressing the unique challenges of these domains [8][20][9][80].

9.2 Blockchain-Enabled Solutions

9.2.1 Supply Chain Transparency in Agriculture

Supply chain transparency in agriculture has become increasingly important as consumers and regulatory bodies demand greater visibility into the origins, handling, and quality of food products. Blockchain technology presents a promising solution to address these transparency challenges by providing a decentralized, tamper-resistant ledger for recording transactions and events throughout the agricultural supply chain. The distributed nature of blockchain ensures that all stakeholders, including farmers, processors, distributors, retailers, and consumers, can access an immutable record of each step a product takes from farm to table [80]. In agricultural supply chains, the integration of blockchain enables the collection and verification of vast amounts of data regarding products and users at each stage of production and distribution. For example, organizations can track the movement of goods, monitor storage conditions, and verify certifications or quality standards in real time. This comprehensive data collection not only

supports transparency but also allows for more informed decision-making, improved accountability, and enhanced trust among participants [25][80]. The ability for consumers to access accurate, product-specific data empowers them to make choices aligned with their values, such as selecting sustainably produced or ethically sourced goods [25]. The architecture of blockchain-based supply chain systems typically involves multiple organizations collaborating on a shared ledger. Each transaction, such as the transfer of ownership, quality inspection, or shipping event, is validated by participant nodes, time-stamped, and added to the chain in a manner that prevents retroactive alteration. This process eliminates reliance on centralized authorities or third-party intermediaries, reducing the risk of fraud and data manipulation [80]. Furthermore, blockchain's cryptographic mechanisms ensure that sensitive information is securely managed, with access controls that can be tailored to the needs of different stakeholders. Smart contracts play a crucial role in enhancing the flexibility and automation of agricultural supply chains. These programmable agreements can automatically execute actions when predefined conditions are met, such as releasing payments upon delivery confirmation or triggering quality assurance checks based on sensor data. By embedding business logic directly into the blockchain, smart contracts reduce administrative overhead and minimize the potential for human error or disputes. Despite these advantages, blockchain-based agricultural supply chains are not without challenges. Scalability remains a significant concern, as the volume of transactions and data generated in large-scale agricultural operations can strain the underlying infrastructure. The application described by Zheyi Lu highlights that while blockchain systems facilitate comprehensive data collection and user interaction, they may encounter performance bottlenecks as the network grows, necessitating further research into optimization strategies [25]. Additionally, the consensus mechanisms required to validate transactions across a peer-to-peer network can introduce latency compared to traditional centralized databases, potentially impacting real-time operations [36]. The transparency afforded by blockchain also extends to feedback mechanisms within the supply chain. Organizations can analyze transaction histories and product flows to identify inefficiencies, optimize marketing strategies, and refine production processes. This feedback loop contributes to continuous improvement and greater responsiveness to market demands [25]. Moreover, the immutable nature of blockchain records provides a

robust foundation for regulatory compliance and traceability, which is particularly valuable in the context of food safety recalls or sustainability certifications [80]. Overall, blockchain-enabled supply chain transparency in agriculture offers transformative potential by ensuring data integrity, fostering trust, and enabling automation through smart contracts. However, realizing these benefits at scale requires addressing technical limitations related to scalability and consensus efficiency, as well as fostering collaboration among diverse stakeholders in the agricultural ecosystem [36][25][80].

9.2.2 Data Privacy and Consent Management in Healthcare

Data privacy and consent management are fundamental challenges in the context of healthcare data sharing, especially as blockchain-based solutions are increasingly adopted to address the security and interoperability needs of electronic health records (EHRs) and personal health records (PHRs). The decentralized and cryptographically secured nature of blockchain provides a robust foundation for ensuring that sensitive health data remains confidential and that access is strictly controlled by authorized parties [80]. In blockchain-enabled healthcare systems, access control mechanisms are designed to guarantee that only users with explicit authorization can view or modify data, regardless of whether the data is stored directly on-chain or off-chain. The complexity of access control increases as health organizations seek to share data not only internally but also with external partners and patients, necessitating sophisticated strategies to manage permissions and ensure compliance with privacy regulations [48][30]. One of the main advantages of blockchain in this domain is its ability to provide patients with greater control over their health information. Solutions like MedRec and HealthBank exemplify how blockchain can empower individuals to manage consent, select which parties may access their records, and maintain an immutable, timestamped log of all consent transactions [80]. This approach enhances transparency and accountability, as every access or modification request is recorded on the blockchain, making it possible to audit data usage and detect unauthorized activities [48][34]. Smart contracts further automate the process of logging data requests and accesses, increasing the security of healthcare data systems by making it difficult for malicious actors to alter records or conceal improper data handling [48]. Consent management is not limited to granting or revoking access; it also encompasses the ability to

specify granular permissions for different types of data and to delegate consent authority, for example, to guardians or caregivers in the case of vulnerable patients [80]. Blockchain-based platforms can facilitate these nuanced consent scenarios by leveraging programmable smart contracts that enforce access rules dynamically, based on the attributes of the requester and the context of the data request. In some advanced schemes, patients themselves can act as attribute authorities, generating and distributing private keys that enable fine-grained access control while mitigating risks of key abuse and privacy leakage [82]. The challenge of maintaining privacy while supporting legitimate research access to anonymized data is also addressed through cryptographic techniques. For instance, critical data payloads are typically encrypted at the source node before being added to the blockchain, ensuring that only authorized parties with the appropriate decryption keys can access the underlying information [83]. At the same time, researchers may be granted access to anonymized datasets, with cryptographic guarantees that prevent re-identification of individuals. The selection of encryption algorithms, such as AES, is influenced by the need to balance security with computational efficiency, especially as file sizes increase [82]. Hybrid blockchain architectures, which combine private and consortium blockchains, offer additional flexibility for managing privacy and consent. In such systems, private blockchains can serve as secure databases within individual medical institutions, while consortium blockchains facilitate controlled sharing of medical data across multiple organizations [30]. Consortium blockchains, governed by a group of stakeholders, provide the benefits of faster transaction processing and selective transparency, allowing only authorized participants to read, append, or validate transactions [48]. This structure supports scalable and secure data sharing without placing control in the hands of a single entity. Despite these advances, the implementation of blockchain-based privacy and consent management in healthcare is not without challenges. Storage requirements can become significant as the volume of transactions and data grows, particularly in unified blockchains where every peer must store a complete copy of the ledger [45][56]. Efficient indexing and retrieval mechanisms are necessary to ensure that authorized users can quickly access the data they need, while maintaining the integrity and confidentiality of the records [82]. Furthermore, the interoperability of cryptographic protocols and the secure exchange of encryption keys among diverse participants remain

open research questions that must be addressed to fully realize the potential of blockchain in healthcare data management [83]. The distributed and immutable nature of blockchain, combined with advanced cryptographic and access control techniques, positions it as a promising solution for enhancing data privacy and consent management in healthcare. By enabling patients to control their own data, automating consent processes, and providing robust audit trails, blockchain can help build trust among stakeholders and support the secure, transparent exchange of health information across organizational boundaries [80][48][30].

9.3 Scalability Needs in Sectoral Applications

Scalability is a fundamental requirement for blockchain adoption in agriculture and healthcare, where the volume and velocity of data, as well as the diversity of stakeholders, demand robust, high-throughput solutions. In healthcare, for instance, the integration of blockchain with IoT devices and electronic health records (EHRs) introduces substantial data flows that must be processed efficiently to ensure timely access and security. The distributed nature of blockchain offers a promising approach to managing transactions among trustless entities, providing an indestructible and confirmable ledger for sensitive health data [49]. However, the sheer scale of healthcare data, including diagnostic images and real-time monitoring information, poses challenges for current blockchain architectures, as storing large raw datasets directly on-chain is infeasible. This limitation necessitates hybrid approaches, where only references or hashes are stored on-chain, while the actual data reside in secure, encrypted off-chain repositories [71][10]. The need for scalability is further underscored by the requirement for rapid authentication and authorization processes in health data sharing frameworks. Smart contracts are increasingly employed to automate these processes, but their execution must not become a bottleneck as user numbers grow [49]. Moreover, the anticipated acceleration of blockchain innovation in manufacturing and agriculture suggests that future value chains will involve even more complex, multi-tiered interactions, with transactions ranging from supply chain traceability to real-time negotiation and audit trails [25]. These use cases demand blockchain systems capable of handling thousands of transactions per second, far

exceeding the throughput of many current platforms [50]. Transparency, a core feature of blockchain, is particularly valued in agriculture and healthcare for its potential to enhance trust and traceability. In agriculture, stakeholders benefit from the ability to track product provenance, ensuring food safety and authenticity throughout the supply chain. Yet, this transparency must be balanced with privacy, as exposing sensitive business or personal information can introduce new risks. Encryption techniques, including homomorphic encryption and public key cryptosystems, are essential for protecting confidentiality while maintaining the benefits of distributed ledgers [23]. The challenge lies in implementing these cryptographic operations at scale without incurring prohibitive computational costs, which is where parallel programming and mathematical optimizations such as the Chinese Remainder Theorem (CRT) can offer significant advantages. In the context of healthcare, the promise of blockchain extends to supporting AI-based tools that rely on trusted data sources. The immutability and auditability of blockchain records can serve as a foundation for secure, transparent AI systems, but the current maturity of blockchain technology is not yet sufficient for widespread, routine deployment in clinical environments [66][28]. The scalability bottleneck, particularly in transaction validation and consensus mechanisms, remains a major obstacle. For example, protocols that rely on proof-of-work (PoW) are energy-intensive and slow, making them unsuitable for high-throughput applications typical in healthcare and agriculture [38][37]. Simulation frameworks such as ChainSim have demonstrated the feasibility of modeling different consensus protocols and attack scenarios, highlighting the importance of optimizing validation strategies to improve performance [38][37]. The experimental deployment of blockchain in healthcare settings, such as with Hyperledger-based networks, reveals that the time required for storing and retrieving data is a critical metric, especially when operating over existing network infrastructures like 4G [26]. As the number of users and transactions increases, the underlying blockchain must scale accordingly to avoid latency and ensure reliability. The use of Merkle trees and append-only data structures provides a foundation for efficient transaction management, but further improvements are needed to match the transaction rates of established payment systems like VISA or Paypal [50]. Ultimately, the scalability needs in sectoral applications such as agriculture and healthcare are driven by the dual imperatives of handling large, complex datasets and maintaining stringent security and

privacy standards. The adoption of advanced cryptographic techniques, parallel processing, and optimized consensus protocols will be crucial for enabling blockchain systems to meet these demands. The ongoing research and development in this area reflect the recognition that scalable, secure blockchain infrastructures are essential for realizing the full potential of distributed ledger technology in critical sectors [38][49][25][23].

9.4 Benefits and Barriers to Adoption

The adoption of blockchain technology in agriculture and healthcare presents a range of benefits, yet several barriers continue to challenge its widespread implementation. One of the most significant advantages is the enhancement of data security and trust. Blockchain's use of asymmetric cryptography and hash algorithms ensures that transaction data is both tamper-resistant and verifiable, which is especially critical for sensitive health records and agricultural supply chain data [38]. The distributed nature of blockchain, secured by consensus mechanisms such as Proof of Work (PoW), further reduces the risk of single-point failures and unauthorized data manipulation [37]. In healthcare, these properties enable the secure sharing of patient data among authorized stakeholders, while maintaining the integrity and privacy of medical records [56]. In agricultural contexts, blockchain can facilitate traceability, allowing stakeholders to verify the origin, quality, and movement of goods, thereby reducing fraud and improving consumer confidence. Transparency is another notable benefit. Blockchain's immutable ledger allows all participants to access a consistent and auditable record of transactions. This transparency is particularly valuable in healthcare for tracking the provenance of pharmaceuticals or medical devices, and in agriculture for monitoring the journey of produce from farm to table [36]. However, the degree of transparency must be balanced with privacy requirements, as excessive openness can risk exposing sensitive information, especially when participant identities are pseudonymous or anonymous [68]. This tension between transparency and privacy is a recurring theme in both sectors. Efficiency gains are also realized through blockchain adoption. By automating data validation and reducing reliance on intermediaries, blockchain can streamline processes such as insurance claims in healthcare or certification in agricultural trade [22]. The reduction of paperwork and

manual reconciliation not only saves time but also minimizes errors and operational costs [36]. In addition, the integration of parallel programming techniques and mathematical tools like the Chinese Remainder Theorem (CRT) can further accelerate cryptographic operations, enabling higher transaction throughput without compromising security [17]. This is particularly relevant in scenarios where real-time data validation is essential, such as monitoring perishable goods in agriculture or processing large volumes of health transactions [56]. Despite these benefits, several barriers impede the adoption of blockchain in agriculture and healthcare. Technological challenges include the immaturity of blockchain platforms, issues with scalability, and the complexity of integrating blockchain with existing IT infrastructures [22]. The performance of blockchain systems can be limited by consensus algorithms and the need for every participant to process all transactions, which may not scale efficiently as the number of users grows [56]. While strategies such as sharding and parallel processing have been proposed to address these issues, their implementation in real-world healthcare and agricultural systems remains nascent [17]. Regulatory uncertainty is another significant barrier. The lack of clear legal frameworks for blockchain-based data management raises concerns about compliance, liability, and data sovereignty, particularly when sensitive health or agricultural data crosses national borders [22]. Privacy regulations such as the General Data Protection Regulation (GDPR) introduce additional complexity, as the immutable nature of blockchain can conflict with requirements for data erasure or modification [68]. Organizational factors, such as limited top management support, insufficient technical expertise, and resistance to change, further hinder adoption [22]. In many cases, organizations are reluctant to invest in blockchain solutions without demonstrable return on investment or proven interoperability with legacy systems. Interoperability and standardization also present challenges. In agriculture, diverse stakeholders and heterogeneous data formats complicate the seamless exchange of information across the supply chain [11]. Similarly, in healthcare, the lack of standardized protocols for blockchain integration with electronic health record systems can limit the utility of blockchain-based solutions [56]. Network effects and the readiness of trading partners or healthcare providers to participate in blockchain networks are critical for realizing the full benefits of the technology [22]. Trust remains a double-edged sword. While blockchain can enhance trust in data and

transactions, the anonymity or pseudonymity of participants may limit the practical value of traceability and accountability, especially when regulatory or legal recourse is necessary [36][68]. Moreover, concerns about the scalability and performance of blockchain systems, particularly in permissionless or decentralized settings, can deter organizations from adopting the technology for mission-critical applications [17]. The authors of Pujol et al. [9] indicate that blockchain's security and transparency are particularly advantageous in applications requiring reliable peer-to-peer communication and data integrity, such as vehicle-to-infrastructure systems, which share similar requirements with healthcare and agricultural IoT deployments. However, the complexity of managing large-scale decentralized networks and ensuring the authenticity of messages without compromising privacy or efficiency remains a challenge. In summary, the adoption of blockchain in agriculture and healthcare is driven by its potential to enhance security, transparency, and efficiency in data management. Nevertheless, technological, regulatory, organizational, and interoperability barriers must be addressed to unlock its full potential in these sectors [22][36][11][56][9][38][37][17][68].

10 Broader Implications and Future Directions

10.1 Impact of Scalability Improvements on Blockchain Adoption

Enhancing the scalability of blockchain systems has a direct and transformative effect on their adoption across various sectors. Scalability, in the context of blockchain, refers to the system's ability to handle an increasing number of transactions per second (TPS) without compromising security or decentralization. The integration of parallel programming techniques and mathematical optimizations such as the Chinese Remainder Theorem (CRT) into cryptographic operations can substantially accelerate transaction validation, which is a core bottleneck in current blockchain implementations. The ability to distribute transaction validation tasks across multiple processors enables the system to process more transactions concurrently, thus reducing latency and increasing throughput. This is particularly relevant for cryptocurrencies like Bitcoin, where transaction validation involves computationally intensive modular arithmetic. By applying CRT, modular

exponentiations and other arithmetic operations required for digital signatures and zero-knowledge proofs can be decomposed into smaller, independent computations, each of which can be executed in parallel. As a result, the overall validation time is significantly reduced, allowing the network to accommodate higher transaction volumes within existing block size and block interval constraints [12][84]. The implications of such scalability improvements extend beyond mere technical performance. In the financial sector, for example, traditional banking systems are often hindered by low efficiency, high costs, and centralized points of failure. Blockchain systems, when scaled effectively, offer peer-to-peer transaction processing, reduced administrative overhead, and enhanced security through distributed storage and encryption. This shift results in lower operational costs and a more robust customer experience, as decentralized systems are inherently more resilient to hacking and data breaches [76][23]. The transition from centralized to scalable decentralized systems can therefore address many of the inefficiencies and vulnerabilities that plague legacy infrastructures. In healthcare, the impact of scalable blockchain solutions is particularly pronounced. The secure and efficient management of large volumes of sensitive medical data is a persistent challenge. Scalable blockchains can facilitate the rapid validation and sharing of medical records among authorized parties while maintaining data integrity and privacy. The use of advanced cryptographic techniques and consensus mechanisms ensures that records are immutable and verifiable, reducing the risk of fraud and unauthorized access [20][4]. Furthermore, by enabling distributed data storage, blockchain systems eliminate single points of failure and support robust audit trails, which are essential for regulatory compliance and patient trust [30][70]. Scalability also plays a crucial role in the adoption of blockchain in supply chain management and agriculture. These sectors require the secure exchange of vast amounts of data among numerous stakeholders. A scalable blockchain infrastructure can support real-time tracking, verification of product quality, and transparent documentation, thereby reducing the need for third-party verification and lowering associated costs [23][22]. However, it is important to recognize that permissioned blockchains, while offering some scalability and control, may introduce limitations in terms of authenticity and immutability if the initiating organization can influence consensus [23]. This highlights the need for careful system design to balance scalability, security, and trust. Adoption of blockchain

technology is also influenced by environmental and organizational factors. The perceived relative advantage of scalable blockchain solutions, competitive pressures, and the complexity of implementation all affect decision-making processes within organizations [22]. As scalability challenges are addressed through parallelization and mathematical optimization, the barriers to adoption are lowered, making blockchain a more attractive option for a wider range of applications. Despite these advancements, challenges remain. Scalability improvements must be accompanied by solutions to issues such as privacy, interoperability, and the lack of universal standards for data exchange. In healthcare, for instance, the absence of standardized data formats and protocols can hinder the seamless integration of blockchain systems with existing health information technologies [27][21]. Nevertheless, ongoing research and development in scalable blockchain architectures, including hybrid models that combine private and consortium blockchains, are paving the way for broader adoption [30]. The authors of Randall et al. [85] indicate that decentralized blockchain environments, particularly those leveraging smart contracts, can remove many of the barriers associated with centralized systems, such as data ownership disputes and delayed benefit recognition. As scalability solutions mature, these benefits become more accessible, further incentivizing adoption across diverse domains. In summary, the advancement of scalability in blockchain technology, through parallel programming, CRT-based optimizations, and innovative consensus mechanisms, directly enhances the system's capacity to serve high-demand applications. This, in turn, accelerates adoption by addressing critical performance, security, and usability concerns in sectors ranging from finance and healthcare to supply chain management and agriculture [12][76][20][22].

10.2 Cross-Industry Opportunities

The integration of advanced blockchain scalability techniques, such as parallel programming combined with the Chinese Remainder Theorem (CRT), opens up substantial opportunities across diverse industries. In agriculture, for instance, the ability to manage and validate large volumes of transactions efficiently is crucial for supply chain transparency, provenance tracking, and real-time data sharing among stakeholders. Enhanced throughput and reduced latency, achieved via parallelized cryptographic

validation and modular arithmetic optimizations, can enable agricultural supply chains to synchronize demand and inventory data among producers, distributors, and retailers, thereby improving coordination and reducing waste. The consortium blockchain model, where only preselected participants access the ledger, further supports secure and collaborative data exchange, mitigating risks of sensitive information leakage while providing a holistic view of supply and demand dynamics [23]. In healthcare, the secure and scalable management of patient records, clinical trials, and e-health transactions is a persistent challenge. Blockchain's immutability and decentralized consensus mechanisms can ensure data integrity and auditability, which are critical for compliance and patient trust [24]. However, as Biswas et al. indicate, integrating blockchain with existing healthcare subsystems, including regulatory bodies, introduces technical and organizational complexities that must be addressed to realize these benefits [45]. The adoption of parallelized validation and CRT-based optimizations can alleviate concerns about transaction throughput and storage bottlenecks, making it feasible to handle the high volume of medical data exchanges without sacrificing performance or security [17][45]. Furthermore, the transparency and traceability inherent in blockchain systems can support robust digital identity management and consent tracking for vulnerable populations, provided that privacy-preserving techniques are integrated [24]. The financial and accounting sectors are also poised to benefit from these advancements. Blockchain's distributed ledger, when optimized for high throughput, can streamline processes such as auditing, reconciliation, and regulatory reporting. Akter highlights that organizational and environmental factors, including top management support and external pressure, drive blockchain adoption in accounting, while technical challenges like complexity and cost remain barriers. The application of parallel programming and CRT can directly address these technical hurdles by reducing computational overhead and enabling real-time validation of financial transactions, thus supporting broader adoption [22]. Moonsamy underscores the need for businesses to adapt their strategies to the digitization enabled by blockchain, as traditional intermediaries and auditing practices become less relevant in a transparent, decentralized environment [13]. In the context of the Internet of Things (IoT), particularly vehicular IoT and smart device ecosystems, the ability to process and validate a massive number of transactions concurrently is essential for security and privacy. Peng et

al. state that combining data from multiple entities increases the risk of privacy leakage, necessitating robust privacy protection mechanisms in blockchain-based IoT environments. The use of parallel processing and CRT can help scale blockchain platforms to accommodate the high transaction rates generated by interconnected devices, while maintaining the security and reliability required for collaborative intelligence and dynamic network environments. Off-chain and DAG-based architectures, as discussed by Peng et al., further contribute to scalability but introduce new challenges in transaction validity and risk management, which can be mitigated by efficient on-chain validation techniques [16]. Voting systems and ownership management platforms also stand to gain from these technological improvements. Yu et al. describe how blockchain can be leveraged for privacy-preserving voting and device/data ownership management without reliance on trusted third parties. The application of scalable validation methods ensures that such systems remain responsive and secure even as the number of participants grows, supporting wider adoption in democratic and IoT contexts [50]. From a technical perspective, the relationship between storage growth and transactional throughput is critical for sustainable blockchain deployment. Melo et al. provide insights into how optimizing transactional models, such as the UTXO model, can balance storage and throughput requirements, a consideration that becomes increasingly important as blockchains are adopted across industries with varying data and performance needs [17]. The consensus mechanisms underlying blockchain, such as proof-of-work, also benefit from parallelization, as described by Sriman et al., since distributing the computational effort across multiple processors can accelerate block generation and reward distribution, further enhancing system efficiency [63]. Finally, the trust and reliability of information exchanged via blockchain are foundational for cross-industry adoption. Li et al. emphasize that blockchain's traceability, verifiability, and immutability elevate the reliability of signals exchanged between parties, reducing the need for central authorities and protecting against data fraud [23]. These properties are particularly valuable in sectors where data authenticity and provenance are paramount, such as supply chain management, healthcare, and digital identity systems [24][23]. By addressing the scalability and efficiency challenges through parallel programming and CRT-based optimizations, blockchain technology can be positioned as a foundational infrastructure for secure, transparent, and

high-throughput data management across a spectrum of industries [15][17][23]. This cross-industry applicability not only enhances operational efficiency but also supports the development of new business models and collaborative ecosystems that leverage the unique strengths of blockchain.

10.3 Open Challenges and Research Gaps

10.3.1 Security Implications of Advanced Computational Techniques

The integration of advanced computational techniques, such as parallel programming and the Chinese Remainder Theorem (CRT), into blockchain transaction validation introduces both opportunities and new security considerations. Parallelization of cryptographic operations can accelerate transaction throughput, yet it also expands the attack surface by increasing system complexity and the number of concurrent processes that must be securely managed. The open, decentralized nature of blockchain systems, which is fundamental to their transparency and immutability, can be challenged by the introduction of parallel architectures, as synchronization and consensus across distributed nodes become more intricate and potentially vulnerable to novel attack vectors. The application of CRT to modular arithmetic in cryptographic routines, while mathematically sound and performance-enhancing, necessitates rigorous scrutiny regarding side-channel resistance and fault tolerance. CRT-based optimizations, if improperly implemented, may inadvertently leak sensitive information through timing or power analysis, especially when parallelized across heterogeneous hardware. The increased efficiency in modular exponentiation and signature verification must be balanced against the risk of introducing subtle flaws that adversaries could exploit to compromise private keys or forge transactions [13]. Zero-knowledge proofs and related cryptographic primitives, often used to enhance privacy and confidentiality in blockchain systems, also present unique security implications when deployed in high-throughput, parallelized environments. The proof length, preprocessing requirements, and management of common reference strings (CRS) become critical factors, as improper handling can degrade both security and scalability. For instance, schemes with shorter proofs may be preferable for transaction efficiency, but may require more complex setup procedures, which, if not securely managed, could undermine

the trust assumptions of the system [84]. Moreover, the adoption of advanced computational techniques must account for the diversity of node types within blockchain networks. Full nodes, light nodes, and archive nodes each have different computational and storage capabilities, and the introduction of parallelized validation may disproportionately benefit well-resourced participants, potentially centralizing control and reducing the overall security of the network. As blockchains grow in size and complexity, only nodes with substantial computational power may be able to participate fully, raising concerns about equitable access and resistance to collusion or Sybil attacks [29]. In sectors such as healthcare, where privacy and data integrity are paramount, the deployment of scalable blockchain solutions leveraging parallel computation and CRT must be accompanied by robust mechanisms for access control, auditability, and compliance with regulatory standards. The challenge is further compounded by the necessity to securely share sensitive clinical data across institutional boundaries, where the risk of data leakage or unauthorized modification is heightened by the increased computational throughput and complexity of the system [54][81][30]. The use of smart contracts and automated processes, which are often accelerated by parallel computation, introduces additional vectors for exploitation. Vulnerabilities in contract logic, race conditions, and reentrancy attacks can be exacerbated in parallel execution environments. Ensuring the correctness and atomicity of contract execution across multiple processors requires advanced formal verification and runtime monitoring techniques [14]. Furthermore, the interplay between scalability and security is not limited to technical aspects but extends to governance and operational practices. As blockchain applications proliferate in domains such as supply chain management, finance, and the Internet of Things, the consequences of a security breach become more severe. For example, in healthcare and pharmaceutical supply chains, the failure to maintain data integrity or confidentiality could have direct impacts on patient safety and public health [20][9]. The ongoing evolution of blockchain technology, driven by advanced computational methods, thus presents a dual-edged sword: while enabling unprecedented scalability and efficiency, it simultaneously introduces complex security challenges that must be systematically addressed through interdisciplinary research, rigorous cryptographic engineering, and adaptive governance frameworks [13][29][84][9].

10.3.2 Standards and Protocol Development

Standards and protocol development remain critical yet unresolved aspects in the advancement of scalable blockchain systems, particularly when integrating parallel programming and mathematical optimizations such as the Chinese Remainder Theorem (CRT). The lack of unified standards for interoperability, data formats, and consensus mechanisms impedes the seamless integration of novel validation techniques across heterogeneous blockchain platforms. This fragmentation is especially pronounced in the context of Layer 2 solutions and rollup technologies, where the absence of standardized interfaces and cross-rollup communication protocols restricts asset and data portability. According to [1], standardization is essential for achieving interoperability, enabling different rollup implementations and Layer 2 networks to interact efficiently. Without such conventions, the benefits of parallelized validation and modular arithmetic optimizations are confined to isolated systems, limiting their broader impact. The challenge of protocol development is further complicated by the evolving landscape of consensus algorithms and validation requirements. In traditional Bitcoin systems, a block is considered irreversible after six subsequent confirmations, a value derived from empirical engineering calculations related to the network's difficulty coefficient [30]. However, hybrid and consortium blockchains may require a different number of validations, reflecting variations in consensus protocols and security assumptions. This diversity underscores the need for adaptable standards that can accommodate varying validation depths and cryptographic primitives, especially when new computational techniques such as CRT-based modular arithmetic are introduced to accelerate transaction processing. Moreover, the development of robust standards must address the security implications of distributed and parallelized validation. Attack vectors such as replay attacks, publish-revert attacks, and message withholding have been identified in advanced sharded and cross-chain protocols, where inconsistent validation rules or insufficient verification depth can undermine agreement and finality. Han et al. [41] suggest that verification rules must ensure that cross-shard transactions become sufficiently deep in input shards before being accepted in output shards, highlighting the necessity for protocol-level safeguards that can be standardized across implementations. In sectors like healthcare and agriculture, the absence of

standardized blockchain protocols poses significant barriers to the adoption of scalable, secure data management solutions. The immutable audit trails and transparency offered by blockchain are only effective if data formats, access permissions, and consensus mechanisms are harmonized across stakeholders [54][9]. Kuo et al. [54] emphasize that the use of hash-chain timestamping and consensus protocols such as Proof of Work (PoW) are foundational, yet their implementation details and interoperability with other systems require further standardization. The need for open, adaptable standards is echoed in the context of electronic health records and multi-application environments, where programmatic mandates and privacy requirements evolve rapidly [85]. The literature also points to a gap in theory-driven empirical research on protocol adoption and standardization, particularly in domains such as accounting and supply chain management [22][23]. While conceptual models abound, there is a lack of comprehensive, empirically grounded investigations that address the interplay between technical standards, organizational adoption, and sector-specific requirements. Akter [22] and Li [23] both highlight the necessity for research that bridges technical innovation with organizational theory, ensuring that protocol development is informed by real-world constraints and stakeholder needs. Finally, as blockchain systems increasingly incorporate parallel computing and advanced cryptographic techniques, the absence of standardized benchmarks and evaluation metrics for protocol performance and security becomes a pressing issue. The deployment of experimental platforms and prototypes, such as those described in [86], provides valuable insights into the computational and communication costs of new protocols. However, the scalability and generalizability of these findings depend on the establishment of widely accepted standards for protocol evaluation and comparison. In summary, the development of standards and protocols is a multifaceted challenge that intersects with technical, organizational, and sectoral considerations. Addressing this challenge is essential for realizing the full potential of parallelized, CRT-optimized blockchain validation and for enabling the secure, scalable management of data across diverse application domains [30][54][1][41][86][9][23].

10.3.3 Interoperability and Integration Issues

Interoperability and integration issues present substantial challenges for the adoption and scaling of blockchain technologies, particularly when considering the integration of advanced computational techniques such as parallel programming and the Chinese Remainder Theorem (CRT) within existing infrastructures. The heterogeneity of blockchain platforms, protocols, and consensus mechanisms often leads to fragmented ecosystems that hinder seamless data exchange and process automation across different networks [36][41]. For instance, the deployment of blockchain in healthcare and supply chain sectors frequently encounters obstacles related to the compatibility of data formats, privacy requirements, and regulatory compliance, which are exacerbated by the immutable and distributed nature of blockchain storage [20][23]. In healthcare, the integration of blockchain with legacy systems and other emerging technologies, such as smart contracts and application layers, is complicated by the need for high throughput and secure, real-time data sharing among multiple stakeholders. The use of smart contracts can automate processes and enhance trust, but their effectiveness is limited if interoperability between disparate blockchain networks and traditional databases is not achieved [20]. Kim et al. [10] state that the adoption of specialized consensus algorithms and shading technologies can improve performance, yet these solutions often require significant adaptation to fit within the operational constraints of existing health information systems. Supply chain applications, particularly in agriculture and food industries, further illustrate the difficulties of integrating blockchain with conventional communication channels and databases. While blockchain enhances traceability and data integrity, its immutability can reduce flexibility in environments characterized by frequent changes in capacity, yield, or lead time. Manual communication methods, such as email or instant messaging, remain more adaptable in certain scenarios, highlighting the trade-off between transparency and operational agility. Moreover, the computational expense of creating new blocks and maintaining distributed ledgers can introduce unnecessary complexity and cost, especially when the benefits of blockchain over traditional methods are marginal in terms of information visibility [23]. The technical barriers to interoperability are compounded by the need for standardized protocols for cross-chain communication and transaction

validation. Sharded blockchains, for example, must synchronize information across shards to maintain consistency, which introduces additional communication overhead and requires trusted coordination mechanisms. Han [41] outlines that solutions such as final committees or lightweight client protocols can facilitate cross-shard transactions, but these approaches add to the storage and communication burden, potentially negating the scalability gains achieved through parallelization and CRT-based optimizations. Furthermore, the integration of blockchain with privacy-preserving technologies, such as searchable encryption and permissioned ledgers, remains an area of active research. Alagha et al. [2] discuss how advancements in blockchain search mechanisms can improve data privacy and efficiency, yet the lack of interoperability between different encryption schemes and blockchain platforms limits the practical deployment of these solutions. The literature also highlights the risk of overestimating blockchain's capabilities due to inadequate technology assessment and misconceptions about its integration potential, particularly in industries like maritime logistics where proprietary solutions and conflicting interests may distort objective evaluations [36]. In summary, addressing interoperability and integration issues is essential for realizing the full potential of blockchain in diverse sectors. This requires not only technical innovations in protocol design and cross-chain communication but also a nuanced understanding of the operational contexts and legacy systems with which blockchain must coexist [20][36][2][41]. Without robust solutions to these challenges, the scalability and efficiency improvements offered by parallel programming and CRT-based approaches may be undermined by systemic fragmentation and integration bottlenecks.

11 Conclusion

The exploration of blockchain scalability through the integration of parallel programming techniques and the Chinese Remainder Theorem (CRT) reveals a promising pathway to overcoming the inherent computational bottlenecks that limit transaction throughput and network performance. By decomposing complex modular arithmetic operations fundamental to cryptographic validation into smaller, independent tasks, and distributing these across multiple processors, it becomes feasible to significantly accelerate transaction

verification without compromising the security or decentralization principles that underpin blockchain systems. This synergy not only addresses the pressing challenge of limited transactions per second within fixed block size constraints but also enhances the capacity of blockchain networks to support a broader range of applications beyond cryptocurrencies.

The implications of these advancements extend deeply into sectors such as healthcare and agriculture, where the secure, transparent, and efficient management of sensitive data is critical. In healthcare, scalable blockchain solutions enable rapid validation and sharing of electronic health records while maintaining stringent privacy and regulatory compliance. Similarly, in agriculture, enhanced throughput supports real-time supply chain transparency and product provenance verification, contributing to improved trust and operational efficiency. The adoption of parallelized cryptographic validation, optimized by CRT, thus serves as a foundational enabler for blockchain's expansion into these data-intensive and security-sensitive domains.

Architectural considerations for implementing these techniques emphasize modularity, interoperability, and robust synchronization mechanisms to ensure consistency and prevent vulnerabilities arising from concurrent processing. The integration of logging gateways, smart contracts, and permissioned blockchain platforms can facilitate the practical deployment of parallel validation workflows, balancing performance gains with the need for auditability and compliance. Moreover, the maintenance of backward compatibility with existing blockchain protocols is essential to preserve network integrity and support gradual adoption of these optimizations.

Despite the clear benefits, challenges remain in managing synchronization overhead, ensuring security against side-channel and fault injection attacks, and addressing the complexities introduced by distributed consensus in parallelized environments. The expansion of the attack surface due to increased concurrency necessitates rigorous cryptographic engineering and formal verification to safeguard against potential exploits. Additionally, the lack of standardized protocols and interoperability frameworks poses

barriers to seamless integration across heterogeneous blockchain ecosystems, particularly in multi-stakeholder sectors with diverse regulatory landscapes.

Future research must continue to address these open issues, focusing on the development of secure, scalable, and interoperable blockchain architectures that leverage parallel computation and mathematical optimization. The establishment of industry-wide standards and evaluation benchmarks will be critical to facilitate widespread adoption and to ensure that performance improvements do not come at the expense of security or decentralization. Furthermore, interdisciplinary collaboration is required to align technological innovations with organizational, regulatory, and sector-specific requirements, thereby enabling blockchain to realize its full potential as a transformative infrastructure for secure, transparent, and efficient data management.

In summary, the convergence of parallel programming and CRT-based mathematical optimization represents a significant advancement in blockchain technology, offering a viable solution to longstanding scalability challenges. This approach not only enhances transaction throughput and reduces latency but also supports the secure and efficient operation of blockchain networks across diverse application domains. By addressing both computational and architectural dimensions, these innovations pave the way for more resilient, inclusive, and high-performance distributed ledger systems that can meet the evolving demands of modern digital ecosystems.

References

- [1] O. Patel, "Blockchain layer 2 rollups, optimistic vs zero knowledge," *INTERNATIONAL JOURNAL OF ADVANCED RESEARCH IN ENGINEERING & TECHNOLOGY*, Feb. 2023, doi: [10.34218/IJARET.14.2.002](https://doi.org/10.34218/IJARET.14.2.002).

- [2] B. Alagha and I. Ozcelik, "AN EMPIRICAL EVALUATION OF BLOCKCHAIN TRANSACTION SEARCH METHODS," Aug. 2025. Available: <https://www.researchgate.net/publication/387930981>
- [3] Q. Luo, "Research and application of chinese remainder theorem," Nov. 2023, doi: [10.54254/2753-8818/9/20240711](https://doi.org/10.54254/2753-8818/9/20240711).
- [4] T. Benil and J. Jasper, "Cloud based security on outsourcing using blockchain in e-health systems," *Computer Networks*, vol. 178, p. 107344, Jun. 2020, Available: <https://doi.org/10.1016/j.comnet.2020.107344>
- [5] V. K. Chattu, A. Nanda, S. K. Chattu, S. M. Kadri, and A. W. Knight, "The emerging role of blockchain technology applications in routine disease surveillance systems to strengthen global health security," *Big Data Cogn. Comput.*, May 2019, doi: [10.3390/bdcc3020025](https://doi.org/10.3390/bdcc3020025).
- [6] T. Alyas *et al.*, "Multi blockchain architecture for judicial case management using smart contracts," *Scientific Reports*, Apr. 2025, doi: [10.1038/s41598-025-92842-8](https://doi.org/10.1038/s41598-025-92842-8).
- [7] S. L. Cichosz, M. N. Stausholm, T. Kronborg, P. Vestergaard, and O. Hejlesen, "How to use blockchain for diabetes health care data and access management: An operational concept," *Journal of Diabetes Science and Technology*, pp. 1–6, Aug. 2018, doi: [10.1177/1932296818790281](https://doi.org/10.1177/1932296818790281).
- [8] T. Kumar, V. Ramani, I. Ahmad, A. Braeken, E. Harjula, and M. Ylianttila, "Blockchain utilization in healthcare: Key requirements and challenges," Aug. 2018.
- [9] F. A. PUJOL, H. MORA, T. RAMÍREZ, C. ROCAMORA, and A. BEDÓN, "Blockchain-based framework for traffic event verification in smart vehicles," Jan. 2024, doi: [10.1109/ACCESS.2024.3352738](https://doi.org/10.1109/ACCESS.2024.3352738).
- [10] S.-K. Kim and J.-H. Huh, "Artificial neural network blockchain techniques for healthcare system: Focusing on the personal health records," *Electronics*, May 2020, doi: [10.3390/electronics9050763](https://doi.org/10.3390/electronics9050763).

- [11] V. Vallois and F. Guenane, "Bitcoin transaction: From the creation to validation, a protocol overview," Oct. 2017. doi: [10.1109/CSNET.2017.8241988](https://doi.org/10.1109/CSNET.2017.8241988).
- [12] J. A. DeNio, "IMPLEMENTATION OF PARALLEL PROGRAMMING TO IMPROVE TRANSACTION SPEED AND SCALABILITY IN BLOCKCHAIN SYSTEMS." Jul. 2021.
- [13] D. Moonsamy, "BLOCKCHAIN READINESS FOR COUNTRIES TOWARDS 2030- THE BARRIERS AND BENEFITS OF ADOPTING BLOCKCHAIN TECHNOLOGY." Apr. 2020.
- [14] X. Zheng, Z. Wan, D. Lo, D. Xie, and X. Yang, "Why does my transaction fail? A first look at failed transactions on the solana blockchain," Jul. 2025, doi: [10.1145/3728943](https://doi.org/10.1145/3728943).
- [15] C. Huang, "BLOCKCHAIN DESIGN FOR INTERNET-OF-THING." The Hong Kong University of Science; Technology, Aug. 2020.
- [16] C. Peng, C. Wu, L. Gao, J. Zhang, K.-L. A. Yau, and Y. Ji, "[Blockchain for vehicular internet of things: Recent advances and open issues](#)," *Sensors*, p. 5079, Sep. 2020.
- [17] D. Melo, S. E. Pomares-Hernández, L. M. X. Rodríguez-Henríguez, and J. C. Pérez-Sansalvador, "Unlocking blockchain UTXO transactional patterns and their effect on storage and throughput trade-offs," Jun. 2024, doi: [10.3390/computers13060146](https://doi.org/10.3390/computers13060146).
- [18] V. Bhatia, B. V. D. University, M. Bhutani, D. Bharati Vidyapeeth College of Engineering, A. Chopra, and S. Kumar, "A comprehensive exploration of the genesis of blockchain technology and the evolution of bitcoin," Jun. 2025, doi: [10.48047/2wnc dx80](https://doi.org/10.48047/2wnc dx80).
- [19] E. Sophia, "Blockchain-based transaction logging in decentralized microservices systems," Jun. 2025, Available: <https://www.researchgate.net/publication/393178488>
- [20] T. K. Mackey, T.-T. Kuo, and B. Gummadi, "'Fit-for-purpose?' – challenges and opportunities for applications of blockchain technology in the future of healthcare," *BMC Medicine*, vol. 17, no. 1, Dec. 2019, doi: [10.1186/s12916-019-1296-7](https://doi.org/10.1186/s12916-019-1296-7).
- [21] A. CLIMA, R. D. ZOTA, and R. CONSTANTINESCU, "Data exchanges based on blockchain in m-health applications," *Procedia Computer Science*, vol. 160, pp. 281–288, Nov. 2019, doi: [10.1016/j.procs.2019.11.088](https://doi.org/10.1016/j.procs.2019.11.088).

- [22] M. Akter, "TOWARDS AN UNDERSTANDING OF THE ADOPTION OF BLOCKCHAIN TECHNOLOGY IN ACCOUNTING." Sep. 2022.
- [23] C. Li, "INFORMATION ASYMMETRY IN SUPPLY CHAINS AND BLOCKCHAIN TECHNOLOGY: AN EMPIRICAL EXAMINATION." Sep. 2022.
- [24] C. Crittenden and M. Sistla, "Blockchain, digital identity and health records: Considerations for vulnerable populations in california." Oct. 2020. Available: <https://escholarship.org/uc/item/29t4c67d>
- [25] Z. Lu, "The architecture of blockchain system across the manufacturing supply chain." 2018.
- [26] T. T. Thwin and S. Vasupongayya, "Blockchain-based access control model to preserve privacy for personal health record systems," Jun. 2019, doi: [10.1155/2019/8315614](https://doi.org/10.1155/2019/8315614).
- [27] A. Shahnaz, U. Qamar, and A. Khalid, "Using blockchain for electronic health records," Oct. 2019, doi: [10.1109/ACCESS.2019.2946373](https://doi.org/10.1109/ACCESS.2019.2946373).
- [28] L. Mertz, "Chain reaction: A blockchain revolution sweeps into health care," *IEEE Pulse*, May 2018, doi: [10.1109/MPUL.2018.2814879](https://doi.org/10.1109/MPUL.2018.2814879).
- [29] A. H. Mayer, C. A. da Costa, and R. da Rosa Righi, "Electronic health records in a blockchain: A systematic review," *Health Informatics Journal*, pp. 1–16, Aug. 2019, doi: [10.1177/1460458219866350](https://doi.org/10.1177/1460458219866350).
- [30] H. Han, M. Huang, Y. Zhang, and U. A. Bhatti, "[An architecture of secure health information storage system based on blockchain technology](#)," *Springer Nature Switzerland AG* 2018, May 2018.
- [31] Y. Wu, X. Tan, and Q. Xie, "Certificateless provable data possession scheme for cloud-based electronic health records system," *Mathematics*, vol. 12, no. 12, p. 3883, Dec. 2024, doi: [10.3390/math12243883](https://doi.org/10.3390/math12243883).

- [32] A. Gkoulalas-Divanis, G. Loukides, and J. Sun, "Methodological review: Publishing data from electronic health records while preserving privacy: A survey of algorithms," *Journal of Biomedical Informatics*, Jun. 2014, doi: [10.1016/j.jbi.2014.06.002](https://doi.org/10.1016/j.jbi.2014.06.002).
- [33] P. D. Dozier, "Banking on blockchain: A grounded theory study of the innovation evaluation process." Oct. 2018. Available: <https://digitalcommons.usf.edu/etd/9638>
- [34] D. C. Nguyen, P. N. Pathirana, M. Ding, and A. Seneviratne, "Blockchain for secure EHRs sharing of mobile cloud based e-health systems," May 2019, doi: [10.1109/ACCESS.2019.2917555](https://doi.org/10.1109/ACCESS.2019.2917555).
- [35] E. Sophia, "Blockchain-based transaction logging in decentralized microservices systems," Jun. 2025, Available: <https://www.researchgate.net/publication/393164891>
- [36] D. Bunduchi, "Emperor's new blockchain: An overview of the technology adoption within the maritime industry." p. 71, 2019.
- [37] B. Wang, "A P2P networking simulation framework for blockchain studies." 2022. doi: [10.26190/unsworks/1628](https://doi.org/10.26190/unsworks/1628).
- [38] B. Wang, "A P2P networking simulation framework for blockchain studies." 2022. doi: [10.26190/unsworks/1628](https://doi.org/10.26190/unsworks/1628).
- [39] D. Ilinca, "Applying blockchain and artificial intelligence to digital health," 2020. doi: [10.1007/978-3-030-12719-0_8](https://doi.org/10.1007/978-3-030-12719-0_8).
- [40] S. Rahmadika and K.-H. Rhee, "Blockchain technology for providing an architecture model of decentralized personal health information," *International Journal of Engineering Business Management*, Feb. 2018, doi: [10.1177/1847979018790589](https://doi.org/10.1177/1847979018790589).
- [41] R. Han, "Scaling permissionless blockchains via sharding." Aug. 2022.
- [42] K. S. R. Puranam, M. C. T. Gaddam, S. K. Panda, and G. S. M. Reddy, "Anatomy and lifecycle of a bitcoin transaction," *SSRN Electronic Journal*, Jan. 2019, doi: [10.2139/ssrn.3355106](https://doi.org/10.2139/ssrn.3355106).

- [43] H. Ju, M. Kumar, E. Valavi, and S. Aral, "Explaining sustained blockchain decentralization with quasi-experiments: Resource flexibility of consensus mechanisms." May 2025. Available: <https://arxiv.org/abs/2505.24663v1>
- [44] K. Balasubramanian, "Security of the Secp256k1 elliptic curve used in the bitcoin blockchain," *Indian Journal of Cryptography and Network Security*, May 2024, doi: [10.54105/ijcns.A1426.04010524](https://doi.org/10.54105/ijcns.A1426.04010524).
- [45] S. Biswas, K. Sharif, F. Li, and S. P. Mohanty, "Blockchain for e-health-care systems: Easier said than done," *IEEE Computer*, p. 57, Jul. 2020, doi: [10.1109/MC.2020.2989781](https://doi.org/10.1109/MC.2020.2989781).
- [46] T.-T. Kuo, H.-E. Kim, and L. Ohno-Machado, "Blockchain distributed ledger technologies for biomedical and health care applications," *Journal of the American Medical Informatics Association*, vol. 24, no. 6, Nov. 2017, doi: [10.1093/jamia/ocx068](https://doi.org/10.1093/jamia/ocx068).
- [47] T.-T. Kuo, H.-E. Kim, and L. Ohno-Machado, "[Blockchain distributed ledger technologies for biomedical and health care applications](#)," *Journal of the American Medical Informatics Association*, pp. 1211–1220, Jun. 2017.
- [48] T. Hardin and D. Kotz, "[Blockchain in health data systems: A survey](#)," May 2019.
- [49] R. Akkaoui, X. Hei, and W. Cheng, "EdgeMediChain: A hybrid edge blockchain-based framework for health data exchange," Jun. 2020, doi: [10.1109/ACCESS.2020.3003575](https://doi.org/10.1109/ACCESS.2020.3003575).
- [50] B. Yu, "Building secure and efficient blockchain systems." Monash University, Sep. 2019.
- [51] Y. Zhang, R. Garg, L. L. Golden, P. L. Brockett, and A. Sharma, "Segmenting bitcoin transactions for price movement prediction," *Journal of Risk and Financial Management*, vol. 17, p. 128, Mar. 2024, doi: [10.3390/jrfm17030128](https://doi.org/10.3390/jrfm17030128).
- [52] G. Nagasubramanian, R. K. Sakthivel, R. Patan, A. H. Gandomi, M. Sankayya, and B. Balusamy, "Securing e-health records using keyless signature infrastructure blockchain technology in the cloud," *Neural Computing and Applications*, pp. 639–647, Nov. 2018, doi: [10.1007/s00521-018-3915-1](https://doi.org/10.1007/s00521-018-3915-1).

- [53] M. Vankani, "Blockchain - more than bitcoin," *GIS- Zeitschrift für Geoinformatik*, May 2022, Available: <https://www.researchgate.net/publication/361227339>
- [54] T.-T. Kuo, H. Z. Rojas, and L. Ohno-Machado, "Comparison of blockchain platforms: A systematic review and healthcare examples," *Journal of the American Medical Informatics Association*, vol. 26, no. 5, May 2019, doi: [10.1093/jamia/ocy185](https://doi.org/10.1093/jamia/ocy185).
- [55] X. Zhao, H.-W. Long, Z. Li, J. Liu, and Y.-W. Si, "Mitigating blockchain extractable value (BEV) threats by distributed transaction sequencing," Mar. 2025.
- [56] A. Roehrs, C. A. da Costa, R. da R. Righi, V. F. da Silva, J. R. Goldim, and D. C. Schmidt, *Journal of Biomedical Informatics*, Mar. 2019, doi: [10.1016/j.jbi.2019.103140](https://doi.org/10.1016/j.jbi.2019.103140).
- [57] T. M. Fernández-Caramés, I. Froiz-Míguez, O. Blanco-Novoa, and P. Fraga-Lamas, "Enabling the internet of mobile crowdsourcing health things: A mobile fog computing, blockchain and IoT based continuous glucose monitoring system for diabetes mellitus research and care," *Sensors*, p. 3319, Jul. 2019, doi: [10.3390/s19153319](https://doi.org/10.3390/s19153319).
- [58] M. A. Meybodi, A. Goharshady, M. R. Hooshmandasl, and A. Shakiba, "Optimal blocks for maximizing the transaction fee revenue of bitcoin miners," *Journal of Combinatorial Optimization*, vol. 49, no. 15, Dec. 2025, doi: [10.1007/s10878-024-01249-0](https://doi.org/10.1007/s10878-024-01249-0).
- [59] G. Yang, C. Li, and K. E. Marstein, "A blockchain-based architecture for securing electronic health record systems," Jul. 2019, doi: [10.1002/cpe.5479](https://doi.org/10.1002/cpe.5479).
- [60] X. Zheng, R. R. Mukkamala, R. Vatrappu, and J. Ordieres-Meré, "Blockchain-based personal health data sharing system using cloud storage," Aug. 2018.
- [61] C. Grunspan and R. Pérez-Marco, "The mathematics of bitcoin," Mar. 2020, Available: [arXiv:2003.00001v1](https://arxiv.org/abs/2003.00001v1)
- [62] S. Biswas, K. Sharif, F. Li, Z. Latif, S. S. Kanhere, and S. P. Mohanty, "Interoperability and synchronization management of blockchain-based decentralized e-health systems," *IEEE Transactions on Engineering Management*, Apr. 2020, doi: [10.1109/TEM.2020.2989779](https://doi.org/10.1109/TEM.2020.2989779).

- [63] S. B. s. Ganesh Kumar, and S. Prabakaran, "Blockchain technology: Consensus protocol proof of work and proof of stake," 2020. doi: [10.1007/978-981-15-5566-4_34](https://doi.org/10.1007/978-981-15-5566-4_34).
- [64] T.-T. Kuo, H.-E. Kim, and L. Ohno-Machado, "Blockchain distributed ledger technologies for biomedical and health care applications," *Journal of the American Medical Informatics Association*, vol. 24, no. 6, Nov. 2017, doi: [10.1093/jamia/ocx068](https://doi.org/10.1093/jamia/ocx068).
- [65] M. Mettler, "[Blockchain technology in healthcare the revolution starts here.](#)" Oct. 2016.
- [66] U. Author, "Blockchain in health care: Hype, trust, and digital health," *The Lancet*, vol. 393, Jun. 2019, Available: <http://www.thelancet.com>
- [67] S. P. Maharani, E. Kurniadi, and S. Sylviani, "Exploring algebraic properties and the applications of chinese remainder theorem," *Indonesian Journal of Applied Mathematics and Statistics (IdJAMS)*, vol. 1, no. 2, pp. 71–78, Dec. 2024, Available: <https://idjams.com/index.php/jms/index>
- [68] S. Tyagi, "Role of zero-knowledge proof in blockchain security," May 2022. doi: [10.1109/COM-IT-CON54601.2022.9850714](https://doi.org/10.1109/COM-IT-CON54601.2022.9850714).
- [69] D. Mukesha, "Optimized blockchain transaction processing with bitcoin-lite: Performance-oriented python implementation," Dec. 2024, doi: [10.5281/zenodo.14275084](https://doi.org/10.5281/zenodo.14275084).
- [70] A. R. RAJPUT, Q. LI, M. T. AHVANOOEY, and I. MASOOD, "EACMS: Emergency access control management system for personal health record based on blockchain," May 2019, doi: [10.1109/ACCESS.2019.2917976](https://doi.org/10.1109/ACCESS.2019.2917976).
- [71] D. R. Chawdhuri, "Patient privacy and ownership of electronic health records on a blockchain," in *Lecture Notes in Computer Science*, Jul. 2019, pp. 95–111. doi: [10.1007/978-3-030-23404-1_7](https://doi.org/10.1007/978-3-030-23404-1_7).

- [72] N. Evangelatos, V. Özdemir, and A. Brand, "Blockchain for digital health: Prospects and challenges," *OMICS A Journal of Integrative Biology*, vol. 24, no. 5, May 2020, doi: [10.1089/omi.2020.0045](https://doi.org/10.1089/omi.2020.0045).
- [73] L. Emma, "Blockchain and smart contracts for secure and transparent transactions," Dec. 2024, Available: <https://www.researchgate.net/publication/386337137>
- [74] R. Casado-Varaa and J. Corchado, "Distributed e-health wide-world accounting ledger via blockchain," *Journal of Intelligent & Fuzzy Systems*, vol. 36, pp. 2381–2386, Oct. 2019, doi: [10.3233/JIFS-169949](https://doi.org/10.3233/JIFS-169949)IOS Press2381.
- [75] K. Ito, K. Tago, and Q. Jin, "I-blockchain: A blockchain-empowered individual-centric framework for privacy-preserved use of personal health data." Sep. 2018. doi: [10.1109/ITME.2018.00186](https://doi.org/10.1109/ITME.2018.00186).
- [76] A. Castro, "Progress report: Information security in banking and the blockchain connection." Dec. 2022.
- [77] Y. Sharma and Prof. B. Balamurugan, "Preserving the privacy of electronic health records using blockchain," *Procedia Computer Science*, vol. 173, pp. 171–180, Jun. 2020, doi: [10.1016/j.procs.2020.06.021](https://doi.org/10.1016/j.procs.2020.06.021).
- [78] B. W. Jo, R. M. A. Khan, and Y.-S. Lee, "Hybrid blockchain and internet-of-things network for underground structure health monitoring," *Sensors*, Dec. 2018, doi: [10.3390/s18124268](https://doi.org/10.3390/s18124268).
- [79] F. Tang, S. Ma, Y. Xiang, and C. Lin, "An *efficient* authentication scheme for blockchain-based electronic health records," Oct. 2019, doi: [10.1109/ACCESS.2019.2904300](https://doi.org/10.1109/ACCESS.2019.2904300).
- [80] F. M. Bublitz *et al.*, "Disruptive technologies for environment and health research: An overview of artificial intelligence, blockchain, and internet of things," *International Journal of Environmental Research and Public Health*, Oct. 2019, doi: [10.3390/ijerph16203847](https://doi.org/10.3390/ijerph16203847).

- [81] T.-T. Kuo, H. Z. Rojas, and L. Ohno-Machado, "Comparison of blockchain platforms: A systematic review and healthcare examples," *Journal of the American Medical Informatics Association*, vol. 26, no. 5, May 2019, doi: [10.1093/jamia/ocy185](https://doi.org/10.1093/jamia/ocy185).
- [82] S. WANG, D. ZHANG, and Y. ZHANG, "Blockchain-based personal health records sharing scheme with data integrity verifiable," Oct. 2019, doi: [10.1109/ACCESS.2019.2931531](https://doi.org/10.1109/ACCESS.2019.2931531).
- [83] P. S. R. Garcia and J. H. Kleinschmidt, "[Sharing health and wellness data with blockchain and smart contracts](#)," *AIEEE LATIN AMERICA TRANSACTIONS*, Jun. 2020.
- [84] J. Partala, T. H. Nguyen, and S. Pirttikangas, "Non-interactive zero-knowledge for blockchain: A survey," doi: [10.1109/ACCESS.2017.DOI](https://doi.org/10.1109/ACCESS.2017.DOI).
- [85] D. Randall, P. Goel, and R. Abujamra, *J Health Med Informat*, vol. 8, no. 3, p. 1000276, Jul. 2017, doi: [10.4172/2157-7420.1000276](https://doi.org/10.4172/2157-7420.1000276).
- [86] J. Xu *et al.*, "Healthchain: A blockchain-based privacy preserving scheme for large-scale health data," *IEEE Internet of Things Journal*, Nov. 2019, doi: [10.1109/JIOT.2019.2923525](https://doi.org/10.1109/JIOT.2019.2923525).