

# Documentation for **QuickFiber** Input and Output Files

Jaime E. Forero-Romero

March 9, 2015

## Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Important definitions</b>                        | <b>1</b> |
| <b>2</b> | <b>QuickFiber inputs</b>                            | <b>2</b> |
| <b>3</b> | <b>QuickFiber inputs data-structure</b>             | <b>2</b> |
| <b>4</b> | <b>QuickFiber outputs</b>                           | <b>2</b> |
| <b>5</b> | <b>QuickFiber output file naming convention</b>     | <b>3</b> |
| <b>6</b> | <b>QuickFiber outputs data-structure</b>            | <b>3</b> |
| 6.1      | Example of PotentialFiberMap construction . . . . . | 4        |

This documents describes the format of the files generated by the **QuickFiber** software.

## 1 Important definitions

Taken from <https://desi.lbl.gov/trac/wiki/Pipeline/FormatsAndNumbering>

- **Tile:** pre-defined locations on the sky. Tiles are pre-defined with a 6-digit ID. 900000 and above are reserved for calibration, commissioning, test, ancillary, and other non-DESI key project tiles, which may not even appear in a DESI tile list.
- **Pointing:** A specific selection of targets within a tile indicating both a pointing of the telescope and the fiber positioners.

This means that a tile may be observed multiple times with different pointings. A pointing may be observed multiple times with different exposures. If even one target changes or any target: fiber mapping changes it becomes a new

pointing. A slightly different positioner location of the same targets on the same fibers is the same pointing.

## 2 QuickFiber inputs

The necessary input of `QuickFiber` are

- `TargetDB`. Data base containing the information of all targets on the sky.
- `SurveyTiles`. File containing the positions of all the tiles to be observed. Currently this ASCII file <https://desi.lbl.gov/trac/browser/code/survey/surveyplan/trunk/data/desi-tiles-full.par>
- `FiberPositions`. File containing the positions of all fibers on the focal plane. Currently this ASCII file <https://desi.lbl.gov/trac/browser/code/desimodel/trunk/data/focalplane/fiberpos.txt>

## 3 QuickFiber inputs data-structure

In the `TargetDB` found in `/project/projectdirs/desi/db` the table of interest is `Target` with the following columns

- `id`: primary key.
- `cand_id`:
- `ra`: degrees [0-360]
- `dec`: degrees [-90 -+90]
- `priority`:
- `nobs`:
- `objtype`: ELG, LRG, QSO, SKY, STDSTAR, GAL, OTHER

`SurveyTiles` is an ASCII file including the following fields

- `tileid` [1:28810]
- `ra`: degree [0-360]
- `dec`: degrees [-90-+90]
- `pass` [1-5]
- `in_desi` [0,1]

`FiberPositions` is an ASCII file including the following fields.

- `fiber_ID` [0:]

- positioner\_ID [0:]
- spectrograph\_ID [0:]
- x: mm, position on focal plane
- y: mm, position on focal plane
- z: mm, position on focal plane

## 4 QuickFiber outputs

The principal outputs of `QuickFiber` are

- `PotentialFiberMap`. The set of targets that can be reached by a set of fibers in a tile.
- `FiberMap`. This is a pointing defining which targets are on which fiber.

The previous two items will be stored in the same FITS file for each tile and pointing. This means that two different assignment algorithms running on the same tile producing different pointings will store the results in different files.

## 5 QuickFiber output file naming convention

Primary output files from `QuickFiber` will follow the naming scheme

`QuickFiber_TTTTTT_PPPPPPPPPPPPP.fits`

where TTTTTT is the 6-digit Tile ID and PPPPPPPPPPPPP is a 12-digit pointing ID. The pointing ID is hash value computed by adding the IDs of all the targets in the pointing.

## 6 QuickFiber outputs data-structure

`PotentialFiberMap` contains the following information

- fiber: [0-4999]
- numtargetid: [1-] Number of potential target IDs associated to each fiber. If a fiber has zero potential targets it has the targetID -1 associated to it.
- targetid: unique target identifier to get back to target selection info. This contains all the targets that can be reached by a fiber. This concatenates the sets of available targets for each fiber.

`FiberMap` contains the following information<sup>1</sup>

---

<sup>1</sup>First defined in <https://desi.lbl.gov/trac/wiki/Pipeline/FormatsAndNumbering>.

- fiber: [0-4999]
- positioner: [0-4999]
- objtype: ELG, LRG, QSO, SKY, STDSTAR, GAL, OTHER
- targetid: unique target identifier to get back to target selection info
- desi\_target0: 64 bit mask of targeting info
- ra: degrees [0-360]
- dec: degrees [-90 - +90]
- xfocal.design: mm from center in positioner coordinate system
- yfocal.deisgn: mm from center in positioner coordinate system

## 6.1 Example of PotentialFiberMap construction

Let's assume for simplicity that we have 4 fibers with IDs [0,1,2,3]. There are in turn 4 different sets of targets that can be reached by each fiber. These sets are [980,203], [736,102,304], [234] and [-1] for fibers 0,1,2 and 3, respectively. The index -1 for fiber 3 means that this fiber cannot reach any target.

In this case PotentialFiberMap has the following fields

- fiber: contains the array [0,1,2,3].
- numtargetid: contains the array [2,3,1,1].
- targetid: contains the array [980,203,736,102,304,234,-1].