

MC Cable — Full Range Product Data

Southwire Type MC-AP™ / Armorlite® Metal-Clad Cable · MVMS Bonney Lake — JCS Construction Solutions

Replaces the 12/2-solid-only cut (SPEC 60100). This is the full-range series cut sheet — SPEC 60240.

Parameter	Specification
Product / Type	Southwire Type MC-AP™ (Armorlite®) Metal-Clad Cable
Spec document	SPEC 60240 (full range) — supersedes SPEC 60100 (12/2 solid only)
Conductors	THHN/THWN-2 copper, 90°C
Size range	14 AWG through 750 kcmil
Conductor form	Solid AND stranded available
Configurations	2, 3, 4+ conductor with insulated/bare EGC (12/2, 12/3, etc.)
Armor	Aluminum interlocked armor (AIA)
Voltage	600 V
Listing	UL 1569 (Type MC); NEC Article 330
This project	#12 AWG, 277 V lighting branch circuit EH-19 (concealed MC per E2.01)
Colors	Order 277 V-colored (brown/gray/green) MC to match phase scheme; or 12/2 (blk/wht/grn) re-identified per NEC 210.5(C)

Official manufacturer cut sheet: [Southwire SPEC 60240 — Type MC-AP / Armorlite](#)

Note: Southwire Armorlite / MC-AP uses aluminum interlocked armor (AIA), not steel. Verify the printed legend on the delivered coils reads Southwire before stamping — confirmed Southwire on site.