Performance Test Results - FDS

FDS-specific performance-report.pdf. Scenario plan is reproducible in principle but NO actual load, latency, throughput or realtime timing data was available from the reviewed repository CI.

DOCUMENT STATUS: NOT TESTED - MEASUREMENTS REQUIRED

1 Testing result and evidence boundary

Required field	Recorded result
Performance testing tool	Not executed / not verified. k6 is a proposed tool, not an observed run.
Target environment	Not provisioned / not verified. Must use isolated staging/test infrastructure.
Git commit tested for load	None. Unit/integration CI at 503465b7eb2c29b56cc2ec0d329d91d6b40853d4 is not performance evidence.
Concurrent users / duration	Not Tested
Request throughput (req/s)	Not Tested
Response time p50 / p95	Not Tested
HTTP / application error rate	Not Tested
Realtime event propagation	Not Tested
NFR-01 result	Not evaluated
NFR-02 result	Not evaluated

2 Proposed safe test scenarios (not executed)

ID	Scenario	Measurement	Status
PERF-FDS-01	Booking search / arrivals / departures	HTTP latency p50/p95, throughput, error rate	Not Tested
PERF-FDS-02	Room status board reads	HTTP p50/p95, request throughput	Not Tested
PERF-FDS-03	Authorized JWT-protected API reads	Auth overhead; 401/403 consistency	Not Tested
PERF-FDS-04	Check-in with synthetic booking and room	Checkout/check-in latency and DB lock contention	Not Tested
PERF-FDS-05	Room change on synthetic assignments	Transaction latency, conflicts	Not Tested
PERF-FDS-06	Checkout with synthetic folio and payments	Transaction latency, event/side effect behavior	Not Tested
PERF-FDS-07	Room status Socket.IO delivery	Event publish-to-client p50/p95 latency	Not Tested
PERF-FDS-08	RabbitMQ checkout and WKMS escalation	Producer-to-consumer end-to-end delay, failure/retry	Not Tested

3 Relevant objectives (targets are NOT results)

Original SRS non-functional performance goal NFR-01: 95% of API requests within 500 ms at 100 concurrent users. Compare p95 latency against 500 ms only after generating actual controlled load results. NFR-02: target inter-service propagation within 1 second (requires a live integrated benchmark). Confirm exact release SRS target values when publishing final evidence.

4 Controlled execution prerequisites

• Use disposable PostgreSQL 16 test schema and synthetic guests/bookings; NEVER performance-test destructive mutations against shared Neon development or production data.

• Use a dedicated test application and RabbitMQ broker/queues; authenticate with test-only identities. Keep JWTs and URLs out of recorded outputs.

• Pin environment versions, node/runtime, hardware tier, code SHA, dataset size and network topology. Record warm-up and steady-state measurements separately.

• Apply incremental virtual users (for example, 1, 10, 25, 50, 100) with stop criteria; do not assume 100 VUs on free shared hosting is safe.

• For write-heavy scenarios create fresh test bookings/rooms per virtual user and clean up disposable fixtures.

• Store raw JSON/CSV summaries plus scripts; cite test run timestamp; document errors, failed requests, rate limits and bottlenecks.

5 Evidence required before marking a scenario PASS

Evidence item	Pending
Command/tool and version	Pending
Test script plus exact environment/commit	Pending
Measured p50/p95 response times	Pending
Measured error rate, throughput and samples	Pending
Threshold pass/fail evaluation	Pending
Screenshots/structured summary and rerun record	Pending

This report intentionally contains no invented numbers. A passing Jest/CI pipeline is not proof of concurrent-load or cross-service performance.