

Super Admin Module

Super Admin registration, login, firm creation, firm admin management, firm modules, and system config.

Base paths: `/api/v1/super-admin` , `/api/v1/super-admin/firms` , `/api/v1/super-admin/config`

1. Authentication

Base: `/api/v1/super-admin`

Method	Path	Description
POST	<code>/api/v1/super-admin/register</code>	One-time registration (fails if already exists)
POST	<code>/api/v1/super-admin/login</code>	Login — no firmCode required

```
Register Super Admin (first run only):
{
  "data": {
    "fullName": "System Admin",
    "email": "admin@nepalcrm.com",
    "username": "superadmin",
    "password": "SuperSecure@123"
  }
}

Login:
{
  "data": {
    "username": "superadmin",
    "password": "SuperSecure@123"
  }
}
```

2. Firm Management

Base: `/api/v1/super-admin/firms`

Method	Path	Description
POST	<code>/api/v1/super-admin/firms</code>	Create a new firm with Firm Admin
GET	<code>/api/v1/super-admin/firms/admins</code>	Get all firm admins across all firms

GET	/api/v1/super-admin/firms/{firmId}/admins	Get firm admins for a specific firm
GET	/api/v1/super-admin/firms/admins/{adminId}	Get firm admin by ID
PATCH	/api/v1/super-admin/firms/admins/{adminId}/toggle	Toggle firm admin status

Create Firm Request:

```
{
  "data": {
    "firmName": "Apex Law Associates",
    "firmCode": "CLAW",
    "firmType": "LAW_FIRM",
    "tenantTypeId": "uuid",
    "adminName": "Rajesh Hamal",
    "adminEmail": "rajesh@apexlaw.com",
    "adminUsername": "rajesh_admin",
    "adminPassword": "Temp@123",
    "address": "Kathmandu, Nepal",
    "phone": "+977-1-4XXXXXX",
    "email": "contact@apexlaw.com"
  }
}
```

On firm creation, the backend:

1. Creates the firm
2. Clones system role templates (FIRM_ADMIN, ADVOCATE, PARALEGAL, CLIENT) for this firm
3. Creates the Firm Admin user with the FIRM_ADMIN role
4. Sends a welcome email to the admin

3. Firm Module Management

Base: `/api/v1/super-admin/firms/{firmId}/modules`

Method	Path	Description
GET	/api/v1/super-admin/firms/{firmId}/modules	Get all modules with status for a firm
POST	/api/v1/super-admin/firms/{firmId}/modules	Enable/disable a module for a firm

Enable Module Request:

```
{
  "data": {
    "moduleCode": "CASE_MANAGEMENT",
    "isEnabled": true
  }
}
```

4. System Config (Super Admin)

Base: `/api/v1/super-admin/config`

Method	Path	Description
GET	/api/v1/super-admin/config	Get all global config values
PUT	/api/v1/super-admin/config	Bulk upsert global config values
DELETE	/api/v1/super-admin/config/{key}	Delete a global config key
GET	/api/v1/super-admin/firms/{firmId}/config	Get per-firm config values
PUT	/api/v1/super-admin/firms/{firmId}/config	Set per-firm config values

```
Update Global Config:
PUT /api/v1/super-admin/config
Body: {
  "SMTP_HOST": "smtp.gmail.com",
  "SMTP_PORT": "587",
  "APP_NAME": "NepalCRM",
  "APP_PRODUCTION": "false"
}

All values are strings (key-value map).
```