



Apache Kafka - Simple Producer Example

Advertisements

[Previous Page](#)

[Next Page](#)

Let us create an application for publishing and consuming messages using a Java client. Kafka producer client consists of the following API's.

KafkaProducer API

Let us understand the most important set of Kafka producer API in this section. The central part of the KafkaProducer API is "KafkaProducer" class. The KafkaProducer class provides an option to connect a Kafka broker in its constructor with the following methods.

KafkaProducer class provides send method to send messages asynchronously to a topic. The signature of send() is as follows

```
producer.send(new ProducerRecord<byte[],byte[]>(topic,
partition, key1, value1) , callback);
```

ProducerRecord – The producer manages a buffer of records waiting to be sent.

Callback – A user-supplied callback to execute when the record has been acknowledged by the server (null indicates no callback).

KafkaProducer class provides a flush method to ensure all previously sent messages have been actually completed. Syntax of the flush method is as follows –

```
public void flush()
```

KafkaProducer class provides partitionFor method, which helps in getting the partition metadata for a given topic. This can be used for custom partitioning. The signature of this method is as follows –

```
public Map metrics()
```

It returns the map of internal metrics maintained by the producer.

public void close() – KafkaProducer class provides close method blocks until all previously sent requests are completed.

Producer API

The central part of the Producer API is "Producer" class. Producer class provides an option to connect Kafka broker in its constructor by the following methods.

The Producer Class

The producer class provides send method to **send** messages to either single or multiple topics using the following signatures.

```
public void send(KeyedMessage<k,v> message)
- sends the data to a single topic, par-titioned by key using either sync or async producer.
public void send(List<KeyedMessage<k,v>>messages)
- sends data to multiple topics.
Properties prop = new Properties();
prop.put(producer.type,"async")
ProducerConfig config = new ProducerConfig(prop);
```

There are two types of producers – **Sync** and **Async**.

The same API configuration applies to "Sync" producer as well. The difference between them is a sync producer sends messages directly, but sends messages in background. Async producer is preferred when you want a higher throughput. In the previous releases like 0.8, an async producer does not have a callback for send() to register error handlers. This is available only in the current release of 0.9.

```
public void close()
```

Producer class provides **close** method to close the producer pool connections to all Kafka bro-kers.

Configuration Settings

The Producer API's main configuration settings are listed in the following table for better understanding –

S.No	Configuration Settings and Description
1	client.id identifies producer application
2	producer.type either sync or async
3	acks The acks config controls the criteria under producer requests are considered complete.
4	retries If producer request fails, then automatically retry with specific value.
5	bootstrap.servers bootstrapping list of brokers.
6	linger.ms if you want to reduce the number of requests you can set linger.ms to something greater than some value.
7	key.serializer Key for the serializer interface.
8	value.serializer value for the serializer interface.
9	batch.size Buffer size.
10	buffer.memory controls the total amount of memory available to the producer for buffering.

ProducerRecord API

ProducerRecord is a key/value pair that is sent to Kafka cluster. ProducerRecord class constructor for creating a record with partition, key and value pairs using the following signature.

```
public ProducerRecord (string topic, int partition, k key, v value)
```

Topic – user defined topic name that will be appended to record.

Partition – partition count

Key – The key that will be included in the record.

Value – Record contents

```
public ProducerRecord (string topic, k key, v value)
```

ProducerRecord class constructor is used to create a record with key, value pairs and without partition.

Topic – Create a topic to assign record.

Key – key for the record.

Value – record contents.

```
public ProducerRecord (string topic, v value)
```

ProducerRecord class creates a record without partition and key.

Topic – create a topic.

Value – record contents.

The ProducerRecord class methods are listed in the following table –

S.No	Class Methods and Description
1	public string topic() Topic will append to the record.
2	public K key() Key that will be included in the record. If no such key, null will be re-turned here.
3	public V value() Record contents.
4	partition() Partition count for the record

SimpleProducer application

Before creating the application, first start ZooKeeper and Kafka broker then create your own topic in Kafka broker using create topic command. After that create a java class named "SimpleProducer.java" and type in the following coding.

```
//import util.properties packages
import java.util.Properties;

//import simple producer packages
import org.apache.kafka.clients.producer.Producer;

//import KafkaProducer packages
import org.apache.kafka.clients.producer.KafkaProducer;

//import ProducerRecord packages
import org.apache.kafka.clients.producer.ProducerRecord;

//Create java class named "SimpleProducer"
public class SimpleProducer {

    public static void main(String[] args) throws Exception{

        // Check arguments length value
        if(args.length == 0){
            System.out.println("Enter topic name");
            return;
        }

        //Assign topicName to string variable
        String topicName = args[0].toString();

        // create instance for properties to access producer configs
        Properties props = new Properties();

        //Assign localhost id
        props.put("bootstrap.servers", "localhost:9092");

        //Set acknowledgements for producer requests.
        props.put("acks", "all");

        //If the request fails, the producer can automatically retry,
        props.put("retries", 0);

        //Specify buffer size in config
        props.put("batch.size", 16384);

        //Reduce the no of requests less than 0
        props.put("linger.ms", 1);

        //The buffer.memory controls the total amount of memory available to the producer for buffering.
        props.put("buffer.memory", 33554432);

        props.put("key.serializer",
            "org.apache.kafka.common.serialization.StringSerializer");

        props.put("value.serializer",
```

```
    "org.apache.kafka.common.serialization.StringSerializer");

    Producer<String, String> producer = new KafkaProducer
    <String, String>(props);

    for(int i = 0; i < 10; i++)
        producer.send(new ProducerRecord<String, String>(topicName,
            Integer.toString(i), Integer.toString(i)));
        System.out.println("Message sent successfully");
        producer.close();
    }
}
```

Compilation – The application can be compiled using the following command.

```
javac -cp "/path/to/kafka/kafka_2.11-0.9.0.0/lib/*" *.java
```

Execution – The application can be executed using the following command.

```
java -cp "/path/to/kafka/kafka_2.11-0.9.0.0/lib/*":. SimpleProducer <topic-name>
```

Output

```
Message sent successfully
To check the above output open new terminal and type Consumer CLI command to receive messages.
>> bin/kafka-console-consumer.sh --zookeeper localhost:2181 --topic <topic-name> --from-beginning
1
2
3
4
5
6
7
8
9
10
```

Simple Consumer Example

As of now we have created a producer to send messages to Kafka cluster. Now let us create a consumer to consume messages from the Kafka cluster. KafkaConsumer API is used to consume messages from the Kafka cluster. KafkaConsumer class constructor is defined below.

```
public KafkaConsumer(java.util.Map<java.lang.String,java.lang.Object> configs)
```

configs – Return a map of consumer configs.

KafkaConsumer class has the following significant methods that are listed in the table below.

S.No	Method and Description
1	public java.util.Set<TopicPartition> assignment() Get the set of partitions currently assigned by the consumer.
2	public string subscription() Subscribe to the given list of topics to get dynamically assigned partitions.
3	public void subscribe(java.util.List<java.lang.String> topics, ConsumerRebalanceListener listener) Subscribe to the given list of topics to get dynamically assigned partitions.
4	public void unsubscribe() Unsubscribe the topics from the given list of partitions.
5	public void subscribe(java.util.List<java.lang.String> topics) Subscribe to the given list of topics to get dynamically assigned partitions. If the given list of topics is empty, it is treated the same as unsubscribe().
6	public void subscribe(java.util.regex.Pattern pattern, ConsumerRebalanceListener listener)

	The argument pattern refers to the subscribing pattern in the format of regular expression and the listener argument gets notifications from the subscribing pattern.
7	public void assign(java.util.List<TopicPartition> partitions) Manually assign a list of partitions to the consumer.
8	poll() Fetch data for the topics or partitions specified using one of the subscribe/assign APIs. This will return error, if the topics are not subscribed before the polling for data.
9	public void commitSync() Commit offsets returned on the last poll() for all the subscribed list of topics and partitions. The same operation is applied to commitAsync().
10	public void seek(TopicPartition partition, long offset) Fetch the current offset value that consumer will use on the next poll() method.
11	public void resume() Resume the paused partitions.
12	public void wakeup() Wakeup the consumer.

ConsumerRecord API

The ConsumerRecord API is used to receive records from the Kafka cluster. This API consists of a topic name, partition number, from which the record is being received and an offset that points to the record in a Kafka partition. ConsumerRecord class is used to create a consumer record with specific topic name, partition count and <key, value> pairs. It has the following signature.

```
public ConsumerRecord(string topic,int partition, long offset,K key, V value)
```

Topic – The topic name for consumer record received from the Kafka cluster.

Partition – Partition for the topic.

Key – The key of the record, if no key exists null will be returned.

Value – Record contents.

ConsumerRecords API

ConsumerRecords API acts as a container for ConsumerRecord. This API is used to keep the list of ConsumerRecord per partition for a particular topic. Its Constructor is defined below.

```
public ConsumerRecords(java.util.Map<TopicPartition,java.util.List<ConsumerRecord>K,V>>> records)
```

TopicPartition – Return a map of partition for a particular topic.

Records – Return list of ConsumerRecord.

ConsumerRecords class has the following methods defined.

S.No	Methods and Description
1	public int count() The number of records for all the topics.
2	public Set partitions() The set of partitions with data in this record set (if no data was returned then the set is empty).

3	public Iterator iterator() Iterator enables you to cycle through a collection, obtaining or re-moving elements.
4	public List records() Get list of records for the given partition.

Configuration Settings

The configuration settings for the Consumer client API main configuration settings are listed below –

S.No	Settings and Description
1	bootstrap.servers Bootstrapping list of brokers.
2	group.id Assigns an individual consumer to a group.
3	enable.auto.commit Enable auto commit for offsets if the value is true, otherwise not committed.
4	auto.commit.interval.ms Return how often updated consumed offsets are written to ZooKeeper.
5	session.timeout.ms Indicates how many milliseconds Kafka will wait for the ZooKeeper to respond to a request (read or write) before giving up and continuing to consume messages.

SimpleConsumer Application

The producer application steps remain the same here. First, start your ZooKeeper and Kafka broker. Then create a "SimpleConsumer" application with the java class named "SimpleConsumer.java" and type the following code.

```
import java.util.Properties;
import java.util.Arrays;
import org.apache.kafka.clients.consumer.KafkaConsumer;
import org.apache.kafka.clients.consumer.ConsumerRecords;
import org.apache.kafka.clients.consumer.ConsumerRecord;

public class SimpleConsumer {
    public static void main(String[] args) throws Exception {
        if(args.length == 0){
            System.out.println("Enter topic name");
            return;
        }
        //Kafka consumer configuration settings
        String topicName = args[0].toString();
        Properties props = new Properties();

        props.put("bootstrap.servers", "localhost:9092");
        props.put("group.id", "test");
        props.put("enable.auto.commit", "true");
        props.put("auto.commit.interval.ms", "1000");
        props.put("session.timeout.ms", "30000");
        props.put("key.deserializer",
            "org.apache.kafka.common.serialization.StringDeserializer");
        props.put("value.deserializer",
            "org.apache.kafka.common.serialization.StringDeserializer");
        KafkaConsumer<String, String> consumer = new KafkaConsumer
            <String, String>(props);

        //Kafka Consumer subscribes list of topics here.
        consumer.subscribe(Arrays.asList(topicName))

        //print the topic name
        System.out.println("Subscribed to topic " + topicName);
        int i = 0;

        while (true) {
```

```
ConsumerRecords<String, String> records = consumer.poll(100);
for (ConsumerRecord<String, String> record : records)

    // print the offset, key and value for the consumer records.
    System.out.printf("offset = %d, key = %s, value = %s\n",
        record.offset(), record.key(), record.value());
}
```

Compilation – The application can be compiled using the following command.

```
javac -cp "/path/to/kafka/kafka_2.11-0.9.0.0/lib/*" *.java
```

Execution – The application can be executed using the following command

```
java -cp "/path/to/kafka/kafka_2.11-0.9.0.0/lib/*":. SimpleConsumer <topic-name>
```

Input – Open the producer CLI and send some messages to the topic. You can put the simple input as 'Hello Consumer'.

Output – Following will be the output.

```
Subscribed to topic Hello-Kafka
offset = 3, key = null, value = Hello Consumer
```

⏪ Previous Page

Next Page ⏩

Advertisements



[Write for us](#) [FAQ's](#) [Helping](#) [Contact](#)

© Copyright 2017. All Rights Reserved.

